

## Actaris



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

**Actaris** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Actaris Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*

| Ürün                                                   | Açıklama                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">G40 Dn 50</a>                              | H3581 Rotary lobe gas meter DELTA Silver Edition no HTB version Nominal size: DN 50 Pressure rating: PN20 Connection: flange according to ANSI 150 Overall length: 171 mm Material: aluminum Gas type: according to DVGW worksheet G260 Reading direction: frontal reading Flow direction: freely selectable ** prepared for 2 immersion sleeves L4 (** please indicate flow direction when equipping with immersion sleeves) Measuring range: 1:20 (max. possible measuring range 1:50 - available for an additional charge) Pulse generator: 2x NF pulse generator + anti-manipulation contact Pulse value: 0.1 cbm Connector: Binder male 2x PR sockets Ermeto EO 6S Operating temperature: - 25 ° C to + 55 ° C (according to MID) Paintwork: without |
| <a href="#">Hf3</a>                                    | G0464 HF pulse tap v. DKZ I = 0.0583 dm3 / imp                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <a href="#">-RBE 1732 1"</a>                           | kit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE 1732 1,5"</a>                          | kit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE1732 3/4 "</a>                          | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE1831-1832 DN40</a>                      | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE1832 DN50</a>                           | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE4731-4732 DN25</a>                      | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE4731-4732 DN25</a>                      | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">RBE4731-4732 DN50</a>                      | KIT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">Repair kit for gas pressure regulator</a>  | Typ RR16-50-54-12N-033 DN50 PN/ANSI 16/5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <a href="#">Repair kit for gas pressure regulato</a>   | Typ RR16-50-42-8N-033 DN50 PN/ANSI 16/5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <a href="#">SN: 000038</a>                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Nominal width: DN 80 Pressure rating: PN16 Connection: |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Quantity gas meter MZ80 DN 80 PN16</a>   | intermediate construction Overall length: 120 mm Material: ductile iron Aluminum turbine wheel Type of gas: according to DVGW worksheet G260 Direction of reading: reading from the front Flow direction: freely selectable** Qmax: 250 m³/h Q min: 10 m³/h 2x NF pulse generator + anti-tampering contact Pulse value: 1 cbm Connector: Binder male Permanently lubricated bearings: yes Oil pump: without Operating temperature: -30°C to +60°C Painting: KTL coating EC Type Examination Certificate: CE-0085BS5061 No. ** for measurements not subject to legal control **                                                                                                                                                                                                                                                                                 |
| <a href="#">Turbine wheel gas meter G100 DN 80</a>   | Fluxi 2000 Nominal width: DN 80 Pressure rating: PN16 Connection: Flange according to DIN Overall length: 240 mm Material: ductile iron Type of gas: according to DVGW worksheet G260 Direction of reading: reading from the front Flow direction: freely selectable** prepared for 2 immersion sleeves (**please specify flow direction if equipped with immersion sleeves) Measuring range: 1:20 Pulse generator: 2x NF pulse generator + anti- manipulation contact Pulse value: 1.0 cbm/pulse Connector: Binder male 2x PR nozzle Ermeto EO 6S Type of lubrication: permanently lubricated (Oil pump available at extra cost) Operating temperature: -25°C to +55°C (according to MID) Painting: water-based paint similar to RAL7035 PTB approval no. DE-10-MI002-PTB001 Revision number: 2 No MID tested ** for measurements subject to legal control ** |
| <a href="#">RBE 1732 DN:1 inç</a>                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <a href="#">RBE 4022 DN:40</a>                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <a href="#">1822 DN:40 PN 16</a>                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <a href="#">1822 DN:50 PN16</a>                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <a href="#">Gas pressure regulator RBE 3212 DN25</a> | H5832 Nominal width: DN 25 Pressure rating: PN5 Connection type: internal thread 1" x 1 1/2" Medium: inert gases according to DVGW G260 Overall length: 130 mm Inlet pressure Pu max.: 5000 mbar Inlet pressure Pu min.: 2000 mbar Outlet pressure Pds: 55 mbar Spring control range: 28-70 mbar Flow rate: ** Nm³/h SAV upper shutdown: yes Pdso: 100 mbar Leadership range: 70 - 130 SAV lower shutdown: yes Psu: 10 mbar Lead range: 5 - 28 Flow direction: ** Ambient temperature: -30°C to +60°C Paint finish: primed                                                                                                                                                                                                                                                                                                                                     |
| <a href="#">RBE 1732</a>                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <a href="#">H5950</a>                                | Gas pressure regulator RBE 4732-D DN80 SAV 8632 Nominal diameter: DN 80 Pressure rating: PN20 Connection type: Flange according to DIN PN25 Medium: inert gases according to DVGW G260 Length: 298 mm Inlet pressure Pu max.: 19.2 bar Inlet pressure Pu min.: ** mbar Output pressure Pds: 3.0 bar Spring guide range: 1.5 - 5.5 bar Flow rate: ** Nm³/h Silencer: no SAV type: 8632 SAV upper cut-off: yes PDSO: 4.6 bar Spring guide range: 3.9 - 4.6 bar SAV lower cutoff: yes Pdsu: 0.90 bar Spring guide range: 0.32 - 1.0 bar Flow direction: left to right Ambient temperature: -30°C to +60°C Paint finish: primed Permissible pressure: 19.2 bar EC type examination certificate: CE-0085CN0360 No.                                                                                                                                                  |

|                                               |                                       |
|-----------------------------------------------|---------------------------------------|
| <a href="#">RR16 DN50-31-8N-033</a>           |                                       |
| <a href="#">RR16 DN50-31-8N-033</a>           |                                       |
| <a href="#">233-12-5-72 (Ex. 233-12-4-72)</a> |                                       |
| <a href="#">142-620-00</a>                    |                                       |
| <a href="#">Rr1680428h-Dn80-Pn16</a>          |                                       |
| <a href="#">133-5-72</a>                      |                                       |
| <a href="#">Dattus-Fm2-Etc-L</a>              | GAS FLOW METER                        |
| <a href="#">Fluxi2200/Tz</a>                  |                                       |
| <a href="#">Rb4731 Dn80</a>                   |                                       |
| <a href="#">Rr16-25-31-8h-Ohne Sav</a>        |                                       |
| <a href="#">155-D</a>                         |                                       |
| <a href="#">Rr16-50-31-12n+rv-Md</a>          |                                       |
| <a href="#">Rr1680828hdn80p</a>               |                                       |
| <a href="#">Rbe4731 Dn80</a>                  |                                       |
| <a href="#">Rr16-25-31-8h-SI-Izn.1</a>        |                                       |
| <a href="#">111e300-13</a>                    |                                       |
| <a href="#">233-12-5-72</a>                   |                                       |
| <a href="#">Rr16-80-42-12n-SI-Izn1</a>        |                                       |
| <a href="#">Zg-Nr: 39906310</a>               | WEAR SET FOR TYPE RBE 1731-1732 DN 25 |
| <a href="#">Rr1680548hdn80pn16</a>            |                                       |
| <a href="#">Rr16-50-42-8n-033</a>             |                                       |
| <a href="#">233-12-5-72 Dn50</a>              |                                       |
| <a href="#">Acd G1.6-Arg</a>                  | 3604700                               |
| <a href="#">Rbe 4732 Acc</a>                  |                                       |
| <a href="#">Ssv Type 033</a>                  |                                       |
| <a href="#">12p-Mm-SI-Izm.1</a>               |                                       |
| <a href="#">Regulatordn50</a>                 |                                       |
| <a href="#">Rr16-80-42-12n</a>                |                                       |