

Arcol



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Arcol Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Arcol Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HS400 100R 5%(J)	Wire resistor in aluminum housing Resistance: 100 ohms Tolerance: $\pm 5\%$ (J) Rated power: 400 watts Nominal voltage: 2,000 V Temperature coefficient: $\pm 150\text{ppm} / \text{K}$ Dimensions (W x H x L): 55.0 x 30.0 x 182.0 mm Connection: solder lugs RoHS (*): Compliant
220164	
220190	
220610	
220630	
220646	
AP836 47R 5%(J)	
FPA100-100RJ	
FPA100-10RJ	
FPA100-1KJ	
FPA600 5K0 5%(J)	
HS 100 1R5	
HS100 2R2 J	
HS100 47R J	
HS100-1KJ	
HS50 4K7 F	
MRA0207 1M B 15PPM TA	

NHS100 E6 100R 5%(J) M193	
RESISTOR HS25 - 2,05 OHM	
RESISTOR HS25 - 5,11 OHM	
RESISTOR HS25 - 8,25 OHM	
HS300 220R 5%(J)	Resistance:220 Ohm Tolerance:±5% (J) Rated capacity:300 Watt Nominal voltage:2500 V Temperature coefficient: ±100ppm/K Dimensions (W x H x L):72.5 x 41.8 x 127.7 mm Connection:screw terminals RoHS (*):Konform
WD300 220R 5% (J)	Resistance:220 ohms Tolerance:±5% (J) Rated capacity:300 watts Nominal voltage:2500V Temperature coefficient: ±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
220981/ HS10 10R 1%(F)	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:10 watts Nominal voltage:160v Temperature coefficient:±100ppm/K Dimensions (W x H x L):16.5 x 8.8 x 15.9mm Connection:solder lugs RoHS (*):Compliant
WD300 220R 5% (J)	Wire resistor in aluminum housing Resistance:220 ohms Tolerance:±5% (J) Rated capacity:±5% (J) Nominal voltage:2500V Temperature coefficient:±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
161227 -WD5 10R 1%(F)	Wire resistor in aluminum housing Resistance: 10 ohm Tolerance: ±1% (F) Rated capacity: 10 watts Nominal voltage: 160v Temperature coefficient: ±60ppm/°C Dimensions (W x H x L): 17.0 x 9.0 x 16.8mm Connection: solder plugs RoHS (*):Compliant
160348 - WD10 10R 1% (F)	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:15 watts Nominal voltage:260V Temperature coefficient:±60ppm/°C Dimensions (W x H x L):21.0 x 11.0 x 20.1mm Connection:solder lugs RoHS (*):Compliant
C300K20RE	
C300K16RE	
6126P-8 1-2E	
Hs50 30r J	
220324	
V5 39r 5%(J)	
Hs50 50k J	
Ordering Code: Hs100 10r J	
Hs100 100r J	

Hs200 20r 1%(F)
Fpa100-100rj Widerstand 100 Ohm / 100 W
08.14 Hs 100 R47 J
Resistor Hs25 - 2,05 Ohm
Hs300hv/50r
Hs100 10r J
Hs100 150r J
Wd25 47r
Hs100-1kj Widerstand 1 Kohm / 100w
Hs200 330r F
220085
220316
220289
Nhs100 4k7 5%(J)
300w 75r 5
Hs100-100rj Widerstand 100 Ohm / 100 W
220317
Fpa100-1kj Widerstand 1 Kohm / 100w
220925
Hs 25 3k9j
Ap836 100r 1%(F) Leistungswiderstand
220911
220508
Hs150 150r 1%(F) (Pack 1x25)
Hs 1001rs2,2,10 Ohm
Hs100 15r
Eg-V314/Vi
Typ Hs100 47r J
284-Hs50-0.27 Mfr Pn: Hs50 0r27 5% 50w 0.27 Ohm 5%

220318	
Resistor Hs25 - 5,11 Ohm	
Ap836 100r 1%(F)	
220266	
Fpa100-10rj Widerstand	
Hs100 2r2 J Widerstand	
Hs100 1r5 5%(J)	Wirewound resistor in aluminum housing Resistance: 1.5 ohms ohms Tolerance: $\pm 5\%$ (J) Rated power: 100 watts watts Rated voltage: 1,900 V Temperature Coefficient: $\pm 100\text{ppm} / \text{K}$ Dimensions (W x H x L): 47.5 x 24.1 x 65.2 mm Connection: solder lugs Customs tariff number: 85332900 Country of origin: Great Britain and Northern Ireland Weight: 0.11 kg Manufacturer Part Number: HS100 1R5 J
Hs10 120r J	
Hs50-10rj	
08 14 Hs 100 R47 J	
Hs50 270r	
220916	
Hs150 75r F	
Hs300 10r 5% (J)	
Resistor Hs25 - 8,25 Ohm	
Hs50 820r 5%(J)	
Acs10s 47r J	
Hs25 R01 J Hs25 0r01 10%(K) And Wd25 0r01 5% (J)	
Wd25 0r01 5% (J)	
Hs200 150r 1%(F) (Pack 1x10)	
220275	
220463	
Hs-100	
300w 75r -5	
Hs50 220r J	
000.001.800	
Hs10 5k6 5%(J)	

Hs300 220r 1%(F) (Pack 1x10)
V5a 18r J
000.000.220
000.001.800 Resistor
Hs50 47r J
Hs200 470r F
Sirvibc100doh9
Hs150 33r 5%(J)
Resistor Hs25 - 12,1 Ohm
Hs50
Hs50 10r 1%
Hs25 0r01 10%(K)
V5a 39r J
Hs 15 10kj
15 Ohm 200w -+5% Hs200 15 R J
V5 18r 5%(J)
Hs25-47rj, By Wd25 47r
Hs25 3k9 J
220274
000.000.220 Resistor
7cs 47r J
Hs25-22r-J
Ap851 25r J 100ppm
Fpa250 10r J
Hs 50 1kj
000.000.047
Hs300 1r8
220253
Acs10s 47r J
000.000.047 Resistor

[Hs150 150r F](#)

[Hs25 100r F](#)

[Msr1r005f](#)