

Argal



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Argal Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Argal Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
0890XMRO20367AG	
0ZMR2036WVD01NZ0	
6051-000	
6051-211	
6100-000	
TMA-01.16-N-WR-V-N1-B-E-N-3	
TMR 16.20P WR E R1 Z	
TMA G2 Self Priming Centrifugal	POS.24/8 O-RING 2 Pieces POS.4 FRONT THRUST BEARING 1 Piece POS.5 IMPELLER 1 Piece POS.6 Center disc 2 pcs POS.7 GUIDE BUSHING WITH FASTENER 2 Pieces POS.25 O-RING 1 Piece POS.29 Duct Casing 1 Piece
TMR-16.20-P-WR-V-R1-B-E-N-3	complete with flanged three-phase motor HORIZONTAL CENTRIFUGAL PUMP WITH MAGNETIC CLUTCH TMR SERIES, TMR TYPE - 16.20 - P (according to attached type description) complete with flanged three-phase motor Characteristic data: Medium: unknown Solids: none Working temperature: approx. 20 °C (assumed) Viscosity: max. 75 mPas Density: max. 1.35 kg/dm ³ Inlet pressure: max. 1.5 bar Desired flow rate: not defined Desired delivery height: not defined operating point Flow rate: see characteristic curve Delivery height: see characteristic curve
Double diaphragm pump 2" PPT	PP/PTFE Housing: PP (glass fiber reinforced) Diaphragms: TPC-ET + TFM (PTFE) Valve balls: PTFE Seals: FKM Valve seat: PP Air inlet: 3/4" BSP F Suction port: 2" ISO flange Discharge port: 2" ISO flange PNEUMATIC DOUBLE DIAPHRAGM PUMP SERIES 2" PLASTIC Characteristic data: Medium: unknown Solids: max. Ø 9 mm Working

	temperature: approx. 20 °C (assumed) Viscosity: max. 30,000 mPas Density: -- Flow rate: up to 715 l/min. Head: up to 80 m Ws Dry suction height: max. 4.5 m Ws Desired: Diaphragm pump 2" flange design
VERTICAL CENTRIFUGAL PUMP	SERIES B80 / KME Medium data: Funding medium: unknown Concentration: -- Density: max. 1.35 kg/dm ³ Medium temp.: approx. 20°C (assumed) Solids content: none grain size:-- Pump data: Type: KME-06.10-P-WR-E-N0-500-E-N-3-B0 Flow rate: not defined Funding level: not defined Immersion depth (dimension H): 500 mm Pressure connection: G 1 1/4 AG Suction connection: G 1 1/4 AG Operating temp.: max. + 70°C Ambient temp.: max. + 40°C Materials: Pump housing: PP/GF Impeller: PP/GF Engine bracket: PP/GF Shaft cover:PP Shaft guide/riser:PP Carrying plate:PP Engine bracket: PP/GF Gaskets: EPDM Plain bearing: PTFE/Al2O3 Three-phase motor: 0.75 kW ; 2900 rpm; 230/400V/50Hz; IP55
6000-032	Thrust ring in front TMR G2 - WR (R1-X1-N1), item 4
6000-041	Wheel TMR-16.20-WR, item 5
6000-105	positioning ring TMR G2-WR, item 6
6000-042	Bearing bush R version TMR G2, item 7
6000-044	O-Ring FPM TMR G2, Pos. 8 ***This article is subject to an export license in accordance with Annex II of Iran Regulation (EU) No. 267/2012. For exports from the European Union, the exporter must apply for an export license from the responsible authorities.
6000-046	containment shell TMR G2 - WR, item 9
6000-112	ISO flange pump inlet TMR G2, item 34
6000-113	Flange adapter pump inlet TMR G2, item 35
6999-999	magnetic drive (item 11)
İNLET FLANGE -ADAPTOR	Equipment (Pump):.....ARGAL BRAND PUMP, MODEL TMR16.20 P WR V R1 B E00 90L, 3KW 3000 RPM ENGINE Description:....İNLET FLANGE -ADAPTOR Ref No:.....35 Post No:727.1
DRIVE MAGNET ASSEMBLY	Equipment (Pump):.....ARGAL BRAND PUMP, MODEL TMR16.20 P WR V R1 B E00 90L, 3KW 3000 RPM ENGINE Description:....DRIVE MAGNET ASSEMBLY Ref No:.....11 Post No:.....855
HORIZONTAL CENTRIFUGAL PUMP SERIES TMA,	TYPE TMA - 01.16 Type TMA-01.16-S-WR-V-R1-B-E-N-3 Pump data: Pump housing: PP/GF Impeller: PP/GF Bearing: HD carbon Gasket: FPM Screws: stainless steel Pressure connection: G 3/4 Suction connection: G 3/4 Engine data: Power: 1.1KW Speed: 2950 rpm. Voltage / Frequency: 230/400V / 50Hz Degree of protection: IP 55 Operating data: Flow rate: max. 1.5 m ³ /h Delivery height: max. 22.5 m Conveying medium: not defined Solids content: none Medium temperature: approx. 20°C (assumed) Density: max. 1.8 kg/dm ³ Viscosity: Pump complete with flanged three-phase

	motor
Centrifugal Pump N. 102163	Ord No. 20-OV000735/5000 TMAA01.16 S WR V RI B EN 3 KW 1,1
P/N:DDE 060 WRN DDPDGLL	
B80/KGK G1	B 80 KGK C 50-200 FC Vertical centrifugal pump Media data: Medium: unknown Density: not closer defined Liquid temperature: not closer defined Share of solids: --- Particle size: ---- Pump data: Type: B 80 KGK C 50/200 FC E N 1500 VR- 4P-4kW Delivery rate: acc. to performance curve Delivery head: acc. to performance curve Immersion depth (size H): 1500 mm Strainer (size P): 55 mm Total length (size H+P): 1555 mm Type of impeller: closed Discharge: DN100 Liquid temperature depending on the immersion depth in °C: max. 70 °C Ambient temperature: 0 until + 40°C Materials: Housing:PVDF/CF Impeller:PVDF/CF Shaft sleeve:PTFE Shaft guide / lifting tube: PVDF Base plate:PP Sealings:EPDM Bearing:Keramik/PTFE Three-phase motor: 4,0 kW, 1450 U/min , 230/400 V , 50 Hz , ISO F pump complete with flanged motor
DDA 125 WR MT TPVG 2 0 – double diagram	
Centrifugal Pump N. 102163	Ord No. 20-OV000735/5000 TMAA01.16 S WR V R1 B EN 3 KW 1,1
0DDE100ALNYTAVGLL	DDE 100 ALN Y T A V G L L
1DDE100ALNYTAVK3	KIT K3 DDE 100 ALN Y T A V
6102194220PPV6G0	POS.3 VOLUTE CASING
5233197820PPV6GV	POS. 5.B IMPELLER
Centrifugal Pump	TMR16.15N GF VR2BEN3 KW 1,5 PERFORMANCE RPM2900 Flow rate m3/h 13,5 TDH rated m 17,6 Motor power 1,50
0DDE060SPNYTSTCLL	DDE 060 SPN Y T S T C L L
0DDE160SPNYTSTCLL	DDE 160 SPN Y T S T C L L
40/125 WRD 137 Pump	
08004j0025aava0	
Kgk A 40/120	
0tmp0608gvrn1pg0	
Gvrn1pg0	
Kgka40/120wren0vr0	
0tmr0230wes01pz0	
0kme1010wvaw1pg0	

Km 25/100 Wr
0kgka412wea4f1i
Kg 50/125
Tmf32/160n Ww V T
Tmr 02.30p Wre
0tmf0316wvtngni
Z50-Torri
Tmf32/160 N Ww V T
Kqk A40/120
Km 25/100 Wr + Motore