

Banner

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Banner Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Banner Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
DX80N2X6S-PM2	3087105 Radio transmission system point-to-point node External antenna (connection RG58 RP-SMA) Integrated signal strength display Configuration via DIP switch Inputs: 4 x PNP, 2 x 0..20 mA Outputs: 4 x PNP, 2 x 0... 20 mA Power consumption: & lt; 60 mA at 24 VDC Deterministic data transmission Frequency hopping FHSS time division multiplexing TDMA Transmission power: 63 mW, 18 dBm conducted, ≤ 20 dBm EIRP max.range: 3200 m
DX80G2M6S-PM2	3087097 Radio transmission system Point-to-point Gateway External antenna (connection RG58 RP-SMA) Integrated signal strength indicator Configuration via DIP switch Inputs: 4 x PNP, 2 x 0..20 mA Outputs: 4 x PNP, 2 x 0... 20 mA Power Consumption: & lt; 60 mA at 24 VDC Modbus RTU communication, RS485 interface Deterministic data transfer Frequency hopping FHSS Time division multiplexing TDMA Transmission power: 63 mW, 18 dBm conducted, ≤ 20 dBm EIRP max.range: 3200 m
SM312LVMHS	Opto-Sensor 3026200 Reflective light barrier cable, PVC, 2 m Protection class IP67 Operating voltage: 10... 30 VDC Bipolar switching output light / dark switching Connection line, 2 m

	maximum range: 300 mm Reduced response time of 0.3 ms, maximum range: 5000 mm
RKC4.5T-10/TXL	Actuator and sensor cable / PUR 6625508 Connecting cable M12 coupling, straight, 5-pin Cable length: 10 meters Sheath material: PUR Sheath color: black Suitable for drag chains Resistant to chemicals, UV and oil Flame retardant (FT2 according to UL 1581, IEC 60332-2-2) Halogen, silicone, PVC and PWIS-free Particularly abrasion resistant Approval: cULus RoHS Compliant Degree of protection: IP67, IP69K
Banner Pulse Pro I/O	
QS18VP6LAFQ5	3073191 Opto-sensor laser diffuse reflection sensor with adjustable background suppression max. range 150 mm cable length 0.15 m cable with connector, PVC, 150 mm, M12 x 1, 4-pin protection class IP67 LED visible from all sides suppression limit adjustable via potentiometer operating voltage: 10...30 VDC PNP- Switching output, changeover
SLM10P6Q	3074966 opto sensor forked light barrier max reach 10mm Male M8x1 Degree of protection IP67 Sensitivity adjustment via potentiometer Operating voltage: 10...30 VDC PNP switching output, light or dark switching
PKG3M-5/TEL	6625059 Actuator and sensor cable / PVC connecting cable cable length 5 m M8 coupling, straight, 3-pin Sheath material: PVC Sheath colour: black Chemical and oil resistant flame retardant Resistant to acids and alkalis Resistant to microbes and hydrolysis PWIS-free Approval: cULus RoHS Compliant Degree of protection: IP67, IP69K Line length: 5.0 meters
REI-43H42S-2B2500-H1181	100011488 Incremental rotary encoder Industrial Line Resolution incremental 2500 ppr Flange without fastener, Ø 100mm Hollow shaft, Ø 42mm Optical measuring principle Shaft material: stainless steel Degree of protection IP 65 on housing and shaft -40 ... +80°C max. 6000 rpm (at 60°C: 2500 rpm) 10...30Vdc
RKC8T-2/TXL	6625142 Actuator and sensor cable / PUR Connecting cable Cable length 2 m M12 socket, straight, 8-pin Sheath material: PUR Sheath color: black Suitable for drag chains Chemical, UV and oil resistant Flame retardant (FT2 according to UL 1581, IEC 60332-2-2) Resistant to welding sparks Free of halogen, silicone, PVC and PWIS Particularly abrasion-resistant Approval: cULus RoHS-compliant Degree of protection: IP67, IP69K Line length: 2.0 meters
778-BMEL632A	MFR PN: BMEL632A
TL50HGYRQ	High Intensity Tower Banner Engineering Tower Lights
QT50ULBQ6	QT50U Analog Series: Banner Engineering Proximity Sensors
Ledrla290ad6-Xq	
	Opto sensor Proximity switch Plug, M12 x 1, 4-pin Degree of protection IP67 Operating voltage: 10 ... 30 VDC PNP switching output, changeover contact LED visible all around

Qs18vp6dq8	Sensitivity adjustment via potentiometer Max. Range: 450 mm Warentarif-Nr.:85365019 Country of Origin: CN EAN: 662488664602 Material group: F3 Weight: 0,022KG
Bmrl1232a	
Q45uliu64acr	
Lx3rz	
Su923qd	
Mqdc-406	
M18tb8q	
3tf5244-1x	
Q45bw13dxq	
Mbcc-306	
Slsp14-1060q88	
TI50blq2y2r2alsq	
Q45bb6lv	
Sm30srl	
Beh58-12s6r-1500-Eq	
Lx3eq-72470	
3086527	
Stecker Mit Kabel Mqdc-430ra	
Sm312lvagqd	
Wls28-2xw28sxmq	
S18sp6lp	
Q45bb6r	
70885	
Ls2k30-1650q88-1re15	
Ea5e300q	
Qs186leq8	
L16f	
Pd45vp6llpq	
Sma91eqd	

Lt3pilvq
Wlb32zc850pbqmb
3tf5433-1xm4
Otc-1-Bk
Smb30mm
1020002300
Lx6rq
Smu315lv
D11sp6fpq
Dee2r-81d
Slm50p6q
Qs18vn6lp
Q406eq
Qs18vn6r-Wlk
Ls2tr30-600q8
Sop-E12-150ss
Smb30sc
Mqdc415ra
Sm312wqd
T30sp6ff400w30
Qs18vp6llp
Qt50rck
72393
Qt50r-Eu-Afsq
3071743
Cl50gryp
Sma30sel
Sm312cvqd
K50lgryp
It230sm900
Otbvp6qd

Sa-M30te12
Qs186leq5
Qs30ff600q
Pd45vn6c100
Qs18vpsrq8
Q456e
Sbrxf1
Qt50r-Eu-Afhq
Mqdc-430ra
Mbcc-406
D10afpy
T18sn6ff50q
Qs18vn6ldq8
Q40sp6rq
T30sp6ff400q
T18vp6ur
K50aplpqxdqp
Q60bb6laf2000q
Mqdec2-550
Brt-Thg-1-100
Vs1an5c10-80653
M18tup6eq
T18sp6ff50q
Imltf12
Brt-51x51x51bm
Pvd100q
Mqd9406ra
Lx6eq
Qs18vp6rq8
Lm3

Pba
Ea5e2100q
Qs30ff200q
Ea5r2100pixmodq
Eza-Te-1800
Stbvp6q5
Dx99n2x1s2n0m2x0d1
T30uv
Mqvr3s-515ra
Otbvp6qdh
Wls28xw990xq
Pba-1
3tf5244-0x
Nv5-Q08-An7v1131
Uc Ls4rl
Brt-40x19a
Ls2e30-600q8
TI50blgyrq
D12ep6fp
Ea5r300pixmodq
Sbexf
3033395
T18aw3r
CI50zra
Ls10eqdh
Cs-A2-02-G-10
T18sp6ff100q
1020002200
No5-Q-08-Ap7
Wlb32zc570pbqmb

Sl10vb6v
PvI225p
R58ecrgb1q Dc10-30v
3tf5433-0x
TI50zgyr
CI50zrac
Maci-1
V1-G-5m-Pur
Sm312lvqd
Pvd100
Bmre1232
Miad9lvagg