

Baumer Thalheim

Garanti: 12 ay
Bu ürüne ait Türkiye
içi kapı teslim fiyat
ve teslim süresi
içeren teklifimizi
almak için
info@yursat.com.tr
e-posta adresine
başvuru yapabilir ya
da ayrıntılı bilgi için
+90 224 240 03 04
numaralı
telefonumuzdan
bizlere
ulaşabilirsiniz.
Baumer Thalheim
Markası, tedarik
süresi için lütfen
bizimle iletişime
geçiniz.

*Firmamız Baumer Thalheim
Türkiye Distribütörü veya
temsilcisi değildir. Firmamız
sipariş durumunda,
belirtilen ürünlerde sadece
Orjinal ve yeni ürün teklifi
sunmaktadır. Bu sitede
gösterilen Özel marka adları
ve ticari markalar ilgili
sahiplerinin
mülkiyetindedir, talep
durumunda
kaldırılmaktadır.*



Ürün	Açıklama
Ktd-3-2a4 Y36	
Eil580p-Tt10.5rf.01024.B-11127688	Materialnr 11127688 Product information incremental rotary encoder EIL580P, programmable EIL580P Installation size Ø58 mm Shaft type Through hollow shaft T Flange (hollow shaft) With stator coupling ø63 mm T Through hollow shaft ø10 mm, clamping ring A-side 10 Protection class IP 65 5 Radial connection cable, 1 m R Operating voltage / output 4.75 ... 30 VDC, TTL / RS422, 6 channel (Vout = 5V) F. Pulses per revolution 01024 Operating temperature -40 ... + 100 ° C B.
Eil580-Tt12.7fn.01024.A-11115128	Materialnr 11115128 Product information Incremental rotary encoder EIL580 EIL580 Installation size Ø58 mm Shaft type Through hollow shaft T Flange (hollow shaft) With stator coupling ø63 mm T Through hollow shaft ø12 mm, clamping ring A-side 12 Protection class IP 67 7 Radial flange socket connection, M23, 12-pin, pin contacts, CCW F. Operating voltage / output 8 ... 30 VDC, HTL / push-pull, 6 channel N Pulses per revolution 01024 Operating temperature -40 ... + 85 ° C A Total weight: 1,530Kg
ITD 21 B14 5000 T NI KR1 S 6 IP65	Materialnr 11059121 Rotary encoder 5000 pulses / revolution IP65 A, B, N track + inversion TTL UB = 5 VDC ± 5% LD output stage Connection cable: 1.00 m, radial Shaft: 6.00mm 90318020 DE
	Origin European Community / Union (Germany - DE - Hesse) Customs tariff number 90318020 Product information incremental rotary encoder EIL580 EIL580 Installation size Ø58 mm Shaft type Through hollow shaft T Flange (hollow shaft) With stator coupling ø63 mm T Through hollow

EIL580-TT12.7FN.01024.A-11115128	shaft ø12 mm, clamping ring A-side 12 Protection class IP 67 7 Radial flange socket connection, M23, 12-pin, pin contacts, CCW F. Operating voltage / output 8 ... 30 VDC, HTL / push-pull, 6 channel N Pulses per revolution 01024 Operating temperature -40 ... + 85 ° C A
Stecker S2BG12 Bu 12pol rdEMV	Customs tariff number 85366990 Connector S2BG12 Socket contacts 12-pin for cable diameter 5-10 mm
EIL580P-SY06.5RF.01024.B-11121855	Materialnr 11121855
ITD 40 B10 1024 H NI KR2 S 11 IP65	Materialnr 11062273 Rotary encoder 1024 pulses / revolution A, B, N track + inversion HTL UB = 8 - 30 VDC GT output stage Connection cable: 2.00 m radial Shaft: Ø11 mm Degree of protection: IP65 Temperature range: -20 ... + 70 ° C
Attachment kit ITD 2. A 4 Y010 / Y015 V1	Material no. 11068155 consists: 1x 40811 1x 510358 1x 510239 3x 501042
Coupling CPS37 K / K L = 24-15 / 06	Material no. 11069573 Divisible, torsionally rigid coupling with a small overall depth Bore d1: Ø15 mm Bore d2: Ø6 mm Length: 24mm Diameter: Ø37 mm
ITD 40 A 4 Y97 1024 H NI H2SK12 S 25	Materialnr 11060916 Rotary encoder 1024 pulses / rev. IP 66/65 A, B, N track + inversion HTL UB = 8 - 30 VDC GT output stage Connection cable: 0.60 m radial Bore: 25.00 mm through H2SK12 assembled on the cable Mounting kit: 50 assembled ! Suitable for V3 attachment. ! Mounting kit: 50 Weight: 0.715 kg
EIL580-BT14.5LN.01024.A-11124271	Product information incremental rotary encoder EIL580 EIL580 Size Ø58 mm Shaft type Blind hollow shaft B Flange (hollow shaft) With stator coupling ø63 mm T Blind hollow shaft ø14 mm, clamping ring A-side 14 Degree of protection IP 65 5 Connection cable radial, 2 m L Operating voltage / output 8...30 VDC, HTL/push-pull, 6 channel N Pulses per revolution 01024
TD41AY702000	
1024HNIKRS IP65	
ITD 40 A 4 Y114 512 H BX KR1,5 S 20	Materialnr 11061626 Encoder 512 pulses/revolution A, B track HTL UB= 8 - 30 VDC GT output stage Connection cable: 1.50 m, radial Bore: Ø20 mm continuous with keyway 6J9 mm Degree of protection: IP54 Fastening set 006 enclosed loose Temperature range -20...+70 °C
Shaft Encoder D-37269	
ITD 40 A 4 Y97 1024 H NI H2SK12 S 25	11060916 encoder 1024 pulses/rev. IP 66/65 A, B, N track + inversion HTL UB= 8 - 30 VDC GT output stage Connection cable: 0.60 m radial Bore: 25.00mm through H2SK12 assembled on the cable Fastening kit: 50 assembled ! Suitable for V3 attachment. ! Fastening set : 50
ITD 20 A 4 Y107 88 H BX D1SA7 S 10	11061148 encoder 88 pulses/revolution, IP54 A, B track HTL UB= 8 - 30 VDC GT output stage Connection M16 - 7-pin, axial Bore: Ø10 mm open on one side Fastening set 039 Temp. range -20...+70 °C
Fastening set 012	11066262 consisting of: 1 x torque arm I 25x28 d5.5 LL 2x pan head screw (DIN 7985) M3x6 TX10
ITD 40 B10 1024 H NI KR2 S 11 IP65	11062273 Rotary encoder 1024 pulses/revolution A, B, N track + inversion HTL UB= 8 - 30 VDC GT power amplifier Connection cable: 2.00 m radial Shaft: Ø11 mm Protection class: IP65 Temperature range: -20...+70 °C
S2bg12	
1699168	
ItD 22 A 4 Y82 2048 - Obsolete,Alternative Is Art Nr. 11062930 , Type Itd22h00 2048 M Ni S21sg8 F 14 Ip54 021 + Art. Nr. 11071188 ,	

Type Fs A-Kabel Mg	
ItD 40 A 4 Y 1 1024 H Ni D2sr12 E 10	
Kdt 3-2 A4	
IId3a 4y18 1024 H Ni Kr1s 15 Ip65 Anr.311546	
ItD 40 B14 Y28 1000 T Ni D2sr1r S 10 Ip66	
ItD480b101024 Hmi Kr2 S11 Mdf-2	
ItD 21 A 4 Y29 1024 H Ni D2sr12 S 12 (11059801)	
Ktd50-6b10y1 Obsolete, Replacement Tdp0,2 Lt-4 B10 55	
D-37269 ItD 41 A 4 Y70	
Rieter Rsb-D 40	DETAILED IMAGE ATTACHED TO MAIL
ItD + Ktd 3 – 3 B10 S12 Hni S11 Ip54 / Enkoder+takogenerator	
ItD21h00 2048 T Ni S21sg8 F 14 Ip54	
ItD21a4y821024tnikr1f14ip5421	
ItD 40 A 4 Y140 1024 H Ni Vr16 S 12	
ItD22h00 2048 M Ni S21sg8 E 14 Ip65	
Lgb-002-100	
ItD 41 B10 5000 Tni Kr1.50	
ItD 22 A4 Y82 2048 Mp3 Kr1 E14 Ip54 21	
Td 3 A 4 Ka Em	
I-D-P 01 (Siehe Anhang)	ENCODER
ItD 40 A 4 Y 2 1024 H Ni Kr1 S 16	
1638054	
ItD 21 A 4 Y82 2048 T Ni Kr1 F 14 Ip54 21	
ItD 40 B10 Y 2 1024 H Ni Vr16 S 11 Ip65	
ItD01a4y41024tbxk10 Sk4 S4ip64 102	
Td41a4y702000hbx1sr7s30ip5450	
Td 3 A 4 Ka Rm	
Ktd 50-6-B10	
ItD 20 A 4 Y50 88 H Bx D1sa7 S 10 Ip54 12	
Fs A-Kabel	
D-37269 ItD A4 Y21 2048 T Ni Kr5 E12ip65 02	
ItD 22 A4 Y82 2048 M P3 Kr1 E14 Ip54 21- Obsolete, Next Model Is ItD 22 A 4 Y82 2048 M Ni Kr1 F 14	
Ktd-3-2b10	
Fs A-Kabel Mg02 K21bg8/A 65-SI Nio-01000	

It21a4y29	
It40a4-2048h-Ni-Kr1-E14	
It21a4y58 2048t	
1643070	
It20 A 4 Y50 88 H Bx D1sa7 S 10	
11126235	
11066120	
It41a4-2048h-Ni-Kr1-E10	
Fs A-Kabel Sw10 K21bg8/A 65-SI Nlo-01000	
Td3a4alkm	
48331	
It01ay41024tbxk10sk4s4	
I-D-A-01	SIEHE ANHANG
Ktd-3-1-A4-15mm-Oswald19110	
8-30 Vdc 6 Mm It21 B14 1024 H Ni Kr1 S 6	
11101781	