

Bk Precision

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Bk Precision Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Bk Precision Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Bk8540	ELEKTRONISCHE DC-LAST, 60V, 30A, 150W
BK 8540	
545	TESTER
2160a Cal D	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60, ROHS COMPLIANT: NA
9151	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:20V, OUTP
2190b Cal Du	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:1
8540cald	PROG DC ELECTRONIC LOAD 60V 150W, DC LOAD TYPE:FIXED, OPERATING VOLTAGE RANGE:0V
2160a	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:60MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI

9173	POWER SUPPLY, PROGRAMMABLE, 2 O/P, 0-20V, 5A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE
8514	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, PRODUCT RANGE:8500 SERIES, POWER RATING:1200W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERAT
8520	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:120V, OPERATING CURRENT MAX:240
Vsp4030	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:40V, OUTPUT CURRENT:30A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
889bcald	BENCH LCR/ESR METER WITH COMPONENT TEST, EXTERNAL HEIGHT:150MM, EXTERNAL WIDTH:2
8522	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:500V, OPERATING CURRENT MAX:120
8500refurb	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE RANGE:0.1V TO 120V, OPERATING CURRENT RANGE:30A, POWER RATING:300W, EXT
1443	OSCILLOSCOPE
4040acal	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION
9171	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-20V, 5A, 100W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE
1541b	OSCILLOSCOPE
2540	DIGITAL STORAGE OSCILLOSCOPE, SCOPE BANDWIDTH:60 MHZ, SCOPE CHANNELS:2, SCOPE TYPE:DIGITAL, SERIES:254X SERIES, RISE TIME:5.83NS, SAMPLE RATE:1 GSA/S
2160a Cal Du	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60
2658a	ANALYZER, SPECTRUM, 50KHZ TO 8.5GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 8.5GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
9123a	POWER SUPPLY, BENCH, 30V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT

CURRENT	
886cald	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4
Xln10014	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:100V, OUTPUT CUR
2692a0s2	AMPLIFIER
Xln6024cal	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
Bk2530b	OSCILLOSCOPE, DIGITAL, 2X25MHZ, 500MS/S, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:25MHZ, METER DISPLAY TYPE:TFT, SAMPLING RATE:500MSPS, INPUT IMP
1823acald	FREQUENCY COUNTER, 2.4GHZ, 8 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:DATA HOLD / FREQUENCY / PERIOD / RATIO / REMOTE SELF TEST / START-STOP / TIME IN
Xln6024-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT CURR
Pr261	SNIFTER PROBE SET, TEST PROBE FUNCTIONS:FREQUENCY, FOR USE WITH:BK PRECISION 2615A, 2620A, 2625 AND 2630 SERIES SPECTRUM ANALYZER, ROHS COMPLIANT: NA
2522c	OSCILLOSCOPE, 20MHZ, 2 CHANNEL, 40MSPS, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:20MHZ, METER DISPLAY TYPE:CRT COLOUR, SAMPLING RATE:40M
1673cal	1673 CALIBRATED
8514cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
2522bcal	20 MHZ-10MS/S DSO W/2 PROBES
9115	POWER SUPPLY, BENCH, AC-DC, 0-80V, 60A, 1.2KW, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX
886caldu	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4
2522bcaldu	20 MHZ-10MS/S DSO W/2 PROBES
1745acald	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP, ROHS COMPLIANT: NA
	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-70V, 1.5A, 105W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF

9172	OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLT
Pr26m	TEST PROBE, TEST PROBE FUNCTIONS:ELECTROMAGNETIC FIELD, FOR USE WITH:B K PRECISION 2650A SERIES HAND HELD SPECTRUM ANALYSERS, PRODUCT RANGE:-, PROBE
1541d Cal	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:40
1790cal	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
2630cal	CALIBRATION WITH CERTS BK P/N 2630 SKU # 52F6288
2125	OSCILLOSCOPE
2652a	ANALYZER, SPECTRUM, 50KHZ TO 3.3GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 3.3GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
4079	WAVEFORM GENERATOR ARB / FUNCTION, 50MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1260	VIDEO TEST INS
9185	POWER SUPPLY, PROGRAMMABLE, 0-600V, 350MA, 210W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE M
1745acaldu	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
Vsp12010	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:120V, OUTPUT CURRENT:10A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950
8502cal	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
4084awg	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V
2658cal	POWER QUALITY ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RA
9182	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-20V, 10A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:
570	TESTER
1791	POWER SUPPLY, BENCH, 64V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:64VDC, OUTPUT CURRENT:10A, POWER RATING:640W, IN

Xln10014-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:100V, OUTPUT CUR
1760acal	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUT
Xln6024cald	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
2190b Cal	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:1
2125a Cal	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
1422	OSCILLOSCOPE 20MHZ
8500caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8510caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1760acald	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:3 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT C
4085	FUNCTION GENERATOR FREQUENCY/PULSE 40MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
8500cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
Vsp6020gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60V, OUTPUT CURRENT:20A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
4075gpib	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
490	TUBE TESTER/ANALYZER
2658caldu	POWER QUALITY ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RA
4040acald	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION, ROHS COMPLIANT: NA
9152	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30
	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY

1790	OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32VDC, OUTPUT CURRENT:20A, POWER RATING:640W, IN
540	TESTER
Vsp2050	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:50A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
Xln8018-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:80VDC, OUTPUT CURRENT:18A, POWER RATING:1.44KW, IN
490b	ANALYZER REJUVENATOR 1/.5AMP 6.3/12V
Xln3640	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:36V, OUTPUT CURR
1790caldu	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
2650a	ANALYZER, SPECTRUM, 50KHZ TO 3.3GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 3.3GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
1657	POWER SUPPLY, AC, 135VAC / 270VAC, 1.5KVA, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:270VRMS, OUTPUT CURRENT:6ARMS, POWER RATIN
8524	PROGRAMMABLE DC ELECTRONIC LOAD 60V 5KW, PRODUCT RANGE:8500 SERIES, POWER RATING:5000W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2522bcald	20 MHZ-10MS/S DSO W/2 PROBES, ROHS COMPLIANT: NA
8510cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8502	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:500V, OPERATING CURRENT MAX:15A
4084	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
4084caldu	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULA
205	VOLTAGE-CONTINUITY TESTER ROHS COMPLIANT: NA
4040acaldu	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION

2120bcald	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30, ROHS COMPLIANT: NA
9130cal	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
4084awgcald	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ,CALIBRATEDW/ DATA
4034	SIGNAL GENERATOR, PULSE, 50MHZ, PRODUCT RANGE:-, NO. OF CHANNELS:1 CHANNEL, SIGNAL GENERATOR TYPE:PULSE, BANDWIDTH:50MHZ, SIGNAL GENERATOR MODULATION:
9130cald	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
1823acaldu	FREQUENCY COUNTER, 2.4GHZ, 8 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY
866b	DEVICE PROGRAMMER, IC PRODUCT TYPE:PROGRAMMER, UNIVERSAL, IC INTERFACE TYPE:PARALLEL, USB, NO. OF DEVICES SUPPORTED:41699, FEATURES:CONNECTOR FOR IN-C
4076	WAVEFORM GENERATOR ARB / FUNCTION, 50MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1476	OSCILLOSCOPE BENCH 10MHZ
3026	FUNCTION GNRTR
8540caldu	PROG DC ELECTRONIC LOAD 60V 150W, DC LOAD TYPE:FIXED, OPERATING VOLTAGE RANGE:0V
4033	SIGNAL GENERATOR, PULSE, 50MHZ, PRODUCT RANGE:-, NO. OF CHANNELS:1 CHANNEL, SIGNAL GENERATOR TYPE:PULSE, BANDWIDTH:50MHZ, SIGNAL GENERATOR MODULATION:
560a	CIRCUIT CARD
8526	PROGRAMMABLE DC ELECTRONIC LOAD 500V 5KW, PRODUCT RANGE:8500 SERIES, POWER RATING:5000W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERAT
2650caldu	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5
Vsp6020	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60V, OUTPUT CURRENT:20A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
1045a	TESTER
4079refurb	BK 4079 REFURBISHED BY NEWARK
	SPECTRUM ANALYZER, ANALYZER POWER SUPPLY:BATTERY/DC, BANDWIDTH MAX:3.3GHZ,

2650	BANDWIDTH MIN.:50KHZ, SPECTRUM ANALYZER TYPE:HAND HELD ROHS COMPLIANT: NA
1541d Cal Du	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:40
1794	POWER SUPPLY, LINEAR, 32V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32VDC, OUTPUT CURRENT:30A, INPUT VOLTAGE:115VAC, LOAD
2640	FIELD STRENGTH METER 2GHZ -45 TO -110DBM, FREQUENCY MEASURING RANGE:100KHZ TO 2GHZ, AMPLITUDE ACCURACY: 3DB, CONNECTOR TYPE:N COAXIAL, EXTERNAL HEIGHT
2522a	OSCILLOSCOPE
4075	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1541d	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:40MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI
2160a Cal	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60
2160	OSCILLOSCOPE
4011acaldu	FUNCTION GENERATOR FREQUENCY/PULSE, 5MHZ, SIGNAL GENERATOR TYPE:FUNCTION, SUPPLY
2540b-Gen	OSCILLOSCOPE, DIGITAL, 2CH, 60MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:60MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMORY
4084awgcaldu	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ,CALIBRATED W/ DATA + UNCERT
1652caldu	TRIPLE OUTPUT DIGITAL DISPLAY DC POWER SUPPLY
8514caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
2650cal	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5
Xln6024	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT CURR
1747	POWER SUPPLY, DC, 60V, 5A, 560VA, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT

4040	FUNCTION GENERATOR
Vsp12010odi	POWER SUPPLY
4078	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1541dcald	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:40MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI
8510	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, PRODUCT RANGE:8500 SERIES, POWER RATING:600W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2120bcal	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
8518	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 60V, PRODUCT RANGE:8500 SERIES, POWER RATING:1200W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2658	POWER QUALITY ANALYZER, ANALYZER POWER SUPPLY:BATTERY/DC, BANDWIDTH MAX:8.5GHZ, SPECTRUM ANALYZER TYPE:HAND HELD ROHS COMPLIANT: NA
2542b-Gen	OSCILLOSCOPE, DIGITAL, 2CH, 100MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:100MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMOR
8510cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
9150	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:5.
2542	DIGITAL STORAGE OSCILLOSCOPE, SCOPE BANDWIDTH:100 MHZ, SCOPE CHANNELS:2, SCOPE TYPE:DIGITAL, SERIES:254X SERIES, RISE TIME:3.5NS, SAMPLE RATE:1 GSA/S
1251	VIDEO TEST INS
4078gpib	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
2650cald	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5, ROHS COMPLIANT: NA
4012acaldu	SWEEP FUNCTION GENERATOR FREQ/PULSE 5MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION

2190b	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:100MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM
2542b	OSCILLOSCOPE, 2-CHAN, 100MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 DIGITAL, BANDWIDTH:100MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMORY DEPTH
866c	PROGRAMMER, EPROM, USB INTERFACE, SUPPORTED FAMILIES:-, KIT CONTENTS:-, FEATURES:FAST AND HIGH PERFORMANCE, POWERFUL PROGRAM SOFTWARE, SUPPORTS WINDOW
4084cald	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULA
8502cald	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1760acaldu	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUT
Xln3640-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:36V, OUTPUT CURR
2534	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, 400MSPS, SCOPE TYPE:DIGITAL, SCOPE CHANNELS:2, BANDWIDTH:60MHZ, METER DISPLAY TYPE:LCD COLOR, SAMPLING RATE:400MSPS, I
9174	POWER SUPPLY, PROGRAMMABLE, 2 O/P, 0-70V, 1.5A, 210W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLT
Xln8018	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:80V, OUTPUT CURR
1856dcald	FREQUENCY COUNTER, 3.5GHZ, 9 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY, ROHS COMPLIANT: NA
Xln6024caldu	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
2120bcaldu	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
2658cald	8.5GHZ SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HANDHELD, FREQUENCY MEASURING RANGE:50KHZ TO 8.5GHZ, ROHS COMPLIANT: NA
886cal	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4

8522refurb	8522 REFURBISHED
8502caldu	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8514cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1745acal	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
1249a	VIDEO TEST INS
1050	TESTER
1476a	OSCILLISCOPE 10MHZ 2CHANNEL
9181	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-36V, 4A, 144W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE
4045	SWEEP FUNCTION GENERATOR, ARB, 20MHZ, SIGNAL GENERATOR TYPE:DDS, MODULATION TYPE:AM / FM, SUPPLY VOLTAGE RANGE:90V TO 264V, EXTERNAL HEIGHT:88MM, EXTENSION
4086awg	SIGNAL GENERATOR, ARB / FUNCTION, 80MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V
1673caldu	1673 CALIBRATED W/ DATA + UNCERT
Vsp2050-Refurb	POWER SUPPLY, BENCH, 20V, 1.2KW, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20VDC, OUTPUT CURRENT:50A, POWER RATING:1.2KW
2125a Cal D	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30, ROHS COMPLIANT: NA
Vsp2050gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:50A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
9184	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-200V, 1A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE
9153	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60VDC, OUTPUT CURRENT:9A, LOAD REGULATION
1673cald	1673 CALIBRATED W/ DATA
2630	ANALYZER, SPECTRUM, 0.15MHZ TO 1.05GHZ, SPECTRUM ANALYZER TYPE:BENCH, FREQUENCY MEASURING

	RANGE:150KHZ TO 1.05GHZ, EXTERNAL HEIGHT:125MM, EXTERNAL WID
9130caldu	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
4086	FUNCTION GENERATOR FREQUENCY/PULSE 80MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
4087	FUNCTION GENERATOR, FREQ / PULSE, 120MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
1795	POWER SUPPLY, LINEAR, 64V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:64VDC, OUTPUT CURRENT:15A, INPUT VOLTAGE:115VAC, LOAD
1856dcaldu	FREQUENCY COUNTER, 3.5GHZ, 9 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY
Vsp4030gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:40V, OUTPUT CURRENT:30A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
2125a Cal Du	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
859	UNIVERSAL, SUPPORTED FAMILIES:WINDOWS 98/ME/NT/2000/XP/2003/XPX64/VISTA, SUPPORTED DEVICES:PC BA
8500cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R