



Blickle

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Blickle Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Blickle Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Lk-Poev 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Heavy duty wheel with elastic solid rubber tires 'Blickle EasyRoll', with Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: black Tread / tires: Made of high-quality elastic solid rubber in smooth running quality 'Blickle EasyRoll'. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Vulcanised tire. Base hardness: 65 ° Shore A Wheel Ø: 125 mm Tire width: 40 mm Load capacity: 250 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 80 ° C
Lk-Poth 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Wheel with thermoplastic polyurethane tread, with heavy Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: dark gray Tread / Tire: Made of high quality, thermoplastic polyurethane. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Base hardness: 94 ° Shore A Wheel Ø: 125 mm Wheel width: 40 mm Load capacity: 350 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 70 ° C
	Heavy-duty flange wheel with Blickle polyurethane tread Softhane®, with cast wheel center Technical specifications: • Wheel Ø: 200 mm, wheel width: 50 mm, load capacity at 4

GSTA 200/4	km / h: 700 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, hole circle Ø: 100 mm Tread: • high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A. • Very high driving comfort thanks to particularly thick, elastic tread • very gentle on the floor, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical bond with the wheel center
101323	
102554	
102556	
106636	
123584	
125/ 15Ê	
137904	
137905	
150131	
150749	
263541	
267302	
577361	
605063	
620989	
850265	
850415	
913866	
ALTH 125/15 K	
ALTH 200	
ALTH 200x50/20-40K	
B-ALST 125K	
B-G 80G	
BH-ALBS 200K	
BH-ALST 100K-3	

BH-ALST 160K - 579557
BH-ALTH-101K-1 (284307)
BH-POEV 160K
BH-SETH 200K
BO-GTH 150K
B-PATH 200R
BPA-TPA 50G
B-PHN 200G
B-POEV 160K
B-RD 162R-VLI
BS-GB 160K
B-V 162R
B-V 202R
B-VE 200R
B-VEHI 125R
B-VPP 160R
FSTH 50X18/17-10K
FTH 52x15/12-12K
F-ZP 125R-F
GB 150/20-50K
GB 152/25K
GB 250/25K
GBN 202/35H7
GSPO 80/20K
GSTN 150/25H7 (754394)
GTH 200/25K
GTHN 200/30H7
GTHN 251/40H7
GTHN 252/40H7
HPO 82X70/20-70K

HRP-POA 63G
HRSP-POA 72G
JPPR 1001 5100
L -RD 202R
L-ALEV 125K-FI
L-ALEV 200K-SG
L-ALST 125K-FI
L-ALST 160K-FI
L-ALST 200K-FI
L-ALST 80K-FI
L-ALTH 100 K FI
L-ALTH 150K
L-ALTH 150K-FI
L-ALTH 150K-FL
L-alth 80K-as
LE-PATH 200R-FI
LE-POEV 160K-FI
LER-VE 100R
LE-VE 200R-FI
LEX-PO 125KD-FI
LEZ-PO 75G-FI
LH-ALBS 160K
LH-ALST 200K
LH-GB 200K
LH-GB 200K-FI
LH-SE 202K-ST-SG
LH-SETH 200K-FI
LH-SPO 175G-FI
LI PHN 102 G
LI-PHN 200G
LK-ALBS 100K-1-FI

LK-ALBS 200K-FI
LK-ALST 100K-1-FI
LK-ALST 160K
LK-ALST-160K-FI 627034
LK-ALTH 80K-FI
LK-G125G-1
LK-POEV 160K
LKR-ALTH 100K-FI-AS
LKR-ALTH 125K
LO-ALTH 250K
LO-GTH 150K
LPA-PATH 50 G-FI
L-PATH 80G-FI
LPA-TPA 100G-FI-ELS
L-POEV 100 K FI
L-POEV 100K
L-POEV 1250K-FI
L-POEV 80K-FI
L-PTH 200R
LRA-TPA 75K-FK-GS10
LRA-TPA75K-FI-FK
LRA-TPA75K-FK
LRA-VPA 50 G FI
LRA-VPA 50 G-ES
LRA-VPA 75K-FA
L-RD 162-Fi-VLI
L-RD125R-FI
LSD-GB 302K-RAH-RI4H
LSD-GTH 302K-RI4H
LSD-GTH-100K

LSD-SE-300K
LS-GB 160K-ST
LS-GB 160K-ST-RI4
LS-GSPO 152K-35
LS-GTH 300K-ST
LS-SETH 125K
L-V 125R
L-V 162R
L-V 200K
L-V 200K-FI
L-V 202R
L-VPP 160R-FI
P 340/25-90K
POEV 100/8K-SG
POEV 125/15R
POEV 160/20
PS 310/25-75K
PS 315/25-75K
PS 430/25MM -90K
PS 430/30MM-90K
RTH 200x85/50-4+2
SPKVS 150K
SPO 125/15G
SPO 125/20K
SP-ZP 100C-FI-F
SP-ZP 80C-FI-F
S-ZP 125R-F
TPA 101/12G-ELS
TPA 80/12G-ELS
V 350/25-75K
WH 160

[BH-ALST-150XK](#)[BH-ALST-150XK FI](#)[LK-SPO 80G](#)

754876 Pressed steel swivel castor, heavy duty, with top plate fitting, Heavy-duty wheel made of polyamide Technical specifications: • Wheel Ø: 80 mm, wheel width: 37 mm, load capacity at 4 km/h: 350 kg, Bearing type: plain bearing, total height: 110 mm, plate size: 100 x 85 mm, Screw hole distance: 80 x 60 mm, screw hole Ø: 9 mm, overhang Castor: 40mm Housing: LK series • Strong sheet steel, electrogalvanised, blue passivated, Cr6-free • Double ball bearing in the slewing ring • Stable central bolt (from wheel Ø 125x50 mm) • Slewing ring seal • Minimum slewing ring play, smooth running, long service life the special dynamic Blickle riveting Wheel: SPO series • high-quality polyamide 6, unbreakable, hardness 70 Shore D, very robust, heavy version, color natural white Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -25 °C to +80 °C, reduced load capacity above +35 °C

[GSTA 250/4](#)

754387 Heavy-duty flanged wheel with Blickle polyurethane tread Softthane®, with cast wheel body Technical specifications: • Wheel Ø: 250 mm, wheel width: 60 mm, load capacity at 4 km/h: 800 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, bolt circle Ø: 100 mm Tread: • High-quality Blickle Softthane® polyurethane elastomer, hardness 75 Shore A • Very high level of driving comfort thanks to the particularly thick, elastic tread • very floor-friendly, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical connection with the wheel center wheel body: • robust cast iron • Center bar with center hole and screw holes • Screw holes with spherical collar countersinks • lacquered, color silver Other characteristics: • Assembly using spherical collar screws and spherical collar nuts according to DIN 74361 • high chemical resistance to many aggressive media • Temperature resistance: -30 °C to +70 °C, briefly up to +90 °C, Reduced load capacity above +40 °C

[L-ALST 150K](#)

755956 Stahlblech-Lenkrolle, mittelschwere Ausführung, mit Anschraubplatte, Schwerlast-Rad mit Polyurethan-Laufbelag Blickle Softthane®, mit Aluminium-Radkörper Technische Daten: • Rad-Ø: 150 mm, Radbreite: 50 mm, Tragfähigkeit bei 4 km/h: 400 kg, Lagerart: Kugellager, Gesamthöhe: 190 mm, Plattengröße: 140 x 110 mm, Schraubloch-entfernung: 105 x 75-80 mm, Schraubloch-Ø: 11 mm, Ausladung Lenkrolle: 60 mm Gehäuse: Serie L • Stahlblech, galvanisch verzinkt, blau passiviert, Cr6-frei • zweifache Kugellagerung im Drehkranz • stabiler Mittelbolzen (ab Rad-Ø 150 mm) • Drehkranzabdichtung • minimales Drehkranzspiel, leichtgängiger Lauf, hohe Lebensdauer durch die spezielle dynamische Blickle-Vernietung Rad: Serie ALST • Laufbelag: hochwertiges Polyurethan-Elastomer Blickle Softthane®, Härte

	75 Shore A, Farbe grün, spurlos, kontaktverfärbungsfrei • Radkörper: Aluminium-Druckguss, Farbe silbergrau Sonstige Eigenschaften: • hohe chemische Beständigkeit gegen viele aggressive Medien • Temperaturbeständigkeit: -20 °C bis +70 °C, kurzzeitig bis +90 °C, verringerte Tragfähigkeit bei über +40 °C
LS-GSPO 150K-35-ST-RI4	Technical data: • Wheel Ø: 150 mm, wheel width: 55 mm, load capacity at 4 km/h: 2,500 kg, Bearing type: ball bearing, overall height: 205 mm, plate size: 175 x 140 mm, screw hole distance: 140 x 105 mm, screw hole Ø: 14 mm, Swivel castor projection: 65 mm Housing: LS series • Particularly robust welded steel construction, galvanized, yellow passivated, Cr6-free • Axial deep groove ball bearings ISO 104 and tapered roller bearings ISO 355 in slewing ring • Welded, very stable central bolt, screwed and secured • Protected against dust and splash water • Grease nipples Wheel: GSPO series • high quality cast polyamide, reaction cast, unbreakable, hardness 80 Shore D, color natural beige
BH-ALST 100K-3	752602 Sheet steel fixed castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm Housing: BH series • Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
LH-ALST 100K-3	684464 Sheet steel swivel castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
	625418 Sheet steel fixed castor, heavy-duty version, with

BH-ALST 125K-3	screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm Housing: BH series • Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
LH-ALST 125K-3-FI	625517 Sheet steel swivel castor, heavy-duty version, with screw-on plate, with 'stop-fix' lock, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, non-marking, non-staining from contact • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
B-Alst 160k Rolle	
Lh-Gsp080k-Fi	
Lk-Alst 100k-1-Fi Rad	
Alth 125/15 K Extrathane Schwerlastrad	
Li-Phn 200ik	
L-V 200k Rolle	
L 150/160 -L-160.60.03	
Le-Path 200r-Fi Rolle	
Bh-Spo 100k-1	
Lk-Alth 80k-Fi Lenkrolle Mit Bremse	
L-Vpp 160r-Fi Drehen. Rolle Mit Bremse (Schwarzer Gummi)	

[Rad Mit Polyurethankabel D-
200mm, Blickle Gth 200/25k
Fuehrungsrolle Fpo 25x10/6-6k](#)

[622106](#)

[Gspo 152/35k](#)

[B-V 162r Stahlblech-Bockrolle](#)

[Bs-Gth 252k](#)

[Bo-Alth-200k](#)

[Lra-Tpa75k-Fi-Fk Umlenkrolle](#)

[F-Zp 125r - F Roller](#)

[Le-Poev 100r-Fistahlblech-Lenkrollen](#)

[Fsth 70x25/20-15k](#)

[L-Poev 1250k-Fi Rolle](#)

[Bh-Seth 200k Rolle Fest](#)

[150*45](#)

[Lenkrolle 150 Mmlh-Seth 150k](#)

[Bh- Alst 100k-3](#)

[L -rd 202r Lenkrollen](#)

[Lh-Gth 200k](#)

[Gth202/30k](#)

[Bh-Gspo 125k](#)

[Bpa-Poa 50g](#)

[Lsd-Gth-100k Rolle Drehbar](#)

[Lk-Albs 100k-1-Fi](#)

[Lsd-Se 250k-Ra](#)

[Bh-Gsp080k](#)

[Bh-Albs 200k Fixierte Rolle](#)

[150749 Le-Poev 201k-Sg](#)

[Lsoa-Albs 200k-Ra-761312](#)

[Lh-Gth 160k](#)

[Gb 200/20k](#)

Lh-Gth 125k-1
B-Poev 160k Rollen Schwenkkrane
Rad Mit Polyurethankabel D- 250mmBlickle Gth 252/30k
102556 Super-Elastik-Vollgummi- Reifenbsev 4.00-4-Rp
B-Rd 162r-Vli Nicht Drehbar Rolle (Grauer Gummi)
Lk-Po 200k-St-Fs
Lk-Poev 160k Drehbarer
Bh-Poev 160k Nicht Drehbar
125/ 15?
L-Alth 150k-Fi Rolle Drehbar
Alev 125/15k
101323 Rad Fest Blickle B-Ve 100rident- Nummer: 101323
B-Alev-161k
L-Alst 160k-Fi
Lk -Alst 100k-1-Fi
Ls-Se 160 K
Bs-Gth 604k
B-Vpp 160r Nicht Drehbar Rolle (Schwarzer Gummi)
Bh-Gspo 100k-3
562876
Lra-Tpa75k-Fk Rolle
Lh-Gth 202k
Bk-G 125g-1
Lez-Po 75g-Fi
Lh-Gb 200k-Fi Lenkrollen
L-Alst 160k-Fi Rolle
Lk-Spo 160g-Fi
850415 B-Poev 201k-Sg

Lh-Gsp080k-St
Lh-Gth 175k
Sp-Zp 80c-Fi-F Lenkrolle Mit Bremse
Bsd-Se 200 K
457283
45336
Fsth 100x25 15k
Gev 520/40k
B-Pth 200r
Gth 504/60k
752607
137904 Lenkrolle Ls-Gb 202 K
Se 252/25 K
Ls-Vle 310k
B-Ve 200r Rolle Fest
106636 Rad Drehbar Mit Bremseblickle Le-Ve 100r-FI Ident-Nummer: 106636
Gspo 80/20k Heavy Duty Polyamide Block Wheel
562884
Rad Alev 125/15k
Bs-Se 160 K
L-V80r-St
Spkvs250k
L-Alst 250k-3-St
Bpa-Vpa 50k
Gthn 252 40h7
Lex-Po 125kd-Fi Roller
Ps 315/25-75k Rad
L-Path 80g-Fi Lenkrolle Mit Bremse
Lh-Gb 200k Lenkrollen
Bh-Alst 200k

Das Rad Fest, Stahlblech, Dbh-Poev 100k-1
Ls-G 250k
Lkra-Tpa 101g-Gs12
Bh-Svs 127k
Lh-Gth 125k-3
Lh-Alst 100k-3
Hrsp-Poa 72g 757023 Radkopf
Gth 202/35k
Gth150/20k
Rth 200x85/50-4+2 Rad
102554 Super-Elastik-Vollgummi-Reifenbsev 3.00-4-Rp
Ls-Alb 200k-Ra-760676
L-Alev 125k-Fi
Lk-Alst 100k-1-Fi P. Roller With Brake
Poev 125/15r Rad
L-Alst 125k-Fi Rolle
150131 B-Poev 201k-Sg
46714
115643
L-Po 125r-Fi-Fp
Geva 300/5
45369
L-Alst 200k-Fi
Ls-Gb 250k-St-Ri2
Brd162r
Se 252/25k
Lh-Gth 100k-3
Lsd-Gth 302k-Ri4h
B-Alth 100k

00227278	
L-Poev 100 K Fi Stahlblech Lenkrollerad- Und Drehkranzbremse "stop-Fix"	
Lh-Albs 160 K Rad Rotor Ohne Bremse	
L-V 162r Stahlblech-Lenkrolle	
Gth 177 / 25k	Wheel with polyurethane tread Blicke Extrathane®, with cast iron wheel center Wheel: Tread / Tires: Made of high-quality polyurethane elastomer Blicke Extrathane®. Tread color: light brown Wheel center / rim: Made of cast iron, with grease nipple, painted. Surface hardness: 92 ° Shore A Wheel Ø: 175 mm Wheel width: 80 mm Load capacity: 1300 kg Bearing Type: Ball Bearing Axle hole Ø: 25 mm Hub length: 80 mm Temperature resistance: -25 ° C to 70 ° C
250/20k	
L-Alth 100 K Fi Stahlblech Lenkrolle Mit Feststeller	
250/20k-Sg	
Lrd162rst	
Lh-Gth 127k-Is	
Albs 100/15k	
451697	
Lsd-Se 200 K	
115646	
S-Zp 125r - F Roller	
Gthn 252/40h7 Radident-Nummer: 104572	
Lk-Albs 200k-Fi Drehbare Rolle	
Lh-Gth 150k	
Lo-Alth-200k-St	
125 15?	
Sp-Zp 100c-Fi-F Lagerung Rad Drehbar Mit Bremsed=100 Mm Sp-Zp 100c-Fi-F	
Bh-Albs 200 K Das Rad Nicht Drehbar Ohne Bremse	
Bs-Gspo 302k	
Bh-Gspo 65k	

Gthn 251/40h7 Ruota Di Frizione
Lra-Vpa 50 G Fi Stahlblech Apparate -
Lenkrollerad- Und Drehkranzbremse
318451
B-Alev 125k
Ls-Vle 310k-Ra
Lkra-Tpa 101g-Fi-Gs12
Das Rad Drehbar Mit Bremse, Blechlh-
Poev 100k-1-Fi
Gspo125/25k
Hth80x40/20-40kk
L-Alth 80k-As Rad Mov.
Hth 60x35/15-35kpolyurethan-
Laufrollenlaufbelag Gegossen
606541
Bh-Spo 150k
L-Alst 80k-Fi Pov. Rolle Mit Bremse
470088
Zwillings-Lenkrolle Lsd-Gth-252k-Rah-
Ri2h
Ls-Ps 310k
B-Alst 200k
Antriebsraeder Rth 200x85/50-4+2
Rk-Hth 060x035/32x09-35-
Zgabelhubwagen-Rolle Mit Polyurethan-
Laident-Nummer: 148149
Gth 200/25k Rad
Rolle Nicht Drehbar D:100
Chape:100x85b-Poev 100k
Lh-Gth 127k
9990014272
Se-252/25k
Sheet steel compact swivel castor with mounting plate Wheel with Blickle Extrathane® polyurethane tread, with steel wheel center Housing: Made of strong pressed steel, with double ball bearing in the turntable, with slewing ring seal.

(754880) Lk-Vsth-65k	Wheel axle bolted. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: light brown Tread / Tire: Made of high-quality polyurethane elastomer Blickle Extrathane®. Wheel center / rim: Made of steel. Tread poured. Surface hardness: 92 ° Shore A Wheel Ø: 65 mm Wheel width: 40 mm Load capacity: 250 kg Bearing Type: Ball Bearing Total height: 92 mm Plate size: 100 x 85 mm Screw hole distance: 80 x 60 mm Screw hole Ø: 9 mm Discharge swivel castor: 40 mm Temperature resistance: -25 ° C to 70 ° C
463935 (Fsth 40x20/10-8k)	
B-Alth 100k Rad Fix.	
L-Rd 162-Fi-Vli Drenen. Rolle Mit Bremse. (Grauer Gummi)	
Gth 200 25k	
L-Alth 150k Rolle Drehbar	
B-G 80g Rad	
B-Alst 200k Rolle	
L-Rd125r-Fi Rollen	
B-Alst 125k Rolle	
595678	
45377	
B-Vehi 125r	
L-Alev 200k-Sg Rad	
Bh-Alst 160k	
Ls-Gth 604k	
Geva 250/4	
B-Phn 200ik	
761312	
Lra-Vpa 50 G-Es Stahlblech Apparate - Lenkrolleeinsteckstift 11mm	
B-Alst 160k	
137905 Lenkrolle Mit Feststeller Ls-Gb 202k-St	
850265 Le-Poev 201k-Sg	
Ls-Gth 252k	
Alt -160/20 K	

L-Poev 100k Rolle
Lh-Seth 200k-Fi Rolle Lenkrolle Mit Bremse Stop-Fix
Ls-Seth 125k Swivel Castors
L-Poev 80k-Fi Rolle
P 340/25-90k Rad
Spo 125/20k Rad
Alev 250/25 K
B-Path 200r Rolle
Li Phn 102 G
Bh-Alst 250k
Rht 225x70/120 – 12 – P
Le-Poev 160k-Fi Rollen Schwenkkrane
Lpa-Vpa 50k
Le-Ve 200r-Fi Rolle Drehbar
L-V 200k-Fi Lenkrolle Mit Bremse
Bh-Po 200k-Fs
Ps 310/25-75k Rad
L-Alev-161k
L-Alst 200k-Fi Rolle
127 P02
Lh-Gth 100k-1
760676
Lpa-Path 50 G-Fi Rolle
51615
Bsd-Spo 160k-35
L-V 125r Stahlblech-Lenkrolle
B-V80r
Fsth 80x25/25-15k
Rad, Stahlblech, Bh-Alth 180k
Gthn 200/30h7 Rad

Ff125