

Bonfiglioli

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Bonfiglioli Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Bonfiglioli Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
2e19011571	Bonfiglioli spur gear with IEC_Motoreingangsflansch C 51 2 P 7.0 P132 B3 Design foot, output shaft 40h6 x80 mm Reduction 7.0 M (perm.) = 630 Nm at n1 = 1400 rpm Motor input P132 300/38 mm Installation position B3 Cast steel primed with P1 alkyd resin base Zinc phosphate silver gray without oil filling Weight 51 kg net Weight gross 70 kg Customs tariff no. commodity code 84834021 spur gear
Vf 44 P1 20 P63 B14 B3	200480129 Bonfiglioli worm gear with IEC flange for motor mounting VF 44 P1 20 P63 B14 B3 Type P (1) slip-on hollow shaft 18H7x64mm Reduction 20 Max. Permissible continuous torque 39 Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange 90mm, motor shaft 11mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
Vf 49 A 36 P71 B5 B3	200620241 Bonfiglioli worm gear with IEC flange for motor mounting VF 49 A 36 P71 B5 B3 Type A foot with hollow shaft 25H7x82mm Reduction 36 Max. Permissible continuous torque 69 Nm at n1 = 1400 rpm Motor input P71 B5 Motor flange 160mm, motor shaft 14mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
Vf 49 A36p71b5 B3	
Ev 063 B09 0,75 Kw I=1/40	
C612ufa121p160 11kw	
Fd Fr37-80b14-36.72-M1 I:36,72	

VF R 49 F1 135 P63 B5 B3	237850210 Bonfiglioli helical worm gear with IEC motor input VF R 49 F1 135 P63 B5 B3 Type F flange short with hollow shaft 25H7x82mm Flange 125/90 / 70H8 mm Reduction 135 Max.permissible continuous torque 59 Nm at n1 = 1400 rpm Max.permissible power 0.09 KW Nm at n1 = 1400 rpm Motor input P63 B5 Motor flange Ø 140 mm, motor shaft Ø 11 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
VF/VF 30/49 A 315 P63 B14 B3 CW2 7 45	Bonfiglioli twin worm gearboxes with IEC Inlet flange VF / VF 30/49 A 315 P63 B14 B3 CW2 7 45 Type A foot hollow shaft 25H7x82mm Reduction 315 7 x 45 Motor input P63 B14 Motor flange Ø = 90mm, motor shaft Ø = 11 mm Max. Permissible continuous torque 95 Nm at n1 = 1400 rpm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling CW2
BXN 63MA 4 115/200/230/400-50 WD1 50	IP54 CLF B14 FD 1.75 NB DIR 8XNB63040008 Bonfiglioli three-phase motor BXN 63MA 4 115/200/230 / 400-50 WD1 50 IP54 CLF B14 FD 1.75 NB DIR IE3 Voltage - winding 1 230/400? / Y - 115/200 ?? / YY 50 Hz Motor flange 90 mm, motor shaft 11 mm Braking torque 1.75 Nm Half-wave rectifier Continuous service S1 Certificates: CE-UKCA-CUS Die-cast aluminum design Unpainted
MP G 130 2 10 STD 130A1 CD 32 S1 OR SB KE	MP1GE2010S0002 TECHNOINGRANAGGI planetary gearboxes MP G 130 2 10 STD 130A1 CD 32 S1 OR SB KE Orthogonal entry level Angle game 15 ' Type of motor coupling clamping device Continuous Service Horizontal installation position Output shaft support Output shaft with key
Repair Kit VF 49 F2 7	
VF/W 44/86 U 480 HS B3 CCW4 24 20 KA	Bonfigliolid twin worm gearboxes VF / W 44/86 U 480 HS B3 CCW4 24 20 KA Hollow shaft version 35 mm Reduction i = 480 24x20 Input shaft HS Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling Type CW1 Option KA
0002308	
0024687+0041196	
0026170+0014622	
0030849	
003120242	
1180 for BN 71 (0.37kw)	
1180 for BN 90 S4	
127050030	
140604	
1452661502	
190.1.6.10.38.80.180.215	
192810006	
192810007	
1EA805020003	
1G28010603023	
1G28010907035	
200350129	
200370069	
200380069	

[200480219](#)[200620309](#)[200630151](#)[200680033](#)[200680271](#)[201060219](#)[20146009](#)[212-FL-02 MVF 86/P](#)[21306L20460018](#)[230/400-50](#)[23888015010000](#)[2388C015010001](#)[25/F210650243](#)[2E1 401 365](#)[2E19011581](#)[2E56G03331](#)[2E56G03334002A](#)[2E60G01555](#)[2E65G04244](#)[2E6AG057440001](#)[2E70G00961](#)[2EA10143000F](#)[2EA101510005](#)[2EA101510008](#)[2EA601210005](#)[2F282087540001](#)[2G200103I3](#)[2G20010934](#)[2G28010661](#)[2G28011256](#)[2G2801341](#)[2G280136H1](#)[2G280136L1](#)[2G320124I1](#)[2G344300610001](#)

2T303L1004005
2T306L2046003S
2T306L2046135
3 03 L1 4.25 FZ SF S5AP T
3 03 L2 i=30,8 HC P112 A
3 06 L2 i=46,5 HC P132
3 07 L 2 38.6 HZ 4R T4AA T
3.00.00.04225
30 1/10 P63 B5
307 R2 19.8 FZ SF V9AA B1
307 R3 83.4 FP P160 B0 G0A BH 160 M 4 W
44P1 10 P63 B14 B3
612600358
612602460
614600414
616302332
6689960610
703C2H22C32R5HE customised
705T2F3HC1E13AUD.1T (OEM)
711C 5" D185 F13-30 6635060080
711C3B26C0153H25W1A42VS, S/N 10130104 / 2010
712205008
714280100
714280101
714280102
714280103
714281009
714285018
714285024
71B 4 230/400-50 IP55 CLF B5
795016490 VF49 P1 45 B5 B3 200680271
802300
812010002
830420150
830520106

830520156
830520356
830720106
830810456
830820106
830820156
8AF240006
8D11020003
8D17020002
8F44020004
8H16140098
8U30030001
A 10 2 UH25 13.9 P80 B3
A 30 2 UH35 F1C 22.8 P90 VB
A 30 3 UH35 356.3 P71 B3 VV BH 71 B 4 W
A 35 2 UH40 74.3 P 90 B3 BH 80 C 4 N FD
A 35 2 UH40 F1B 20.4 S3 B7 M 3 LC 4 W
A 41 2 UH45 79.2 P90 B3 BH 90 LA 4 W
A 41 2 UH45 79.2 P90 VA BH 90 LA 4 W U1
A 41 2 US 45.1 P90 B8 BE 90 LA 4 W
A 412 UR 28.3 P90 VA
A 50 3 UH50 45.0 S3 VA M 3 LA 4 IP55 N FD R AA EN3
A 50 3 UH50 56.8 HS B8
A 50 3 UR 35.6 P132 B3
A 503 UH50 173.4 P90 B3 – BE90LA4
A 55 2 UH60 15.7 S5 B3 M 5 SB 4 IP55 CLF W
A 60 3 UH60 70.4 S4 B3 M 4 SA 4 IP55 CLF W
A 60 4 UH60 351.2 P90 B3
A102 UH25 23.8 P71 VB BN 71 C 2/4 FD R N
A202
A202 UH30
A302 UH40 F1C 43.4 S3 ME 3SA 4
A503 NR PB2
A503 UH50 32.4 P90 VA LQ
A602 UH60 16.7 P160 B3

AB 35 132 KW3 8P B3
ACT 401-37 A
ACU 401-05 FA
ACU201-13 FA
AGL4071FA0001
ATZ090031
BE 90 LA 4 230/400-50 IP55 CLF B5
BF 008B
BH 200 L 4 400/690-50 IP55 CLF B3
BN 63B 4 B14
BN 71 B 4 230/400-50 IP54 B14 FD
BN 71B 4 B14
BN 90LA 4 B5 FD26 1.5kW
BN 90S 4 230/400-50 IP55 B5 FA R
BN132S4, Nr 28517
BN56 B4
BN71B4 230/400-50
BN80 B4 FD B5
BN90 FD/FA R
BN90S4
BNI00LA4
BONFIG.VFR150 P2 -90 P90 B5 V6
BX90 LA4
C 22 2 P 12.4 S3 B3 M 3SA 4 W
C 22 2 P 2.7 P90 B3
C 22 2 U 11.1 P80 V1
C 22 2 U 29.6 P80 V1
C 312 PP100
C 32 2 P 12.3 P90 B3
C 32 2 P 12.3 S3 B3 M 3 LB 4 W
C 32 2 P 7.2 HS B3
C 32 2 U 52.4 P80 V1
C 41 2 P 25.0 HS B3
C 51 2 P 18.9 S3 B3 M3LA4 W FD R
C 61 3 P 140.5 P80 B3
C 80 2 P 39.1 S4 B3

C312 P 22.6 P90 B3
C35 3 UFA P08 B5
C412 UFB 31.4 P90 B5
C512 P 16.6 P132 B5
C512 P 33.0 S3 B3 M 3LA 4 W
C512 P 7.0 P132 B3
C71539A0910003
C721C9I0230001
DS150302782
DS603446300
EM-ENC02
F 51 2 H50 23.8 S3 H1 M 3 LB 4 W
F 51 2 H50 P112 H3 i=37,1
HL07063EH006
HL09080EE001
I65801440001
KE6005060
KM0010144
KM0010207
LC 090 1 7 STD 80A1 CD 19 KE
LC90211L220001
M00380060003)
M0062006016A
MAS 16 F RATIO 1/18,89
ME360106000H
ME76G057002O
ME78G042002A
ME82A0390010
ME84G0030027
ME84G051000M
MEA602120002
MF241039001Z
MF701032000H
MG2406270008
MG-Z00ZA12C-X01P-N
MP 053 1 9 STD 40B CD 9 S5 OR SB KE

MP 060 1 5 STD 40B CD 11 S1 VA SB KE
MP 060 1 7 STD 80A CD 14 S1 OR HB KE
MP 060 2 20 STD 40B CD 11 S1 VB SB KE
MP 060.2.100.15.11
MP 080 1 4 STD 95A CD 19 S5 OR SB KE
MP 080 2 40 STD 40B CD 11 S1 OR SB KE
MP 080.3.48.17'.19.40.95.115.S1.AR
MP 105-1-6-15-19-40-95-130
MP 130 3 125 STD 80 A 2 CD 19 S1 OR SB KE
MP G 130 2 6 STD 130A1 CD 28 S1 OR SB KE
MPD2015S001E
MPE1007S0004
MPE3125S0006
MPE3280L0002
MVF 110/N
MVF 30 1-10 P63 B14
MVF 44/N
MVF 44/P i=20 0,5HP, 063 B14
MVF 49/P 071 B14
MVF44 VF/VF 30/44 F2 P63B14 M602 79 B 00008 BATCH 10/04 I=420
NB710210013
NFF 11 90 EE UU
R911305623
RAN 15 D A 1 HS B3
RAN 20 S A 2 HS VA
RAN 25 D A 1 HS B3/127410030
RAN 28 D B 7.7 HS B3
RAN 28 S A 1 HS B3
RAP130 DN
reducer for M2SB4, Nr:60688940008
S101 P71 B3 I=3.2
S101 P71 B3 I=4.7
SIACT525000001
SIACU515010001
SYN10 S220 05AF

SYNPLUS
TA 70 70 D A 20.3 HS C AL
TA 70 70 D A HS
TR 080.1.10.3'.19.60.110.145.S1.AR
Typ TA45-50/D 15 HS A
TYP: TR 080.2.16.3?.19.40.80.100.S1
UF 49 P I:10 P71 B5-B7
V 0.5 U PF71 D14 HS B3 A 1
V 1 F D19 P80 B3 1
V 5.5 F D28 P112 B3 1
VE04C03310004
VE12 B 55510001
VF 110/N
VF 130 F1 10 P132 B5 B3
VF 150 P1 56 P112 B5 V5 BN 112 M 4 W FD
VF 27 F1 20 P27 B3
VF 30 A 15 P63 B14 B3
VF 30 F1 15 P63 B14 B3
VF 30 F1 20 P63 B14 B3
VF 30 P1 10
VF 30 P1 20 P63 B5 B3
VF 30 P1 7 P63 B14 B3
VF 44 A 28 P63 B5
VF 44 F – 14 P71 B5 B3
VF 44 F1 10
VF 44 F1 14 P63 B5 B3
VF 44 F1 14 P71 B14 B3
VF 44 F1 14 P71 B5 B3
VF 44 F1 15 P63 B14 N
VF 44 F1 7 P63 B14 B3
VF 44 F1 70 P63 B14 B3
VF 44 P 7 P63 B14 B3
VF 44 P1 20 P71 B14 B3
VF 44 P1 35 P71 B5 B3 BN 71B 4230/400-50 IP55 CLF W
VF 44 P1 60 P63 B14 B3

VF 44 P1 7 P63 B14 B3
VF 44 U 7 P71 B14 B3
VF 49 A 10 P80B5 B3
VF 49 A 14 P80 B14 B3 (200620128)
VF 49 A 24 P71 B5 B3 BH 71 B 4 W
VF 49 F1 18 P71 B5 B3 + BN 71C 2 230/400-50 IP55 CLF B5
VF 49 F1 60 P71 B14 B3
VF 49 F1 60 P71 B5 B3
VF 49 F2 60 P71 B14 B3
VF 49 F2 60 P71 B5 B3
VF 49 L1 18 P71 B14
VF 49 P1 10 P71 B14
VF 49 P1 100 P63 B14 B3
VF 49 P1 18 P71 B5 B3 (200680151)
VF 49 P1 24 P71 B14 B3
VF 49 P1 36 14/140 B3
VF 49 P1 36 P63 B5 B3
VF 49 P1 36 P71 B14 B3
VF 49 P1 45 P71 B14 B3
VF 49 P1 45 P71B14
VF 49 P1 7 P71 B14 B3 BN 71B 4 230/400 IP55 CLF (M00680030027)
VF 49 P1 7 P71 B5 B3 BH 71 B 4 W
VF 49 P1 7 P80 B14 B3
VF 49 V 18 P71 B5 B3
VF 49 V 24 P71 B14 B3 BH 71 C 4 W
VF 49 P I:18 B 14 B 3 (25-14-200)
VF 62/FC
VF 63 FC2 P80 B14 B7
VF 63 N 45 P80 B14 B8 BH 80 B 4 W
VF 63 P1 7 P80 B14 B3
VF M0038012000630 P1 P63 B14
VF R 49 A 300 P63 B5 B3
VF R 49 V P63 B5
VF/VF 30/44 F2 420 P63 B14 B3 CCW4 15 28

[VF/W 44/75 UF2 D30 525 P63 B5 CCW4 BH 63B
4-W](#)[VF/W 44/75 UFC1 D28 300 P71 B5 B3 CW4](#)[VF/W49/110 UF1 540 P80 B14 B3 CCW1 18 23](#)[VF30 F2 10 P63 B14 B3](#)[VF30 N D30 15 P63 B14](#)[VF30 P1 7 P63 B5 B3](#)[VF49 P 18 P71 B14 B3 P=0,55KW I=18
REDUCTOR](#)[VF49 P 24 P71B14+ BN 71B4 B14](#)[VF49 P1 7 P71 B5 B3](#)[VF49 PN14 PAM80 BN80B4](#)[VF49P1 14 P80 B5 B3](#)[VF72?P1?60?P80?B14?B3?](#)[VF86 FC2 30 HS B3](#)[VFR 49 P1 300 P63 B5 B3](#)[W 110 U 20 P132 B5 V6 - BE 132S 4](#)[W 110 U 20 S3 B3](#)[W 110 U 64 P80 B5 B6](#)[W 110 UF1 100 P90 B5 B3](#)[W 110 UF1 46 P100 B5 B3 L0 - BN 100LA 4
230/400-50 IP54 CLF B5 FD40 NB 230](#)[W 63 L2 UF2 80 P71 B5 B7](#)[W 63 U 15 P71 B14 B8](#)[W 63 U 24 P80 B5 V5](#)[W 63 U 7 P90 B14 B8](#)[W 63 U 7 P90 B5 B3](#)[W 63 UFC1 100 P71 B14 V5](#)[W 63 UFC1 45 P71 B14 B3](#)[W 63 UFC2 24 P80 B5 V5 BN 80 A 4 W FD R](#)[W 75 U 40 P90 B5 B3](#)[W 75 U D30 15 P90 B5 B3](#)[W 75 U D30 20 S3 B3 M 3 LA 4 W](#)[W 75 U D30 50 P90 B5 B3](#)[W 75 U D30 7 HS B8 RB](#)[W 75 UF1 D30 10 P112 B14 B6](#)[W 86 U 20 P90 B5 V5](#)[W 86 U 20 S3 B3 M 3 LB 4 W](#)

W 86 U 56 P90 B14 B7	
W 86 U D30 20 S3 B3 M 3LB 4 W	
W 86 UFC2 20 P112 B5 B7	
W 86 UFC2 80 P80 B14 B3	
W/VF 63/130 FC2 400 P80 B5 B7 CCW4	
W/VF 86/150 F1 300 HS B3 CW4	
W110 U 56 P100B5 B3	
W110 UFC1 80 P90B5	
W2T300L1007112	
W63 U 24 P71 B14+ BN 71B4 B14	
W63 U 24 P80 B14+BN 80 A4 B14	
W63 U 30 S1 B3 M 1LA 4 W	
W63 U 7 P80 B14 B3	
W63 U P90 B14	
W63 U19 HS B3	
W63 U19 HS B3 RB	
W63 U 19 P80 B5 B3	
W75 U D30 P80B5	
W86 U HS) B3 i=100	
WM40460270005	
worm gear for P71 B14 B3 VF-44-P I : 10	
WR 110L1 U138 P90 B5 B7	
ype: TR 130 1 5 STD 130A1 CD 28 S5 OR SB KE	
TA 35 35 DA 10 HS A	
W86 U 46 24/160 B3 (for conveyor belt)	
W63 U10 P90 B14	
W66 U 10 P90 B14 i=7 (for conveyor belt)	
BX 80B 4 230/400-50 IP54 CLF B5 FA 15 230 SA	8AF04002H Bonfiglioli three-phase brake motor BX 80B 4 230/400-50 IP54 CLF B5 FA 15 230 SA 0.75 kW, 1425 rpm, Flange 200mm, motor shaft 19mm with attached spring pressure brake 3x230V~ 15 Nm FA , Version Aluminum die-cast, unpainted Option SA separate terminal board
TA 35 35 D 19,5 A HS LO	145061120AOS Bonfiglioli flat gear TA 35 35 D 19.5 A HS Reduction : 19.5 Max. permissible continuous torque 380 Nm at n1 = 1400 rpm Max. permissible power 3.0 KW Nm at n1 = 1400 rpm Weight : about 18 kg Installation position : A Output hollow shaft: 35 H7 x 124 mm Drive shaft : 19 h6 x 40 mm splash lubrication Color scheme : manufacturer standard
	145071120A Bonfiglioli flat gear TA 35 35 D A 19.5 HS A Reduction : 19.5 Max. permissible continuous torque 380 Nm at n1 = 1400 rpm Max. permissible power 3.0 KW Nm at n1 = 1400 rpm Weight : about 18 kg

TA 35 35 D A 19.5 HS A	Installation position : A Output hollow shaft: 35 H7 x 124 mm Drive shaft : 19 h6 x 40 mm splash lubrication Delivery without oil filling Required oil capacity: 1.10 liters Color scheme : manufacturer standard Option A backstop
Doseahorse Planet Motor and Redüktörü	Model ; 3 07 L 2 32.6 FP E0SD A G0A LM + A 41 2 UH45 53.1 P90 B3 Same brand or equivalent brand, shaft diameter and foot dimensions are the same as the existing gearbox * Delivery date is very important
VF 49 P1 36 P71 B5 B3...KW 33 (1)	Bonfiglioli worm gear with IEC flange for motor mounting VF 49 P1 36 P71 B5 B3 Type P(1) push-on hollow shaft 25H7x82mm Reduction 36 Max. permissible continuous torque 69 Nm at n1 = 1400 rpm Max. permissible power 0.42 kW at N1=1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling 200680241
VF 49 P1 07 P71 B5 B3...KW 48 (1)	Bonfiglioli worm gear with IEC flange for motor mounting VF 49 P1 07 P71B5 B3 Type P(1) push-on hollow shaft 25H7x82mm reduction 07 Max. permissible continuous torque 54 Nm at n1 = 1400 rpm Max. permissible power 1.3 KW Nm at n1 = 1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling 200680031
VF 44 P1 20 P63 B14 B3...KW 45 (2), KW 06/23 (5)	200480129 Bonfiglioli worm gear with IEC flange for engine mounting VF 44 P1 20 P63 B14 B3 Type P(1) slip-on hollow shaft 18H7x64mm Reduction 20 Max. permissible continuous torque 39 Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange 90mm, motor shaft 11mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF 49 A36P71B5 B3	
C612UFA121P160 11KW	
BN71.C 2	
WM0037009002301	
MP 053 1 3 STD IS S1 OR SB KL	MPA1003S0010 Planetary gear MP backlash MP 053 1 3 STD IS S1 OR SB KL angle game 15' Drive shaft protruding continuous service Horizontal installation position Motor to output shaft support Output shaft without key
RAN 20 CAV0 SA HS	127310120 Bonfiglioli bevel gear RAN 20 CAV0 SA HS Design SA Input shaft HS Die-cast aluminium, primed with oil
W R 86 U FC1 60 HS B7 RB G30042407001	Bonfiglioli helical worm gear prepared for cultivation of one three-phase motor W R 86 U FC1 60 HS B7 RB Design UFC flange short hollow shaft 35H7x140mm Output flange short dimensions=210x172x152 H8mm Reduction 60 Max. permissible continuous torque 380 Nm at n1 = 1400 rpm Max. permissible power 1.2 KW Nm at n1 = 1400 rpm Design HS input shaft 19h6x40mm Installation position B7 Die-cast aluminum, unpainted including synthetic oil filling Option RB 2nd shaft end 25h6x50mm
W 86 UFC1 30 P90 B5 B3	W 86 UFC1 30 P90 B5 B3 2G28041851 Bonfiglioli worm gear prepared for Attachment of a three-phase motor W 86 UFC1 30 P90 B5 B3 Design UFC Flange short push-on Hollow shaft 35H7x140mm Output flange dimensions=210x176x152H8 mm Max. permissible continuous torque 370 Nm at n1 = 1400 rpm Max. permitted power 2.4 kW at n1=1400 rpm Reduction 30 Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
8AF240006	BX 90LA 4 B5 3x230/400 +/-10% V 50/60 Hz ISO F IP 55...KW 32 (2) Bonfiglioli three-phase motor BX 90LA 4 3x230/400 +/-10% V 50/60 Hz ISO F IP 55, 1.5 kW, 1430 rpm, 10.0 Nm motor flange 200mm, Motor shaft 24mm IEC 60034-30:2008 "Efficiency classes for single speed three-phase Squirrel cage asynchronous motors (IE code)" High efficiency, IE3 Die-cast aluminum design Unpainted

RAN 20 CAV0 SA HS	127310120 Bonfiglioli bevel gear RAN 20 CAV0 SA HS Design SA Input shaft HS Die-cast aluminium, primed with oil
ATVF/VF 49/86 A 480 HS B3 CW1 24 20	Bonfiglioli twin worm gearbox ATVF/VF 49/86 A 480 HS B3 CW1 24 20 Version A foot hollow shaft 35 mm Reduction i=480 (24 20) Max. permissible continuous torque 550 Nm Input shaft HS 14h6x40 mm Installation position B3, CW1 Die-cast aluminium, unpainted including synthetic oil filling
W 86 U 30 P90 B14 B3 (only reducer)	2G28011811 Bonfiglioli worm gear flange for Installation of an IEC standard motor W86U30P90B14B3 Design U slip-on hollow shaft 35H7x140mm Max. permissible continuous torque 370 Nm at n1 = 1400 rpm Max. permissible power 2.4 kW at n1=1400 rpm Reduction 30 Motor input P90 B14 Motor flange Ø 140 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted including oil filling
BN71A6	
VF49P71 B5B3 i:36	
C612 UFA 12.1 P132 11 KW	
W 110 U 64 P90 B5 B3	2G32013051001 Bonfiglioli worm gear prepared for Attachment of a three-phase motor W110U64P90B5B3 Design U slip-on hollow shaft 42H7x155mm Reduction 64 Max. permissible continuous torque 530 Nm at n1 = 1400 rpm Max. permissible engine power 1.7 KW at n1 = 1400 rpm Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted
W 75 U D30 60 P80 B5 B3	2G24012741001 Bonfiglioli worm gear flange for Installation of an IEC standard motor W 75 U D30 60 P80 B5 B3 Design U slip-on hollow shaft 30H7x127mm Max. permissible continuous torque 200 Nm at n1 = 1400 rpm Max. permissible motor power 0.75 KW at n1 = 1400 rpm Reduction 60 Motor input P80 B5 Motor flange Ø 200 mm Motor shaft Ø 19 mm Installation position B3 Die-cast aluminum, unpainted including oil filling
A 41 3 UR 184.4 P80 B3 2E67A01231	Bonfiglioli bevel gear for mounting IEC standard motor A413UR184.4P80B3 Design UR one-sided output shaft 45h6x80mm Reduction 184.4 Max. permissible continuous torque 850 Nm at n1=1400 rpm Max. permitted power 0.74 kW at n1=1400 rpm Motor input P80 B5 Motor flange Ø 200 mm Motor shaft Ø 19 mm Installation position B3 Cast steel primed with P1 alkyd resin base zinc phosphate
W 75 U D30 60 P80 B14 B3 2G240127H1001	Bonfiglioli worm gear for mounting an IEC standard motor W 75 U D30 60 P80 B14 B3 Design U slip-on hollow shaft 30H7x127mm Max. permissible continuous torque 200 Nm at n1 = 1400 rpm Max. permissible engine power 0.75 KW at n1 = 1400 rpm Reduction 60 Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 Die-cast aluminum, unpainted including oil filling
VF44 F1 10 P71 B5 B3	Bonfiglioli worm gear CODE 200450063 composed of VF 44 P1 10 P71 B5 B3 200480063 Bonfiglioli worm gear with IEC flange for engine mounting VF 44 P1 10 P71 B5 B3 Type P(1) slip-on hollow shaft 18H7x64mm Reduction 10 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permissible power 0.51 KW Nm at n1 = 1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
C 41 2 UFB 4.7 P112 B5	2E15060962 Bonfiglioli spur gears C 41 2 UFB 4.7 P112 B5 Design U universal flange 110f7/130 mm, output shaft 35h6x70 mm Flange FB 180f7/215/250 mm Reduction 4.7 Motor input P112 B5 250/28mm Max. permissible continuous torque 260 Nm Installation position B5 Cast steel primed with P1 alkyd resin base Zinc phosphate silver grey including synthetic oil filling
Screw flange F for VF44P/VFR44P...KW ? (10)	194000104 Screw flange F for VF44P/VFR44P Flange F short for VF44/VFR

W 86 U 40 P90 B5 B8	44 Flange F short 110/87/60H8 mm 2G28012158 Bonfiglioli worm gear prepared for attachment of a three-phase motor W86U40P90B5B8 Design U slip-on hollow shaft 35H7x140mm Max. permissible continuous torque 330 Nm at n1 = 1400 rpm Max. permissible power 1.6 kW at n1=1400 rpm Reduction 40 Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B8 Die-cast aluminum, unpainted including synthetic oil filling
BX 90S 4 B5 3x230/400 +/-10% V 50/60 Hz	ISO F IP 55...KW 03/23 (5) 8AF14000C Bonfiglioli three-phase motor BX90S4 B5 3x230/400 +/-10%V 50/60Hz ISO F IP 55, 1.1 kW, 1430 rpm, 7.4 Nm motor flange 200mm, motor shaft 24mm IEC 60034-30:2008 "Efficiency classes for single-speed three-phase Squirrel cage asynchronous motors (IE code)" High efficiency, IE3 Die-cast aluminum version
W 86 U 40 P90 B5 B3	2G28012151 Bonfiglioli worm gear prepared for attachment of a three-phase motor W86U40P90B5B3 Design U slip-on hollow shaft 35H7x140mm Max. permissible continuous torque 330 Nm at n1 = 1400 rpm Max. permissible power 1.6 kW at n1=1400 rpm Reduction 40 Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
VF 49 P1 14 P80 B14 B3 RB	000680128 Bonfiglioli worm gear with IEC flange for engine mounting VF 49 P1 14 P80 B14 B3 RB Type P(1) slip-on hollow shaft 25H7x82mm Reduction 14 Max. permissible continuous torque 65 Nm at n1 = 1400 rpm Max. permissible power 0.9 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling Option RB second shaft end
W 63 UFC1 19	
W 63 UFC1 19 P90 B5 B3	2G20041251 Bonfiglioli worm gear prepared for attachment of a three-phase motor W 63 UFC1 19 P90 B5 B3 Design UFC1 flange short hollow shaft 25H7x120mm Output flange short dimensions=180x150x115 H8 mm Reduction 19 Max. permissible continuous torque 150 Nm at n1 = 1400 rpm Max. permissible power 1.4 KW Nm at n1 = 1400 rpm Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
W 63 U 24 P80 B14 B3	2G200115H1 Bonfiglioli worm gear prepared for Attachment of a three-phase motor W63U24P80B14B3 Type U hollow shaft 25H7x120 mm Reduction 24 Max. permissible continuous torque 155 Nm at n1 =1400 rpm Max. permissible power 1.2 KW Nm at n1 =1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
TA45.50/D İ:25 MOUNT POS:M.A INPUT SHAFTØ28 OUTPUT	SHAFTØ50
VF 49 P1 10 P71 B5 B3	200680061 Bonfiglioli worm gear with IEC flange for engine mounting VF 49 P1 10 P71 B5 B3 Type P(1) slip-on hollow shaft 25H7x82mm Reduction 10 Max. permissible continuous torque 59 Nm at n1 = 1400 rpm Max. permissible power 1.0 kW at n1=1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
W 86 U 30 P90 B5 B3	2G28011851 Bonfiglioli worm gear prepared for Attachment of a three-phase motor W86U30P90B5B3 Design U slip-on hollow shaft 35H7x140mm Max. permissible continuous torque 370 Nm at n1 = 1400 rpm Max. permitted power 2.4 kW at n1=1400 rpm Reduction 30 Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
A 41 3 UH45 184.4 P90 VA PV	2E67G012440002 Bonfiglioli bevel gear for mounting IEC standard motor A 41 3 UH45 184.4 P90 VA PV Design UH hollow shaft 45G7x186 mm Reduction 184.4 Max. permissible continuous torque 850 Nm at n1=1400 rpm Max. permitted power 0.74 kW at n1=1400 rpm Motor input P90 B5 Motor flange Ø 200 mm Motor shaft Ø 24 mm Installation

	position FA Cast steel primed with P1 alkyd resin base zinc phosphate including synthetic oil filling Option PV Viton sealing rings
MVF 49/P B3 i:14	Kod: 000680129
F603H60 P71 H5+VFL49P P71B14 + 0.37KW 4P	
W 75 U D30 100 P71 B5 B3 2G24013331	Bonfiglioli worm gear prepared for Attachment of a three-phase motor W75U D30 100 P71 B5 B3 Design U slip-on hollow shaft 30H7x127mm Max. permissible continuous torque 150 Nm at n1 = 1400 rpm Max. permissible motor power 0.40 KW at n1 = 1400 rpm Reduction 100 Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
A412UR	
VF 49 P1 07 P71 B14 B3...KW 21 (2)	200680039 Bonfiglioli worm gear with IEC flange for motor attachment VF 49 P1 07 P71 B14 B3 Type P(1) push-on hollow shaft 25H7x82mm reduction 07 Max. permissible continuous torque 54 Nm at n1 = 1400 rpm Max. permissible power 1.3 KW Nm at n1 = 1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF 44 P1 07 P71 B14 B3	200480038 Bonfiglioli worm gear with IEC flange for motor attachment VF 44 P1 07 P71 B14 B3 Type P(1) push-on hollow shaft 18H7x64mm reduction 07 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permitted power 0.71 KW Nm at n1 = 1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF 44 P1 10 P71 B14 B3	200480068 Bonfiglioli worm gear with IEC flange for motor attachment VF 44 P1 10 P71 B14 B3 Type P(1) push-on hollow shaft 18H7x64mm Reduction 10 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permissible power 0.51 KW Nm at n1 = 1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF44-P1-7-P71-B14-B3	
W/VF 86/150 F1 300 HS B3 CW1 15 20	C7215900230002 Bonfiglioli twin worm gears W/VF 86/150 F1 300 HS B3 CW1 15 20 Input shaft HS Ø 25h6 mm x 50 mm Design F1 with hollow shaft 50H7x175 mm Flange long 350/290/200 mm Total reduction 300 (15x20) Primed including synthetic oil filling W86 die-cast aluminium, VF 150 cast steel permissible torque 2600 Nm Installation position B3 Type CW1
W 110 UFC1 30 P100 B5 B6 2G32041866007	Bonfiglioli worm gear prepared for Attachment of a three-phase motor W 110 UFC1 30 P100 B5 B6 Design UFC Flange short push-on Hollow shaft 42H7x155mm Output flange dimensions=280x230x170H8 mm Reduction 30 Max. permissible continuous torque 700 Nm at n1 = 1400 rpm Max. permissible motor power 4.4 KW at n1 = 1400 rpm Motor input P100 B5 Motor flange Ø 250 mm Motor shaft Ø 28 mm Installation position B6 Die-cast aluminum, unpainted without oil filling
200680219	200680219 Bonfiglioli worm gears with IEC flange VF 49 P1 28 P71 B14 B3 Type P(1) slip-on hollow shaft 25H7x82mm Reduction 28 Max. permissible continuous torque 74 Nm at n1 = 1400 rpm Max. permissible power 0.55 kW at N1=1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 mm Installation position B3 Variable Die-cast aluminum, unpainted including synthetic oil filling
S 10 1 F 4.7 P63 B52	2F520218130001 Bonfiglioli spur gear with IEC_Motor input flange S10 1F4.7 P63 B52 Type F flange 160 mm, output shaft 14h6x30mm Reduction 4.7 Max. permissible continuous torque 12 Nm at n1=1400 rpm Max. permitted power 0.38 KW at n1=1400 rpm Motor input P63 B5 Motor flange Ø 140 mm Motor shaft Ø 11 mm Installation position B52
	2G26014536 Bonfiglioli helical worm gear prepared for cultivation of one

W R 75 U D30 300 P71 B5 B6	three-phase motor W R 75 U D30 300 P71 B5 B6 Type U hollow shaft 30H7x127 mm Reduction 300 Max. permissible continuous torque 180 Nm at n1 = 1400 rpm Max. permissible power 0.20 KW Nm at n1 = 1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B6 Die-cast aluminum, unpainted including synthetic oil filling
VF 44 P1 07 P71 B14 B3	200480038 Bonfiglioli worm gear with IEC flange for motor attachment VF 44 P1 07 P71 B14 B3 Type P(1) push-on hollow shaft 18H7x64mm reduction 07 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permitted power 0.71 KW Nm at n1 = 1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF 44 P1 10 P71 B14 B3...KW 22 (1)	200480068 Bonfiglioli worm gear with IEC flange for motor attachment VF 44 P1 10 P71 B14 B3 Type P(1) push-on hollow shaft 18H7x64mm Reduction 10 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permissible power 0.51 KW Nm at n1 = 1400 rpm Motor input P71 B14 Motor flange Ø 105 mm Motor shaft Ø 14 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF44-P1-10-P71-B14-B3 REDUCER	
C 70 F 8.0 P200 B5	
VF 49 P1 100 P63 B14 B3	200680427 Bonfiglioli worm gear with IEC flange for motor attachment VF 49 P1 100 P63 B14 B3 Type P(1) push-on hollow shaft 25H7x82mm Reduction 100 Max. permissible continuous torque 49 Nm at n1 = 1400 rpm Max. permissible power 0.13 KW Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange Ø 90 mm Motor shaft Ø 11 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
VF 44 P1 28 P63 B14 B3	200480159 Bonfiglioli worm gear with IEC flange for motor attachment VF 44 P1 28 P63 B14 B3 Type P1 slip-on hollow shaft 18H7x64mm Reduction 28 Max. permissible continuous torque 39 Nm at n1 = 1400 rpm Max. permitted power 0.29 KW Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange Ø 90 mm Motor shaft Ø 11 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
GEARBOX MVF44/P 1:28 PAM71 B14	
VF 44 P1 20 P63 B14 B3	200480129 Bonfiglioli worm gear with IEC flange for engine mounting VF 44 P1 20 P63 B14 B3 Type P(1) slip-on hollow shaft 18H7x64mm Reduction 20 Max. permissible continuous torque 39 Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange 90mm, motor shaft 11mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
BE 63A 4 230 /400-50 IP54 CLF B14 FD 3.5 230 SD	
VF 44 P1 70 P63 B14 B3 BE 63B	4 230/400-50 IP55 CLF B14
JB00022471	X_BXT 71C 6 230/400-50 IP55 CLF B14 TP
LC12106S540002	LC 120 1 10 STD 110B1 CD 22 KE
VF 49 P1 10 P80 B14 B3	200680068 Worm gear with IEC flange for engine mounting VF 49 P1 10 P80 B14 B3 Type P(1) slip-on hollow shaft 25H7x82mm Reduction i=10 Max. permissible continuous torque 59 Nm at n1 = 1400 rpm Max. permissible power 1.0 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
	200680068 Type P(1) slip-on hollow shaft 25H7x82mm Reduction i=10

VF 49 P1 10 P80 B14 B3	Max. permissible continuous torque 59 Nm at n1 = 1400 rpm Max. permissible power 1.0 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
VF 49 P1 10 P80 B14 B3	200680068 Bonfiglioli worm gear with IEC flange for motor attachment VF 49 P1 10 P80 B14 B3 Type P(1) push-on hollow shaft 25H7x82mm Reduction i=10 Max. permissible continuous torque 59 Nm at n1 = 1400 rpm Max. permitted power 1.0 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
VF 49 U 10 P80 B14 B3	200640068 Bonfiglioli worm gear with IEC flange for engine mounting VF49U10P80B14B3 Design U universal with hollow shaft 25H7x82mm Reduction i=10 Max. permissible continuous torque 59 Nm at n1 = 1400 rpm Max. permissible power 1.0 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
W 75 U D30 7 19/140 B3	2G240103H1015 Bonfiglioli worm gear prepared for attachment of a three-phase motor W 75 U D30 7 19/140 B3 Design U slip-on hollow shaft 30H7x127mm Max. permissible continuous torque 190 Nm at n1 = 1400 rpm Max. permissible motor power 4.4 kW at n1 = 1400 rpm Reduction 7 Motor input P90 B14 Motor flange Ø 140 mm Motor shaft Ø 19 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
3 05 L 2 22.7 HC 4L S5AP A	2T305L20220068 PLANETARY GEAR - 3 05 L 2 22.7 HC 4L S5AP A PLANETARY CYLINDRICAL SOLID OUTPUT SHAFT WITH KEY Pam Danfoss OMP-OMR 50-315 d25 Brake 4L Pam White HS-02-15 SAE A d25 Pam White RS-08-24 SAE A d25 Pam torque motor MAB d25 A Horizontal installation position Cast steel primed without oil filling
WMF1020150012	
C 36 3 P 62.0 S2 B6 ME 2SA 4 230/400-50	IP54 CLF W 30 FD 15 NB 230 SA MEA401260010 C 36 3 P 62.0 S2 B6 ME 2SA 4 230/400-50 IP54 CLF W 30 FD 15 NB 230 SA Type P foot, output shaft 35h6 x70 mm Reduction 62.0 Speed: 22.6 rpm Torque: 295 Nm Service factor 1.5 Highly efficient IE2 three-phase brake motor ME 2SA 4 230/400-50 IP54 CLF W 30 FD 15 NB 230 SA PN = 0.55 kW Euro voltage GS Brake braking torque 15 NM half-wave rectifier 230 V D.S. Separately- brake supply voltage COMPACT GEAR MOTOR
A 35 2 UH40 65.8 S3 VB MX 3SA 4	230/400-50 IP54 CLF W 30 FD 26 NB 230 SA ME6A0660040 Bonfiglioli bevel gear brake motor A 35 2 UH40 65.8 S3 VB MX 3SA 4 230/400-50 IP54 CLF W 30 FD 26 NB 230 SA HOLLOW OUTPUT SHAFT WITH KEYWAY OUTPUT SHAFT DIMENSION(DXL)= 40X177 mm IE3 Efficiency Premium engine MX 3SA 4 230/400-50 IP54 CLF W 30 FD 26 NB 230 SA PN = 1.1 kW Euro voltage GS Brake braking torque 26 NM half-wave rectifier 230 V D.S. Separately- brake supply voltage COMPACT GEAR MOTOR
LC 120 1 10 STD FM CD 32 KE	LC12106SFM0005 TECHNOINGRANAGGI Planetary gear LC 120 1 10 STD FM CD 32 KE
MVF 72 P i:1/60	SUA_609C_3A_71-04F-TH-TF
TARE A60 2 UR C4	CODE 08060703 MOUNT POS B i=20.6 With engine with M4LB4FD H1 CODE 8673020178 214/15 HZ 50 ip54 N°6063340 Kw 9.2 Min-1 1445 I.cI F S1 D3 70,2 230/400+-10%
TR 130 1 10 STD 130A1 CD 32 S1 OR SB KE	TRF2012S0006 TECHNOINGRANAGGI planetary gearbox TR 130 1 10 STD 130A1 CD 32 S1 OR SB KE Angle play 5' type of motor coupling Clamping device Continuous Service Horizontal installation position Output shaft support Output shaft without feather key
W R 110 UFC1 240 P80 B5 B3	2G34043341 Bonfiglioli spur gear worm gearbox prepared for cultivation of one three-phase motor W R 110 UFC1 240 P80 B5 B3 UFC flange short push-on design Hollow shaft 42H7x155mm Output flange dimensions=280x230x170H8 mm Max. permissible continuous torque

	560 Nm at n1 = 1400 rpm Max. permissible motor power 0.61 KW at n1 = 1400 rpm
BG3 VCB 400-115 OL 1.2 EAL-1	VCB 400-115 OL 1.2 Bonfiglioli frequency converter 3 x380-460V +/-10% 50Hz, Overload 20% 60 sec Rated current, 115 A, 55 kW HxWxD 602x300x298 Protection class IP20
BN90LA4	
W75 UD30 P90B14 1,5 kBT 1400 o6.	
VF49 F1 100 P63 B14 B3	CODE 200650427 VF 49 P1 100 P63 B14 B3 200680427 Bonfiglioli worm gearbox with IEC flange for Engine attachment VF 49 P1 100 P63 B14 B3 Design P(1) slip-on hollow shaft 25H7x82mm Gear ratio 100 Max. permissible continuous torque 49 Nm at n1 = 1400 rpm Max. permissible power 0.13 KW Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange Ø 90 mm Motor shaft Ø 11 mm Installation position B3 / variable Die-cast aluminum, unpainted
Screw flange F for VF49P/VFR49P	194000108 Screw flange F short for VF49P/VFR49P Flange dimensions 125/90/70H8 mm short Mounted in terminal box position W
3 03 L 4 2243 MC P71 T	2T303L4M43003 Planetary gear 3 03 L 4 2243 MC P71 T Design cylindrical output shaft 60x105 Gear ratio 2243 Motor input P71 B5 Permissible torque 2000 Nm Primed cast steel Installation position T Vertical installation position and output shaft below without oil
3 03 L 4 2243 MC P71 T	Reducer Connection: P71 - Metric Motor Adaptor IEC 71 Equipment code TEM-TK-12 Installed Power (kW): 0,25
A 50 3 UD 109.4 P90 VA LO	2E70E042440001 Bonfiglioli bevel gearbox for attachment IEC standard motor A 50 3 UD 109.4 P90 VA LO Design UD double-sided shaft 50h6x82mm Reduction 109.4 Max. permissible continuous torque 1500 Nm at n1=1400 rpm Max. permissible power 2.2 kW at n1=1400 rpm Motor input P90 B5 Motor flange Ø 200 mm motor shaft Ø 24 mm Installation position VA Cast steel primed with P1 alkyd resin base Zinc phosphate Option LO with synthetic oil filling
LC 070 1 5 STD 40C CD 8 KL	
C 22 2 F 3.7 S3 B5 MX 3SB 4 230/400-50	IP55 CLF 20W MEA70232003J Bonfiglioli spur gear motor C 22 2 F 3.7 S3 B5 MX 3SB 4 230/400-50 IP55 CLF 20W Flange design 160/130/110f7 mm, Output shaft 25h6 x50 mm Gear ratio 3.7 Speed: 386 rpm Torque: 35 Nm Motor MX3 SB4 IE3 3x230/400 +/-10% V 50/60 Hz ISO F IP 55, 1.5 kW, 1445 rpm, Installation position B5 Terminal box position W Die-cast aluminum version unpainted including oil filling
VF 30 F1 10 P63 B14 B3	200350069 Bonfiglioli worm gear for motor attachment VF 30 F1 10 P63 B14 B3 Type F flange with hollow shaft 14H7x55mm Flange 80/68/50H8 mm Gear ratio 10 Max. permissible continuous torque 16 Nm at n1 = 1400 rpm Max. permissible power 0.3 KW Nm at n1 = 1400 rpm Motor input P63 B14 Motor flange Ø 90 mm Motor shaft Ø 11 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
W R 86 U 120 P80 B5 B3	2G30013941 Bonfiglioli spur gear worm gearbox prepared for cultivation of one three-phase motor W R 86 U 120 P80 B5 B3 Design U hollow shaft 35H7x140 mm Gear ratio 120 Max. permissible continuous torque 390 Nm at n1 = 1400 rpm Max. permissible power 0.72 KW Nm at n1 = 1400 rpm Motor input P80 B5 Motor flange Ø 200 mm motor shaft Ø 19 mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
VF 49 P1 14 P80 B5 B3	200680123 Bonfiglioli worm gear with IEC flange for motor mounting VF 49 P1 14 P80 B5 B3 Design P(1) hollow shaft attachment 25H7x82mm Gear ratio 14 Max. permissible continuous torque 65 Nm at n1 = 1400 rpm Max. permissible power 0.9 kW at n1=1400 rpm Motor input P80 B5 Motor flange Ø 200 mm motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling

VF 49 A 14 P71 B5 B3	200620121 Bonfiglioli worm gear with IEC flange for motor mounting VF49 A 14 P71 B5 B3 Design A foot with hollow shaft 25H7x82mm Gear ratio 24 Max. permissible continuous torque 63 Nm at n1 = 1400 rpm Max. permissible power 0.9 kW at n1=1400 rpm Motor input P71 B5 Motor flange Ø 160 mm Motor shaft Ø 14 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
VF 44 F1 10 P63 B5 B3	200450061 Bonfiglioli worm gear with IEC flange for motor mounting VF 44 F1 10 P63 B5 B3 Type F short flange with hollow shaft 18H7x55mm Flange F short 110/87/60H8 mm Gear ratio 10 Max. permissible continuous torque 29 Nm at n1 = 1400 rpm Max. permissible power 0.51 KW Nm at n1 = 1400 rpm Motor input P63 B5 Motor flange Ø 140 mm Motor shaft Ø 11 mm Installation position B3 / variable Die-cast aluminum, unpainted including synthetic oil filling
W R 75 U D30 120 P80 B5 V6	2G26013345 Bonfiglioli spur gear worm gearbox prepared for cultivation of one three-phase motor W R 75 U D30 120 P80 B5 V6 Design U hollow shaft 30H7x127 mm Gear ratio 120 Max. permissible continuous torque 305 Nm at n1 = 1400 rpm Max. permissible power 0.59 KW Nm at n1 = 1400 rpm Motor input P80 B5 Motor flange Ø 200 mm motor shaft Ø 19 mm Installation position V6 Die-cast aluminum, unpainted including synthetic oil filling
4001-1000193915	REDUCER
MPMB105315STD110A1C	reducer
A202 UH35 35.4	
v49 p71 b14-HS BATCH 07/04-B3-i:45	
Flange bearing shield A BN/BE/BX132 B5	614260274
309L 316 2HCP160TS081A	
W86U P90B5	
W 63 U 10 HS B3	
W63U15P80	
VF 49 N 14 P80 B14 B3	200610128 Bonfiglioli worm gear with IEC flange for motor mounting VF 49 P1 14 P80 B14 B3 Design P(1) hollow shaft attachment 25H7x82mm Gear ratio 14 Max. permissible continuous torque 65 Nm at n1 = 1400 rpm Max. permissible power 0.9 kW at n1=1400 rpm Motor input P80 B14 Motor flange Ø 120 mm Motor shaft Ø 19 mm Installation position B3 variable Die-cast aluminum, unpainted including synthetic oil filling
192620200	Screw base A,N,V VF49P/VFR49P Contains 2 pieces! Screw base A,N,V VF49P/VFR49P for Conversion VF/VFR 49 P in version A,N,V
BE 80A 4 230/400-50 IP55 CLF B14	8U0203000V Bonfiglioli three-phase motor BE 80 A4 B14 3x230/400 +/-10% V 50/60 Hz ISO F IP 55, 3x 230/400V +/-10% V 50 Hz ISO F IP 55, 0.55 kW, 1380 rpm, 3x 265/460V +/-10% V 60 Hz ISO F IP 55, 0.66 kW, 1670 rpm, Motor flange 120mm, motor shaft 19 mm Die-cast aluminum version Unpainted Energy class IE 2 Dimensions identical to corresponding IE 1 motor BN80 A4
W63U38 P80	
VF 110 FC1 P100B5 İ	
Bn 71b 4 Fa B14	
Bn 80 B4 0,75kw 4p B5 230/400/50 Ip54 Clf. Ba	
Ran-20-S-A-1-Hs-B3	
Vf 63 A 30 P80 B5 B3, Code: 003120242	

Vf 130 Fc1 7 Hs B	
Qazj1001-Hb	
Type:Mas 25/F210650243..	
Iec-Motor Bn 63a 4 230/400-50 Ip55 Clf B5	
Be90 S4 1.1kw 4p B5	
Vf 130 P1 23 P132 B5 B3	
Bn71a4	
15 Kw- 4p- Ip55-B5-400v-50hz	
145061030a	
Vf 30 F1 40 P63 B14 B3	
W63 U P71b5 B3	
F41 3 H45	
Mvf 86/P 1/23 Pam 100	
Mvf 86/F 1/80 Pam 80	
Bn 80b 6 230/400-50 Ip55 Clf B5	
W 63 U 100 P80 B5 B3 (2g20013341)	Bonfiglioli worm gear prepared for Installation of a three-phase motor W 63 U 100 P80 B5 B3 Type U slip-on hollow shaft 25H7x120mm Max. Permissible continuous torque 115 Nm at n1 = 1400 rpm Reduction 100 Motor attachment P 80B5 Motor flange 200mm, motor shaft 19mm Installation position B3 Die-cast aluminum, unpainted including synthetic oil filling
2t305r30540000	
Vf 130 Fc1 80 P100/112 B5 B3	
Vcb400-090	FREQUENCY INVERTER VCB 400-090, SPECIAL PRODUCT
10316943 I=1/15 W 86-U-Hs-B7	
Mvf 44/F 1/14 Pam 71	
Acu40125a	
Vf 130 P1 64 Hs B3	
Bc 120 - 24-2700-240 63/B5	
C51	
Kr30506fm0002 / Kr 030 5 Std H Fm Cd 24 St U/S	
3/Hdo 17 Coppia Nm 175000	
14-200-313	
Bn71b42/3b5	
Type:Mas 25/F210650243 , C 22 2 Ufc 14.5 P80 B5	
2ea 702520003	
Mas25p	

A 50 3 Uh50 89.5 P100/112 B3	
Bni00la4 By 8u12030001	
Krg-15 55kw/1500 D/Dak	
Mvf 86/N 1/15 Pam 100	
Vf 130 F1 56 P100/112 B5 B3	
A413 Uh40 I 184,4 P 80 B3	
Vf 130 Fc1 40 Hs B3	
329.79x3.53 279 715303261	
A 70 3 Uh70 23.5 P180 B3	
Acu401-43a	SERVO INVERTER
Vf 130 Fc1 40 P100/112 B5 B3	
707 T N1ne1 A 188 E0wc X L1	
Mvf 44/N 1/60 Pam 63	
711c 5quot; D185 F13-30 6635060080	
Lc 090 2 100 Std 95a Cd 11 KI	
Vf 130 P2 80 P90 B5 B8	
Mvf 86/N 1/10 Pam 100	
Mvf 44/N 1/70 Pam 63	
Vf 130 Fc1 64 P90 B5 B3	
8g56020082	
Dt399,4 C360 713cb 6660800230	
Ran25/Sa1/1	
3 13l4 352 Fz P180 A	
Bra400060bf2	INVERTER
A 102 Uh25 7,2 Pam 71 B3	
200250061, Vf 27 F1 10 P27 B3	
Vf 130 P1 7 P132 B5 B3	
Code: Ve10c01110015, Type: V0,25 Fd 11 P63 V0 B3	
30 2 Nuh 59.4 N140tc B3	
C 22 2 Ufc 14.5 P80 B5	
Be 100lb 4 B5	
Clb 90x110x12 DI Nbr (Code 710308650)	
Vf 130 F1 64 P100/112 B5 B3	
P71b5b3+bn71b4-Fdr	
Vf 130 P1 46 Hs B3	

30513276pcs3e
11302885
Bn 44c 4 0,09 Kw
Vf 130 P1 7 Hs B3
Vf 30 P1 20 P56 B14 V6
Vf 49 P1 14 P63 B5
3/Hdo 16 Coppia Nm 130000
Vf 30 N 15 P63 B14
Vf 130 Fr1 30 P132
Mvf 49/N 1/10 Pam 80
31114724fzp160
3 05 R 3 54.2 Hc P132 P1
Vf 30 P1 30 P71 B5 B14
Vf49 P - P71 B14
Bn71b4
Mvf49 F/Pam
3 11 R 2 27.0 Fz Sf B1 S044a Ra
C 22 2 F 24.3 P90 B5
Vfr 150 P1 300 P90
W63
Vfr 130
Vf 130 F1 7 P132 B5 B3
Lcvt034
830321000
C413 P 64,3
B-Mvf49
2010996
Vfr 44 F1 350 S44 B3
Mvf 49/N 1/28 Pam 71
307 R3 120 Hz P160 B0 W0a Lo Pv
C1121p60-2eo3022132
C 212 U 26,7 Pam 80 B5
W201480392500017
Ve14b06010002
Wme52i0450020
A 60 3 Uh60 156.0 P100/112 B3

3/Hdo 21 Coppia Nm 615000	
Vf 130 P1 56 Hs B3	
A 20 2 Uh30 63.1 P90 Va Vv	
C514p263.8p80	
W 86	
Mvf 49/N 1/70 Pam 63	
183.52x5.33 Pk 2-366 715307366	
Mt305I32702j	
C212 F 21.9 S1m1la4	
Bn71b4 230/400-50 Ip55 Clf B5w	
Vf 130 Fc1 40 P132 B5 B3	
C412 P-P100	
Mvf 86/N 1/64 Pam 80	
W63u38p71b5	
V10-F-D38-P132-V5-1	
Mvf 63/N 1/100 Pam 71	
Vf 30 F1 10 P63 B14 B3	
Tr 080. 2. 16. 3 . 19.40.80.100.S1.Ar	
306 L 4 2916 Fz Sf Hoaa T	
8u0303001d	
Bn 71a 2 B5	
10315341 I=1/15 W 86-U-Hs-B7	
Vf 27, Nr:12.500.001	
2t305I2038015	
Mp 080 1 4 Std 50d Cd 14 S5 Or Sb Ke	Planetary gear MP MP 080 1 4 STD 50D CD 14 S5 OR SB KE old MP 080.1.4.15'.14.30.50.95
Vr375 Fp 77901	
Mt306I2050ao	
Bn 80a 4/8 400-50 Ip55 Clf B14	
Vf63fc45p80	
Kmag-170vp-1	
Lc-090-2-15-Std-80a1-Cd-19-Kl	
C302f5op112b5	
Nrao 45/Dn Hp 1	
Mt305I4d701l	

Vf63fc	
830720156	
A 202 Uh30 P90 W 7024/1000 By A 20 2 Uh30	
63.1 P90 Va Vv	
1le1003-1ab52-2fb4-Z F70 Kw3 4p B5	
1la7073-4ab11	
Mvf 86/F 1/10 Pam 100	
C112 F 13.4 S1m1la4	
Acu 401	
Ran24/D B R1/1	
Mgsd/Omrs 160 1t213167000	
3/Hdo 15 Coppia Nm 98000	
Ts56a4	
Mvf 44/P 1/46 Pam 63	
Mvf44a R20 Pam71b5	
Vf 130 P1 40 P100/112 B5 B3	
Mvf 30/F 1/60 Pam 63	
Mvf 49/F 1/18 Pam 71 B14	
2t301l2012101	
Vf 130 Fc1 46 P100/112 B5 B3	
Vf88/N-100b3	
C412 P100 Code:2e1 501 1851	
C 212 P S2 W B3	
Vcb400-180	FREQUENCY INVERTER
Vf49 F1 7 P71 B5 B3	
VF 130 FC1 30 P132 B5 B3	201460216 Bonfiglioli worm gear prepared for Attachment of a three-phase motor VF 130 FC1 30 P132 B5 B3 Design FC1 flange short 320/255/180 mm hollow shaft (dxl) = 45H7 x165 mm Reduction 30 to. Torque (at n1 = 1400 rpm) 1050 Nm Max.permissible power 6.6 kW at n1 = 1400 rpm Motor input P132 B5 Motor flange Ø 300 mm, motor shaft Ø 38 mm Installation position B3 Cast steel primed with P1 alkyd resin base Zinc phosphate without synthetic oil filling
C052-11.2 S05 M05a4	
Vf86	
Fd03	
F803 H90 45.3 P160 H5	
309l13.43hcpama2f	
Rao 50/Dc	
Vf86/N100b3h5	
P14500tr/2si	

W63u Hs	
Mfb90sc4b	
K71 B2 No:802300 Obsolete	
Vf49f114p71b5kw025	
I=1/15 W 86-U-Hs-B7 Rb	
Vf 49 P1 80 P63 B14 B3	
Mp 060 (Code Mpb1006s001u)	
Mvf86p180-Hp1	
301 R3 - Hc - 85,2	
3/Hdo 23 Coppia Nm 830000	
Vf 130 Fc1 7 P132 B5 B3	
W86?Ufc1?Xx?P80?B14?B3?2d3d-130	
A 41 3 Uh45 146.9 P90 B3 Vv	
A 102 Uh25 12,3 Pam 71 B3	
C323 F 74.4	
Vf 44 F1 28 P63 B5 B3	200450151 Bonfiglioli worm gear with IEC flange for motor mounting VF 44 F1 28 P63 B5 B3 Type F1 short flange with hollow shaft 18H7x55mm Flange F short 110/87 / 60H8 mm Reduction 28 Max. Perm. Permanent torque 39 Nm at n1 = 1400 rpm Motor input P63 B5 Motor flange 140mm, motor shaft 11mm Installation position B3 variable Die-cast aluminum, unpainted Incl. synth. oil filling
Vf 130 P1 30 Hs B3	
Vf 130 Fc1 80 Hs B3	
309r219.8hzsfe2aab0 2t309r2019004 B2	
Mvf 44/F 1/46 Pam 63	
Vf 130 F1 23 P132 B5 B3	
Vf 130 P1 64 P100/112 B5 B3	
A 41 2 Uh45 F1a 71.3 P90 B3	
F40 2 H45 29,9 P100	
830820105-E42349	
509008005	DRIVE
Bn63 A4 230/400-50 Ip-55 Clf B14	
A 102 Uh25 18,6 Pam 63 B3	
Bn 132mb 4 Fd	
Vf 63 P1 10 P90 B5 B3	
Vf 130 F1 40 P132 B5 B3	
Bn 112m 4 Fd, 352988	

603414000	INVERTER
8g55020**4	
W63u38	
Worm For Vf 130p1p100b5lo	
Vf30 F1 60	
W 63 L1 Ufc1 7 P80 B14 B6	
Mvf 72/Fc 1/7 Pam 90 B14	
Mvf 86/Fc 1/23 Pam 100	
Ran20da	
F70 3 H70 196 P100	
A603-34.3s4	
W 75	
Siact515010001	INVERTER
A 90 3 Ur Hs	
W1281a70300001 B3-3	
Bc 240-110-1500-200	
Bn 132s 4 230/400-50 Ip55 Clf B5 S1ot	
C052-11.2s05m05a4	
Mvf 44 P	
W 110 U 80 P80 B5	
Mvf 44/F 1/20 Pam 63	
F25 2 H40 36,4	
2e67q009410017	
310 L 2 38,6 Fz P160 A	
A 102 Uh25	
A 102 Uh25 13,9 Pam 90 B3 Pv	
Vf 49 P1 28 P71 B14	
Ad71c4/8+mvf72/Pd30	
A 503 Uh 50 40.9 S3 B3 Lo-M3lb 4 230/400-50 Ip55 Clf	
P112b5b3+bn-Fdr	
C 112 P 13,4 Pam 80 B3	
71428001	
Vf 130 Fc1 56 P100/112 B5 B3	
Vf 44 P I=46 P63	
Vf 49 P1 60 P71 B5 B3	
Vbd0,5fp71b5v5/2	

Be 100la 4 B5 Kw 2,2	
Me2301300001	
Fb80I2	
Bn 63b 4 B5	
Code: G00450090031, Type: Vf44 F1 P63 B5	
Vf 130 Fc1 23 P132 B5 B3	
830n2410m	
2132613641	
Sb710210013	
C35 3 P S2w	
Vf 130 P1 80 P100/112 B5 B3	
Vf 130 Fc1 56 Hs B3	
Mvf 86/F 1/100 Pam 80	
301 L2 Fz Sfs5aqa	
Mvf 49/A 1/10 Pam 80 B 14	
Bn71b2 Hp:0.75	
C403 P S3 5378/1000, Cod:Me1601030036	
Mvf 86/N 1/23 Pam 100	
Ran 28 D A 1 Hs B3	
BX 100LA 4 B5	3x230 / 400 +/- 10% V 50/60 Hz ISO F IP 55, 8AFC40007 Bonfiglioli three-phase motor BX100LA4 B5 3x230 / 400 +/- 10% V 50/60 Hz ISO F IP 55, 2.2 kW, 1430 rpm, 14.7 Nm, motor flange 250mm, motor shaft 28 mm IEC 60034-30: 2008 "Efficiency classes for single-speed three-phase Squirrel cage induction motors (IE code) " High Efficiency, IE3 Die-cast aluminum design Unpainted
Type Bn80 A4 Motor For W86 P80 B14	
A412 Uh45 I 17,8 P 100 B3	
Mvf86/P- Pam80	
Hdo100 3 Lp R 1 Vp	
714285019	
Be 80b 4 230/400-50 Ip55 Clf B14	
Mvf 49/N 1/10 Pam 63	
Wr75u	
306I2-46.5-Pc-Sa E M4Ia4	
200680337	
303 M2c 1-24	
Mvf63p	

3/Hdo 18 Coppia Nm 260000	
W 110?Ufc1?Xx?P90?B14?B6?2d2d-130	
Vf 130 F1 30 P132 B5 B3	
A102uh25	
C20 3p 261.0 S1 B3m 1sd 4 230/400-50 Ip55 Clf W Red	
Rs485	
Mvf30a	
F603 H60	
Spl200 03f	
Kg2401300	
714285042	
Vf 130 P1 80 P90 B5 B8	
W 75 U30	
Bn71b4 230/400-50 Ip55 Clf B14 P=0,37kw N= 1370 Motor	
Vf 49 F2 7 P71 B14 V5	
Type: Act 401-23a	
Ran38/Sa	
612501015	
C402 P100 Code:2e1 401 365	
Ran20/Sb2 127220060 Mount Pos.B3	
Lc 120 1 10 Std 110b Cd 19 Ke	TECHNOINGRANAGGI Planetary transmission LC 120 1 10 STD 110B CD 19 KE Serial: C121 B-003228
Pulley For Bn 63b 4 Cod. 830520156	
Be 100 Lb4 3kw 4p B5 Ie2	
Mvf 86/A 1/80 Pam 80	
Vf49 L1 N P71b14	
Type Be90 La4 Motor For W110 P90 B14	
3ool2 18.2pcsfs Sapf	
Bonfiglioli-Anbauflansch-F3;R-Vf49-Fi-Hs- Obsolete-Alternative-612501015-Istanbul- Turkiye	
Bn 71b 4 Ba B5	
Vf-150p2-100-Hs-B8	
Vf 130 Fc1 46 Hs B3	
Bn 71a 4 B5	
605551652	SOLAR INVERTER MODULE AEC500-50A IN1000V DC 340A

Bomvf44a466314 + Bobn63b4b14	
C322 P26,9	
Mas60/Dp	
Bn-100-L-A-4-Fb	MOTOR 3KW 230/480V 60HZ
Vf 130 Fc1 23 Hs B3	
Bn 71a 6 230/400-50 Ip55 Clf B5	
1390rpm	
Mvf 49/F 1/10 Pam 80	
400-034	
30312 24hc	
W086 U Rel. 1/30 Pam 71b5	
Bn80a4 Kw 0,55 4p B5	
Be 100la 4 230/400-50 Ip55 Clf B5	
Vf 130 P1 46 P100/112 B5 B3	
Lc 120 2 100 Std 95a Cd 14 Kl	
Vf86 Fc2 46 Hs B7	
Bra-400-034-Bf1	INVERTER FREQUENCY
Bn 80b 4/8 400-50 Ip55 Clf 14	
Bc 220 - 24-3000-280 63/B5	
W 86 U 15 P100 B5 B8	Bonfiglioli worm gear prepared for Attachment of a three-phase motor W 86 U 15 P100 B5 B8 Type U slip-on hollow shaft 35H7x140mm Max. Permissible continuous torque 330 Nm at n1 = 1400 rpm Max.permissible power 3.8 kW at n1 = 1400 RPM Reduction 15 Motor input P100 B5 Motor flange Ø 250 mm, motor shaft Ø 28 mm Installation position B8 Die-cast aluminum, unpainted
Lck-070-2-10-Std-60a1-Cd-14-Ke	
309 L1 3.43 Hc Pam A2f 1000 A	
Act 401 25 A	
P/N: 200650151 Type: Vf49 F1 P7 Ib5	
303 L3 77,2 Fz Sf Hoaa A	
Vf 130 P1 30 P132 B5 B3	
305 R3 78.7 Hz P132 B0 W0a Lm Pv	
Vf 130 Fc1 64 Hs B3	
Vf 110 Fc1 15 Hs B3	
Bn 56b 4 B14	
Bn920lb4	
Bn 80b 6 230/400-50 Ip55 Clf B5-	
Bn180m4b5	

Mvf 86/F 1/23 Pam 100
Vf 44 F1 7 P63 B5 B3-
A 60 3 Ur 34.3 P160
3/Hdo 25 Coppia Nm 1200000
C 51 3 P 79.9 P100/112 V6
F413 H45
Mvf63a
Mvf 49/V 1/70 Pam 63
A 10 2 Us 7.2 S1 Vb/M 1sd 2 0,55 Kw W/Code Me529006001c
714280127
Mvf 30/P 1/40 Pam 63 B14
Vf 130 P1 40 P132 B5 B3
830c2110m
Mt303I2050dc
Mas 20p
C 41 2 P 12.4 P132 **
Vf 130 P1 40 P100 B5 Lo, Code: 20148024150032
Bn 63b 4 230/400-50 Ip55 Clf B5 Code: 830520106
C 12 2 P 6.2 P71 V6
Vf 130 P1 56 P100/112 B5 B3
A50 Fa
Mvf 63/F 1/64 Pam 71
Repair Kit For Vf 49 F2 7
Vf44 P28
2t301I2024047
P90b5b3
W 86 U 64 P80 B5 B3-
Krg-12 22 Kw /1500 D/Dak.
Mvf49a R7 P80
831020156
306 R4 214 Hz P132 B0 W0a Lh Pv
2e52a027310004
Vf 30 A 15 P63 B5 B3
Vf 130 F1 46 P100/112 B5 B3

Vf 130 P1 40 Hs B3	
Vf 130 Fc1 64 P100/112 B5 B3	
Vf 49 F1 14 P71 B5 B3-	
Lc-090-2-15-Std-80a1-Cd-19-Ke	
3 11 R 2 27.0 Fz Sf B3 S043a Ro	
Vcb400-300	FREQUENCY INVERTER
2024109	
Vf44f17p63b5kw018	
Type: Tr 130 2 20 Low 95a1 Cd 24 S1 Or Sb Kl Code:Tre2020I0003	
Vf30 P1 10 P63 B14 B3 (Code M00380060003)	
W 75 U D30 80 P80 B5 B3	
Vf 130 F1 80 P100/112 B5 B3	
Upper Bearing Housing For:305 L3 Mz	
2t709t4va79a	
Vf185	GEAR REDUCER 1:100RATIO 9/16INCH FLANGE INPUT
148.59x5.33 Pk 2-360 715307360	
F25 2 H40 40,7	
Ls 80 Lt, No:L260220pa054	
W63 P80b14	
Tr 105 2 40 Std 80	
Flanschkit Vf 30 F Code: 194000103	
21166116a0001	
Vf 130 P1 80 Hs B3	
Muf63f	
A503 Uh50 P112	
Vfr 150	
Bn-100-L-A-4-Fd	MOTOR 3KW 230/480V 60HZ
300 R4 291 Fz P80	
?Sm 2043596 Gtcao 60x43d13	
W8f60020575	
Vf 130 Fc1 7 Hs B3	
300 L2 41.5 Hc P90	
Vf 130 Fc1 30 Hs B3	
Input Drive Assembly For: 305 L3 Mz	
Vf 130 P1 23 Hs B3	
3/Hdo 19 Coppia Nm 440000	

Mvf 86/N 1/80 Pam 80
Boc112f4
Vf150f2 30p132 B5 B3
Code:W1281a70300001 B3 -3
700 Tw
30 Kw Rs 232 Bra 400-060 Bf2
300r2
Vf49f114p71b5
8u12030001 (Be 100 La4 Clf B5)
Mvf49-P1-P63b
100b5kw3+a603uh60f1
Bn80a6
Mvf 49/N 1/14 Pam 80 B14
710210013
71428021
Mvf 63/P 1/80 Pam 71
Mvf 44/F 1/20 Pam 63 B14
Ss 126 C
Mvf44f
W 110 U 15 P100 B5 B3
Vf86 Fc2 23 Hs B7 Rb