

Cavotec

Garanti: 12 ay
Bu ürüne ait Türkiye
içi kapı teslim fiyat
ve teslim süresi
içeren teklifimizi
almak için
info@yursat.com.tr
e-posta adresine
başvuru yapabilir ya
da ayrıntılı bilgi için
+90 224 240 03 04
numaralı
telefonumuzdan
bizlere
ulaşabilirsiniz.
Cavotec Markası,
tedarik süresi için
lütfen bizimle
iletişime geçiniz.

*Firmamız Cavotec Türkiye
Distribütörü veya temsilcisi
değildir. Firmamız sipariş
durumunda, belirtilen
ürünlerde sadece Orjinal ve
yeni ürün teklifi
sunmaktadır. Bu sitede
gösterilen Özel marka adları
ve ticari markalar ilgili
sahiplerinin
mülkiyetindedir, talep
durumunda
kaldırılmaktadır.*





Ürün	Açıklama
GSK 50-18/58-18/180/DV/Hz	A00-14-LT0009 Slip ring assembly with housing 17x 25A + PE, 600V - Ms / Cu gap 16x 16A + PE, 24V - Ms / Cu with heating 110V, 20W (mounted in the housing) SRK for use down to -25 ° C Wiring of the rings with special cables - 2.0m Lapp Ölflex FD 855 CP 18x2.5mm² (power rings) Shield connected to PE Lapp Control TM 18x1.0mm² (data rings) Wiring of the pantograph - 2.0m from the housing Lapp Ölflex FD 855 CP 18x2.5mm² (power rings) Shield connected to PE Lapp Control TM 18x1.0mm² (data rings) Lapp Tray II 5GAWG14 (heating) Housing with cable glands: 1x M32x1.5 1x M25x1.5 1x M20x1.5 (heating cable) Lines potted in the axis Flange without cable gland Total height 414mm . according to Drawing no .: A00-14-LT0009 and wiring diagram index B . !New variant!
40632810UA0305	

A06-B01980-OZ	
40632810UA0305	
FTL 28501820HA4704	313521.15-2
I/O MODULE MC-KB-4 EXi	
FLT 50712812UB0305	A00-01-CFR072 4 x 90A + PE, 500V with direct wiring Trigger direction of rotation: left Winding length: 22 m (load case 8) with the cable mounted on the jacket - 27m Semoflex 5 x 16mm ² (Ø 25.3mm / 1.17 kg / m) with holding stocking type T-25 galv. (A. with thread in the flange M50x1.5 with cable gland in the housing M40x1.5 Hood Ø 205 mm / a = 205 mm
PC4-VX04-0700	
PC4-WX04-0700	
PC5-VX04-1500	SOCKET, X5, 3x420A+E+2p/1kV 120/150mm ²
Type : GSK 58-16/110/DV/So	Cavotec slipring column Type : GSK 58-16/110/DV/So Serial Nr. : S1806576.10-10 No of poles/current/tension : 3X 16A + PE; 230V Year : 1118
001-RE090	
11 SN:442	
1604872.10-1	
1604872.30-1	
331442	
58-06/110/KL/So oem	
AG300K1	
AP300KM1	
Buflex-M 3x120+3G25	
CAB01-03240-000	
Collector(with brushes) for K424/FC V1000/Nr:081957/1	
D 25426 N132M8VC-B5	
FLT 19291420BA4504	
FLT 25330610FA5806 (OEM)	
FLT19361420 DA4605	
GSK 02-04/98-10/205/KL	
GSK 47-04/140/KL/So 11 Kw	
GSK 47-04/140/KL/So 7.5 Kw	
GSK 47-04/140/KL/So oem	
GXO-KMD66-000000	
KK270 CD 1240.3240/253/R + GR2-1	
KP-BRUSH	

M5 1080 3600
M5-1031-3452
M5-1051-3600
M5-1080-3600 the same as M5-1080-3699
M5-1080-3699
M5-2321-4111
M9-1051-3003
M 9-1051-3600
M9-1120-5020
M9-1510-3600
M9-2021-9005
N132M8VC B5
N15 250/28
PC2-EX-SB04-0500/M50S
PC4-SX04-0700 OEM!!
PC4-SX04-0702
PC4-SX37-0025
PC4-WX37-0025
PC5 RX04 S7004P
PC5 SX04 S700R4P
PC5-RX04-S700
PC5-SS05-S0700B
PC5-SX04-S700
PC5-SX04-S700R
PC5-TX04-1850.
PC5-VX04-1500
PC5-VX04-K0500
PC5-VX04-S700
PC5-WX04-1850
PC5-WX04-1850 OEM
PC6-RS04-3000
PCS2-SX01-1500
PCX-11010-051 oem
PCX-12010-048 oem
PCX-16006-038 oem
PCX-21410-0401 oem

RM4D2_032530	
S00SG205601	
S02-00440-010	
S22-00460_110	
S70-00005-100	
A00-14-CFR033	
A00-01-CFR073	
060-SCR A00-01-CFR073	Spring cable drum according to type plate
DACO-50	
Model: MC-2-3	Specification - IP66 rating, 6 two-step push-buttons, 4 selector switches with LED, emergency stop button, comes with MC-IRX base station unit
A00-14-CFR033	
Spring cable reel 4600	
M5-2152-1209	SWITCH,TOGGLE,0>1
M5-2129-3002	BOOT,SEALING,FOR TOGGLE SWITCH
M5-2121-6700	PUSHBUTTON,BLACK
M5-2129-3105	CAP,NEOPRENE,FOR PUSHBUTTON
M5-2116-1616	SWITCH,ROTARY 21MM,16 POS HEX
M5-2160-0913	ARROW ,FOR 21MM OPERATING HANDLE
M5-2129-3109	BOOT,SEALING BLACK,FOR ROTARY HEX SWITCH
M5-2119-4917	HANDLE,OPEARTING,15MM FOR POT
M5-2117-2002	POTENTIOMETER,W/15MM KNOB
M5-2119-4912	CUP,FOR OPERATING HANDLE
M5-1060-5220	LCD,DISPLAY 2X20
M5-1020-4300	MODULE,PROCESSOR
M5-1040-3306	JOYSTICK,FOR BOARD CONNECTION
M5-2935-3303	LED(LIGHT EMITTING DIOD),YELLOW 3MM
M5-2935-3302	LED(LIGHT EMITTING DIOD),GREEN 3MM
M5-2935-3301	LED(LIGHT EMITTING DIOD),RED 3MM
M5-2211-0100	JOYSTICK,JC-100
M5-2121-6711	PUSHBUTTON,WITH GREEN LED
M5-1510-3314	SUPPORT,STRAP MC-3300
M5-2502-9002	FUSE,AUTO,2-P,6A
M5 2129-3100	
M5 2121-6700	
M5 2121-6710	

M5 2153-1229	
GSK 02-04/98-10/205	KL 3X50A+PE, 10X25A. 500V.
KK270CD1120.3120/440.353R	
GSK 02-04/98-10/205/KL	3X50A+PE, 10X25A. 500V.
PC5 IEC80005-3 version -350 Amper	
Sc-120414-Afi	
Sr2-00594-000	
Flt40632810ua9820	
Pc5-Vx04-K0350	
Nmb202393	
Sr2-S0116-000	
Sr6-S0217-000	
Pc2-Px01-2400/M50	
N112ml4/1-85	
S01-H1200-003	
22301820dc5826	
Sr2-00598-000	
22361430eb4504	
M5-1042-4100	
Flt50802813ua-0703	
Kv44/8s	
F-Cc-1231016-001	
Pc2-Tx01-2400/M50	
28431820ha5826	
28461110ha9820	
28461110ha-9820	Artikel-Nr.: A00-01-CIT304 Spring line drum of the type Special flange with mounted cable on the jacket - 20m reelable cable 24 x 2,5mm ² (Ø 16,9mm / 0,41kg / m)
Pc5-Sx04-1504	
S01-20t70-341	
Jetcable	
Sr2-01083-000	
Pc5-Tx04-1500	
S1606225.180-8 - Model : Flt 40632820sa0205 / Semoflex 5x10 Mm²	
Mc-2-3	HAND HELD RADIO REMOTE CONTROL
S78-70000-006	

[Sr2-00593-000](#)

[Pc5-Wxo4-1850](#)

[Pc4-Ss05-0700](#)

[Pc5-Tx04-1850](#)

[Sr6-S0325-002](#)

[S17-Ae112-004](#)

[40.6 Vm509-40g K424/7](#)

[S22-40618-9s0](#)