

Chauvin Arnoux



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Chauvin Arnoux Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Chauvin Arnoux Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
F65	P01120761
C.A 762	Voltage tester
ELE.2902 MEGAOHMMETRE	
C.A 773 (alternative for pos1)	Voltage tester Supplied with: 1 instruction manual in 5 languages, 2 batteries 1.5 V LR06 / AA, 1 set of detachable Test probes Ø 2 mm with transparent protective cover, 1 tip protective cap, 1 strap with Velcro fastener
C.A 6534	Isolation tester Delivered in a transport bag for hands-free use, 2 safety measuring lines 1.50 m (red + black), 1 crocodile clip (red), 1 test probe (black), 2 pickups (red + black), 6 batteries LR6 or AA, 1 instruction manual on CD, 1 safety data sheet, 1 CD with software megohmmeter transfer
C.A 6526	Isolation tester Delivered in a transport bag for hands-free use, 2 safety measuring lines 1.50 m (red + black), 1 crocodile clip (red), 1 test probe (black) 6 batteries LR6 or AA, 1 instruction manual on CD, 1 safety data sheet, 1 CD with software megohmmeter transfer.
F405, 1000A TRMS	F405 multimeter Lot number: 90303100 Country of origin: People's Republic of China L / W / H in mm (gross): 335/140/70 Weight in kg (gross): 1.15 Supplied with: 1 set of test leads, 1 set of test probes, 1 alligator clip, 4 x 1.5 V batteries, 1 transport bag, 1 quick start guide and operating instructions in 5 Languages on CD-ROM
F407 Power and Harmonics Clamp	Warennummer: 90303100 Ursprungsland: People's Republic of China L / B / H in mm (brutto): 335 / 140 / 70 Gewicht in kg (brutto): 1,06 Geliefert mit: 1 Satz Messleitungen, 1 Satz Prüfspitzen, 2 Krokodilklemmen, 4 x 1,5 V-Batterien, 1 Transporttasche, 1 Kurzanleitung und Bedienungsanleitung in 5 Sprachen auf CD-ROM

C.A 8336 Power and Energy Analyzer	• Measure all voltage, current and power parameters of a network • Immediate display of the most important power quality parameters • All power quality parameters, transients (210), alarms and waveforms capture and record simultaneously • Including inrush mode with up to 10 minutes for inrush currents • Supplied with free Power Analyzer Transfer software for configuration of the device, reading out the memory and display of the measurement results and Analyzes on a PC, data export to Excel • 5 voltage and 4 current inputs - Supplied with: 1 bag for device and accessories, 5 voltage measuring leads 3 m long with Ø 4 mm banana plugs, 5 alligator clips, 1 set with 12 colored ones Marking parts for test leads and connection sockets, 1 screen Scratch protection film (already attached), 1 USB cable, 1 power cable, 1 power supply unit, 1 Safety data sheet, 1 CD with operating instructions in several languages, 1 CD with the evaluation software (Power Analyzer Transfer)
C.A 6117	Installation tester including DataView + C.A 1510 • FREE C.A 1510 tester for indoor air quality: ventilate in good time, use the professional measuring device for COVID 19 prevention! • Comprehensive multifunction device with extended measuring and Evaluation functions for demanding tests of electrical installations according to DIN VDE 0100-600, DIN VDE 0105-100 ... • Testing of RCD / FI type AC, A, B, B +, F, EV in ramp or pulse mode, with and without triggering • Powerful lithium-ion battery for increased autonomy with up to 30 Hours of operation • With additional measurements such as selective earthing measurement with clamps, voltage, Current with clamp, power, waveforms and harmonics, voltage drop • Structured storage on 3 levels according to location / room / object • Integrated fuse table for loop measurement • With efficient context help for every measurement including connection diagrams and Warning notices Supplied with: 1 transport bag, 1 mains adapter / charger type 2, 1 Li-ion battery pack Ion, 1 USB cable A / B 1.80 m with ferrite, 1 x 3-pole measuring line with 3 Safety measuring leads (r + bl + gr), 3 test probes Ø 4 mm (r + bl + gr), 3 Alligator clips (r + bl + gr), 2 safety measuring lines 3 m (angled-straight, r + sw), 1 x 3-pole Euro power cable, 1 x 2-pole Euro power cable, 1 probe for Remote control, 1 wrist strap, 1 shoulder strap for hands-free operation (4 points), 1 ICT software on CD, 1 operating manual on CD, 1 DataView software
Current clamp C177A (200A)	• Accessories for installation testers C.A 6116N / C.A 6117 • Pliers with a diameter of 52 mm • Enables current measurement (5.0 mA - 199.9 A), power measurement (110 kW: 1- phase, 330 kW: 3-phase), harmonic measurement (up to the 50th order) and selective earth measurement
KAL-CA6117	Factory calibration C.A 6117 with calibration certificate
P01102021	Accessory set for earth measurement - 2 earth electrodes (50m) • Complete set of high quality measuring accessories for measuring Earthing resistances and specific earth resistances Supplied with: 1 "Standard" transport bag (380 x 280 x 200 mm), 1 drum with 50 m measuring line (red), 1 drum with 50 m measuring line (blue), 1 reel with 10 m test

	lead (green), 2 earth electrodes (T-shaped), 1 hammer, 1 set of 5 adapters Cable lugs / 4 mm
P01145901	C.A 6710 "Installation" didactic case Supplied with: 6 safety measuring leads (25 cm) with axial socket, 1 adapter FR / D sockets, 1 power cord
Chauvin Arnoux	
Chauvin Arnoux	
Chauvin Arnoux	
Chauvin Arnoux	
CA8436 Power Quality Analyser	
Sattop 4841-TC Type K	
C.A 8336	Power and Energy Analyzer • Measure all voltage, current and power parameters of a network • Immediate display of the most important power quality parameters • All power quality parameters, transients (210), alarms and waveforms capture and record simultaneously • Including inrush mode with up to 10 minutes for inrush currents • Supplied with free Power Analyzer Transfer software for configuration of the device, reading out the memory and displaying the measurement results and Analysis on a PC, data export to Excel • 5 voltage and 4 current inputs Supplied with: 1 bag for device and accessories, 5 voltage test leads 3 m long with Ø 4 mm banana plugs, 5 crocodile clips, 1 set with 12 colored ones Identification parts for measuring lines and connection sockets, 1 screen Scratch protection film (already attached), 1 USB cable, 1 power cord, 1 power adapter, 1 Safety data sheet, 1 CD with user manual in several languages, 1 CD with the evaluation software (Power Analyzer Transfer)
P01103058Z	Alternate or optional item Set of 2 magnetic measuring tips red / black • Magnetic measuring tips for voltage measurement • 1000V CAT III / 600V CAT IV • Ø of the measuring tip: 6.6 mm • Angle socket Ø 4 mm • 4 A
P01102149	Alternate or optional item Reeling Box - cable reel with magnet • Voltage measurement leads and connection leads from current transformers conveniently wind up • Magnetic back for easy hanging in the control cabinet or magnetic surfaces • Maximum overview of the measurement environment
P01102150	Alternate or optional item Mains adapter PA31ER for Qualistar CA 833x
AC adapter/charger PA30W	INPUT: 90V AC..264V AC 50/60 HZ 65V OUTPUT: 15 V DC 2A 30W IP 40
C.A 6524	insulation meter Commodity number: 90303320 Country of origin: France L / W / H in mm (gross): 250 / 140 / 160 Weight in kg (gross): 1.4024 Supplied with: 1 hands-free carrying case, 2 safety test leads (1.5 m long, straight/angled plugs, red/black), 1 red alligator clip, 1 black

	test tip, 6 batteries LR6 or AA, 1 multilingual User manual on CD, 1 quick start guide, 1 multilingual safety data sheet *** C.A 6525 discontinued - C.A 6524 as alternative model ***
Software DataView (Alternatice)	
Remote control probe #3 (alternative)	
P01380103	TRIAD T3- with 2x output +/-20mA DC (80-265V AC/DC auxiliary p.) T302 with optical interface Configuration with TRIADJUST2 software (Requires optical probe P01330403, Software Triadjust to download) TRIAD2 T302, 2 outputs, +/-20mA, auxiliary supply 80-265V AC/DC, with optical connection To be configured with Triadjust software (needs optical cable P01330403)
P01380107	TRIAD2- with 4x output +/-20mA DC (80-265 V AC/DC auxiliary p.) T304 with optical interface Configuration with TRIADJUST2 software (Requires optical probe P01330403, Software Triadjust to download)
P01330403	Optical probe USB for ENERIUM 50/150, TRIAD2, Elog
P01380400	Alternative or optional item 30 sheets of 2 labels each for TRIAD2
P01139711	C.A 6545 Isolationsmessenger 5 kVH • Robust insulation meter for demanding applications to measure very high Insulation resistances up to 10 TΩ with test voltages up to 5 kV •Large, illuminated LCD display with digital display and analogue bar graph •Automatic calculation of insulation quality parameters (DAR, PI, DD) •With 4 fixed and one adjustable test voltage from 40 V to 5100 V •Adjustable test duration for improved assessment of insulation at longer applied test voltages •Curve drawing R(T): Automatic storage of measured values Tests with programmed duration •Smooth function: smoothing of unstable measurement results for better reading readability Supplied with: 1 transport bag, 2 safety high-voltage cables with HS plug and HS crocodile clip (red/blue, 3m), 1 protected safety High-voltage line with HS plug with rear contact and HS alligator clip (black, 3m), 1 protected safety high-voltage line with HS plug and HS plug with rear contact (blue, 35cm), 1 mains connection cable 1.8 m, 8 simplified operating instructions, 1 USB stick with operating instructions
C.A 8336 Power and Energy Analyzer	• Measure all voltage, current and power parameters of a network •Immediate display of the most important power quality parameters •All power quality parameters, transients (210), alarms and waveforms capture and record simultaneously •Including inrush mode with up to 10 minutes for inrush currents •Supplied with free Power Analyzer Transfer software for configuration of the device, reading out the memory and displaying the measurement results and Analysis on a PC, data export to Excel •5 voltage and 4 current inputs Supplied with: 1 bag for device and accessories, 5 voltage test leads 3 m long with Ø 4 mm banana plugs, 5 crocodile clips, 1 set with 12 colored ones Identification parts for measuring lines and connection sockets, 1 screen Scratch protection film (already attached),

	1 USB cable, 1 power cord, 1 power adapter, 1 Safety data sheet, 1 CD with user manual in several languages, 1 CD
P01120526B	Ampflex A193-450 (diameter 140mm) • Circumference Ø: 140 mm / loop length: 450 mm • Safety according to IEC 61010: CAT III 1000 V / CAT IV 600 V • Measuring range with PEL 51 / 52: 200 mA...3 kA AC • Measuring range with PEL 102 / 103 / 104 / 105 / 106: 200 mA...10 kA AC • Measurement range with C.A 8331 / 8333 / 8336 / 8436: 100 mA...10 kA AC • Measuring range with C.A 8332B / 8334B / 8335 / 8435: 30 A...6500 A AC • Measurement range with C.A 8345: 100 mA...10 kA AC • Measuring range with C.A 8220 / C.A 8230: 10 / 30 A...6500 A AC
P01103058Z	Set of 2 magnetic measuring tips red / black • Magnetic measuring tips for voltage measurement • 1000V CAT III / 600V CAT IV • Ø of the measuring tip: 6.6 mm • Angle socket Ø 4 mm • 4 A
P01102149	Reeling Box - cable reel with magnet • Voltage measurement leads and connection leads from current transformers conveniently wind up • Magnetic back for easy hanging in the control cabinet or magnetic surfaces • Maximum overview of the measurement environment
P01102150	Mains adapter PA31ER for Qualistar CA 833x • Accessories for Qualistar network analyzers C.A 833X • PA31ER type 2-wire mains adapter with axial socket • For the direct supply of the Qualistar via a mains phase conductor with 100 V up to 1000 V AC or DC • Connection to the voltage inputs • Protection class IP53 • IEC 61010 CAT III 1000V / CAT IV 600V
P01102095	Software DataView • Universal software platform • Creation of detailed reports and measurement logs at the touch of a button • View measurement results in real time • Reading out stored measured values • One-time purchase for use with all compatible devices - included free updates
P01184102	C.A 852 Digital-Manometer 200 mbar • Ideal device for measuring pressure levels (tyres, air conditioning, etc.) • Measurement of the differential pressure to determine the pressure level • Accurate and easy to use • Timed monitoring mode • Measuring span: -138 to 138 mbar • Max. Pressure level: 1.38 bar • Selectable units of measure: psi, bar, mbar, inH2O, mmH2O. Supplied with: 1 transport case, 2 connecting hoses L = 500 mm - inner Ø = 6mm, 1 x 9V battery
P01160511	C.A 8331 Power and Energy Analyzer • Measure all voltage, current and power parameters of a network • Immediate display of the most important power quality parameters • Acquire and record all power quality parameters simultaneously • Supplied with free Power Analyzer Transfer software for configuration of the device, reading out the memory and displaying the measurement results and Analysis on a PC, data export to Excel • 4 voltage and 3 current inputs Supplied with: 1 bag for device and accessories, 4 voltage test leads 3 m long with Ø 4 mm banana plugs, 4 crocodile clips, 1 set of 12 colored ones

	Identification parts for measuring lines and connection sockets, 1 screen Scratch protection film (already attached), 1 USB cable, 1 power cord, 1 power adapter, 1 Safety data sheet, 1 CD with user manual in several languages, 1 CD with the evaluation software (Power Analyzer Transfer)
P01654550	C.A 1550 Mikromanometer • Compact manometer for measuring differential pressure, air speed and air flow rate • Manual or automatic temperature compensation • Atmospheric air pressure compensation •Cartographic display in MAP mode • Convenient MIN, MAX, average and hold functions •Selective or continuous measurement recording of up to 1 million values •Housing with integrated magnetic holder and compatible with the Multifix Accesories Supplied with: transport bag, 3 alkaline batteries 1.5 V AA, 2 clear Connection hoses, USB cable, test report, quick start guide
LS9N423X	Synchronizer L96 110Vdc
F605 Multimeter Clamp	• TRMS AC+DC multi-meter clamp for mixed AC+DC applications as well Maintenance and service at high currents up to 2000 A AC / 3000 A DC •Circumference Ø: 60 mm •With True InRush function: starting currents of motors and power requirements of Identify assets easily •Immediate measurement of active, reactive and apparent power as well as power factor PF •Harmonic Analysis: Measure THD values of distorted signals •Basic functions: V AC, V DC, V AC+DC, A AC, A DC, A AC+DC, frequency, resistance, acoustic Continuity test, diode test •Additional functions: MIN / MAX, phase sequence of the external conductors (2-wire), power, THDf / THDr, Peak+ / Peak-, True InRush, relative measurement Supplied with: 1 set of test leads, 1 set of test probes, 1 alligator clip, 4 x 1.5 V batteries, 1 transport bag, 1 brief guide and operating instructions in 5 ;
8332B	
C.A 6550 insulation meter 10 kV	P01139715 Insulation tester with test voltages of up to 10 kV for insulation tests up to 25 TΩ with optimal security and accuracy •With 5 fixed and one adjustable test voltage from 40 V to 10 kV as well Step or ramp voltages • Various test methods for assessing insulation non-destructive tests and for examining the aging of insulating materials •Automatic calculation of insulation quality parameters (DAR, PI, DD) •Quick overview of insulation quality: graphical representation of progress the insulation resistance and the test voltage •Integrated reading memory and USB interface for DataView software for detailed evaluations and reports Supplied with: 1 transport bag, 2 safety high-voltage cables with HV plug and HS alligator clip (red/blue, 3m), 1 protected safety High-voltage line with HS plug with rear contact and HS alligator clip (black, 3m), 1 protected safety high-voltage line with HS plug and HS plug with rear contact (blue, 0.5m), 1 mains connection cable 2m, 1 optical USB cable, 1 USB stick with operating instructions and software DataView
	Insulation tester with test voltages of up to 15 kV for insulation tests up to 30 TΩ with optimal security and accuracy •With 5 fixed and one adjustable test voltage from

C.A 6555 Isolationsmesser 15 kV	40 V to 15 kV as well Step or ramp voltages • Various test methods for assessing insulation non-destructive tests and for examining the aging of insulating materials • Automatic calculation of insulation quality parameters (DAR, PI, DD) • Quick overview of insulation quality: graphical representation of progress the insulation resistance and the test voltage • Integrated reading memory and USB interface for DataView software for detailed evaluations and reports Supplied with: 1 transport bag, 2 safety high-voltage cables with HV plug and HS alligator clip (red/blue, 3m), 1 protected safety high-voltage cable with HV plug with reverse contact and HS alligator clip (black, 3m), 1 protected safety high-voltage line with HS plug and HS plug with rear contact (blue, 0.5m), 1 mains connection cable 2m, 1 optical USB cable, 1 USB stick with operating instructions and software DataView
F607 power and harmonics clamp meter	L / W / H in mm (gross): 335 / 140 / 70 Weight in kg (gross): 1.07
TPOKE50-C110	Relay monostable 6c 110vdc + diode + led
PAIR240	Socket PAIR240
4001-DC-42	RPB48
4001-EC-11	Anti-twist protection (plug-in orienting pins 59)
TRIAD 2 T304, 4 out. ± 20 mA, aux. 80-265VAC/DC	TRIAD 2 - Configurable digital transmitter with programmable Accuracy class / Programmable digital transducer with programmable accuracy class Model / Model: T3 - Large Model / Large Model Outputs / Outputs: 4 Output signal / Output signal: ± 20mA Power / Supply: 80-265V AC / 110-365V DC Tropenfest / Tropicalization: No / No Communication / Communication: Optical interface for configuration via TRIADJUST 2 software (free to download), optical probe P01330403 required / optical interface for configuration via software TRIADJUST 2 (download free of charge), optical lead P01330403 required RS485 and Ethernet communication only possible via factory configuration (TRIAD2-CFG), please contact us.
TRIAD 2 T304, 4 out. ± 20 mA, aux. 19-58VDC	TRIAD 2 - Konfigurierbarer digitaler Messumformer mit programmierbarer Genauigkeitsklasse / Programmable digital transducer with programmable accuracy class Modell / Model: T3 - Großes Modell / Large Model Ausgänge / Outputs: 4 Ausgangssignal / Output signal: ± 20 mA Stromversorgung / Supply: 19-58 V DC Tropenfest / Tropicalization: Nein / No Kommunikation / Communication: Optische Schnittstelle zur Konfiguration über Software TRIADJUST 2 (kostenlos zum Download), Optischer Tastkopf P01330403 erforderlich / Optical Interface for configuration via software TRIADJUST 2 (download free of charge), Optical Lead P01330403 required
30 sheets of 2 labels each for TRIAD2	30 sheets of blank labels
P01330403	Optical probe USB for ENERIUM 50/150, TRIAD2, Elog
P01102129	Mains adapter/charger PA30W-2 type 2 without mains cable
	P01120947 • TRMS AC+DC multi-meter clamp for mixed

F407 power and harmonics clamp meter	AC+DC applications as well Analyzes and diagnostics at medium currents up to 1000 A AC / 1400 A DC •Covering Ø: 48 mm / Simultaneous display of 3 measured values •With True InRush function: starting currents of motors and power requirements of Identify assets easily •Immediate measurement of active, reactive and apparent power as well as power factor PF and displacement factor DPF •Harmonic analysis up to the 25th order (frequency analysis): THD values measure from distorted signals •Measurement data recording and Bluetooth: determine short-term faults, data analyze on the PC and create reports! •Basic functions: V AC, V DC, V AC+DC, A AC, A DC, A AC+DC, frequency, resistance, acoustic continuity test •Additional functions: MIN / MAX, power, THDf / THDr, displacement factor, Peak+ / Peak-, True InRush, Harmonics (0 to 25th order), Ripple, Data logging, PC software, Bluetooth Supplied with: 1 set of test leads, 1 set of test probes, 2 alligator clips, 4 x 1.5 V batteries, 1 transport bag, 1 brief guide and operating instructions in 5 languages on CD-ROM
C.A 8336 Power and Energy Analyzer	P01160591 Measure all voltage, current and power parameters of a network •Immediate display of the most important power quality parameters •All power quality parameters, transients (210), alarms and waveforms capture and record simultaneously •Including inrush mode with up to 10 minutes for inrush currents •Supplied with free Power Analyzer Transfer software for configuration of the device, reading out the memory and displaying the measurement results and Analysis on a PC, data export to Excel •5 voltage and 4 current inputs Supplied with: 1 bag for device and accessories, 5 voltage test leads 3 m long with Ø 4 mm banana plugs, 5 crocodile clips, 1 set with 12 colored ones Identification parts for test leads and connection sockets, 1 screen scratch protection film (already attached), 1 USB cable, 1 mains cable, 1 power pack, 1 Safety data sheet, 1 CD with operating instructions in several languages, 1 CD with the evaluation software (Power Analyzer Transfer)
Ampflex A193-450 (diameter 140mm)	P01120526B • Circumference Ø: 140 mm / loop length: 450 mm •Safety according to IEC 61010: CAT III 1000 V / CAT IV 600 V •Measuring range with PEL 51 / 52: 200 mA...3 kA AC •Measuring range with PEL 102 / 103 / 104 / 105 / 106: 200 mA...10 kA AC •Measurement range with C.A 8331 / 8333 / 8336 / 8436: 100 mA...10 kA AC •Measuring range with C.A 8332B / 8334B / 8335 / 8435: 30 A...6500 A AC •Measurement range with C.A 8345: 100 mA...10 kA AC •Measuring range with C.A 8220 / C.A 8230: 10 / 30 A...6500 A AC
Set of 2 magnetic measuring tips red / black	P01103058Z • Magnetic measuring tips for voltage measurement •1000V CAT III / 600V CAT IV •Ø of the measuring tip: 6.6 mm •Angle socket Ø 4 mm •4 A
T 11C (COMPLEX)	PROGRAMMABLE TRANSDUCER, FOR 1 PHASE OR 3 PHASE BALANCED SYSTEMS (1 OUTPUT) VALUES THAT CAN BE MEASURED: CAN BE PROGRAMMED TO ONE OF I, V, F, P, Q, S, Cos f (Phi). AUXILIARY SUPPLY: 80 - 230 V. AC., 110 - 325 V. DC. (UNIVERSAL FEED) OUTPUT : (milliamps) - 20 / +20 mA. BETWEEN OUTPUT : (volts) - 10 / +10 V.

TRIAD 2 T304, 4 outputs ± 20 mA, aux.80-265V AC/DC	TRIAD 2 - Konfigurierbarer digitaler Messumformer mit programmierbarer Genauigkeitsklasse / Programmable digital transducer with programmable accuracy class Modell / Model: T3 - Großes Modell / Large Model Ausgänge / Outputs: 4 Ausgangssignal / Output signal: ± 20 mA Stromversorgung / Supply: 80-265 V AC / 110-365 V DC Tropenfest / Tropicalization: Nein / No Kommunikation / Communication: Optische Schnittstelle zur Konfiguration über Software TRIADJUST 2 (kostenlos zum Download), Optischer Tastkopf P01330403 erforderlich / Optical Interface for configuration via software TRIADJUST 2 (download free of charge), Optical Lead P01330403 required RS485 und Ethernet-Kommunikation nur über Werkskonfiguration möglich (TRIAD2-CFG), sprechen Sie uns an. RS485 and Ethernet-Communication only possible via factory configuration (TRIAD2-CFG), please contact us.
TRIAD 2 T302, 2 outputs ± 20 mA, aux.80-265V AC/DC	TRIAD 2 - Konfigurierbarer digitaler Messumformer mit programmierbarer Genauigkeitsklasse / Programmable digital transducer with programmable accuracy class Modell / Model: T3 - Großes Modell / Large Model Ausgänge / Outputs: 2 P01380103 Ausgangssignal / Output signal: ± 20 mA Stromversorgung / Supply: 80-265 V AC / 110-365 V DC Tropenfest / Tropicalization: Nein / No Kommunikation / Communication: Optische Schnittstelle zur Konfiguration über Software TRIADJUST 2 (kostenlos zum Download), Optischer Tastkopf P01330403 erforderlich / Optical Interface for configuration via software TRIADJUST 2 (download free of charge), Optical Lead P01330403 required RS485 und Ethernet-Kommunikation nur über Werkskonfiguration möglich (TRIAD2-CFG), sprechen Sie uns an. RS485 and Ethernet-Communication only possible via factory configuration (TRIAD2-CFG), please contact us.
TRIAD 2 T304, 4 outputs ± 20 mA, aux. 19-58V DC	P01380115 TRIAD 2 - Konfigurierbarer digitaler Messumformer mit programmierbarer Genauigkeitsklasse / Programmable digital transducer with programmable accuracy class Modell / Model: T3 - Großes Modell / Large Model Ausgänge / Outputs: 4 Ausgangssignal / Output signal: ± 20 mA Stromversorgung / Supply: 19-58 V DC Tropenfest / Tropicalization: Nein / No Kommunikation / Communication: Optische Schnittstelle zur Konfiguration über Software TRIADJUST 2 (kostenlos zum Download), Optischer Tastkopf P01330403 erforderlich / Optical Interface for configuration via software TRIADJUST 2 (download free of charge), Optical Lead P01330403 required RS485 und Ethernet-Kommunikation nur über Werkskonfiguration möglich (TRIAD2-CFG), sprechen Sie uns an. RS485 and Ethernet-Communication only possible via factory configuration (TRIAD2-CFG), p
C.A 1110 Luxmeter	• Compact device for checking illuminance • Separate light sensor to avoid the formation of shadows • Operator or can be fixed to the device for one-handed measurements • Compensation of the spectral error in LED or fluorescent light sources • MAP function for cartographic representation of illuminance • IEC spectral correction and angle of incidence correction • Individual storage of measured values or continuous recording of up to 1 million. Values • USB and Bluetooth interface, PC software and Android app for

	evaluation and configuration Supplied with: 1 carrying case, 3 1.5 V AA alkaline batteries, 1 USB cable, 1 Test report, 1 quick guide (complete operating instructions and software data
CA 6161	CA 6161 machine tester P01145811 • Multifunctional test device for testing the electrical safety of machines, Control cabinets and electrical devices with HV testing up to 3 kV •Very user-friendly thanks to express command keys, color touch display, help screens with connection diagrams, large measured value memory, ... •Most modern communication: USB interface or remote access via WLAN Use of the included machine tester transfer software •Automatic and user-defined test sequences, expandable through Test instructions with text or images •Configure custom visual inspections to address specifics of each to be able to enter into the examination •Large variety of additional functions for other applications (Zs, Zi, RIso, RCD, W, current via clamp, direct and differential leakage current measurement, ...) •Practical optional accessories for greater safety and efficiency Measurements (foot switches, warning lamps, scanners, label printers, ...)
ca8332	
6555 15kVdc	15,000 V insulation tester included below ; accesories HX0056-Z USB Optical cable P011030623 Croc clips kit RED/BLUE /BLACK P01295174 Mains lead 2P EUR. P01295454Z Moulded test probes CAT 4 1 kV RD/BK P01295465 Set of 3 simplified HV Leads for 10/15KV P01295517 CROCO HT 3M 15kV RD K44 P01295518 CROCO HT 8M 15kV RD K44 P01295519 CROCO HT 15M 15kV RD K44 P01295520 CROCO HT 3M 15kV BU P01295521 CROCO HT 8M 15kV BU P01295522 CROCO HT 15M 15kV BU P01295523 CROCO HT 3M 15kV BK GUARD P01295524 CROCO HT 8M 15kV BK GUARD P01295525 CROCO HT15M 15kV BK GUARD P01295526 CORD HT .5M BU15KV-STACKK P01298066 Standard Carrying Bag 380x280x200
6555 15kVdc R2	15,000 V insulation tester included below ; accesories HX0056-Z USB Optical cable P01295174 Mains lead 2P EUR. P01295517 CROCO HT 3M 15kV RD K44 P01295520 CROCO HT 3M 15kV BU P01295523 CROCO HT 3M 15kV BK GUARD P01295526 CORD HT .5M BU15KV-STACKK P01298066 Standard Carrying Bag 380x280x200
ENERDIS TRIAD2 T303	151535JGH
Mtx162ue	
Mtx3292	
P01123512a	CA6456, EARTH LOOP TESTER.
P01174902	
Ca6462	
P01102040	

P01167302	CA42, MF400- MAGNETIC FIELD PROBE.
P01139701	5000V DC, CAT.III 600V, C/W CARRY CASE LEADS.
Mx0002bm	
P01173114	
Mx0059hdl	
Mtx3282b-Com	
P01120053a	
P01196731	
Ae0193	
P01191741a	
P01145602	CA6121, MACHINE TESTER, DIGITAL, CAT. III 300V, IP54.
Ox7042-Csd	OX7042-C SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 2X 40MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX0030B), 1X BNC/PROBIX ADAPT (HX0031), 1X PROBIX/4MM ADAPT (HX0033)
P01120301	
Ha2004-Z	
P01196775	
Hx0061	
Vx0003	
P01102085	
P01651272	CA1888HT15, RAYCAM, THERMO/OPTICAL CAMERA , - 20.1500C, 24X18 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
Hx0063	
Ha050	
P01651403z	
Ox5022-Ck	OX5022-CK, HANDSCOPE, PORTABLE OSCILLOSCOPE, 2 X 20 MHZ, DELIVERED SAME AS VERSION CPLUS 1 X OPTICAL USB COMMUNICATION CABLE AND 1 CD CONTAINING SX-METRO/P SOFTWARE AND USB CABLE DRIVERS.
P01160740	GREENTEST FTV200, I-V TRACER, WITH PYRANOMETER PT100 PROBE C/W 3M CABLES, SET OF MC4 ADAPTERS, MAGNETIC STYLUS FOR TOUCH SCREEN, USB KEY, FLEXIBLE PROBES, SOFTWARE AND CARRY CASE.

P01295290z	
Mtx3281b	
P01160730	GREENTEST FTV 200, PYRANOMETER + 5M CABLE.
P01196777	
P01160738	
Mtx1052b-Rk	
P01102030	
Sx-Metro/P	
P01122015	CA6416, EARTH CLAMP, CAT. IV, 600V, 35MM CLAMPING , COMPLETE WITH CASE CL1 CALIBRATION LOOP.
P01157050	
P01120508	
P01167202b	
P01173107	
P01184102	
P01196707z	
P01295218	
Hx0090	
P01651524	RAYCAM REPORT SOFTWARE.
P01126506	CA6470N, EARTH RESISTIVITY TESTER, 0.01- 99.9 KOHMS, C/W CHARGER S/W
Mx2034	TRANSMITTER
P01120405	
P01123513a	CA6456 T, EARTH LOOP TESTER, WITH 2X T RODS, HAMMER, 2X 50M RED BLUE REELS, 1 X 10M LEAD GREEN.
P01160585	NO CURRENT CLAMPS.
P01120963	
P01120336	
P03197529a	
Ox6062b-Csdo	OX6062B-CSDO, 2 CH. 60 MHZ DIGITAL OSCILLOSCOPE WITH HX0028 HARMONIC OPTION, HX0029 RECORDER OPTION HX0077 50K MEMORY OPTION C/W STYLUS, PROGRAMMING MANUAL ON CD-ROM, 1 GB SD CARD, SD CARD ADAPTER, 2

Gx320-E	
Hx0190	
Hx0053	
Mx0670	
P01101917	
P01160731	
P01654623	
Ox7204-Csdo	OX7204-CSDO, OSCILLOSCOPE/M/METER: COLOUR, 4X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W C/W 1X SX-METRO/P SOFTWARE, 50K MEMORY OPTION (HX0077), HARMONICS OPTION (HX0028), HAR
Hx0027	HX0027, PROBE 1/1000 30MHZ 20KV.
P07604145	
P01101892a	
P01120564	
P01126501	
P01167304	CA42, MF05- MAGNETIC FIELD PROBE.
P01185502	
P01651270	CA1888, RAYCAM, THERMO/OPTICAL CAMERA , -20.600C, 24X18 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
P01139706	15,000V DC, CAT. IV, C/W CARRY CASE, LEADS AND SOFTWARE.
P01167301	CA42, FREQUENCY ANALYSIS OPTION.
P01651273	CA1888BT, RAYCAM, THERMO/OPTICAL CAMERA , -20.600C, 24X18 LENS C/W RAYCAM REPORT, SD CARD, CHARGER, BATTERY BLUETOOTH.
P01102020	
P01101996	
P01102056	
P01651813	
P01120303	
P01156301z	
P01651620	CA1875, THERMOGRAPHY TRAINING BENCH.

P01191303	
P01298055	
P01120308	
Ca6549	
P01126505	CA6471, EARTH RESISTIVITY TESTER, 0.01- 99.9 KOHMS, C/W 2X C182 CLAMPS, CHARGER S/W.
P01160745	GREENTEST FTV200, I-V TRACER, C/W 3M CABLES, SET OF MC4 ADAPTERS, MAGNETIC STYLUS FOR TOUCH SCREEN, USB KEY, FLEXIBLE PROBES, SOFTWARE AND CARRY CASE.
P01651302z	
P01196773	
P01196734	
P01160720	GREENTEST FTV100, PYRANOMETER, PHOTO-VOLTAIC ANALYSER, 3 SOURCE DC, C/W CLAMPS, LEADS, PROBES, SOFTWARE AND CARRY CASE.
P01126502c	CA6462, EARTH TESTER, DIGITAL, 4 WIRE, 0.01.1999 OHM C/W INTEGRAL NIMH MAINS CHARGER.
P01102057	
P01145801a	CA6160, APPLIANCE MULTITESTER, C/W LEADS AND ACCESSORIES BAG.
P03652922	
Ox7202-Csd	OX7202-CSD, OSCILLOSCOPE/M/METER: COLOUR, 2X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX00030A), 1X BNC/PROBIX ADAPT (HX00031), 1X PROBIX/4MM ADAPT (HX00033)
Acca4162	
P03652918	
Ax502	
P03197531a	
Mtx1052cw-Pc	
Mtx202-Z	
P01120945	
Mtx3291	
P03197524a	
P01295470	

P01191740z	
P01120561	
P01167303	CA42, MF400H- MAGNETIC FIELD PROBE.
P01120425b	
Hx0084	
P01157152	PEL102, POWER ENERGY LOGGER, 0-1000 V AC DC, C/W ACCESSORIES BUT W/O CURRENT CLAMPS.
P01120526b	Alternate or optional item Ampflex A193-450 (diameter 140mm) • Circumference Ø: 140 mm / loop length: 450 mm •Safety according to IEC 61010: CAT III 1000 V / CAT IV 600 V •Measurement range with PEL 10X series: 200 mA...10 kA AC •Measuring range with C.A 8331 / C.A 8333 / C.A 8336 / C.A 8436: 100 mA...10 kA AC •Measuring range with C.A 8332B / C.A 8334B / C.A 8335 / C.A 8435: 30 A...6500 A AC •Measuring range with C.A 8220 / C.A 8230: 10 / 30 A...6500 A AC
Hx0206	
P01120005a	
Hx0073	
P01120403	
Erl310	
P01120083	
Mx0044hd	
P01650301z	
100361	DIGITAL
Minipince 5	
P01120761	
Okfc-110vdc	
P01102044	CA6474, TOWER TESTER, (REQUIRES CA6472).
P01120055a	
P01160621	
Hx0052c	
Hx0055	
P01157150	PEL102, POWER ENERGY LOGGER, 0-1000 V AC DC, C/W ACCESSORIES MA193 MINIFLEX CLAMPS.

P01120907z	
P01651261	CA1886HT10, RAYCAM, THERMO/OPTICAL CAMERA , - 20.1000C, 20X15 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
P01296041	
P01160736	
P01120550	
Hx0059b	
P01123511a	CA6454, LOOP TESTER.
Hx0080	
Mx0035d	
P01122011	CA6410, EARTH CLAMP, CAT. III 150V C/W CASE CL1 CALIBRATION LOOP.
P01120316	
Ca861	
Ox5042-Ck	OX5042-CK, HANDSCOPE, PORTABLE OSCILLOSCOPE, 2 X 40 MHZ +USB CONNECTION DELIVERED SAME AS VERSION C PLUS 1 X OPTICAL USB COMMUNICATION CABLE AND 1 CD CONTAINING SX-METRO/P SOFTWARE AND USB CABLE DRIVE
P01651215	CA1882, THERMAL CAMERA, 160X120 PIXELS, -20...250, 38X28, C/W BATTERY CHARGER, DOCKING STATION, 2GB MINI- SD CARD, SD CARD READER, VIDEO CABLE, RAYCAM PREVIEW SOFTWARE ON CD ROM, OPERATING MANUALS AND M
P01120417	
P01175020	CA1052, HEVAC 5:1 MULTIFUNCTION DEVICE, VELOCITY, VOLUME, PRESSURE, TEMPERATURE, HUMIDITY C/W S/W AND PROBES.
P01197451	
Ha050-1	
P01196522e	
Ox6062b-Cfg	OX6062B-CFG, 2 CH. 60 MHZ DIGITAL OSCILLOSCOPE WITH OPTION OF 1 EXTENSION OF EITHER HX0028 HARMONIC OPTION, HX0029 RECORDER OPTION HX0077 50K MEMORY OPTION C/W STYLUS, PROGRAMMING MANUAL ON CD-ROM, 1
P01196311f	
Ca6460	
P01120406	

Px0120	
P01298006	
P01120067a	
Hx0060	
P03652919	
Hx0064	
P01191733z	
P01120965	
Mtx3293-Bt	
P01126510	CA6474, TOWER TESTER, C/W 4X 5M AMPFLEX AND ACCESSORIES (REQUIRES CA6472).
P01191736z	
Ox7042p-Csdk	OX7042P-CK SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 2X 40MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP WITH ALL ENABLED OPTIONS: HARMONIC ANALYSER (HX0028), RECORDER (HX0029) POWER (HX0075)
P01120315	
Ox7104-Csdo	OX7104-CSDO SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 4X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X SX-METRO/P SOFTWARE, 50K MEMORY OPTION (HX0077), HARMONICS OPTION (HX0028),
P01191745z	
01nc8050	
P01295458z (Ex P01101855)	
P01157151	PEL103, POWER ENERGY LOGGER, 0-1000 V AC DC, C/W ACCESSORIES MA193 MINIFLEX CLAMPS.
P01105101z	
Dsd181319shw	
P01157702	DTR 8510, RATIO METER, DIGITAL, CAT. III 300V C/W LEADS CARRY CASE.
P01157153	PEL103, POWER ENERGY LOGGER, 0-1000 V AC DC, C/W ACCESSORIES BUT W/O CURRENT CLAMPS.
Ox7204-Bus	OX7204-BUS, 200MHZ OSCILLOSCOPE WITH BUILT-IN RECORDER FUNCTION, 4 CHANNELS, 600V / CAT III, 1000V / CAT II, C/W STYLUS, 1 STRAP, 1 OPERATING MANUAL, 1

PROGRAMMING MANUAL ON CD ROM, 1 EXTERNAL POWER S	
Mx0021-Z	
P01103065	
Hx0041	
Hx0072	
P01160587	CA8435 QUALISTAR+, IP67 FIELD USE POWER ANALYSER, 3 PHASE, C/W S/W, VOLTAGE LEADS, CLIPS AND A196-450 CURRENT CLAMPS.
2129.83	MICRO-OHMMETER MODEL 6292 (200A, 120/230V, DATAVIEW SOFTWARE) (6292)
Mtx1050-Pc	MTX1050PC, 1 GHZ PC VIRTUAL SPECTRUM ANALYSER C/W S/W, USB LEAD, MAINS LEAD AND DOCUMENTATION
P01120703a	
P03199612a	
Mtx1054b-Rk	
P01298056	
P01120575z	
P03199613a	
Ox0530	
P01132504	
P01120054a	
Mtx112u	
Ox7104-Csdk	OX7104P-CK SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 4X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W ALL SOFTWARE OPTIONS INSTALLED: HARMONICS OPTION (HX0028), RECORDER OPTION (HX00
Hx0039	
P03197530a	
P01141626	
12548e-000-E-Female	
P01120943	
Mtx3250-P	
12548e-000-E-Male	

P01295452z	
P01380002 (Ex. T101)	
P01170305	
P01120751c	
P01255104	WATTMETER, RW 5012.
P01651260	CA1886, RAYCAM, THERMO/OPTICAL CAMERA , -20.600C, 20X15 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
Ca6524	
Hx0008	
P01120073	
P01197404	
P01120418	
Hx0036	
Mtx3292-Bt	
Hx0083	MTX1050, 20DB AMP FOR HX0082
P01105103z	
P01120407	
P01196771	
P01139705	10,000V DC, CAT. IV 1000V, C/W CARRY CASE, LEADS AND SOFTWARE.
Mtx1032-Crk	
P03197526a	
P01140804	
P01160737	
P01102014	
Hx0082	MTX1050, PROBE KIT, H-FIELD, 3GHZ.
P01140802d	
P01196521e	
P01651262	CA1886HT15, RAYCAM, THERMO/OPTICAL CAMERA , -20.1500C, 20X15 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
Mx0675	

P01651001z	
P01197401	
P01170304	
P01160541	NO CURRENT CLAMPS.
P01120580	
P01120057a	
Ox5042-C	OX5042-C HANDSCOPE, PORTABLE OSCILLOSCOPE, 2 X 40 MHZ +USB CONNECTION, DELIVERED WITH 1 PROBE (1/10, 1000V) 1 BNC/ BANANA LEADS, 1 MAINS ADAPTOR, 1 SET OF 6AA NIMH BATTERIES, 1 HANDS- FREE BAG, 1 CD-R
Hx0038	
Mx0023-Cg	
P01160632	CA8230, POWER QUALITY ANALYSER, SINGLE PHASE, C/W DATA VIEWER PRO S/W, BAG, LEADS A193- 450MM CLAMP.
Ox7104-Csd	OX7104-CSD SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 4X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX00030B), 1X BNC/PROBIX ADAPT (HX00031), 1X PROBIX/4MM ADAPT (H
Hx0003	
P01651278	CA1878, DIACAM, THERMO CAMERA, 100X80 PIXELS, -20... 250, 12X10, C/W BATTERY CHARGER, 2GB SD CARD, SD CARD READER, DIACAM PREVIEW SOFTWARE ON CD ROM, OPERATING MANUALS AND MEASUREMENT REPORTS.
P01102903	
Pt100	
P01652401z	
P01120069	
Sx-Asyc2hd	
P01102012	
Hx0033	
Ca6547	
P01120410	
Ca201	
Ha030-1	
P01157030	

Mx0058hdl	
Hx0050	
1045caldu	MEGOHMMETER MODEL 1045 (DIGITAL W/ANALOG BARGRAPH, ALARM, TIMER, BACKLIGHT, 250V
P01120047	
Ca5231	
P01120415	
P01120502	
P01139703	5000V DC, CAT III 600V, C/W RS232 AND ANALYSIS SOFTWARE.
1045kitcal	MEGOHMMETER FIELD KIT, MODEL 1045 (MODEL 1045, REMOTE TEST PROBE FIELD CASE)
P01120901z	
P01299930	CA6474, TOWER TEST KIT, C/W P01126504, P01126510 AND P01102024.
P01156402	
P01651526	
P01120501	
P01157060	
P01101941	
P01651271	CA1888HT10, RAYCAM, THERMO/OPTICAL CAMERA , - 20.1000C, 24X158 LENS C/W RAYCAM REPORT, SD CARD, CHARGER BATTERY.
P01122012	CA6412, EARTH CLAMP, CAT. III 150V C/W CASE CL1 CALIBRATION LOOP.
P01157010	
Mtx3354e-C	
Hx0075	
Re3000 127 Vdc	
F203	
P01102083	
P01160631	CA8230, POWER QUALITY ANALYSER, SINGLE PHASE, C/W DATA VIEWER PRO S/W, BAG, LEADS MN93A CLAMP.
P01185301	

P01139702	5000V DC, CAT.III 600V, C/W RS 232 AND SOFTWARE.
Hx0079	
Hx0056-Z	
Mtx2022w-Pc	
Ox5022-C	OX5022-C, HANDSCOPE, PORTABLE OSCILLOSCOPE, 2 X 20 MHZ, DELIVERED WITH 1 PROBE (1/10, 1000V) 1 BNC/ BANANA LEADS, 1 MAINS ADAPTOR, 1 SET OF 6AA NIMH BATTERIES, 1 HANDS- FREE BAG, 1 CD-ROM CONTAINING U
Hx0032	
P01196521f	
P01145901	CA6710, TRAINING CASE, 17TH ED. ELECTRICAL INSTALLATION.
P01120309	
Hx0028	
P01255103	WATTMETER, RW 521.
Mx0407	
Mtx3282b-Bt	
Ax0503a	
P01295274	
P01167307	
P01160620	
9001.2	
P01120460	
P01160591	NO CURRENT CLAMPS.
P01120079b	
Mx0024b-Cl	
P01120576z	
P01167001b	CA41, FIELDMETER, 0.1.2.5 GHZ, C/W EF1 PROBE CARRYING CASE.
Ox6202b-Cfg	OX6202-CFG, 2 CH. 200 MHZ DIGITAL OSCILLOSCOPE WITH OPTION OF 1 EXTENSION OF EITHER HX0028 HARMONIC OPTION, HX0029 RECORDER OPTION HX0077 50K MEMORY OPTION C/W STYLUS, PROGRAMMING MANUAL ON CD-ROM, 1
P01298078	
	OX7042-M SCOPIX, OSCILLOSCOPE/M/METER: MONO, 2X

Ox7042-Msd	40MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX0030B), 1X BNC/PROBIX ADAPT (HX0031), 1X PROBIX/4MM ADAPT (HX0033),
P01160630	CA8230, POWER QUALITY ANALYSER, SINGLE PHASE, C/W DATA VIEWER PRO S/W, BAG AND LEADS. INSTRUMENT ONLY.
P01170501	
P01145450a	CA6116, INSTALLATION TESTER, COMBINED, CAT. IV 300V C/W LEADS, CLIPS, PROBES, SOFTWARE CARRY CASE.
Mx0025d	
Hx0052	
Ox6202b-Csdo	OX6202B-CSDO, 2 CH. 200 MHZ DIGITAL OSCILLOSCOPE WITH HX0028 HARMONIC OPTION, HX0029 RECORDER OPTION HX0077 50K MEMORY OPTION C/W STYLUS, PROGRAMMING MANUAL ON CD-ROM, 1 GB SD CARD, SD CARD ADAPTER, 2
P01138902	1000V DC, CAT.III 600V, C/W RS 232 AND SOFTWARE.
P01197403	
P01120335	
P01120752	
Hx0078	
212467	HAND-HELD OSCILLOSCOPE MODEL OX7104III 100MHZ (4X100MHZ, COLOR, 50K MEMORY, HARMONICS, RECORDER, POWER)
Mx0406b	
Hx0071	
P01295469	
P01101995	
Mtx3290	
Hx0220	
P01651522	
P01102115	
Ae0190	
P01651277	CA1877, DIACAM, THERMO CAMERA, 80X60 PIXELS, -20...250, 10X8, C/W BATTERY CHARGER, 2GB SD CARD, SD CARD READER, DIACAM PREVIEW SOFTWARE ON CD ROM, OPERATING MANUALS AND MEASUREMENT REPORTS.

P01650201z	
P01120961	
P01120304	
P01120314	
Mtx203-Z	
P01167002a	CA43, FIELDMETER, 0.1.2.5 GHZ, C/W EF2 PROBE, EMIGRAPH SOFTWARE, OPTICAL LINK CARRYING CASE.
P01120068	
Hx0034	
P01170303	
Sx-Dmmk2	
P01120110	J93, AC/DC, 50.3500AC/5000DC, 72MM , SINGLE, BLACK.
Mtx1054cw-Pc	
Mx9030-Z	
P01143200	CA6240, MICROHMMETER, 4 WIRE, 0.01.10A DC C/W 2M KELVIN CLAMP CABLES.
P01295220 (Ex C.A6547)	
Hx0210	
P01120030a	
P03652917	
Sx-Acq.V2	
P01132503	
P01102025	
P01295468	
P03197522a	
P01126511	CA6474, TOWER TESTER, C/W 4X 8M AMPFLEX AND ACCESSORIES (REQUIRES CA6472).
P01101914	
Mtx3293	
Hx0057	
P01122016	CA6417, EARTH CLAMP, CAT. IV, 600V, 35MM CLAMPING , COMPLETE WITH CASE CL1 CALIBRATION LOOP.

P01140801d	
12548e-000-K-Male	
P01120503	
Ox7204-Csd	OX7204-CSD, OSCILLOSCOPE/M/METER: COLOUR, 4X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX00030A), 1X BNC/PROBIX ADAPT (HX00031), 1X PROBIX/4MM ADAPT (HX00033)
Hx0029	
Mx553	
Mx0021	
Hx0004	
P01651228	CA1884, RAYCAM, THERMAL CAMERA, -20.250C, 20X15 LENS C/W RAYCAM REPORT, USB CABLE, CHARGER BATTERY.
Mtx2024w-Pc	
F603	
212494	OSCILLOSCOPE CII SERIES POWER KIT (ACCESSORY KIT FOR OSCILLOSCOPES CII SERIES)
P01160511	NO CURRENT CLAMPS.
P01298075	
P01156302z	
1015caldu	MEGOHMMETER MODEL 1015 (ANALOG, 500V, 1000V, RESISTANCE, CONTINUITY)
Ox7202-Bus	OX7202-BUS, 200MHZ OSCILLOSCOPE WITH BUILT-IN RECORDER FUNCTION, 2 CHANNELS, 600V / CAT III, 1000V / CAT II, C/W STYLUS, 1 STRAP, 1 OPERATING MANUAL, 1 PROGRAMMING MANUAL ON CD ROM, 1 EXTERNAL POWER S
Hx0005	
Mx1	
Mx0022	
P01298009b	
P01196311e	
Mtx3283b-Com	
Ca6255	
P01295451z	

Ox7102-Csd	OX7102-C SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 2X 100MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSERVER/FTP C/W 1X 1/10 PROBIX (HX00030B), 1X BNC/PROBIX ADAPT (HX00031), 1X PROBIX/4MM ADAPT (HX0
Ca8335	
Hx0052b	
Ax0501a	
Hx0002	
P01295217	
Hx0077	
Hx0035b	
1060caldu	MEGOHMMETER MODEL 1060
P01120404	
P01650101z	
P01102113	
P01139704	5000V DC, CAT.III 600V, C/W CARRY CASE LEADS.
212982	MICRO-OHMMETER MODEL 6290 (200A, MANUAL AND DATAV SOFTWARE)
P01167305	ELECTRIC FIELD PROBE.
P01295480	
P01295288z	
Sh-Ca6415-2-1-26	
At0057	
P01295214	
P01120923	
P01101916	
1045kit	MEGOHMMETER FIELD KIT, MODEL 1045 (MODEL 1045, REMOTE TEST PROBE FIELD CASE) (2117.31)
P01167003	CA42, LF FLELDMETER DC-400KHZ, 1V/M-30KV/M,C/W CHARGER,RS232,TRIGGER CARD,LOG42 PC S/W AND CARRY BAG.
Mx0059hd	
Mx0058hd	

Ox7062-Csd	OX7062-C SCOPIX, OSCILLOSCOPE/M/METER: COLOUR, 2X 60MHZ ISOLATED INPUTS, 2.5GS/S~12 BITS, ETHERNET/WEBSEVER/FTP C/W 1X 1/10 PROBIX (HX00030B), 1X BNC/PROBIX ADAPT (HX00031), 1X PROBIX/4MM ADAPT (HX00
Mx0002b	
P01126504	CA6472, EARTH RESISTIVITY TESTER, 0.001- 100 KOHMS, C/W 2X C182 CLAMPS, CHARGER S/W.
P01156401	
P01651263	CA1886BT, RAYCAM, THERMO/OPTICAL CAMERA , -20.600C, 20X15 LENS C/W RAYCAM REPORT, SD CARD, CHARGER, BATTERY BLUETOOTH.
P01120111	J193, AC/DC, 50.3500AC/5000DC, 72MM , SINGLE, BLACK.
P01102013	
L225g2r0	
P01167300	
Mx0001-M	
Ox6062b-Csd	OX6202B-CSD, 2 CH. 200 MHZ DIGITAL OSCILLOSCOPE WITH NO OPTIONS, C/W STYLUS, PROGRAMMING MANUAL ON CD-ROM, 1 GB SD CARD, SD CARD ADAPTER, 2 X 1/10 PROBES, 1 CROSSED ETHERNET CABLE 1 USB / RS232 CABLE.
P01255102	WATTMETER, RW 511.
Hx0040	
Cx1651	CX1651, MULTIFUNCTION CALIBRATOR, ELECTRIC, TEMPERATURE ENERGY PARAMETERS.
Hx0051b	
P01138901	1000V DC, CAT.III 600V, C/W CARRY CASE LEADS.
P01140201	
P01102018	
P01120402	
Hx0086	
Mx0355-Z	
P01101935	
P01120753c	
Hx0011	
	GREENTEST FTV100, PYRANOMETER, PHOTO-VOLTAIC

P01160700	ANALYSER, SGL SOURCE DC, C/W CLAMPS, LEADS, PROBES, SOFTWARE AND CARRY CASE.
P01140804b	
Ae0226	
P01255101	WATTMETER, RW 501.
P01102009z	
P01101994	
212458	HAND-HELD OSCILLOSCOPE MODEL OX7102III 100MHZ (2X100MHZ, COLOR, 50K MEMORY, HARMONICS, RECORDER, POWER)
Ae0216	
P01157140	AL834, SIMPLE LOGGER, 4 CH. AMPFLEX, 5.300/15.3000A AC, TRMS, CAT.IV 600V C/W SOFTWARE BLUETOOTH.
P01295472	
Hx0042	
P01157135	ML914, SIMPLE LOGGER, 4 CH. MINIFLEX, 1.100/5.1000A AC, TRMS, CAT.IV 600V C/W SOFTWARE BLUETOOTH.
Hx0191	
Ox0530-S	
P01295457z	
P01120302	
P03197528a	
P01120051a	
P01129501	
P01143201	CA6250, MICROHMMETER, 4 WIRE, 0.001.10A DC C/W 2M KELVIN CLAMP CABLES.
212488	OSCILLOSCOPE POWER KIT (ACCESSORY KIT FOR OSCILLOSCOPES)