

Comer Srl

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Comer Srl Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Comer Srl Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
DRIVE AX - 100K.2	ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) * POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 4,0 kW (Duty S1) * RATED TORQUE : 25,3 Nm * RATED FREQUENCY : 51,7 Hz * RATED CURRENT : 9,3 A * RATED SPEED : 1510 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 PTC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * INSULATION CLASS : F * ENCODER ELTRA EH80C1024Z5/28L14X3MR.197+295 1024ppr 10pins * PAINTING : BLACK RAL 9005 * NOTES : motor will be provided with free connector for encoder, without 3 mt. of cable
Drive AX 100K.5	
Drive AX 100K.3	

[Drive AX 100K.2](#)[Drive AX 100K.1](#)[DRIVE AX - 100K.2](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) * POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 5,6 kW (Duty S1) * RATED TORQUE : 25,1 Nm * RATED FREQUENCY : 72,6 Hz * RATED CURRENT : 12,4 A * RATED SPEED : 2130 r.p.m. * CONSTANT POWER SPEED : 3650 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 x KLIXON NC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * INSULATION CLASS : F * ENCODER SICK DFS60- (PLEASE SPECIFY PPR) - TTL or HTL (PLEASE SPECIFY) * PAINTING : BLACK RAL 9005

[DRIVE AX - 100K.2 , encoder SFM60-HMKT 0K02](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 5,6 kW (Duty S1) * RATED TORQUE : 25,1 Nm * RATED FREQUENCY : 72,6 Hz * RATED CURRENT : 12,4 A * RATED SPEED : 2130 r.p.m. * CONSTANT POWER SPEED : 3650 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 x KLIXON NC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * MAXIMUM ABSOLUTE SPEED : 6000 r.p.m. * INSULATION CLASS : F * Encoder SFM60-HMKT 0K02 absolute multi-turn HIPERFACE (Sick) 1024ppr * PAINTING : BLACK RAL 9005

[15KW RPM3030](#)[DRIVE AX 100K.2](#)[Rtlpvr 160 S Dc Motor](#)[Pwt132 K.5](#)[100k.3 Drive-Ax Motor](#)[Skr 80-2b 380v](#)[615/12](#)[Tetravec -160l.3](#)[Ntb 47ca](#)[Rtlpvr 160 S](#)[17 8-Mka Fd C8](#)[Skq 63-2a](#)

Tetravec - 160l.5	
Type: Ax/Ac 132 K4	
814/12	
Pg 502 Mc 23,1 Elc42	
Mp77s ? K40	
Tvc-Pvr 132 K5	
17 8-Mka Cb C8 Motorbetriebskondensator	
Ntb 900 Cc	
Drive Ax 100k. 5 Motor	
Ersatzkette Fur Comer Să196;Ge E21 F Nr. E21-Ksk-Ef404-68	
603/12	
Mp77s - K40	
Tetravec 132k.4	
100k.3	
Skg 63-2a.	
Tetravec 132.L2 26 Kw, 1500 U/Min, 380 Volt	
458.20n V24 F40 Nm400	
Comer-Srl-F3;R-Bremse-45820n-V24- F40-Nm400-Istanbul-Turkiye	
Pwt160lip54	
Skg 63-2a. Electric Motor	
17 8-Mka Cb C8	
Ntb 47	
17 8-Mka Fd C8 Motorbetriebskondensator	
Drive Ax - 100k.3	
11510016	
Comer Motor	TS-PVA100L5 V3
Drive Ax 100k.5	

614/12

Ersatzkette Fur Comer Säge E21 F Nr.
E21-Ksk-Ef404-68

Ntb 900 Cc Bimetallic Thermostat

Drive Ax 160l.3