

Cortem

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Cortem Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Cortem Trkiye Distribtr veya temsilcisi deēildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
rp-236/1	Electronic ballast 230V 50/60Hz 2x36W RP-236/1 replaces Ballast RP-236 , which is obsolete and no longer available. RP-236/1 is identical in fit, form and function
B-0267	Lampholder 250V 4A
PT100 7xE201	
GRD-4200	EARTHING SYSTEM 230V EARTHING SYSTEM / EARTHING MONITORING DEVICE made of low-copper cast aluminum alloy, polyester powder-coated RAL7035, Ex II 2 (1) GD Ex d [ia Ga] ia IIB + H2 T6 Gb Ex tb [ia Da] ia IIIC T85 ° C Db IP66 Voltage: 230V AC 50 / 60Hz with 2 cable entries 3/4 "ISO 7/1; delivery takes place with: - pliers with cable 8m, connected via sealing screw connection - 1x Ex d blind plug galvanized steel; - LED indicator lights green and red; ambient temperature: -20 ° C to + 55 ° C; Certificate: CESI 04 ATEX 129 Weight: 20kg
	LIGHT.FIX. EX II 2GD EX DE MB ALU Lighting fixture with high efficiency LED strips for normal operation;Ex II 2GD - Ex db eb mb IIC T6/T6/T5 Gb - Ex tb IIIC T62°C/T67°C/T77°C (+40°C / +50°C / +60°C) Db IP66with anodised aluminium body, impact and high temperature resistant glass diffuser; galv. steel brackets adjustable -30°/0°/+30°; real power 31,5W (rated 30W), 100-

LIFEX-ME-0630	277Vac, 50/60Hz; 4018lm, 1564cd, 128lm/W; Standard 2xM20 entries (side 1) with 1x Exd Plug PLG1IB and 1x Exd cable gland NAV20IB (6,5-14mm), both brass nickel pltd. (M25, entries on both sides on request); ambient temp. -60°C +40°C/+50°C/+60°Cweight: 2,5kg - CML 20 ATEX 3018X HS Code: 94054099
LIFEX-ME-1230N	LIGHT.FIX. EX II 2GD EX DE MB ALU Lighting fixture with high efficiency LED strips for normal + emergency operation;Ex II 2GD - Ex db eb mb IIC T6/T6/T6 Gb - Ex tb IIIC T65°C/T70°C/T80°C (+40°C / +50°C / +60°C) Db IP66with anodised aluminium body, impact and high temperature resistant glass diffuser; galv. steel brackets adjustable -30°/0°/+30°; real power 30,2W (rated 30W), 110-277Vac, 50/60Hz; 3901lm, 1556cd, 130lm/W; Discharge time: 180 Min.Standard 2xM20 entries (side 1) with 1x Exd Plug PLG1IB and 1x Exd cable gland NAV20IB (6,5-14mm), both brass nickel pltd. (M25, entries on both sides on request); ambient temp. -20°C +40°C/+50°C/+60°Cweight: 4,5kg - CML 20 ATEX 3018X; HS Code: 94054099
EVF-18ENX	Copper free aluminium alloy Normal + emergency lighting fixture with Exit label, Ex II 2GD Ex d IIC T5 tD A21 IP66,230Vac 50/60Hz, suitable for 1x8W bipin fluorescent tube, electronic ballast, 2,5Ah battery, autonomy 150min.With 2 entries 3/4" NPT threaded, 1 of them with aluminium plug (PLG2NA). weight: 3,5kg - CESI 03 ATEX 098
SX-16.1N	JUNCTION BOX EX II2GD EX D IIC Round junction box made in aluminium alloy, not painted.Ex II 2GD Ex d IIC T Ex tb IIIC T°C Db IP66/67 Diameter of the lid: 89mm.4 entries 1/2" NPT (1 each side - "X"). weight: ca. 0,5kg - CESI 03 ATEX 059UHS Code: 76169990
FIXTURE, FLUORESCENT LIGHTING; VOLTAGE:	100-277 V AC, WATTAGE: 30 W, LENGTH: 1200 MM, LAMP: LED, MOUNT: CEILING TALL MODEL TYPE "U", TYPE: LED, ENCLOSURE: IP 66, CLASSIFICATION: GROUP II LIFEX-ME, STANDARD: CENELEC EN60079-0: 2018, EN60079-1: 2014, EN60079-7: 2015, EN60079-18: 2015, EN60079-31: 2014 AND EUROPEAN DIRECTIVE 2014/34/EU IEC60079-0: 2017, IEC60079-1: 2014, IEC60079-18: 2014, IEC60079- 31: 2013, IEC60079-7: 2015; FFT: 2 SIDE HOLES M25, MOUNTING KIT INCLUDED: 2 CABLE GLAND NAV20IB - BRACKET TYPE: U COMPLETE WITH SCREWS:G-0609; APPLICATION: COLD MILL COMPLEX LIGHTING SYSTEM .; P/N: LIFEX-ME-1230N /CC,
FP-23 PLUG 2 P+E FOR FSQC	Copper free aluminium alloy plug RAL7035 electrostatic powder painting. Ex II 2GD Ex d IIC T6 Gb Ex tb IIIC T85°C Db, IP65. Suitable for socket series FSQC. 2P+T, 63A 690V 50Hz. 1 entry 1" ISO 7/1 threaded. Weight: 0,82kg - CESI 04 ATEX 043
FP-23/TS PLUG 2 P+E FOR FSQC 24V (Special)	Copper free aluminium alloy plug RAL7035 electrostatic powder painting.Ex II 2GD Ex d IIC T6 Gb Ex tb IIIC T85°C Db, IP65. Suitable for socket series FSQC.2P+T, 63A 24V. 1 entry 1" ISO 7/1 threaded.NOTE: For Sockets FSQC with ATEX and ISO thread (to connect to plug) only.Weight: 0,82kg - CESI 04 ATEX 043
FP-24 PLUG 3 P+E FOR FSQC	Copper free aluminium alloy plug RAL7035 electrostatic powder painting.Ex II 2GD Ex d IIC T6 Gb Ex tb IIIC T85°C Db, IP65. Suitable for socket series FSQC.3P+T, 63A 690V 50Hz. 1 entry 1" ISO 7/1 threaded. Weight: 0,83kg - CESI 04 ATEX 043
18ENX Battery pack Ni-Cd 2,5 Ah	- 6,5 V BATT2,5AH/NC

EVF-18ENX Frame with battery pack and electronic	board 230V 50/60Hz normal + emergency - G-0451/1
EVF-18ENX EXPROOF EMERGENCY	LIGHTING FIXTURES LED TUBE (COMPLETE)
1/2 non-armoured gland cable diameter 6-12 mm	
CRV-420/100	
CSC-316	
EFSCO-66	
EPRC1-1Q63B	
EVS2	
FV-1	
G-0309B	
GF2G	
GF2G 3/4	
SC-24.1	
SC-24.EDM.2	
YFC-E31Z11	
M-0440	
M-698	
MT2	
M-0429/R	S/M PUSHBUT. EX D RED Pushbutton Ex II 2GD Ex d IIC Gb Ex tb IIIC Db IP66 red colour. Complete with 1NO + 1NC contacts
M-0457/3V24	SIGN.LED GREEN 24V Indicator light, green, with three high-brightness LEDs Ex II 2GD Ex db IIC Gb; Ex tb IIIC Db; IP66consumption of 20mA and estimated life of around 50.000 hours
M-0457/3R24	SIGN.LED RED 24V Indicator light, red with three high-brightness LEDs Ex II 2GD Ex db IIC Gb; Ex tb IIIC Db; IP66consumption of 20mA and estimated life of around 50.000 hours
M-0457/3G24	SIGN.LED YELLOW 24V Indicator light, yellow with three high-brightness LEDs, 24V ac/dc Ex II 2GD Ex db IIC Gb; Ex tb IIIC Db; IP66consumption of 20mA and estimated life of around 50.000 hours
M-0429/V	S/M PUSHBUT. EX D GREEN Pushbutton Ex II 2GD Ex d IIC Gb Ex tb IIIC Db IP66 green colour. Complete with 1NO + 1NC contacts
M-0429/BI	S/M PUSHBUT. EX D W Pushbutton Ex II 2GD Ex d IIC Gb Ex tb IIIC Db IP66 white colour. Complete with 1NO + 1NC contacts.
M-0445	S/M MUSHR.ROT.UNLOCK EX D Mushroom pushbutton "rotate to release" Ex II 2GD Ex d IIC Gb Ex tb IIIC Db IP66 red colour.

GRD-4200	Earthing equipment with electronic control system, installed in aluminium alloy box painted RAL7035. Voltage 230Vac. Ex II 2(1)GD Ex d [ia Ga] ia IIB+H2 T6 Gb Ex tb [ia Da] ia IIIC T85°C Db IP66. With wall fixing brackets, 2 entries 3/4" ISO 7/1 (1 of them with galvanized steel plug). Earthing clamp attached to 8 meters cable. certificate: CESI 04 ATEX 129; customs: 85371098; Weight: 20kg;
SB-26N	JUNCTION BOX EX II2GD EX D IIC Round junction box made in aluminium alloy, not painted. Ex II 2GD Ex d IIC T Ex tb IIIC T°C Db IP66/67 Diameter of the lid: 89mm. 2 entries 3/4" NPT (side+bottom).
SB-26NV	JUNCTION BOX NPT Same but painted in RAL7035
FLF-L / FLFE-L	LED tubes (e.g. FLF/E-211L)
LIFEX	LED strip. (e.g. LIFEX-ME-0630 or LIFEX-ME-1230)
Junction box,SC-26.1I, Cortem	Code: SC-26.1I Thread:Metric Gland Diameter: M25 Number of holes: 2 Pieces (right and left) Protection class: IP66/67 ATEX Group: Ex d IIC T6 Gb and Ex tb IIIC T85 Db
H50 Fixing Clamp (GRP)	
M8x25 Fixing Set (SS 316)	
Cable duct,040 UKFG 50,EAE	
Suspension element,BR 462 BINRAK,EAE	
M8x25 Fixing Set (SS 316)	
YFC-E43-Z11	LIMIT SWITCH EX D Limit Switch Ex II 2GD Ex d IIC T6 tD A21 IP66/67 with body cover in copper free aluminium alloy, painted RAL7035. Complete with roller lever with steel ball bearing, snap action contacts (1NP+1NC). SIRA 07 ATEX 1316
EJB-1	EXD IIB+H2 HOUSING w/hinged cover 1 Housing complete with 1 Internal Aluminium mounting plate CORTEM (BFE-1) 1 Momentary Green Pushbutton 2NO CORTEM (M-0429/V) 1 Momentary Red Pushbutton 2NC CORTEM (M-0429/R) 12 2.5 Sqmm terminal block WEIDMULLER WDU2.5 1 2.5 Sqmm earth terminal block WEIDMULLER (WPE2,5) 1 Rotary handle for selector switch pad lockable in off position CORTEM (M-0553L) 1 3 POSITION SELECTOR SWITCH 1NO+1NC CONTACTS IN POSITION HAND AND AUTO BLUMEL (U2-10E/R) Execution according to Drawing 3548DWG-E11-NiLi (attached) (corresponds to the production of 2020)
PY432R	SOCKET 3P+N+E 32A 380/415V Copper free aluminium alloy socket. RAL7035 electrostatic powder painting. Red closing PVC plug. Ex II 2GD Ex d IIC T6 Gb; Ex tb IIIC T76°C Db, IP65. Ambient temperature -20 +50°C. 3Ph+N+E, 32A 380/415V. Non automatic interlocked switch. Suitable for wall mounting. 2 entries 1" ISO 7/1 (1 on top and 1 on bottom).
GRD-4200	ELECTRONIC GROUNDING SYSTEM 230 VAC Earthing equipment with electronic control system, installed in aluminium alloy box painted RAL7035. Voltage 230Vac. Ex II 2(1)GD Ex d [ia Ga] ia IIB+H2 T6 Gb Ex tb [ia Da] ia IIIC T85°C Db IP66. With wall fixing brackets, 2 entries 3/4" ISO 7/1 (1 of them with galvanized steel plug). Earthing clamp attached to 8 meters cable. certificate: CESI 04 ATEX 129; customs: 85371098; Weight:

	20kg; NOTE: cable length attached to GRD is max 8m. For 11m you need a cable reel.
YFC-E52Z11	LIMIT SWITCH EX D Limit switch Ex II 2GD Ex d IIC T6 tD A21 IP66/67 with body and cover in copper free aluminium alloy, painted RAL7035. Complete with adjustable lever with s.s. roller, snap action contacts (1NO+1NC). Weight: approx. 0,400kg; SIRA 07 ATEX 1316;
EVL-070070	High bay led Lighting fix 120 EXD IIC-70W
BZ-4200	BARRIER ZENER FOR GRD-4200
TYPE-B-50MF	CAPACITOR:400W,HPS,VAPOUR LAMP,METAL,FOR EASY SERIES LIGHTING FIXTURE,TYPE B,50MF,250VAC,50/60HZ
ARM.ILL. EX II 2GD EX EB MB TB	Round LED lighting fixture. Body in aluminum alloy. Shock-resistant flat tempered glass cover. RAL7035 electrostatic powder painting. Ex II 2GD Ex db eb mb IIC T5 Gb Ex tb IIIC T86°C Db, IP66. Ambient temperature -20 +40°C. 100-277Vac 50/60Hz, 80W, 10646lm, 5000K, light beam 120°. Adjustable mounting bracket included. 1 entry Ø20.5mm complete with 1xNAV20SIB (Ø6.3÷11.6mm). NOTES - EVL series fixtures are in phase-out, so we quoted equivalent luminaires from the new FLOWEX series.
YFC-E91Z11	Limit switch Ex II 2GD Ex d IIC T6 tD A21 IP66/67 with body and cover in copper free aluminium alloy, painted RAL7035. Complete with stainless steel multidirectional spring actuator, snap action contacts (1NO+1NC).
LIFEX-PN-0645	ARM.ILL. EX II 3G 2D EX EC PC LED linear lighting fixture. Body in GRP. Transparent part in polycarbonate, resistant to impacts. Ex II 3G Ex ec IIC Gc - Ex II 2D Ex tb IIIC Db, IP66. Ambient temperature and Temperature Class as per attached datasheet. 220-240Vac 50/60Hz, 45W, 5472lm, 5000K, light beam 120°. 2 entries Ø20.5mm complete with 1xNAVP20IXE (Ø7-12mm) and 1xPLG1ILXE7. NOTES - Mounting brackets not included, available on request (please specify the required installation type).
SA141410	ENCLOSURE EX II 2GD EX E IIC Copper free aluminium alloy junction box. RAL7035 electrostatic powder painting. Ex II 2GD Ex e IIC Gb Ex tb IIIC Db, IP66. External dimension 147x147x100mm. NOTES - Mounting frame and internal components are not included; in case of order, it will be necessary to fill in an installer declaration.
Eva-5060	
Rp-236 (Ex. Rt-236)	
Yfc-E51z11 S/N 09/226813	
M-0612/3v24	
Exel-236ef4	
Exel-218	
Np3g	
Evl-60	
Evgc-5060	

Ejbx-7
Avn-236
Evl-70
Revd3nb
Ballast For Lamp Exel-236,Eb4236/M
Sc 26.1
Flfe-236
G-0312e/1450b
Lampnav250wplushigh Press Soudium Vapour Lamp 250w
Floodlight Ex Ii 2gd Ex De Iib
Ejb8
Csg302318
Db3pvc
Fgab2bk/3
Fp-24
M-0436/V
Db6pvc
Eb4218/M
Unp7xe
Ws2-10e/R/X8490
Spy216b
Eb4236/M
Fb7bk
Sa473018/P,Ce 0722
Ejb-2
R-400na - Ball.400w For Sodium Lamps
M-0445
Sfc-14.1v
Uni3xe
Fb5bk
Fsqc-23463
Fga1nak

Elfe-222l	
Elf-236	
Model Egb45ba Exproof	
Lamp136w21	
Unp9xe	
Fb1bk/3	
Spy332r	
Py316r	
Csg623018	
Avf-2411 Obsolete	
Exel-V236s	
M-0457/3i230	
Efsco-63	
Ejbx-55	
Py232b	Socket 2P+E 32A 200/250V
Py216b	
Fb6bk	
Evf-158eb	
Rlfe-110im6	
M-0436in/V1	
Spy232b	
G-258	
A4-32e/R	
Rv-236	
Revd4nb	
Exel-118ee7	
Fb8bk	
S.N.13/282440	
Crv420/1000	
B36-363	
Revd1nb	
Gub-03	

Py432r	Socket 3P+N+E 32A 380/415V
Ebv-1	
Csc-R	
Fb4bk	
2x36w, :Flfe-236 Or Flfe-222l	
Ewngc80-N5	
St-16.1v	
Spy316r	
Cs623018/P	
Sn:09-148013m57971	
M-0436in/V	
Unp1xe	
Db2pvc	
Py232r	
Ets60/109db230v	
Ewl-801	
Csc-2i	
M-0531	
M-0457-G	
Ejbx-5	
M-0604/1z	
M-0429/B	
Ewl-100	
Fgab1bk/3	
Eb4136/M	
Rp-258	
Flfe-258	
M-0603/V	
G-0480	
Cortem S Serisi Exproof Buat	
Fp-23/Ts-24	
G-0312e/1450g	
Db8pvc	

[Evgc 4060- Obsolete, Replaced By Evgc-5060](#)[Fp-23/24](#)[Sa111108](#)[M-0457-R](#)[Fb2bk/3](#)[Ycf-E52-Z11](#)[Np8g](#)[Unp8xe](#)[M-0603/R](#)[Fb3bk/2](#)[M-0429/N](#)[Exel-236ef7](#)[Revd2nb](#)[Cca-03c](#)[Flfe-22l/20st](#)[Ecd-115s](#)[M-0436/V1](#)[Fp-23/Ts , Fp-23/24](#)[Ccai2020](#)[M-0457-I](#)[LampI18w21](#)[Ejbx-6b](#)[Ccfe-3b](#)[Sc-26.1 Cesi 02 Atex 091](#)[Exel-236](#)[Grd 4200](#)