

A-342



Crosby

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Crosby Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Crosby Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Typ G-417	7013035 Bow rope sleeve type G-417 Diameter 32-35 mm
G-417	7013048 Bow rope sleeve type G-417 Diameter 44-48 mm
7013035	Bow rope sleeve type G-417 Diameter 32-35 mm
7013048	Bow rope sleeve type G-417 Diameter 44-48 mm
Liste 18 Pos.	Bitte um Kontrolle und Angebot
Crane pennant, 2 meters long 6x19 IWRC Galv	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv	. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye(SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders) 8 ton SWL x 5m long.	22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders) 5 ton SWL x 5m long.	6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 16mm x 19mm, SWL 3.25 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 19mm x 22mm, SWL 4.75 ton
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 22mm x 25mm, SWL 6.5 ton
	bow shackles with safety bolt, to EN13889, hot dipped

Green pin standard shckles,	galvanized, 25mm x 28mm, SWL 8.5 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 32mm x 35mm, SWL 12 ton
1000 kg SWL Chain blocks with certificate	
Crane pennant, 2 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 2 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long	6x19 IWRC Galv. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders)	8 ton SWL x 5m long. 22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders)	5 ton SWL x 5m long. 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
1090125	Crosby safety hook set SS-4055 - 11.5to for old hooks 319, 320 and 322
1093541	Crosby safety hook set SS-4055 - 22to 22 to. - for old hooks 319, 320 and 322
G-450 16 mm	7504530-2 Crosby wire rope clips G-450 Nominal width 16 mm 5/8 "- HOT GALVANIZED"
G-450 9-10 mm	Crosby wire rope clips G-450 Nominal width 9-10 mm 3/8 "- HOT GALVANIZED"
G-429 14 - 16 mm	Crosby wire rope clips G-429 Nominal width 14 - 16 mm 9/16 - 5/8 "
3313042	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 3/4 in., WLL: 25 t EN 13889 Nominal size 1 3/4 in., WLL: 25 t

3313212	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 1/4 in., WLL: 12 t EN 13889 Nominal size 1 1/4 in., WLL: 12 t
3313210	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 in., WLL: 8.5 t EN 13889 Nominal size 1 in., WLL: 8.5 t
25 TON MCKISSICK BLOCK, FOR WIRE SIZE 28.5 MM	M-491G/2032315 MCKISSICK
12 TON MCKISSICK BLOCK, FOR WIRE SIZE 19 MM	M-491G/2021163 MCKISSICK
4 TON MCKISSICK BLOCK, FOR WIRE SIZE 10 MM	M-491G/2020170 MCKISSICK
7504529	Crosby wire rope clips G-450 Nominal size 3 - 4 mm "1/4" "- HOT GALVANIZED" As an alternative to HG223, we offer: Crosby - with fork-fork
3013085	Crosby rigging screw galvanized HG-228 1/4 "x 4" fork - fork
6000000	Crosby rigging screw galvanized HG-228 5/16 "x 4-1 / 2" fork - fork
Range 143-163PSI	
RANGE 131-149PSI	
4100743	IP lifting clamp IPU10 0.5 EN 13155 Load capacity: 0.5 tons Gripping range 0-16MM
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM
Crosby S-265 (1290848)	WLL: 3,2
G2130A 4-3/4T 3/4" ALLOY BOLT TYPE SHK	1219516
G2130A 6-1/2T 7/8" ALLOY BOLT TYPE SHK	1219534
S265 1,2TX13MM	Ersetzt Art. 1290740
Rope Terminal Ø10mm	
BEP MBL 90T	Shackle Mooring No 852
1068389	HR1000M M36X130MM 6000000
(S65) CROSBY - 1068389	FAM 02TD2
CROSBY G341 16MM 5/8" WELDLESS SLING LINK GALV.	

CROSBY G209 3/4T 5/16" SCREW PIN ANCHOR SHACKLE	
CROSBY 1208 WEST 4" SHEAVE bb	
CROSBY G341 10MM 3/8" WELDLESS SLING LINK GALV	
CROSBY A336 8-10MM 3/8" GR6 LOK-A-LOY	
A-1337 32-10 (ID: 1015181)	Crosby Lock-a-loy
WLL: 25T (ID: 1262095)	Crosby Bow shackle with safety bolt
1018552	CROSBY G209 9-1/2T 1-1/8" SCREW PN ANCH
1018516	CROSBY G209 6-1/2T 7/8" SCREW PIN ANCH. SHACKLE
1018598	CROSBY G209 13-1/2T 1-3/8" SCREW PIN AN SHACKLE
Crosby HR125 - 1"A, ID: 1016964	
DOUBLE CLEVIS LINK S-247	Material item number : 00013195 Manufacturer : CROSBY Manufacturer part no. : 1013049
ALLOY CHAIN 8MM	Material item number : 00013196 Manufacturer : CROSBY Manufacturer part no. : Gr. 100 - 273729
LEBUS L-140 STANDARD RATCHET	Material item number : 00013197 Manufacturer : CROSBY Manufacturer part no. : 1048404
G-8142 EYE NUT M20 DIN 582	
LIFTING EYE GR8	Material item number : 00013199 Manufacturer : Green Pin Manufacturer part no. : GPAL20
LIFTING EYE LENGTH AS DIN580 GR8	Material item number : 00013200 Manufacturer : Green Pin Manufacturer part no. : GPAL20DIN
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM 2701663
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM 2701665
4100745	IP lifting clamp IPU10 2 EN 13155 Load capacity: 2 tons Gripping range 0-35MM 2701677
1.1/2G2.1/1 JLT-J05-15-A	
Crosby G209	1018491
2092120/	CROSBY Wirbelhaken - SHUR-LOC S-1326 10 MM
KLEMENSİ 16 MM G-450 crosby	
KLEMENSİ 28 MM G-450 crosby	
Crosby Wire Rope Clips G-450 Nominal width 16 mm "5/8 "" -	

7504530-2/	HOT GALVANIZED"
7504531/	Crosby Wire Rope Clips G-450 Nominal width 28-30 mm
G-2140	Alloy Bolt type Anchor Shackle WLL: 40T, ID: 1021138
Clip 3/8" Wire G-429 Fist Grip(Gergi Halatı Clamsi	
589714	EGKN-10-10
IPH10--2703297	
5-S-3 Stock No : 297235	
HR 125 M16	
Shackle 1/4" Crosby 2130 Grade6 bolttype	
Shackle 3/8" Crosby 2130 Grade6 bolttype	
Shackle 1/2" Crosby 2130 Grade6 bolttype	
Shackle 5/8" Crosby 2130 Grade6 bolttype	
Shackle 3/4" Crosby 2130 Grade6 bolttype	
Shackle 1" Crosby 2130 Grade6 bolttype	
G-2130	Crosby G-2130 Bolt Type Anchor Shackle WLL: 0,5T, Part No.: 1019466
951111MFA-P:VALVE	~ OMNI 951, 3/4 MNPT X 1 FNPT, 316 SST MATERIALS WITH METAL SEAT, THREADED CAP, PED
HG-228 G-6323 -	1032714 SSGPMBGG191 2 163 403 412 ROPE TENSIONER, JAW-JAW, 3/4" X 12", 2.36 TONS
HG-228 G-6323 -	1032778 SSGPMBGG221 8 163 407 818 ROPE TENSIONER, JAW-JAW, 7/8" X 18", 3.27 TONS
HG-228 G-6323 -	1032830 SSGPMBGG251 8 163 410 018 ROPE TENSIONER, JAW-JAW, 1" X 18", 4.54 TONS
HG-228 G-6323 -	1032894 SSGPMBGG321 8 163 411 418 ROPE TENSIONER, JAW-JAW, 1-1/4" X 18", 6.90 TONS
HG-228 G-6323 -	SSGPMBGG642 4 ROPE TENSIONER, JAW-JAW, 2-1/2" X 24", 27.20 TONS
G-450 G-6240	1010079 CLGRP08 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 8 MM (5/16"), EN 13411-5 TYPE B
G-450 G-6240	1010097 CLGRP10 STEEL ROPE TERMINAL, HOT DIP

G-450 G-6240	GALVANIZED, 10 MM (3/8"), EN 13411-5 TYPE B 1010131 CLGRP12 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 13 MM (1/2"), EN 13411-5 TYPE B
G-450 G-6240	1010195 CLGRP19 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 19 MM (3/4"), EN 13411-5 TYPE B
G-414	G-6120 1037675 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 10 MM (3/8")
G-414	G-6120 1037791 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 22 MM (7/8")
1035018	
1014155	
1048636	
Swivel 3 Te	Swivel No: 3-S-2, Steel, Red Operating Temperature: -40° C to +204° C Onshore Working Load Limit: 3 Tons
Crosby Shackles x 8 ea.	Crosby G 2130, Steel, Galvanized, Operating Temperature: - 40° C to +204° C Onshore Working Load Limit: 2 Tons
98832835	SHACKLE, BOLT TYPE ANCHOR, WLL 1.5T
98871566	SAFETY, SHACKLE, 4 PART ANCHOR, BOW, - G-2130, SWL 3.25T C/W COTTER PINS
END LINK WELDLESS S340 1/2 SUPPLIER CODE: 75535	
SHACKLE ANCHOR S-213 2T SUPPLIER: 75535,	
SHACKLE ANCHOR S-213 3 1/4 TON SUPPLIER: 75535,	
LINK, END WELDLESS S-340 (312) SUPPLIER:	75535
VALVE, RLF, CROSBY, 95114XMFA- SPL, 261PSI	Valves, Relief Type of bonnet/cover CLOSED Type of construction CONVENTIONAL Flow, max 7.327 m³/h Set pressure 17.99 bar 261 psi Temperature, max 38 °C Temperature, min -35 °C Size, inlet 1/2 in Size, outlet 1/2 in Size, orifice, actual 0.545 cm² Mat, body MONEL Service(s) SEAWATER Type of end connection NPT MALE x FEMALE Mat, bonnet MONEL Mat, spring INCONEL X750 Type, cap SCREWED Manufacturer THE CROSBY GROUP Manufacturer Part Number 95114XMFA-SPL
3K4 JOS-E-45-J	
CHAIN HOOK / MODEL:S1317	SHUR-LOC CLEVIS HOOK, 6MM PIN AUTOMATIC LOCKING HOOK, CAPACITY:1450KG, EN 1677-3 (CERTIFICATE INCLUDED) / CROSBY / 1028991 /
1.5d2 Jbs-E-55-J/Spl	

961101mfa	
1019579 Hochfeste Schäkel	
1019533 Hochfeste Schäkel G 2130	
1.5h3 Jbs-E-15x-J -Spl	
G2150 1019953	Shackle straight with nut and split pin
1018516 (G209)	
1019686 Hochfeste Schäkel S 2130	
089115 (Obsolete - No Replacement) Nozzle	
G-340	Crosby G-340 1014093 WLL: 2,95 t.
1014365	CROSBY Master Link A-342
1025896-L1327	Eye hooks
1019953 Hochfeste Schäkel G 2150	
1.5d2 Jlt-Jos-E-56x-J/Spl-Spl	
G-450	G-450 1/2" 12-13 MM 1010131
P/N:136161	
1.5h3jos-E15c-Pspl	
A-1337	
1019524 Hochfeste Schäkel S 2130	
1022923	
1.5h3 Jbs-E-Or-15-L	
1018614	
G-209	Crosby anchor shackle with eyelet pin G-209 EN 13889 Nominal size 5/16 in., WLL: 0.75 t
G 2150 1019873	Shackle straight with nut and split pin
1022238	
1019677 Hochfeste Schäkel G 2130	
123834	
1010015 G450	
1018534.	
L320an-1022457	Eye hooks

Uni1950	
10143604	
04-4749-065	
1022260	
1019613 Hochfeste Schäkel G 2130	
S-91740	
1.5g2.5 Jbs-E-45-J	
A-345	Master Link Assembly WLL: 38,5to Crosby-Artikel-Nr.: 1014814
1.5e2 Jos-E-55x-J /Spl-Spl	
1014348 Aufhängeglied	
Z091147b1ra5p1	
1014342-Obsolete-Alternative 1014348 Master Link	
A-342	Alloy Master Links
1014348	
1022293	
Grade 100 Alloy Chain	Nominal thickness: 26mm Crosby Item No .: 1210232
S-91328 / Inconel 625	
1.5g2.5 Jos-E-26-D	
1.5h3 Jos-E-26-D	
1019953	CROSBY Schäkel G-2150 - 25 to
1019622 Hochfeste Schäkel S 2130	
G2150 1019935	Shackle straight with nut and split pin
1015104	
0.5t Ip10 222.701.674	
951101mfa	
1022246	
Lok-A-Loy 10 Alloy Connection Link	WLL: 41,0to Crosby-Artikel-Nr.: 1015181
320/C	
961111mfa	

1.5f2 Jbs-E-16-L	
G-408	G-408 1/2" 11-13 MM 1037595
1037318	
951101ma	
1014319 Aufhängeglied	
1022932	
101517 2	
1019515 Hochfeste Schäkel G 2130	
L320an-1022446	Eye hooks
1019962 Hochfeste Schäkel S 2150	
1018570	
1022424	
1019542 Hochfeste Schäkel S 2130	
10195794	
Hg-228 1/2x12"	3000000
039973 (Obsolete - No Replacement)	
Disc Bushing	