

Denios

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Denios Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Denios Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
201352	Spiral earthing cable with 1 stainless steel earthing clamp Medium Duty 120 mm and 1 eyelet, 3 m extension length, ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type MD: length 120 mm, opening angle approx. 15 mm (for barrels, containers up to 200 liters) - Cable cross section: 4 mm ² , total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 60 Outer width (mm): 25 Outer depth (mm): 3180 Equipment: 1 stainless steel pliers MD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 3000
	Spiral earthing cable with 1 stainless steel earthing clamp Medium Duty 120 mm and 1 eyelet, 5 m extension length,

[201353](#)

ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type MD: length 120 mm, opening angle approx. 15 mm (for barrels, containers up to 200 liters) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 60 Outer width (mm): 25 Outer depth (mm): 5180 Equipment: 1 stainless steel pliers MD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 5000

[201354 Heavy Duty](#)

ALTERNATIVE TO POS 1 Spiral earthing cable with 1 stainless steel earthing clamp Heavy Duty 235 mm and 1 eyelet, 3 m extension length, ATEX avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable - With 1 ring eyelet and 1 earthing clamp type HD: length 235 mm, opening angle approx. 40 mm (for containers from 200 liters, larger system parts, IBCs, Mixing tanks, mobile tanks, tank vehicles etc.) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 105 Outer width (mm): 40 Outer depth (mm): 3295 Equipment: 1 stainless steel pliers HD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 3000

[201355 Heavy Duty](#)

ALTERNATIVE TO POS2 Spiral earthing cable with 1 stainless steel earthing clamp Heavy Duty 235 mm and 1 eyelet, 5 m extension length, ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type HD: length 235 mm, opening angle approx. 40 mm (for containers from 200 liters, larger system parts, IBCs, Mixing tanks, mobile tanks, tank vehicles etc.) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 105 Outer width (mm): 40 Outer depth (mm): 5295 Equipment: 1

	stainless steel pliers HD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 5000
117044	
117138	
117138W	
165242	
214474	
250676	
31408	
715033	
Für RAL 5010	
GFT 33.15	
PE Blau	
RAL 5010	
117721	Heating jacket for 30 liter drums, 0 - 90°C thermostat, 870 - 1020 mm, 200 watts Suitable for: 25 - 30 liter steel and plastic drums Intended use : Keep warm/warm up Version : jacket heating Place of installation : indoors External width (mm) : 1020 External depth (mm) : 80 External height (mm) : 400 Cable length (mm) : 5000 Container circumference min (mm) : 870 Material : Nylon, polyurethane coated Surface : Teflon coated Color: Black Power (W) : 200 Rated Voltage (V) : 240 Control range max (°C) : 90 Fabric Material : NYLON/POLYESTER Approval / Certificate : EU Directive (2014/35/EU), EU Directive (2014/30/EU), EU Directive (2011/65/EU) Equipment : analogue temperature controller Degree of protection IP : IP 44 Weight (kg) : 1.8 Customs tariff number: 85144000 Country of origin : United Kingdom
156179	HEATING JACKET FOR 205 LITRE DRUMS, 0 - 90°C THERMOSTAT, 1800 - 1950 MM, 1100 WATT Heating jacket for 200 liter drums, 0 - 90°C thermostat, 1800 - 1950 mm, 1100 watts - Medium power heating jacket: for rapid heating of media in applications requiring require a fast heating rate up to approx. 50 - 70°C Suitable for: 200 - 220 liter steel and plastic drums Intended use : heating Version : jacket heating Place of installation : indoors Outside width (mm) : 1950 External depth (mm) : 100 External height (mm) : 850 Cable length (mm) : 5000 Container circumference min (mm) : 1800 Material : nylon/glass fiber thread silicone b Color: Black Power (W) : 1100 Rated Voltage (V) : 240 Control range max (°C) : 90 Fabric material : NYLON Approval / Certificate : EU Directive (2014/35/EU), EU Directive (2014/30/EU), EU Directive (2011/65/EU) Equipment : analogue temperature controller Degree of protection IP : IP 44 Weight (kg) : 5
	Base-line collection tray made of polyethylene (PE) for 2

267371	barrels, with PE grid Grating: plastic Version: accessible Material: plastic Collection volume [l]: 220 Total load capacity [kg]: 760 Weight [kg] : 27.5 External width [mm]: 865 External depth [mm] : 1245 External height [mm]: 375 Approval: DIBt Approval / Certificate Description 1 : Z-40.22- 252 Color orange Brand: DENIOS base line Storage capacity: 200 liter barrels: 2
267499	Collection tray classic-line made of polyethylene (PE) for 2 barrels, with PE grid, 1330x930x410 - Access pockets in the floor area enable safe transport and assembly with barrel lifters, pallet trucks and forklifts from all 4 sides. - Highly resistant to oils, acids, alkalis and other aggressive substances - Legally compliant: seamlessly manufactured and absolutely liquid-tight - Stable construction with good shock and impact resistance, even for large ones Temperature fluctuations Grating: plastic Version: accessible Material: plastic Collection volume [l]: 220 Total load capacity [kg]: 800 Weight [kg] : 43.9 External width [mm]: 1330 External depth [mm]: 930 External height [mm]: 410 Approval: DIBt Approval / Certificate Description 1 : Z-40.22- 55 Brand: DENIOS classic line Storage capacity: 200 liter barrels: 2
M28-0051-200-10	
K22-0193-14	
Kbe 9050	
M28-083610	
129124	
Dgf 4	
195-291	
M28-0836-14	
Gefahrstoffregalanlage	
183-508	
M32-0062-10	
M28-0845-10	
M32-0096-10	