



Doseuro S.R.L.

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Doseuro S.R.L. Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Doseuro S.R.L. Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Piston Gasket Set, Pos.3 And 12, For A125n-12/C-32	+ Stuffing box, pos.6, for A125N-12/C-32
D101n-90/B-13 Tn	Diaphragm metering pump 1 x mechanisch angetriebene Membrandosierpumpe mit manueller Hublängenverstellung 0-100% Typ: D101N-90/B-13 Dosiermenge: 0 - 271 l/h max. Betriebsdruck: 5 bar Hubfrequenz: 120 Hübe/min Anschluß: 3/4" Außengewinde Material: Pumpenkopf: PVC Membran: PTFE beschichtet Ventile: PVC Ventildichtungen: Viton Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55 Gewicht, brutto: ca. 12 kg
A350n-89/B-11, Ss/Nbr	Piston metering pump directly controlled piston metering pump with manual stroke length adjustment 0-100% Type: A350N-89 / B-11 Dosing quantity: 0 - 1,458 l / h Max. Operating pressure: 4 bar Stroke frequency: 112 strokes / min Connection: 1 1/2 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.75kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
A250N-76/B-11, SS/NBR	Piston metering pump 1 x directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A250N-76 / B-11 Dosing quantity: 0 - 766 l / h Max. Operating pressure: 6.5 bar Stroke frequency: 112 strokes / min Connection: 1 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.55kW, 3ph, 230 / 400V, 50Hz, 4 pol., IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 26 kg / 30 kg
D101N-90/B-13	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 5 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.25 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy

	Weight, net / gross: 10 kg / 13kg
Pump head, PVC, ø90mm	Customs tariff number: 84139100 Country of origin: Italy Weight, net / gross: 0.4 kg / 0.6 kg
Valve set, AC13-13, PVC / Viton, for D101N-90 / B-	consisting of suction and pressure valve Customs tariff number: 84139100
Membrane with support plate, ø90mm	Zolltarifnummer: 84139100 Herkunftsland: Italien Gewicht, netto/brutto: 0,15 kg / 0,25 kg
D90 DIAPHRAGM AND PROTECTION POZ.20 + POS.22	
D100N-90/B-13 TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
AC5-31	Valve set, AC5-31, PP / Viton consisting of suction and pressure valve
AC13-14	Valve set, AC13-14, PVC / Viton consisting of suction and pressure valve
AB13	Valve set, AB13, SS / Viton consisting of suction and pressure valve
AC8-31	Valve set, AC8-31, PP / Viton consisting of suction and pressure valve
D050N-50/B-13	Diaphragm metering pump D050N-50 / B-13, PVC / Viton, for FeCl3 mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / B-13 Dosing amount: 0 - 49 l / h Max. Operating pressure: 10 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy
D100N-70/B-13	Diaphragm metering pump D100N-70 / B-13, PVC / Viton, for Polyelectrolyte mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-13 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
FM50N-50/B-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP

	Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 IT
FM50N-50/D-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h Max. Operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-70/B-11, SS/Viton	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-11 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Membrane: PTFE coated Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 12 kg
B125N-12/C-43 DV	Diaphragm metering pump hydraulically linked diaphragm metering pump with manual stroke length adjustment 0-100% Type: B125N-12 / C-43 DV Dosing amount: 0 - 7.4 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
Diaphragm, �65 / 50, PTFE, for B125N-12 / C-43	Membrane
FM50N-50/B-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy
Diaphragm	Membrane with support plate, �50mm. for FM50N-50
Membrane with support plate, �50mm. for FM50N-50	
Valve set, AC5-31, PP / Viton	consisting of suction and pressure valve
Valve set, AC13-13, PVC / Viton	for D100N-90 / B-13
FM50N-50/B-12	mechanically driven diaphragm metering pumps with manual Stroke length adjustment 0-100% Type: FM50N-50 / B-12 Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Weight:

	approx 8 kg Customs tariff number: 84135040 Country of manufacture: Italy
Membrane with support plate, ø30mm.	for D050N-30 / F-12
D100N-90/B-13 TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13kg
Piston, ø89, ceramic, for A250	
Piston, ø89, ceramic, for A350	
Gearbox 250	Gearbox A250, without motor, without pump head, with pump holder and motor bell
Gearbox 350	Gearbox A350, without motor, without pump head, with pump holder and motor bell
A125N-11/C-11 DV	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A125N-11 / C-11 DV Dosing amount: 0 - 6 l / h max.operating pressure: 20 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
D100N-90/B-13 TN	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13k
Typ: D100N-70/C-12 DV TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
D=100N-90/B-13TN	Q=27-330 litre/hours Pmax= 5 bar Power= 0.18 Kvt
	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A125N-12 / C-77 DV Dosing amount: 0 - 7.2 l / h max.operating pressure: 88 bar Stroke frequency: 96

A125N-12/C-77 DV	strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: ceramic Piston packing: PTFE energ Valves: SS316L Valve seals: PTFE or similar Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
D101N-120/C-11	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-120 / C-11 Dosing amount: 0 - 334 l / h max.operating pressure: 3 bar Stroke frequency: 96 strokes / min Connection: 1 "external thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.37 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-120/F-13	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-120 / F-11 Dosing quantity: 0 - 219 l / h max.operating pressure: 1.5 bar Stroke frequency: 58 strokes / min Connection: 1 "external thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D050N-50/C-11 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / C-11 DV Dosing amount: 0 - 39 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-70/B12 DVTN	
Piston packing set, ø89mm, Viton, for A250N	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering Push rod, item 208, for A250N Spring, for adjustment, item 213, for A250N Scale, item 225, adhesive picture, for A250N Spring, for gear, item 226, for A250N
Piston packing set, ø89mm, Viton, for A350N	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering. Push rod, item 208, for A350N Spring, for adjustment, item 213, for A350N Scale, item 225, sticker, for A350N Spring, for gear, item 226, for A350N
Pos.3 A250NandA350N	Piston packing set, ø89mm, Viton, for A250N and A350N 2 x packing rings Material resistance must be checked by the customer before ordering.
Pos.10 A250NandA350N	Wiper, ø89mm
Push rod, item 208, for A250N	
Spring, for gear, item 226, for A250N	
Push rod, item 208, for A350N	
Spring, for gear, item 226, for A350N	
Adjustment, complete, for A250	Item 210, 211, 212, 213, 221, 222, 225, 263

A350N ADJUSTMENT LEVER	Adjustment, complete, for A350 Item 210, 211, 212, 213, 221, 222, 225, 263,
NN HOSE	Suitable for Ragazzini Psf1 Pump
A175N-38/C-34 Piston metering pump	directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A175N-38 / C-34 Dosing amount: 0 - 115 l / h max.operating pressure: 13 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: SS316L Piston packing: EPDM Valves: SS316L Valve seals: EPDM Motor: 0.25kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
FM50N-50/D-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 4.5 kg / 6 kg
Motor - 230V - Hp 0,75	Degree of protect - IP54 Flow rate 102 l/min Tank capacity - 40l Pressure - 1,8bar High circulation pump for descaling, cleaning and power lushing traditional and underfloor heating systems. Ergonomic and easy to handle. Fitted with flow reverser. With cleaning powder.
D100N-90/B-13	
D-100N-90/B-13TN	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
FM50N-50/D-12 DV	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
Piston packing set	Piston packing set, ø76mm, NBR, for A250N, item 3 + 10 2 x packing rings and 1 x wiper
D100N-70/C-12 DV TN	Diaphragm metering pump D100N-70 / C-12 DV TN, PP / Viton mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / C-12 DV TN Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55

D0B07010122N1AA00	Diaphragm dosing pump D-100N-70/B-12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
Valve set, AC13-13	Valve set, AC13-13, PVC / Viton, for D101N-90 / B-13 TN consisting of suction and pressure valve
Diaphragm for D100N-70/B-12 DVTN	Diaphragm with support plate, ø70, for D100N-70/B-12 DVTN
AP A-125N-16/C-82 DV	AP A-125N-16/C-82 DV SPRING RETURN - PLUNGER DOSING PUMP
Diaphragm for D100N-90/B-13 TN	Diaphragm with support plate, ø90, for D100N-90/B-13 TN
D121N-120/B13 - 230400V 50/60Hz - 3phase	
FM50N-50/B12 - 230/400V 50/60Hz - 3pahse	
D100N-70/C12	230/400V 50/60Hz - 3pahse
A250N ADJUSTMENT LEVER-Doseuro to A350n-A250n	
A350N ADJUSTMENT LEVER-Doseuro to A350n-A250n	
OIL LEVEL INDICATOR-Doseuro will be suitable for	A350n-A250n.
27MM*35*MM*7MM PRESSURE SEAL-It will be suitable	for Doseuro A350n-A250n.
OIL FILLING DRAIN PLUG - It Will Be Suitable For	Doseuro A350n-A250n.
D100N-70/F13 DV	Dosing Pump
KIT0MS007000000000	Membran + Schild KIT
KIT0MS012000000000	Membran + Schild KIT
D100N-70/B12	
KIT0MS009000000000	Diaphragm and diaphragm shield (pos. 20+22) for pump D100N, article number KIT0MS009000000000
D100N-70/B12 DV	
AC00000022000M020	DOSEURO SUCTION CHECK VALVE AC-22/20N BODY PVC, BALL SS316, O-RING FPM 1" FOR D121N-120/B 13 PUMP (POLYMER DOSAGE) Set consisting of suction and pressure valve
KIT0MS012000000000.	DOSEURO DIAPHRAGM AND DIAPHRAGM PROTECTION D.120 P. 20 + P. 22, FOR PTFE/NBR D121N-120/B 13 PUMP
A125N-12/C-77 DV.	Model Description : Piston metering pump

A125N-30/B20	Chemical to dose: CHLORINE WATER Cl ₂ + H ₂ O Max Chem. Temp (°C): 40 Working Pressure (Barg): 2.00 Max Viscosity (Cps): -1.00 Suction Pressure (Barg): N.A. Ambient Temperature: (-20 / +40) °C ΔP (Barg): 2.00 Req. Capacity (Lt/h): 60.00 Model: A125N-30/B-20 Mechanism Type: SPRING RETURN Max Capacity (Lt/h):62 @50Hz Pump Type: Plunger Stroke per minutes: 116 @50Hz Max Pressure (Barg): 14.00 Metal, 10.00 Plastic Stroke length (mm): 12.50 Adjustment: Manual 0 - 100% of stroke length Connection: 1/2" BSPPm Diaphragm Ø (mm): N.A. Valve Type: Double ball Plunger Ø (mm):30 Pump Area: SAFE AREA PUMP HEAD PVC DIAPHRAGM N.A. BALL VALVE* PYREX PLUNGER S.S.316L PLUNGER GASKET NBR VALVE O-RING FPM * for pump with valve size 1 INCHES - ball valve is in PTFE Power Supply:3PH - TRI-PHASE 4 POLES Area: SAFE AREA Protection:IP55 Insulation Class:F Installed Power: 0,18KW Voltage: 400.00 Frequency: 50 HZ Inverter Use: NO
A250N-64/C19	
A175N-38/C19	
FM050N-50B-12	Filtered Level Floater Type: Float with Filter Supply: 24 V DC Signal: 4-20 Ma Model: Axial Inner Coating: Plastic
Dosing pump D100N-70/C12	
FM050N-50/D12	
FM050N-50/F-03	
FM050N-50/F-12	
D100N-105/C-12	
D100N-120/I-23	
SDI-175-12/B-05 DV	E.motor 0,25 KW 3Ph 4 Poli IP 55 Cl. F 400-440V 50-60Hz Size 71 B14 IE2 KIT PRESSURE GAUGE INOX 0-16 BAR
Diaphragm Dosing Pump with Electric Motor SR Serie	SDI-175-12/B-05 DV Type or Name of Liquid: BELGARD EV 2050-100% V/V
Diaphragm Dosing Pump with Electric Motor SR Serie	Model: SDI-175-12/B-05 DV Type or Name of Liquid: BELITE M8-5-7% V/V
D0C09010111N1AA00	type: PUMP D-101N-90/B-11 - - TN 4/3PH-230/400/50/60 SPRING RETURN - MECHANICAL DIAPHRAGM DOSING PUMP required capacity: N.S. l/h max: 271 l/h required pressure: N.S. bar max: 5 bar
AC13/14 Valve	item number AC00000013000M014 (AC 13/14 N (PVC + PYREX + FPM) in ¾" suitable for D100N-90/B13) Both valves are included in the valve set, i.e. suction and pressure side.
CHECK VALVE UNDERSET.	For dosing pump with code d-100n-90/b-13
D100N-70/B12	Diaphragm dosing pump

D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
A125N-25/B-20	Execution: 20 PUMP HEAD PVC PLUNGERS S.S.316L PLUNGER GASKET NBR VALVE SEAT PVC VALVE BALL PYREX VALVE GASKET FPM Please check the execution. In the best case, tell us the operating points or the materials.
SUCTION CHECK VALVE AC-13/14N	Art. Nr. AC00000013000M014
SUCTION CHECK VALVE AC-13/14N,	Art. Nr. AC00000013000M014
STAFSJÖ WB DN150 PN10/16 NBR	Manual Knife Valve
Piston dosing pump A125N-25/I-11 with servomotor	4-20 mA
Mechanical dosing pump D-050N-50/C-23 DV	
BTM0D000700081P13	PP pump head
KIT0MS00700000000	Membran
6115145778477	Expansion Tank LR119079046S
FM050N-50/B-11 340/400V 50/60Hz	
KIT0MS00300000000	membrane+membrane shield
A250N-89/C37	piston pump
PRESSURE CHECK VALVE D70/12 AC-8/31N	
SUCTION CHECK VALVE D70/12 AC-8/31N	
ACD0000008000M031	Suction and discharge valve SET AC8/31,
EDI0S006350000G02	Piston Gasket set d64 in FPM
A-125N-11/B13	piston dosing pump

D121N-120/F13	diaphragm dosing pump
RELIEF VALVE VSC-10/43 PVC	VS000000100000043
PISTON GASKETS SET G10-8 P7-8	
S.S.420 PISTON D.14	
PISTON GASKET SET G10-14 P7-14	
CERAMIC PISTON D.8 WITH GRAINS 6X8	
D-121N-120/B-13 - 4/3PH-230/400/50/60	D0I1201013111AA00
Diaphragm dosing pump FM-50N-50/B12 DV, 230/400V	50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 47l/h - max. pressure 5 bar - 1/2" BSP male connection
D-101N-90/B-13	TN 4/3PH-230/400/50/60 D0C09010131N1AA00
FM050N-50/B-12 DV	F0B050301221AA05
D-101N-105/B-13 - - - 4/3PH-230/400/50/60	D0C1051013111AA00
D-101N-70/C-11	TN 4/3PH-230/400/50/60
D-101N-105/B-13	4/3PH-230/400/50/60
A175	Ball check valve part located in the inlet and outlet line of A175 piston dosing pump
KIT0MS01050000000	Membrane with support plate, ø105mm, Pos.20+22
Suction and pressure valve AC13/14 (PVC+PYREX+FPM)	
A125N-8/B-32 DV	
PUMP D-101N-90/B-12 - - TN 4/3PH-230/400/50/60	D0C09010121N1AA00
SUCTION/DELIVERY VALVE SET AC-13/14N G/M	AC00000013000M014
SUCTION/DELIVERY VALVE SET AC-13/31N	AC00000013000M031
SK10MS00+0205	SCL K10MS TMS BPA MOR IE3 M.E. Gr.132 - 11kW - 13kW 660-720/380-415V 50Hz 760-830/440-480V 60HzIE3 - ATEX 3GD - IP65 - CL. F - TROP. PTO - PAINTED - ANOD.+IMPR.+V.INOX II 3GD - Ex h IIC T3 Gc - Ex h IIIC T200°C Dc
PUMP A-250N-89/B-20 - - 4/3PH-230/400/50/60	A0H0891020111AA00
FM050N-50/B-12 DV, 230/400V 50/60Hz	

A0E01620822111110	AP A125N-16/C-82 DV, 1PH SINGLE-PHASE 4 POLES 230V IP55 50 HZ
PUMP AI-350-89/A-13, 400V 50 Hz 1.1 KW, IP55	Eexd II C T4 with ABB Motor Atex Zone 2G T4 IOL08940111110201
D0B09010131N1AA00	Diaphragm metering pump D-100N-90/B-13, 230/400V 50/60Hz in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
D-100N-90/B-13, 230/400V 50/60Hz	D0B09010131N1AA00 in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
B0H0752043111AA00	PUMP B-250N-75/C-43 - -- 4/3PH-230/400/50/60
Spring (Pos.226)	
D-100N-70/B-12 DV, 230/400V 50/60Hz	D0B07010122N1AA00 mechanically driven diaphragm dosing pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-12 Dosage: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "external thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55
D101n-90/B13	
A0e25m3011v11aa00	
Metering Pump Doseuro Typ A250n-89/B-19	1 x plunger pump with manual stroke length adjustment 0-100% Type: A250N-89/B-19 Capacity: 0 - 1042 l/h max. pressure: 4,8 bar stroke frequency: 112 strokes/min connection: 1" male thread Material: Pumphead: SS316L Plunger: SS316L Plunger packing: Viton Valves: SS316L Valve gaskets: Viton Motor: 0,55kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
Type : D-101n - 120/B 11	
Push Rod Gasket (Pos.223)	
D101n-70/B-12 Dv Tn	Diaphragm metering pump mechanically driven diaphragm dosing pump with manual stroke length adjustment 0-100% Type: D101N-70 / B-12 Dosage: 0 - 180 l / h Max. Operating pressure: 8 bar Stroke frequency: 120 strokes / min Connection: 1/2 "external thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.25kW, 3ph, 230 / 400V, 50Hz, 4-pin, IP55 Weight, gross: approx. 12 kg
D- 105/90 Ptfe/ Nbr	Diyafram For this pump (B-175N-40/c)
Set Of Endless Screw (Pos.205) And Worm Wheel (Pos.206), For Model A250	
	plunger dosing pump type DOSEURO A125N-14/F-33 with manual stroke length adjustment 0-100% Capacity: 6 l/h

Metering Pump Doseuro Typ A125n-14/F-33	Max. operating pressure : 65 bar Strokes frequency : 58 strokes/min Connection: 1/2" BSP male Material : Pumphead: SS316 Plunger: SS420 Plunger packing: PTFE Valves: SS316 Valve gaskets: PTFE Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
206- Worm Wheel	
A-125n-11/C-19	
Flexible Coupling (Pos. 209/1/2/3)	
209/2- Flexible Insert	
Key, 5 X 5 X 20mm (Pos.227)	
Fm50-50/B-12	Metering Pump Doseuro mechanical diaphragm dosing pump with manual stroke length adjustment 0-100% Type: DOSEURO FM50-50/B-12 Capacity: 47 l/h Max. operating pressure : 5 bar Strokes frequency : 116 strokes/min Connection: 1/2" BSP male Material : Pumphead: PP Diaphragm: PTFE coated Valves: PP Valve gaskets: Viton Motor: 0,09kW, 3ph, 230/400V, 50Hz, 4 poles, IP65
209/3- Flexible Coupling (Top)	
Dosing Pump D-101n-70b-11 Tn Membranes	2 MEMBRANES FOR PUMPS THAT DISTRIBUTE SOLUTION TO FURNACE