



Dwyer

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Dwyer Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Dwyer Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Wwdp-2-Lcd	DIFFERENTIAL PRESSURE TRANSMITTER Type: WWDP-2-LCD Measuring ranges: 10, 20, 50,100 psid, selectable With LCD display
13-102931-00	3000MR-1KPA Photohelic 24 VDC range 0-1Kpa
CDT-5D40-CO2	CARBON DIOXIDE TRANSMITTER Range: 0 to 5000 PPM CO2 range Configuration: Duct mount No temperature output, no options
ADPS-03-2-N-C	Adjustable differential pressure switch set point range 0.20 to 2.00" w.c., (50-500Pa) M20 connection. Includes A-481 Installer kit, includes 2 plastic static pressure tips & 7' 2.1 m of PVC tubing
2000-60PA	
2300-120PA	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Zero centre range 60-0-60Pa
V6EPS-S-D-3-S-CSA	Costruction: Expöosion proof Body: Stainless steel Circuit (Switch): DPDT Tee Connection Size: 1" Tee Material Stainless steel ***** Option: CSA approved construction with junction box*
2000-500PA	Maghenelic GAuger Range 0-500Pa 90262080 USA
V6EPS-S-S-6-0	FLOW SWITCHES V6 FLOTECT® MINI-SIZE FLOW SWITCHES
A3000-250PA	PHOTOHELIC® PRESSURE SWITCH/GAGE Measuring range: 0 ... 250 Pa (please check, it can also be mm H2O or cm H2O)
0-60 Pascal Magnelic Normaldruck	
SFI-100MP-1-1/4	DWYER MIDWEST SIGHT FLOW INDICATOR Body style: single window, bronze body, ABS impeller Body option: 150 psig maximum pressure option, includes fluoroelastomer gaskets Body size: 1 -1/4 inch connection size Options: none
DWYER MIDWEST SIGHT FLOW	SFI-100MP-3/4 Body style: single window, bronze body, ABS impeller Body option: 150 psig maximum pressure option,

INDICATOR	includes fluoroelastomer gaskets Body size: 3/4 inch connection size Options: none
TEMPERATURE SENSOR,	Ex-Proof, 4-20 mA OUTPUT, 24 V DC SUPPLY, TEMPERATURE MEASUREMENT RANGE: -40/+80, IP>23
CFS2-DNBPN-60	R2-124816-23
A-457	R3-124 816-50 COUNTERWEIGHT
A-459	R3-124 816-52 CABLE HANGER
R6-124812-00	SPPM-24 PRG PANEL MTR
SBLT2-170M-200M	
MPCJR-484	9032896060
DXW-11-153-2	Differential pressure switch brass and fluoroelastomer wetted materials, NEMA 4X, 1/4" NPT connections, SPDT, range 10 to 25 psi.
RMA-25-SSV	Rate-Master® Polycarbonate Flowmeter Measuring range: 10....100 l/min air With stainless steel valve
2320	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGE Measuring range: -10 – 0- 10 Pa
Differential pressure gauge type Photohelic cod.	3000MR-500PA range 0÷500Pa 24 Vcc
2000-60PA-SS	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Measuring range: 0...60 Pa Option: Corrosion resistant brushed stainless steel 304 bezel
2000-100PA-SS	MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES Measuring range: 0...100 Pa Option: Corrosion resistant brushed stainless steel 304 bezel
MAGNEHELIC® DIFFERENTIAL PRESSURE GAGES	Type: 2300-120PA Type: Zero centre range 60-0-60Pa
MSX-W 22	MAGNESENSE® DIFFERENTIAL PRESSURE TRANSMITTER Replacement for MS2 measuring range 2
Typ: RHP-3E44	HUMIDITY/TEMPERATURE TRANSMITTERS European style wall mount Humidity/Dew Point Output: 4-20 mA/0-5 VDC/0-10 VDC Temperature Output: 4-20 mA/0-5 VDC/0-10 VDC
RHP-3S2B	Humidity Temperature Transmitter 3% Accuracy OSA w/Sintered Filter 0 to 10V 10K @ 25°C Thermistor Type II
L6EPB-B-S-3-B	FLOTECT® LIQUID LEVEL SWITCHES Installation: Brass external float chamber (tee) Float material: Polypropylene spherical Process connection: NPT
170221-00	150-1850 ml/min
	RATE-MASTER® POLYCARBONATE FLOW METER Measuring range: 0.5...5 l/min air With stainless steel valve

RMA-26-SSV	Temperature limit: 54°C (130°F) Pressure Limit: 100 psi (6.9 bar) Accuracy: 4% Process connection: 1/8" NPT internal thread Weight: 4 oz (113.4 gr.)
SFI-300-1-1/4	Dwyer MIDWEST SIGHT FLOW INDICATOR Double window, bronze body, ABS impeller 1-1/4" connection size
Typ: MSX-W11-PA	Wall mount Unidirectional Range 1: 1 in w.c., 250 Pa, 25 mm w.c. Pressure units: Pascal Accuracy: ±1% FSO. Stability: ±1% FSO/year. Temperature Limits: -4 to 158°F (-20 to 70°C). Pressure Limits: Ranges 2, 3 and 4: 6 psi max operation, 6 psi burst. Power Requirements: 10-36 VDC (2-wire), 17-36 Output Signals: 4-20 mA (2-wire); 0-10V or 0-5 V selectable (3-wire). Response Time: Instantaneous (default) or 3 s (selectable). Zero and Span Adjustments: Digital push-button
674-424	1.00 " wc = 1 inH2O = 249.0889 pascal = 2,490889 mbar
616KD-10	Differential Pressure Transmitter Measuring range: 0...250 Pa Accuracy: 2%
Sx-Re/43ca	
1950g-20-B-24	
830-0032 Rma-13-Ssv	
(377a6888p0001)	
M2300-100 (100-0022)	
4010	
616w-0m-Lcd	
Cdt-5d44-Rly	
Act-Da07	
Da-31-153-4	
Series 477av	
475-6-Fm Mk Hand Held Digit Manometer Dual Range 0-30 Psi	
641-12	
Rmb-50d-Ssv	
004-0001 Ms-221	
Rmb-85b-Ssv 02-28.85.Ssv	
Series 4g	
Rmb-52-Ssv	
Rma-42-Ssv	

1626-5	
Series 8b	
Series Hm28	
672-3-A (840-0014) Range: 0-25 In W.C. Output: 4-20 Ma, 2-Wire	
Magnehelic-2000-500pa-Asf	
Dm-1107	
Sgx-D8022n	
Dm-2000	
810-0009	
Dwyer 668b-19-1	
Avu-3-V	
Typ: 15 Vdo	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 15 VDO Mark 1, magnetic coupling Output: Transmitter 1 k Ω Potentiometer 1/2%. 4 to 20 mA. Switch Type: 2 x SPDT, Rated: 10 A @ 125/250 VAC (~), 1/3 PS @ 125/250 VAC (~), 1/2 A @ 125 VDC (), 1/4 A @ 250 VDC (), 4 A at 125 VAC (~) (tungsten). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Rmb-84-Ssv	
Ms2-W 102 (840-0014)	
Ms-321	
830-0076 Vfb-67	
Rma-33-Ssv 02-28.33.Ssv	
2000-50mm	
167-12	
Model:H2s-2	
840-0013 Afh2	
Act-Da04	
Series Sppm2	Voll vor Ort konfigurierbares 16-Bit-Farb-Touchscreen-Display
810-0007	
M2000-1.0(Ex 2000-1kpa)	
A-396a	

Act-Da11	
Cct50-202	
1950-0-2f	
Series 8c	
Series Mm	
Dm-1102	
A605c (840-0014)	
Adps-06-2-N	
Series 16c	
Da-7031-153-1	
Series Dm-1000	
Ms-121	
830-00xx Rma-7-Ssv	
Da-31-153-2	
Ms2-D102 (840-0014)	
477-0-Fm , No	
M2000-1.0	
2000-300pa	
004-0001 Adps-03-2-N-C	
Rma-1-Ssv	RMA Rate Master Flowmeter 6837
300u	
Series 2000-Sp	
1823-80	
244	
Series 2500	
Act-Da03	
Series Scd	
Series Ptgd	
Type: 3-5-A-D-0	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 3-5-A-D-0 Mark 3, multiple turns Output: Transmitter 1 kΩ Potentiometer 1/2%. 4 to 20 mA. Switch type: 1 x SPDT, nominal value: 15 A @ 125/250/480 VAC (~); 1/8 hp at 125 VAC (~), 1/4 hp at 250 VAC (~), 1/2 A at 125 VDC (), 1/4 A

@ 250 VDC (). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Act-Da13
682-8
2001
Cat. No: Rma 12 Ssv
Series 16b
Magnehelic-2000
43300
Dm-1112
1823-10
Series Pfg2
M2300-120 Differential Pressure Gauge With Analog Display
Dr200332
840-0014/ 2060
F 195 02-F195
Rma-34-Ssv
Modell: Bf-4
840-0013 A-177 2ã39;X4ã39;
Series 4000
1638
Memb-1950g
626-00-Ch-P1-E5-S1
628-00-Ch-P1-E5-S1
Series 4b
1910-1-Wp
Act-Da09
182310
Vfa-22
Wfa-22
Series At22000

840-0013 A-178 1ã39;X5ã39;	
Bb-523-3-9s	
Dah-7041-153-24e	
Gfc-1111	CONTROLLER GAS MASS FLOW 0-15LPM 12VDC
Rma-26-Ssv	
Rmb-101-Ssv	
Tmp2000	
672-2-A (840-0014) Range: 0-15 In W.C. Output: 4-20 Ma, 2-Wire	
02-475-00-Fm	
Dm-1109	
Dm-1104	
840-0013 A-179 3ã39;X3ã39;	
Hadp-Uc-06	
1823-2	
Te-Dfg-D0844-00	
Act-Da06	
350 Af Measuring Range 0-4	
Tbx1-Dn100--20/140;c-G1/2	
V6epbbs1b	
Act-Da10	
1823/2a	
Act-Da05	
Act-Da02	
At2ms Pressure Transmitter	
475-X(Xx)-Fm	
M2300-60	
S160-18pm	
1910-00 Spdt Pressure Switch Range 0.07-0.15quot;W c (17.5-37pa)	
628cr-81-Gh-P1-E1-S1	

840-0013 A190	
Rma-22	
Pg-2010d-10778	
Rhp-3w22	
637-0	SERIES 637 ADJUSTABLE RANGE PRESSURE TRANSMITTER
890-000x 4002	
1626-1	
Da-35-2-2a	PRESSURE SWITCH 5-10AMP AT 120-240VDC
Rf1-01-00-1	TRANSMITTER EXPLOSION PROOF ULTRASONIC LEVEL
Ms 222	
840-0013 Da-7031-153-4	
V10	
BtIm312101	
840-0013 A-174	
Ms-311 / Ms2-W102 (840-0014)	
Typ: 1910 - 00, Art.-Nr.: 02-1910.00	
1950g-20-B-24-Na	
Series 4c	
840-0014 /2500	
Rmb-85d-Ssv	
Series 2000	
Dm-1110	
32-231-0s	CONTROL VALVE 3-15PSI
840-0013 477a-3	
Dm-1108	
M700 Pa 02-700.00.750	
1223 - M400-W/M	
4215-15psi	PRESSURE GAUGE DIFFERENTIAL CAPSUHELIC 0-15PSIG
182300	
250 Af Measuring Range 0-4	

Series Scd-8	
Tpl-03-300	
2000-80cm	
840-0013 A-175	
1950g-20-B-240	
1950 00-2f	
477a-4	
Type: 45 Vdo	POSITION INDICATOR / SWITCH / TRANSMITTER Type: 45 VDO MARK 4, through shaft Output: Transmitter 1 k Ω Potentiometer 1/2%. 4 to 20 mA. Switch Type: 2 x SPDT, Rated: 10 A @ 125/250 VAC (~), 1/3 PS @ 125/250 VAC (~), 1/2 A @ 125 VDC (), 1/4 A @ 250 VDC (), 4 A at 125 VAC (~) (tungsten). Direct Drive (or Yoke) with visual display Housing aluminum, painted black
Mda-211	
Afg-2	
Catno1823	
Cdtr-5-W-4-0	
A299 (840-0014)	
840-0013 628-13-Gh-P1-E2-S1	
Series 1500	
A-605	
840-0013 2000-200mm	
1950 10-2f	
1823-1	
Dm-1105	
1227m	
100-0221	
Dm-1111	
628cr-91-Gh-P1-E4-S1	
Rpo04926	
Rma-11-Ssv	
1950 P - 2 - 2f Art.-Nr.: 02-1950.P.2	
Typ: Ms-121	

477a-5	
Model V10 Flotect	
840-0014 /2360	
Hfb-4-35	
Rhrr	
2002vs42231	VALVE 3-15PSI LIN-E-AIRE HI FLOW PNEUMATIC CONTROL
V6eps-S-D-3-S-Csa	
Series 2600	
1950g-20-B-120-Atex	
840-0013 Da-7031-153-5	
Rhp-2s11	
Series 16l	
Sgx-D7122n	
Ms-111-Lcd	
Gfm2-Air-010-A-B-A-N-B-2	
Act-Da14	
840-0013	
Series Vf	
1820-2	
Dmf-41404	DMF-41404 DMF N2 0-100 ML/MIN
Qbmb1-5 50..50pa	
F7-Sb	
Photohelic Serie 3000 Mr	
Rma-171 Ssv	
2000-500pa	
Series 476a	
840-0013 Da-7031-153-6	
Series 477b	
Series 16a	
Series 490a	

Series 8g
123-153
Rmb-84-Bv , 830-005x / Rmb-84-Ssv!!!
710-0001
Rma-21-Ssv
Series Vfi-300
Air X 100
Rhu-R004
1950-1
01-20.Skala
Dpg-107
Act-Da08
Series 16g
1950p20-B
477-000-Fm , No
100-0030
3000 Mr 02-30.00.500.Mr
1/4 Hp 240v Ac
Tmp 1823-2-Expl
Act-Da01
890-000x 4010
810-0013
Cat. No:1823-40
Series 478a
Rmb-83-Ssv
Vtt-A-N-D2
Series 8600
Series 32dz
Rma-33-Ssv
Series Vdpm
628-13-Gh-P1-E2-S1

Rma-22-Ssv
Series 32a
Dxw-11-153-4
166t(840-0014)
Rmc-107-Ssv
444124-03
840-0013 Da-7031-153-1
Dwyer 668b-08-1
Series 475
Series Sfi-100
M1430 , No
Act-Da12
004-0001 Te-Dfg-E-06-4-4-00
1950p1-B
102.5
840-0013 A-176 1ã39;X4ã39;
Dm-1103
840-0013/ V10 Ss
Aps-350
Series 2-5000
1626-10
Da-21-2-10s
1910-0
Ms2-W101
830-005x / Rmb-84-Ssv
Rma-32-Ssv
Rma-13-Ssv
Rmb-85d-Ssw
V6epb -S-D-3-S-Csa (By V6eps-S-D-3-S-Csa)
Sfi-300mp-3/4quot;

