



Electronicon

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Electronicon Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Electronicon Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
E90.G58-443300	3,3 kV 50 Hz 150 kVar
E56.A44-50423U	
28,2 kVar 440Vac 3x154µF K	3-phase power capacitor Type: 275.186-515400 221K02 Power: 25.0 kVar / 28.2kVar / 33.3kvar Voltage: 415 Vac / 440Vac / 480Vac / 50Hz Capacity: 3 x 154µF Dimensions: 116 x 230 mm Connection: clamp Fixing: bolt M12 Note: Attach the discharge module separately Customs tariff number: 8532 1000
E62.L95-253G10	Kondensator PE_25mF 1400DC 850AC 65x95 G1 oil BAM
E62.L95-503G10	50,0µF 1.000Vdc/640Vac 65x95 MKP AC Capacitor Capacitance: 50uF Voltage: 1,000 Vdc / 640 Vac Dimension: 65 x 95mm Connection: threaded connection
MKP 276.036 - 506610/221K02	116394 (D) Power capacitor 66 uF400-480V, 50 Hz, single phase 50x145mm, type D1, oil-filled, Double bottle plug
25kVar/ 525V	
20kVar 525V	
10 kVar 525V	
20 kVar 525V	
40 kVar 525V	
70 kVar 525V	

1010056
1020259
1030053
1030065
1051287
118900
275.100-10120
275.188-615400/221402
275.266-607700/221K02
275.288-615400/221K02
4,5?F 280Vac 25x48 K Si
9,0?F 280Vac 25x68 K Si
E12/B58 300600
E33.C68-5006/15220001
E50.R23-105NT0
E50.R29-105N10 12202
E51.L12-681R20
E62.G85-103G10 (package 1 x 21)
E62.G85-682G10
E62.L13-154G10
E62.L16-254G10
E62.N17-403C20 40uF
E62.P17-204C20
E62.R17-303C20
E62.R17-303C60
E62.R24-603C20
E62.S32-105C20
E62-C58-221E10
E63. N17-114C20
E65.P17-204C20
MKP UHD25/440 280.399-

313701/221302	
MKPg 275.193-516600	
E50.N13-424NT0	420�F 1.100Vdc 85x136 G MKP DC Capacitor Type : E50.N13-424NT0 Capacitance: 420�F Voltage: 1100 Vdc Dimension: 85 x 136 mm Connection: internal thread M6x10mm
50,0�F 450Vac 45x143 U Si	motor capacitor Type: E33.F43-505025 Capacitance: 50.0�F Voltage: 450Vac Dimension: 45*143mm Connection: double flat plug Note: Cond. with overpressure protection
E33.G48-506005/220001	60.0�F 450Vac 50x148F Si AC capacitor Type: E33.G48-506005/220001 Capacitance: 60.0�F Voltage: 450Vac Dimension: 50*148mm Connection: solder lug Note: Cond. with overpressure protection
276.078-506800/221402	
25,0 kVar 400Vac 3x166�F K	1051287 Power capacitor 3-phase Type: 275.186-516600 221K02 Power: 25.0kVar ; 30.0kVar; 36.0kvar Voltage: 400Vac ; 440Vac; 480Vac Capacitance: 3 x 166�F Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark:
275.186-515400 221K02	28,2 kVar 440Vac 3x154�F K Power capacitor 3-phase Power: 25.0kvar / 28.2kvar / 33.3kvar Voltage: 415Vac / 440Vac / 480Vac / 50Hz Capacitance: 3 x 154�F Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark: Install discharge module separately
275.100-10120	Resistance module 120kOhm for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
275.288-615400 221K02	28,2 kVar 440Vac 3x154�F K EW Power capacitor 3-phase Power: 23.2kVar ; 28.2kvar; 33.4kVar Voltage: 400Vac ; 440Vac 480Vac Capacitance: 3 x 154�F Dimension: 116*245mm Connection: terminal incl. discharge resistor Fastening: M12 bolts
E65.S23-563M30	34,4 kVar 850Vac 3x55,7�F K Art. Nr. 1051286 Power capacitor 3-phase Type: E65.S23-563M30 Power: 25.0kvar; 34.4kVar; 37.9kvar Voltage: 690Vacrms; 810Vaceff; 850Vac RMS Capacitance: 3 x 55.7�F Dimension: 136*230mm Connection: clamp Fastening: M12 bolts Remark: Gas filled Install discharge module separately
275.288-615400 221K02	28,2 kVar 440Vac 3x154�F K EW Art. Nr. 1051316 Power capacitor 3-phase Type: 275.288-615400 221K02 Power: 23.2kVar ; 28.2kvar; 33.4kVar Voltage: 400Vac ; 440Vac 480Vac Capacitance: 3 x 154�F Dimension: 116*245mm Connection: terminal incl. discharge resistor Fastening: M12 bolts Remark:
275.176-707700/221702	
275.546-703800 221K02	Leistung: 7,03kVar; 8,36kVar; 9,87kvar Spannung: 440Vac, 480Vac 525Vac / 50Hz
Type: 265.278-707700/221K02 Leistung: 11,6kVar 20,0kVar	

20,0 kVar 525Vac 3x77µF K EW	24,00kvar Spannung: 400Vac/50Hz 525Vac/50Hz 525Vac/60Hz
28,2 kVar 440Vac 3x154µF K	Leistungskondensator 3-phasig Type: 275.186-515400 221K02 Leistung: 25,0 kVar / 28,2kVar / 33,3kvar Spannung: 415 Vac / 440Vac / 480Vac / 50Hz
40µF 2.000Vdc/1.200Vac 85x176 KB	MKP AC Capacitor Type : E62.N17-403C6W Capacitance: 40uF Voltage: 2,000Vdc / 1,200Vac Dimension: 85*176mm Connection: threaded connection (M10), plastic bushing
E62G12-104G10	
275.176-707700/221702	
50kVAR- 400V- 7%	
50kVAR- 690V- 7%	
E62.G15-103D30	
E62.M16-113L30 (1051273)	
E62.M16-972L30	
E62.K15-902D30	
E62.G15-902D30	
E62.H15-123D30	
E67.R31-704W40	
E59.G50-255020	
E59.G50-105010	
LA41	
E62.R23-104M30	
E62.R23-104M33	1051423 3x100,0µF 750Vac 116x230 K Power capacitor 3- phase Voltage: 750Vac / 530Vac rms Capacitance: 3 x 100µF Dimension: 116*230mm Connection: M-clamp Fastening: M12 bolts Note: Install discharge module separately
E62.G12-104G10	
28,2 kVar 440Vac 3x154µF K	Type: 275.186-515400 221K02 1051288 Power: 25.0kvar / 28.2kvar / 33.3kvar Voltage: 415Vac / 440Vac / 480Vac / 50Hz Capacitance: 3 x 154uF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark: Install discharge module separately
Resistance module 120kOhm	for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
Resistance module 120kOhm	1059009 for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
	MKP AC voltage capacitor Type: E62.F81-503D10 Capacity:

50,0µF 700Vdc / 420Vac 45x81 U	50.0µF Voltage: 700Vdc / 420Vac Dimensions: 45 x 81 mm Connection: double flat plug Remark:
E62.K85-223D10	
ECAP480334	
WHD007 400V 50KVAR	
WCK3-74K00	
14,1 kVar 440Vac 3x77µF K	Power capacitor 3-phase Type: 275.166-607700/221K02 Power: 20.0kVar; 16.7kVar; 14.1kVar; 12.5kVar Voltage: 525Vac 480Vac, 440Vac, 415Vac / 50Hz Capacity: 3 x 77µF Dimensions: 95 x 230 mm Connection: terminal Fastening: M12 bolts Note: discharge width. grow additionally
Resistance module 300kOhm	for 3-phase terminals Type: 275.100-10300 Voltage: 760Vac
275.556-705800- Obsolete , Replaced By 15.0-275.556	
275.186-405600/221305 Mkpg Leistungskondensator 3x56µf 600-690v, Dreieckschaltung 116x230mm, Bauf	
275.186-515400 221k02 (1051288)	
478.159-6932a	
Mkpg 275.156-714410221202	
275.176-513700221502	
E51.R11-302r20	
1051140	
275.256-507700/221k02	12,5kVAr 415V QCap Type
E63.R24-105c20	
275.196-406203 221405	
Type: E50.R23-105nt0	
E06.E90-302510 220001	
275.546-506800 221502	
70cpe04175 Capacitor 120jlf	
275.548-506800/221k02	15kVAr 480V QCap
E50.N22-604nt1	
277.169-516600/221402, Obsolete Replaced By 275.186-516600 221402	
E62f10-102b20	

275.186-515400/221402	
458.259	
Ctb 6,0-440	
275.186-516600/275.100-10120(50)	
Electronicon-275186-405600221305-Mkpg-Leistungskondensator-3x56f-600-690v-Dreieckschaltung-116x230mm-Bauform-L-Gasgef3;Llt-Istanbul-Turkiye	
E62.P12-222c20	
112367	
E62.Q16-223I30	
E62. C58-502e10(1x72 Pcs.)	
275.186-405600/221K02	25.0 kVar 690Vac 3x56µF K Power capacitor 3-phase Power: 14.50kvar 25.0kvar Voltage: 525Vac 690Vac Capacitance: 3 x 56µF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark:
275.186-516600/221402	
275.556-508200/421102	
275.186-515400/221402 , 275.186-515400 221k02	
275.186-809600	
1056010	
E62.L95-503g10	
263.190-96400, Obsolete Replaced By E63.R24-105c20	
E50.N13-424nt0 - Dc Kondansatör -420 µf 1100 V	Kondensator PK16XC_420 µf 1,1kVDC_85x136_NT_rs_NF
E62.S32-603cr0	
275.196-616601/275.100-10120(52)	
188-615400/221402	
275.176-513700/421502	
275.156-714410 221202	
114393 Metallized Polypropylene Capacitor	
114392	
E50.N13-424nt0	

[275.100-10300 Entlademodul, 3 X
300kohm Discharge Module Cct No
8533210](#)

[15.0-275.556](#)

[Type: 275.100-10120 \(1059009\)](#)

[E50.N25-564nt0](#)

[275.196-616601/275.100-10120\(52\)
Mkpg Capagrip Capacittance 3x166 Q
\[kvar\] At 400v 25 Dimensions 136](#)

[275-116-510000/221502](#)

[Elec20 525](#)

[E62.R16-253I30](#)

[E01.E95-302510, Alternative E06.E90-
302510 220001](#)

[276.173-502301/221108](#)

[275.186-515400 221k02](#)

[1030052](#)

[275.546-506800/221k02](#) 3x68mF 400-440V 50 Hz 75x230mm

[E50.R23-175nto](#)

[275.186-612300/221302, 112757](#)

[E62.S23-204m30](#)

[E62 E58 203d10](#)

[275.186-516600/421502](#)

[E51.R11-402r20](#)

[265.286-709600 221k02 - Alternativ](#)

[40µf 2.000vdc/1.200vac 85x176 Pb](#)

MKP AC voltage capacitor Type : E62.N17-403C20 Capacity:
40µF Voltage: 2,000 Vdc / 1,200Vac Dimensions: 85 x 176
mm Connection: threaded connection (M10), ceramic bushing

[E50.N21-654nz0](#)