

Elero

Garanti: 12 ay
 Bu ürüne ait Türkiye içi kapı teslim fiyatı ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Elero Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Elero Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Junior 1	Special version 0 ----- - Variant g ----- ----- - Construction / setting dimensions: Stroke length 46 mm permissible stroke reduction 10 mm Construction AMIN 235 mm Setting dimension min 235 mm Setting dimension max 281 mm ----- - Attachment: VA fastening elements. no Attachment piston. Hinge eye rotated 90 ° Fastening housing double eye (plastic) ----- - Technical specifications : Thrust 1100 N Tensile force 1100 N Lifting speed 4.00 mm / s Operating voltage 24V DC Operating mode S3 - 40% Circuit diagram GS0400 Cable type standard Cable length 1.50 m Current consumption 1.2 A Power consumption 30W Low temperature range no Piston sealing simple Degree of protection IP54 Options: Poti-type standard potentiometer 1KOhm ten-turn Absolute encoder no ----- ----- - Pulses per mm stroke 0.00 pulses / mm
PICOLO XL	761996601 Special version 0 Stroke length 300 mm Setting dimension min 23 mm Mounting type axial mounting (eye-eye) Attachment piston. Hinge eye Fastening of the housing hinge eye Corrosion protection V2A Electrical connection type cable Cable length 5.00 m Rotary pulse encoder with pulse encoder Nominal voltage 230V 1AC 50Hz Distance fixing construction 730 mm Operating mode KB - 5min permissible stroke reduction 50 mm Cable type UV-resistant PUR cable (gray) Tensile force 1200 N Thrust 1200 N Lifting speed 6.00 mm / s Current consumption 0.55 A. Power consumption 126W Circuit diagram WS0800 Degree of protection IP65 (can be used on all sides) Pulses per mm stroke 6.00 pulses / mm Parallel connection no
	762071901 Special version 0 ----- - Variant k ----- ----- - Construction / setting dimensions: Stroke length 70 mm permissible stroke reduction 10 mm Construction AMIN

Junior 1	235 mm Setting dimension min 265 mm Setting dimension max 335 mm ----- - Attachment: VA fastening elements. no Attachment piston. Hinge eye Fastening housing double eye (plastic) ----- -- - Technical specifications : Thrust 2000 N Tensile force 2000 N Lifting speed 2.00 mm / s Operating voltage 24V DC Operating mode S3 - 40% Circuit diagram GS0400 Cable type standard Cable length 1.50 m Current consumption 1.2 A Power consumption 30W Low temperature range no Piston sealing simple Degree of protection IP54 Options: Absolute encoder no ----- - Pulses per mm stroke 0.00 pulses / mm
Seri:140025240	
762265901	compact Special version 0 low temperature range no low temperature range ----- - variant f ----- ----- - Construction/adjustment dimensions: Stroke length 223mm Permitted stroke reduction 10 mm A minimum dimension 575 mm ----- - Fastening : Fastening type axial fastening (eye-eye) Construction AMIN 575 mm A dimension maximum 798 mm VA mounting element. no attachment piston. spring-loaded articulated eye rotated 90° Fastening housing swivel eye rotated 90° Power spring GA 15000 N ----- - Technical specifications : Thrust 15000 N Tensile force 15000 N Lifting speed 5.50 mm/s Operating voltage 400V 3AC 50Hz Operating mode ED S3-15% Circuit diagram DS9911 supply voltage EL 24V_DC Cable type standard Cable length 5.00 m Current consumption 1.3 A Power consumption 900VA Degree of protection IP54 Options : ----- - Encoder no Pulses per mm stroke 0.00 pulses/mm ----- - connection voltage Brake 24V DC
Junior 2	762381201 Special version 0 ----- - variant j ----- ----- - Construction/adjustment dimensions: Stroke length 100 mm Permitted stroke reduction 10 mm Construction AMIN 291 mm A minimum dimension 291 mm A dimension maximum 391 mm ----- - Fastening : VA mounting element. no attachment piston. Threaded bolt M12x20 Fastening housing single eye rotated 90° ----- - Technical specifications : Thrust 4500 N Tensile force 4500 N Lifting speed 2.20 mm/s Operating voltage 48V DC Operating mode S1 Circuit diagram GS0200 Cable type standard Cable length 5.00 m Current consumption 1.5 A Power consumption 72W Degree of protection IP54 low temperature range no Options : ----- - Pulses per mm stroke 0.00 pulses/mm ----- - connection voltage Brake 24V DC
Junior 1	762348301 Special version 0 ----- - variant g ----- ----- - Construction/adjustment dimensions: Stroke length 100 mm Permitted stroke reduction 10 mm Construction AMIN 235 mm Setting dimension at least 235 mm Setting dimension max 335 mm ----- - Fastening : VA mounting element. no attachment piston. articulated eye Fastening housing double eye (plastic) ----- - Technical specifications : Thrust 1000 N Tensile force 1000 N Lifting speed 4.50 mm/s Operating voltage 24V DC Operating mode S3 - 60% Circuit diagram GS0200 Cable type standard Cable length 1.50 m Current consumption 1.1 A Power consumption 27W low temperature range no Piston seal easy Degree of protection IP54 Options : Absolute encoder none ----- - Pulses per mm stroke 0.00 pulses/mm
280016065	
3H0051-15	Linear drive Elero Compact E electromechanical 400V,50Hz,H250,F12kN
JUNIOR 2 150mm 24V-DC	VHUB: CA 3,3MM/S Fdyn: 4500N ACTUATOR
762835301	Junior 1 Special version 0 ----- - Variant d ----- ----- - Construction/setting dimensions: Stroke length 100 mm Permissible stroke reduction 10 mm Constr. AMIN 285 mm Setting dimension min. 285 mm Setting dimension max 385 mm ----- -- - Fastening: VA fastening element. no Attachment of piston. Joint eye Fastening housing double eye (plastic) ----- - Technical data : Thrust force 250 N Tensile force 250 N Lifting speed 10.00 mm/s Operating voltage 24V DC Operating mode S1 Circuit diagram GS0400

	Electrical connection type cable Cable type standard Cable length 1.50 m Current consumption 0.8 A Power consumption 20W Low temperature range no Piston sealing simple Protection class IP54 Options: Absolute encoder no ----- - Pulses per mm stroke 0.00 imp/mm ----- ----- - Bellows type V6-679
762896901	Compact Special version 0 Low temperature range no low temperature range ----- - Variant h ----- - Construction/setting dimensions: Stroke length 200 mm Permissible stroke reduction 100 mm A-dimension minimum 450 mm ----- - Fastening: Type of fastening: axial fastening (eye-to-eye) Constr. AMIN 450 mm A dimension maximum 650 mm VA fastening element. no Attachment of piston. Joint eye rotated 90° Fastening housing joint eye rotated 90° ----- - Technical data : Thrust force 15000 N Tensile force 15000 N Lifting speed 2.00 mm/s Operating voltage 24V DC Operating mode ED S3-15% Circuit diagram GS9112 Supply voltage EL 24V_DC Cable type standard Cable length 3.00 m Current consumption 8 A Power consumption 200W Protection class IP54 Options: Poti type analog output 0-10V ----- ----- - Rotary pulse encoder no Pulses per mm stroke 0.00 imp/mm Customer part no. NE10083308
762938101	Junior 1/s Special version 0 ----- - Variant i ----- - Construction/setting dimensions: Stroke length 100 mm Permissible stroke reduction 10 mm Constr. AMIN 263 mm A-dimension minimum 263 mm A dimension maximum 363 mm ----- ----- - Fastening: VA fastening element. no Attachment of piston. Joint rod head Fastening housing double eye (plastic) ----- ----- - Technical data : Thrust force 2900 N Tensile force 2900 N Lifting speed 2.50 mm/s Operating voltage 24V DC Operating mode S1 Circuit diagram GS0400 Cable type standard Cable length 1.50 m Current consumption 1.3 A Power consumption 32W Protection class IP54 Low temperature range no Options: ----- - Pulses per mm stroke 0.00 imp/mm ----- - Load torque lock no
Junior 1	763000901 Special version 0 ----- - Variant f ----- - Construction/setting dimensions: Stroke length 100 mm Permissible stroke reduction 10 mm Constr. AMIN 235 mm Setting dimension min. 235 mm Setting dimension max 335 mm ----- ----- - Fastening: VA fastening element. no Attachment of piston. Joint eye Fastening housing double eye (plastic) ----- ----- - Technical data : Thrust force 800 N Tensile force 800 N Lifting speed 5.00 mm/s Operating voltage 24V DC Operating mode S3 - 40% Circuit diagram GS0400 Electrical connection type cable Cable type standard Cable length 1.50 m Current consumption 1.2 A Power consumption 30W Low temperature range no Piston sealing simple Protection class IP54 Options: Absolute encoder no ----- - Pulses per mm stroke 0.00 imp/mm ----- - Customer part no. Y011468
130004778, Type: Junior 1 758215001	
140004214	
Junior 2 Nr.:110005868 For Kã246;Nig Amp; Bauer Ag	
Fdyn4600 N	
Dfm 250 Nhk	
24119.0003 / Dfm/Dfe	
759393601	
759681901	
758606101	ACTUATOR

Brake Lining For Dfm 250	
Typ: Aton 3 Nr. 110005212 , Alternative Is Nr. 759577201 , Type Insolis 3	
Junior 2	
Nr. 759577201 , Type Insolis 3	
40004214	
120024439 // D-07381	
140021942	
757245301 Junior 2	
Junior 2, Art N: 759671001	
Junior 1s	
100012885	
410510002	
Junior 1s, D-07381	
3mr 240 1059ds	
Econom 2	
243500101	
3h0051-03	
Junior 1 Un: 24v-Dc P:20 W Fdyne:1000 N In:0,8a Ip54	
130008138 (759143701)	
Roltop M50 230v/50 Hz	tubular motor with assembly and operating instructions Type 9/5 no longer available
Junior 1	
4100036	
759366601	
Motor Dfm 750	
Junior 1/S (758705001)	
Econom 01 Hub 50mm 400v Fdyn4600 N	
Type Econom 01 D/A Nr. 97093661	
759739601	
24136.0001 / Dfm/Dfe	
Junior 1/S	760922801 Special version 0 ----- Variant f ----- - - Construction / setting dimensions: Stroke length 100 mm permissible reduction in stroke 10 mm Constr. AMIN 235 mm A dimension minimum 235 mm A dimension maximum 335 mm ----- ----- - - Fixing: VA Befestigungselem. No Attachment of the piston. joint eye Attachment housing double eye (plastic) ----- --- - - Technical specifications : Thrust 1800 N Tensile force 1800 N Lifting speed 3.50 mm / s Operating voltage 24V DC Operating mode S3 - 15% Schematic GS0400 Cable type standard Cable length 1.50 m Current consumption 2.5 A Power consumption 60W Degree of protection

	IP54 Tieftemperaturber. No Options: ----- - - Pulses per mm stroke 0.00 Imp / mm ----- - - Load torque lock no
Sw.Key.00.Omo	
757365001	