

Elgo

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Elgo Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Elgo Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Emix2-000-04.0-2-00	733290035 Magnetic length measuring system
Mb20 20 10 1 R	Magnetband for EMIX
P8822-007-024-00-R	Zweiachsige Positionsregelung 24VDC
P9511-000-024-0	Axis compact control without program memory with relay outputs 000 = standard version 024 = supply24VDC 0 = signal input A / B24V
15-42-1000	Rotary pulse encoder 1000 = 1000 pulses / revolution Supply: 10-30 VDC Outputs: A, B HTL with the cable gland Weight: 1.0 kg Customs tariff number: 9031499000 Country of manufacture: CZ
P9511-000-024-0	1-axis compact control without program memory with relay outputs 000 = standard version 024 = supply24VDC 0 = signal input A / B24V
EMIX2-000-04.0-2-00	Magnetic length measuring system Sensor and evaluation electronics in the sensor housing 000 = standard version 04.0 = cable length 4.0m 2 = resolution 0.01mm 00 = supply / level 10-30VDC / 10-30VHTL
MB20-20-10-1-R	Magnetic tape for EMIX

IZ15 Mode/I sensor Ms250	
LMIX2-032-02.0-1-01	Magnetic length measuring system 032 = special version (with 2k encapsulation, protective diode, shield is not on the housing, PWM error output) 02.0 = cable length 8.0 m 1 = resolution 0.1 mm 01 = supply / level 10-30 VDC / 5V TTL RS422
LIMAX2-00-030-62N5-SSG0-D9M1	Absolute length measurement system for Liftengs 00=Standardversion 030=cable length 3.0 m 62N5=resolution 62.5 µm SSG0 = SSI - interface (25 - Bit Gray code) D9M1 = 9 - pole . D - SUB - Stecker / Rifle
AB20-80-10-1-R-D-15-BK80	LIMAXMagnetband(NULLinside)
LIMAX2MWSET	Mounting bracket for LIMAX2
555100040	Montageset LIMAXRMS
IZ16E SENSOR	
MB20-50-10-1R 636 MM	
MB20-25-10-1R 636 MM	
2000306N5SSG0GD9M1 / HW:02.1/SW:3.5	
0030050-4SSI-UGXV IP55	HW:003/SW:2.4
Floor Magnetic Reader plastic	
MA06LS	
FMAX-00-005-0010-SSB0-U	Guided sensor head for Guide railFSMAB 00=default version 005=cable length 0.5m 0010=resolution0.01mm SSG0=SSI interface U=unguided version
FSMAB-000-0500	guide rail incl. Magnetic tape for FMAX series (max. measuring length 650mm) 000=default version 0500=total length 500mm (total length=measuring length+150mm)
P8721	
IZ16E-043-1-0.30-0	761161046 Incr. position display With external sensor, battery operated 7-digit LCD display, digit height 14mm 043=for FOW/FLW 1=integrated battery compartment (1xC) with cover 0.30=cable length 0.3m 0=fixed cable outlet
MB20-25-10-1-R	Magnetband for IZ16E
LMIX2-000-10.0-1-01	Magnetisches Längenmesssystem Sensor und Auswerteelektronik im Sensorgehäuse 000 = Standardversion 10.0 = Kabellänge 10,0 m 1 = Auflösung 0,1 mm 01 = Versorgung / Pegel 10 - 30 VDC / 5V TTL
LMIX2-000-08.0-1-00	Magnetic length measuring system Sensor and evaluation electronics in the sensor housing 000 = standard version 08.0 = cable length 8.0 m 1 = resolution 0.1 mm 00 = supply

	/ level 10-30VDC/10-30VHTL
EMIX2-000-0.50-2-01	Magnetic linalgmes system 000=Standard version 0.50=cable length 0.5 m 2= resolution 0 .0 1 mm 01=Perspilion/level 10-30 V DC / 5 V TTL
MB20-20-10-1-R	Magnetband for EMIX
FMAX-00-005-0010-SSB0-U	Guided Sensor for FSMAB 00 = Standard version 005 = Kabel length 0.5 m 0010 = resolution 0.01 mm SSB0 = SI - interface (25 Bit Binary Code) U=unded
FSMAB-000-0500	GUIDE RAILS INCL. Sagnet- band for FMAX 0500 = length 500 mm Measurement length 350 mm TOTAL LENGTH = MEASUREMENT LENGTH + 150 mm
P9521	
P8822	13 cm x 13 cm with a depth of 8 cm
EMIX2-000-10.0-2-00	EMIX2-000-10.0-2-00 Magnetic Linear Encoder Magnetic length measuring system Sensor and evaluation electronics in the sensor housing 000 = standard version 10 .0 = cable length 10.0 m 2 = resolution 0.01mm 00 = supply / level 10 - 30 VDC / 10 - 30 VHTL
MAN.DG244 EMAX-016-00.4-2-422-0-2	
LIMAX2-09-040-0500-CO1TG	
LIMAX3CP-00-050-1000-CO1TG-0 ID-X/125k/0/1.	
732000110	MS2060 - 08.0 Magnetsensor for Z60 - 014
P9521	
P8721-000-024-0- P	
Az16e3013	
E Mix3-000-01.0-2-11	
Model Lmix2 Code 039.01.01.01	
Z16-042-001-1.0	
Emix2-000-01.5-2-11	
Z-20e	
5-37-0050-02,0	
See The Attached Files	
Azs-000-1-03.0-1	
Z89-000-024-4	
P9521-005-024-0 -	

99521-000-024-V
Lmix2-032-02.0-1-00
56.500.024
799999999, Emax0015001042009k6
Mix2-039-03 0-10j
799999999, Emal0015001042009k6
15 - 32 - 0250 - 20.0-S
Z60-000-024-111
Emix2-000-02.0-2-00 (73329006)
Mix1-000-01.0-1-11
Spare Parts Plexiglass For Fluorescent Lamps Owf-2x36-003
711p88001 P8822-000-230-00-R-En
L M I X 3 - 0 0 5 - 0 . 3 0 - 1 - 0 0
733290011
71p/110v Ac - P8511-000-115-0-R-En (711p8504)
Kt-E-B-0124 00
701166005
701hw0001 Hd 15 - 000 - 001
Z16-000-001-0-5 New Iz16-000-1- 01, 0-0
810508
Gmix1a-000-01.5-1-00
I Z 1 5 E - 0 3 1 - 3 - 0 0 , 5 - 0
Gmix2-000-06.0 24vdc
Mb 20.2 5
54.500.024 Obsolete By Z50-054-024-0 (701500105)
I Z 1 6 E - 0 0 0 - 1 - 0 2 , 0 - 0
P8511-000-115-0-R-En (711p8504)
733210007, Mix3-000-0000-1-00

Lmix1 - 010 - 10.0-1 -11
5-0090-000200
56.500.024sn173 Ng20 729395- 19.12.2002 Sv018 V1-0.
Ms20.25
Mix3-000-3-00
Z59 X0x
Z16-032-001-N - , No
Emix23-000-30.0-0001-01-L
Z15
P9521-002-024-02
Emax00015010a2038k 4 0 - - - - A - - --
7310031002
Counter 220 Vac
71.P.Sn002
Model: Z-16
85 P Sp370
P/N: 733240040 Type: Emix3-000-05.0- 2-11
Lmix 22-000-03.0-0100-00
Z89-000-024-00x
15-32-0250-03.0
65699967
733280145 Lmix2-000-08.0-1-11
Mix3-000-0000-5-11
P 2288
P 9 5 2 1 - 0 0 0 - 0 2 4 - 0
733280145 , Type Lmix 2 000 08 0111
Mb20-20-10-1-R (73100015)
Iz15e-001-4-01,0-0
004 0194 124

Z16-028-001-0,6-E Art.Nr.:701160030 : By: Iz16e-000-1-00,6-0-Cap	
86910902/S	
7621 0101	
7 0 1 5 8 6 0 0 2	
70064660980	
Elgo P8822	(DC Supply-P8822-013-024-00-R-EN-80074590560)
2688	
Lmix2-000-008.0-1-00	
810514	
P8822 24 Dc	
Az17e-600-3-Xx.X-1	
Z 5 8 - 6 0 0 - 0 2 4 - 1	
Lmix3-000-08.0-1-00-V	
Emix2-000-10.0-2-11 0987586	
Z60-000-024-111	3-axis position indicator Digit height 7mm 0 0 0 = S t a n d a r d v e r s i o n 0 2 4 = 2 4 V DC supply 1 1 1 = S i g n a l i n g a n g A / B / Z P e r s p i l i o n t / level 1 0 - 3 0 V DC / 1 0 - 3 0 V H T L ATTENTION: C o n n o c t i o n o f a x e 3 only via D - S U B - P e c k e r ! Replacement for Z89-000-024-000
P8511-003-024-0-R	
P/N: P9511-000-230-M	
Lmix2 P/N: Tp93 ? 6716 ? 671607125 ? C	
Cpu 235	
M S 2 0 6 0 - 0 2 . 0	
Iz16e-000-1-00,6-0-Cap	
Iz16e -000 -1-00,2-0 701166004	
Mb 20.50	
Please See The Attached Pictures..	
Emax-029-01.5-7-A22-2	
Mb20. 20	
733280145	

7999999999	
P 9 5 2 1 - 0 0 0 - 0 2 4 - 0 (7 1 1 9 5 2 0 0 6) 1 - A C H S K O M P A K T S T E U E R U N G 0 0 0 = S T A N D A R D V E R S I O N 0 2 4 = V E R S O R G U N G 2 4 V D C 0 = S I G N A L E I N G A N G A / B 2 4 V	
Iz16e-000-8-03.6-1-Ag-Cap	
Type 15.62	
P8721-000-115-0-En	
Gmix1a-000-3.0	
Ab20-40-10-1-R-11	
733250022	
Wdr Ds 01019217	
Z50-54-024 - 0	
7480	
Lmix1	
Lmix2 - 047 - 03.0 - 1 - 01	Magnetic length measuring system Sensor and evaluation electronics in the sensor housing 047 = special version 03.0 = cable length 3.0m 1 = resolution 0.1 mm 01 = supply / level 10-30VDC / 5V TTL
Typ71	
Z16-034-001-3.3-Ag , Iz16e-000-8-03.6-1-Ag-Cap	
7 0 1 5 0 0 1 0 5	
Elg02688	
Type: 71.P , P8511-000-230-0-R-En	
Type: 87p2	
Emix2-000-10.0-2-11	
Lmix1-000-01.0-1-11	
Lmix2-000-08.0-1-11	
Lmix M820-50-10-1-R	
15-32-0250-02.0 715320052	
15-62-0250-01.5	
1024 P Encoder 24 V Dc	

731031003, Mb Endkappe 20mm	
Cable For 56.500.024.Sn173.Ng20	
50.610.60.20 Iw 4 , By 705570013	
Emax2-00-015-F10-420-19k2	
Lmix2 -000-08.0-1-00 1983719	
Mb Endkappe10 Mm / Set	
Type 453	
Ma06ls	
Mb20-20-10-1- R	
LIMAX2-00-030-62N5-SSG0-D9	743002003 Absolute length measuring system for lift systems 00=standard version 030=cable length 3.0m 62N5=resolution 62.5µm SSG0=SSI interface (25-bit gray code) D9M1=9-pin D-SUB plug/socket
Plastic Lids For Tips,For Fluorescent Lamps Owf-2x36-003	
A Z 1 6 E - 0 0 0 - 1 - X . X X - 1 (7 6 2 1 6 0 1 0 1)	
Lmix2-047-03.0-1-01	
Z 2 5 - 0 0 0 - 0 2 4 - 0	
Z16-Sn000-001-0,2-0 , By Iz16e -000 - 1-00,2-0 701166004	
Mix3-000-0000-2-11	
99521-000-024-V (720303-17.12.2001 ? Sv001 V3-3)	
Type: Z-59e	
201-M-Pnp	
P8511-000-230-0-R-En	
701560001	
733260022	
Ms16.	
P8822-000-024-00	
Lmix1-000-03.0-1-00 733250022	
731000274, Ab20-50-20-2-R-12	
705570013	

Emix2-000-02.0-2.00
P 40
Z89-000-024-99x
A B 2 0 - 4 0 - 1 0 - 1 - R - 1 1 (7 3 1 0 0 0 0 7 4)
Mb 20-25-10-R For Z15
Lmix2-000-0.50-1-00-D2
I Z 1 6 E - 0 0 0 - 1 - 0 0 , 5 - 0
M I X 1 - 0 0 9 - 0 3 . 0 - 1 - 0 1
Z59 000
Az16 (*)
Kt-E-B-0194-00
Iz16e-00-1 -00 , 5 - 0
Mix 3 - 000 - 0000 - 2 - 00
A Z 1 6 E - 0 0 0 - 1 - X . X X - 1 (2 G)
731000110, Emab
80-B2
P8822 220 Ac
Egc- M1- 1428315