

Elomatic



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Elomatic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Elomatic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Fd0065.Nm00cwals.Yd14sna.00	Drive the EL-O-MATIC F series, DIN, F05, double acting, 90 ° clockwise rotation, Square mount 14mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
11629	POSIFLEX positioner electro / pneumatic 4-20 mA TYPE F 20 IP 65, M20x1.5 according to Data sheet D3.301.2 (VA368.00.164), incl. Cable gland.
11708	Position feedback 4-20mA, type PTF20, for POSIFLEX positioner F 10/20, as Plug-in module for F20 circuit board, according to Data sheet D6.202.1
FD0065.NM00CWALS.YD14SNA.00	Drive the EL-O-MATIC F series, DIN, F05, double-acting, 90 ° turn clockwise, Square adapter 14mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
FD0150	
FD0350.NM00CWALL.YD22SNA.00XX	drive the EL-O-MATIC F series, DIN, F10, double acting, 90 ° rotation in Clockwise, square socket 22mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 95 ° - closed position 10 ° to - 5 °,

	standard temperature version - 20 ° C to + 80 ° C.
FD1600.NM00CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, double acting, 90 ° rotation in Clockwise, square socket 46mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 93 ° - closed position 10 ° to - 3 °, standard temperature version - 20 ° C to + 80 ° C
FD2500.NM00CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, double acting, 90 ° rotation in Clockwise, square socket 46mm, diagonal according to DIN, with double Stroke limitation: setting range open Position 80 ° to 93 ° - closed position 10 ° to - 3 °. Standard temperature version - 20 ° C to + 80 ° C
FS0100.NM50CWALL.YD17SNA.00XX	drive the EL-O-MATIC F series, DIN, F07, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 17mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C Country of origin: Malaysia Customs tariff number: 84123900
FS0200.NM50CWALL.YD22SNA.00XX	drive the EL-O-MATIC F series, DIN, F10, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 22mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C
FS0600.NM50CWALL.YD27SNA.00XX	drive the EL-O-MATIC F series, DIN, F12, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 27mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 95 ° - closed Position 10 ° to - 5 °, Standard temperature version -20 ° C to + 80 ° C.
FS0950/ 50	
FS0950.NM50CWALL.YD36SNA.00XX	drive the EL-O-MATIC F series, DIN, (drilling pattern F14), single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square socket 36mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C
S1600.NM50CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, (drilling pattern F16), single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 46mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.
FS2500.NM50CWALS.YD46SNA.00XX	drive the EL-O-MATIC F series, DIN, F16, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square adapter 46mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.

FS4000.NM50CWALL.YQ55SNA.00XX	drive the EL-O-MATIC F series, DIN, drilling pattern F25, single acting, spring set 50, 90 ° rotation clockwise / spring-to-close, Square socket 55mm, diagonal according to DIN, with double stroke limitation: setting range open position 80 ° to 93 ° - closed Position 10 ° to - 3 °, Standard temperature version -20 ° C to + 80 ° C.
ED 0100-M2A00A	
ED 0200-M2A00A	
ES 0200-M2A04A	
ED 0350-M2A00A	
FS0200.NM40CCALT.NL22SNA.00XX	17354 Drive of the EL-O-MATIC F series, ISO, F10/F07, single acting, spring set 40, 90° rotation counterclockwise / spring opening, Square mount 22mm parallel, with double stroke limitation adjustment range open position 80° to 95° - closed position 10° to - 5°, Standard temperature version - 20°C - 80°C.
POSIFLEX F10 11630	pneumatic positioner POSIFLEX F10, IP65; 0.2 - 1 bar (3-15psi); air connection G1/4", for 90° rotation (368.00.014) country of origin: Germany Customs tariff number: 90328100
FS0200.NM40CCALT.NL22SNA.00XX	18848 Drive of the EL-O-MATIC F series, ISO, F10/F07, single acting, spring set 40, 90° rotation counterclockwise / spring opening, Square mount 22mm parallel, with double stroke limitation: adjustment range open position 80° to 95° - closed position 10° to - 5°, standard temperature version - 20°C - 80°C incl. display
pneumatic positioner POSIFLEX F10	IP65; 0.2 - 1 bar (3-15psi); air connection G1/4", for 90° rotation (368.00.014) incl. PU tubing on bridge (stainless steel) according to VDI / VDE 3845, pitch circle 80 x 30mm, Height 45mm, for pneumatic drives EL-OMATIC, sizes E/F25 to E/F350, incl. mounting screws.
11629	POSIFLEX positioner electro/pneumatic 4-20 mA TYPE F 20 IP 65, M20x1.5 acc Data sheet D3.301.2 (VA368.00.164), incl. cable gland.
13269	Wear parts set consisting of all Seals, bearings and guide bands for ED/ES100, (repair kit) -20°/+80°C, - 4°F/+176°F (VA902.90.531) (VA001-454-25)
992.14.103 B	
750.73.053. 200 Va Transformer	
Pd2500.D1b00a.00n0	
992 14 103b	
Ef-H3bpl-25-Ed25-M	
Fs0600.Nm50cwalt.0000hna.00xx	
Typ: F 20 Ip 65 Art.No. Va368.00.164	

Ed25	
Ed0025m1a00a00n Group-2 Only Actuator	
Fs0350m60cwalt0000sna00	
368 00 164	
Ed0200.D1a00a.22no	
Fs0350.Nm30cwall.Yd22hna.00xx	
Fd0040.Nm00cwals.Yd14sna.00xx	
750 73 053	
Es0024m1a04a00n0 , Fs0025m40cwallyd11sna00	
F 20	
Type:Es0024m1a04a00n0 , Fs0025m40cwallyd11sna00	
Rb2c-190/60	
F20 368.00.164	
EI 1600 380 -415v 50/60 Hz,	
EI-200 380-415v/ 50 Hz	
Typ: Ptf20 Art.No. Va368.92.100	
368.90.011	
Es0200.Mia05a.00n , By Fs0200.Nm50cwall.Yd22sna.00xx	
Va001-454-43	
Va836.00.620	
Es0025.Mia05a.00n0 , By Fs0025.Nm50cwall.Yd11sna.00xx	
11712	2 pieces micro switch V3, type S2, for POSIFLEX positioner F 10/20, Cable entry M20x1.5, according to data sheet D 6.204, VA368.90.232.
Type: Es0025.M1a05a	
Fs0025m50cwallyd11sna00	
750.73.053	
Gasket For Type: Es0025.M1a05a , Fs0025m50cwallyd11sna00	

E350	
Ed1600.H1a00a.00n0	
368.00.014	
79000811	CONTROL CARD
Va368.00.014	
Vaed1600.D1a00a.46n0	
Ed25 A	
9136950003	
Ed0040.M1a00a.00n0 Replaced By Fd0040.Nm00cwals.Yd14sna.00xx	
36928-2 Selector Switch(Local/Off/Remote)	
Ed0040.M1a00a.00n0 267226079 /11	
Ed0200.D1a00a.17no	
El 200	
Fs0350.Nm30ccalt.NI27hna.00xx	
10156 Type Fs0025.Nm50cwall.Yd11sna.00xx	
Fs0600.Nm30ccalt.0000hna.00xx	
Fs0600.Nm30cwall.Yd27hna.00xx	
Ed0950	
368 00 014	
Ec7960x000001d0	
9139170001	
13181 Type Fd0040.Nm00cwals.Yd14sna.00xx	
Doppeltwirkender Pneumatik-Antrieb, Fabrik: El-O-Matic, Typ: Ed 950, Funktion: Code: "a"	
Ed950	
Ed25/A	
E0100	
Fs0350.Nm50cwall.Yd22sna.00xx	

750.73.053.
EI526
EI55
Type: F0100m - Old Name, New Name - Fs0100.Nm50cwall.Yd17sna.00xx
EI 1600
Dc-Ed-15-304 Butterfly Valve 3" With Pneumatic Actuator
Es0350.M1a05a.00n0 / By Fs0350.Nm50cwall.Yd22sna.00xx
Doppeltwirkender Pneumatik-Antrieb, Fabrik: El-O-Matic, Typ: Ed 950, Funktion: Code: Quot;Aquot;
Fs0600.Nm30ccall.Yd27hna.00xx
368.00.110,Obsolete,Replacement By Va368.00.164
Ed100
510/Tspn0237.1
Elf20
Ed0025.D1a00a.11no
Vaps2500.D0d14a.00n0
Es0200.M1a05a.00n0 , Fs0200.Nm50cwall.Yd22sna.00xx
11629 (Typ F 20 Ip 65)
750.73.053 B Transformer
Fs0200.Nm50cwall.Yd22sna.00xx
Ed0100 ACTUATOR
E20100.M1a05a.00no /F8
Fs0350.Nm30ccall.Yd22hna.00xx
368.00.164 Type F20
Es600
Ed 100
530/Ldn Is2
510/Tspn0257

[Es 950](#)[Elomatic-Ed0100d1a00a017n1-Type-Ed-100-Replaced-By-Fd0100m00cwallyd17sna00-Hochtemperatur-Ausf3;Hrung-20;C--120;C-Istanbul-Turkiye](#)[368.00.164 Posiflex Positioner, Electro/Pneumatic](#)[368.92.100](#)[368.00.164 Typ F 20 Ip 65 D3.301.2](#)[368.90.232](#)