

Elster

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Elster Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Elster Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Multi-jet meter M100 / M100 i Artist DN25	length 260
M-Bus module kit Falcon	
ENCORE FC1	
MSER4 MULTISERIAL 4 CHANNEL , FCMSE4	
ENCORE CPU BOARD , FCCPU3	
MSER4 MULTISERIAL 3 CHANNEL+1 LAN , FCESE4	
DISP3 U1.20 , 08120001	
CPU3 BASE , 08100001	
BATTERY, 3V, LITHIUM, SIZE CR2 , CR2	
QA 40R25-40	Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 40 m3/h, measuring range: 3.3-65 m3/h(b), Rp internal thread, DN 25, E1: 10 pulses/m3, E200: 500 pulses/m3 pu max. 4 bar, for gas and air Stat. Warenummer 90281000 Ursprungsland: SK
A1500	Technical Specifications; 3X58/100 V MV Measurement Feature 0.5 CL
Gas flow corrector EK270 ELSTER	

QA 250Z800-40	Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 250 m ³ /h, measuring range: 20-400 m ³ /h(b) Intermediate flange DN 80, E1: 1 pulse/m ³ , E200: 187.5 pulses/m ³ pu max. 4 bar, for gas and air Stat. Warennummer 90281000
TRZ G 650 DN 150 Class 150	turbine gas meter TRZ G 650 DN 150 Class 150 for measurements subject to legal control Measuring range 50 - 1000 m ³ /h Housing in nodular iron with maintenance-free, permanently lubricated bearings PED approval according to 97/23EG EC approval according to EEC 71/318/EEC national type approval European standard EN 12261 Measuring range 1:20 standard Index head S1 with attachable LF pulse generators (reed contacts) With IN-S 10 as standard (Reed contact pulse generator with 2 counter contacts and 1 monitoring contact for cable break and manipulation)
Testing costs TRZ DN 150 to 250	(factory test / calibration)
QAe 400Z100-40	47124010 Flow meter with electronical counter head For metering gas where no calibration is required, display of the quantity consumed, key-date value, key date, current flow rate and high resolution of the quantity consumed, with E200 pulse generator. Nominal flow rate: 400 m ³ /h, measuring range: 32-650 m ³ /h(b) Intermediate flange DN 100, E200: 187.5 pulses/m ³ pu max. 4 bar, for gas and air M-Bus interface
48115426	REFALIT flange seal DN 100 - HTB PN 10/16 DIN 2690, without bores, 115 x 162 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
QAe 160Z80-40	47121680 Flow meter with electronical counter head For metering gas where no calibration is required, display of the quantity consumed, key-date value, key date, current flow rate and high resolution of the quantity consumed, with E200 pulse generator Nominal flow rate: 160 m ³ /h, measuring range: 13-250 m ³ /h(b) Intermediate flange DN 80, E200: 187.5 pulses/m ³ pu max. 4 bar, for gas and air M-Bus interface
48115425	REFALIT flange seal DN 80 - HTB PN 10/16 DIN 2690, without bores, 90 x 142 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
QA 25R25-40	47102525 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 25 m ³ /h, measuring range: 2.5-40 m ³ /h(b) Rp internal thread DN 25, E1: 10 pulses/m ³ , E200: 500 pulses/m ³ pu max. 4 bar, for gas and air
QA 40R25-40	47104025 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 40 m ³ /h, measuring range: 3.3-65 m ³ /h(b), Rp internal thread, DN 25, E1: 10 pulses/m ³ , E200: 500 pulses/m ³ pu max. 4 bar, for gas and air
1/ P/F GAS PRESSURE REGULATORS.	IN/OUT PRESSURE: 3KG.CM2 / 0.95 KG/CM2, MAX PRESSURE: 4KG/CM2;390 - 520 NM3/H; FULL CAP.:3673, LOADING SPRING, 140 TO 1035 MBAR; 2-15PSIG; LIGHT GREEN/BLUE, PART NO.: J12309-051",
2/ P/F GAS PRESSURE REGULATORS.	IN/OUT PRESSURE: 3KG.CM2 / 0.95 KG/CM2, MAX PRESSURE: 4KG/CM2;390 - 520 NM3/H; FULL CAP.:3673, SPARES KIT, CODE: 2309-03; SIZE 50MM,
3/ GAS PRESSURE REGULATORS.	TYPE: LR AND LRP, UNIT COMP. REGULATORS, 50MM, MODEL: J123HP; 2IN. ; CL150 RF; INLET PRESSURE: 3 KG/CM2 ; OUTLET PRESSURE: 0.95 KG/CM2; FLOW CAPACITY: 390 - 520 NM3/H ; FULL CAPACITY: 3673 NM3/H ; MAX. WORKING PRESSURE: 4KG/CM2; DIAPHRAGM: REINFORCED BUNA N,

4/ GAS PRESSURE REGULATORS.	TYPE: LR , UNIT COMP. REGULATORS, REGULATOR MODEL: 1803B2; DIAPHRAGM: REINFORCED BUNA N,
SM-RI-X-L	FI - Flow Indicator, P Max: 18.8 Bar, QMIN: 800 M3/H, QMAX: 16000M3/H, Grate: 10000
VGBF 50F40-3	86048010 gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 50 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
75438983	Spring 220-350 mbar, black/green Spring (black/green) for VGBF 50 (220- 350 mbar) and VAR (221-340 mbar) for outlet pressure changes: for VGBF 50, Outlet pressure range 220 - 350 mbar for VAR 50, Outlet pressure range 221 - 340 mbar
MR50 F, PN 1 SM	47545022 Gas pressure regulator with safety diaphragm default setting pd 80 mbar pso180 mbar HTB version, with flange connection DN 50, PN 16 Overall length: 220 mm HTB - execution Inlet pressure Pe max. 1 bar with built-in SAV
48115423	REFALIT flange seal DN 50 - HTB PN 10/16 DIN 2690, without bores, 61 x 107 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent operation, EC type tested and certified in conjunction with Elster Kromschroder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
Turbine gas meter calibrated	
AS3000, 100A directly connected, 230/400V.	
Q400 DN150 PN10	
METER NATURAL GAS DN150 PN20 ELSTER G650 H	
De 400z150-40b	
Q650	
A1830-Ze3kmer00lm	
In-S11	
Dt200-1ek220-1	
84331384	
72701310	
J125	
Tc 116 V05t	
0000998	
Mr50 Sf6-Sbv	
83039727/2007	
A/R X Zio165 L35	
Uvs10 Elster	

Qa65 Dn50
A1500
74921995
1-595-A 616 Mt
74330321
Dg 50t
Vgbf50
Type ? 1500 ()
Eco 1-595-A
88650082
Zai 6mm
Zio/Bio/Bic
Qae65
Es 10ra1000
74330411
Q65 Dn50 Pn10
Alpha Smart As230
Tuv 03 Atex 2123
Qa65 Dn 50
Cn114.80
A 1350-W 325- 441-Qse 1037- Bdb00
A1200 Alpha Meter
9018868
Mr25 Sf10
Alpha Smart As330d
73016551
74330261
Trz-G400a1sdn100ansi600
A/R X Br 125 L35
Qa 100zi Dn80 Pn16 Bar
73012343
A/R X Br 140 L35
Alpha Smart As300p
9014808
Mr 50 F5
A1882-Ze3kp4r32lp-05s

H4000
Ec000482
A1500-W043-741-Osl-1565x-V4h00
Gehv 20r10
A1800 - A183raIns2
Dgdl
Gfk 50f60-6
74338391
Vgbf100
M120 Mtr-S 6 Art.No:0757993
73016551 / In-S11
Qa160z80
Mr50sf6
J125-S2
Vgbf80
Sk-4809-01 Jeavons J48
Ser-C 162/148-W2900f2
A/R X Br 100 L35
74330401
AinrtI (Obsolete - Replaced By A3n)
Alpha Smart As1440
Qae 400 150 Zi-Obsolete,Replaced By De 400z150-40b
Ek260
Vgbf 40r10-3z *Z
Trz2 G1000
Qa40 Dn 40
Alpha Smart As3000
Ecooo231
Trz2-G160dn80pn16
Baf2
A/R Br65 L35
Q75 Dn 50
A1800
As1440-Alpha
9018869

Mr 50 Sf-6 Dn50 Pn6 Bar
Uvs6
A1500-W043-A41-Osl-1165x-V4h00
A1500-W043-741
34482170
74921607-G
Gfk 15/20
8531721
Trz2 G-1000 Dn150 Ansi150
As1440-W32c-441-Ose-1a37s-Bdb00
Lf Pals Generator And Socket
Dg50u-6
Qae160
74951913
Qa6550z1
Du50
Sensor For Q650 1000m3
83570550
Es 20ra1000
Zmi/Zio/Bio
Ek280 Ptz 4 -20 Bar