



Erhardt + Leimer

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Erhardt + Leimer Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Erhardt + Leimer Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
STD 018-70	Shielded cable 6 x A 0.14 3 m long, with 1 angle coupling and 1 JST connector IP 40 Net weight approx. 0.200 kg. Country of Origin: Germany (DE) HS 85444993
FX 4200	00363593 Edge sensor ultrasonic, digital, Measuring range +/- 3 mm, according to dimension sheet 158320 with microprocessor, software Dat.Prot. 1.0 + 2.0, LED display scale with membrane keyboard, M16 connector for operating voltage 24 V DC and CAN bus, protection class IP 54, clear width 124 mm, fork depth 52 mm Net weight approx. 0.932 kg. FX 4100 has been replaced by FX 4200. Country of Origin: Germany (DE) HS 90318020
Motor + encoder + gear system is required	
00327361 - VS 3536 -12	
00323892 - RK 4004 controller card	
VG 2021 PIVOTING ROLLER	
00100776-PD 2335	Load cell 1,50kN
FX4631	Software ZC3510-8002F_ZG01 352101
00835595	Load cell 0.15kN 00835595-PD 2525
TYP: SE4051	Typ: DC 5501
00457279-PD 2125	Load cell 0.75kN-00457279 00457279-PD 2125
SWS9573	
type BT0121	Nr.209180 with two shaft output
ultrasonic edge sensor fx 4631	
NR. 229370	

TYP: AG2591	
FX 51010	212048
TYP:AG2595	24V DC I:2.9 A S:+/-75 MM ID NO:710246866 G9192
TYP:AG 2529 226921	AG 2529 NR:226921 24VDC 2,9A S=t/75MT
FR 0901	
00220906	
Pd 2117	PD 2117 Load cell for bearings D 17 mm Nominal measuring force 0.10 kN, right Special version according to KBS5079-10583691 Plug on the side Net weight about 1,888 kg. Material no. 220829 has been replaced by 489431. Origin: European Union (EN) HS 90318080
Cv 2201	Web force measuring amplifier for DIN rail mounting, Operating voltage 24 V DC, Output 0-10V or 0 / 4-20mA Origin: European Union (DE) HS 85437090
Ch-328284-1	
Ch-349658	
Cv2201-U24vdc-P4w	
Ch-006462	
00043330 Pd 2145	
00302990 Cv 2201	
F 31e	F 31E edge sensor mechanically right, with 2 individually finely adjustable silver contacts for max. 60 V 0.2 A, control bandwidth 0.5 - 30 mm and contact force of the feeler lever adjustable, protection class IP 33, max. 80 degrees C including 2 m connection cable Origin: European Union (DE) HS 90318080
Ag2491	
Dc1340	
9100001	
349658	
Fr6011	
Ag2591	
00230567	
Fm3085t	
00006462	
Rk4004-8403-F-Z101	

Ag 2595	AG 2595 Actuator with DC geared motor 50 W with incremental encoder, Travel +/- 75 mm, positioning speed 25 mm / s, force 1000 N Origin: European Union (EN) HS 85013100
00100783	
Fr 5503	FR 5503 infrared edge sensor for clamping frames according to dimension sheet 10514704 Measuring range +/- 10 mm with microprocessor, LED display scale with membrane keyboard, Plug for operating voltage 24 V and CAN bus, with mechanical scanning and with spring clip. Net weight about 0.625 kg / piece. Origin: European Union (EN) HS 90314990
Va5021	
Ch-323230	
Pd 2535	Light metal force transducers in flange construction, according to dimension sheet M 057626 without ball bearings and circlips for pin diameter 35 mm Version open on one side Nominal measuring force 1.5 kN, protection class IP 54 Country of Origin: Germany (DE) HS 90318080
00320961	
00003235	
FR 5503	"Ident No:1810430279" Infrared edge sensor for clamping frame according to dimension sheet 158289 Measuring range +/- 10 mm with microprocessor, LED display scale with membrane keyboard, Plug for operating voltage 24 V and CAN bus, with mechanical scanning and with spring clip. Net weight approx. 0.625 kg. Country of Origin: Germany (DE) HS 90314990
00302990	
Pd2535 1,5 Kn Loadcell	
Fx 4631	Edge sensor ultrasound, digital, Measuring range +/- 3mm, inside width 30 mm, with 3,000 mm cable and M16 angle plug Origin: European Union (DE) HS 90318020
Fx4060	
00352056	
006462	
Rk 4080 For Kr 6 ...	Spare parts package
Do2000	
Std_018-70	Cable shielded 6 x A 0,14 10 m long, with 1 angle coupling and 1 JST plug IP 40
00351779	

[Dig000](#)