



## Ewon

Garanti: 12 ay  
 Bu ürüne ait Türkiye  
 içi kapı teslim fiyat  
 ve teslim süresi  
 içeren teklifimizi  
 almak için  
[info@yursat.com.tr](mailto:info@yursat.com.tr)  
 e-posta adresine  
 başvuru yapabilir ya  
 da ayrıntılı bilgi için  
 +90 224 240 03 04  
 numaralı  
 telefonumuzdan  
 bizlere  
 ulaşabilirsiniz.  
**Ewon** Markası,  
 tedarik süresi için  
 lütfen bizimle  
 iletişime geçiniz.

Firmamız Ewon Türkiye  
 Distribütörü veya temsilcisi  
 değildir. Firmamız sipariş  
 durumunda, belirtilen  
 ürünlerde sadece Orjinal ve  
 yeni ürün teklifi  
 sunmaktadır. Bu sitede  
 gösterilen Özel marka adları  
 ve ticari markalar ilgili  
 sahiplerinin  
 mülkiyetindedir, talep  
 durumunda  
 kaldırılmaktadır.

Ürün	Açıklama
<a href="#">WEC61330 Ewon COSY 131 VPN/Ethernet</a>	4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 108.8 x 98.3 x 43.6 mm (H x D x W) Operating temperature: -25 ° C to 60 ° C
<a href="#">Ewon Cosy 131 - 3G</a>	
<a href="#">Ewon Cosy 131 - WiFi</a>	
<a href="#">WEC61330</a>	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
	Ewon COSY 131 VPN/Ethernet/WLAN 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN

<a href="#"><u>WEC6133C</u></a>	connection via LAN + WLAN 802.11 b / g / n Output power 19dBm WiFi antenna included Note: When using accessory antennas, observe the permissible transmission power SD card slot for configuration / device update, 2x DI and 1x DO, Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#"><u>WEC6133G</u></a>	Ewon COSY 131 VPN/Ethernet/LTE-Modem Europa 4x RJ45 LAN/WAN 10/100 Base (integrierter 4-fach Switch konfigurierbar) 1x USB-Port WAN-Anbindung über LAN und GSM/GPRS/EDGE/UMTS/HSUPA/LTE mit bis zu 150 Mbit, Frequenzbänder für Europa (1, 3, 7, 8, 20) SD-Kartenlaufwerk zum Konfigurieren/Geräte-Update Integriertes Webinterface für Konfiguration OpenVPN für sichere Internet-Verbindung mit Talk2M Größtmöglicher Schutz durch Zugriffskontrolle Spannungsversorgung: 12-24 VDC Abmessungen: 106 x 99 x 40 mm (H x T x B) Betriebstemperatur: -25°C bis 70°C
<a href="#"><u>Router eWon 2005CD</u></a>	
<a href="#"><u>WEC61330</u></a>	Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#"><u>FLEXY201</u></a>	
<a href="#"><u>FLB3204</u></a>	Ewon Flexy 201 M2M and remote maintenance router 4x RJ45 LAN 10/100 Base (integrated switch) 1x SD card slot for configuration / device update 2x digital input 1x digital output 4x slot for expansion cards Integrated web interface for configuration Routing function for remote maintenance access Ethernet / serial Communication protocols to controls (e.g. Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and email BASIC editor for free programming Integration of your own HTML pages with eWON tags OpenVPN for a secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 80 x 89 x 134 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C
<a href="#"><u>Cosy 131</u></a>	
<a href="#"><u>WEC6133D</u></a>	Ewon COSY 131 VPN/Ethernet/3G+-Modem 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN and GSM / GPRS / EDGE / UMTS / HSPA + modem, SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions:

106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

#### [131 EC 61330 00MA/S](#)

#### [FLEXY205](#)

Ewon Flexy 205 remote maintenance router 4x RJ45 LAN / WAN 10/100 Base (integrated switch configurable) 1x SD card slot for configuration / device update 2x digital input 1x digital output 2x slot for expansion cards Integrated web interface for configuration Communication protocols to controls (e.g. Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and email BASIC IDE / JAVA for free programming Integration of your own HTML pages with eWON tags OpenVPN for a secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 133 x 122 x 55 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C

#### [WEC61330](#)

Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN/WAN 10/100 Base (integriert 3-fach Switch konfigurierbar) 1x USB-Port WAN-Anbindung über LAN SD-Kartenlaufwerk zum Konfigurieren/Geräte-Update Integriertes Webinterface für Konfiguration OpenVPN für sichere Internet-Verbindung mit Talk2M Größtmöglicher Schutz durch Zugriffskontrolle Spannungsversorgung: 12-24 VDC Abmessungen: 106 x 99 x 40 mm (H x T x B) Betriebstemperatur: -25°C bis 70°C

#### [WEC61330](#)

Ewon COSY 131 VPN/Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

#### [WEC61330](#)

Ewon COSY 131 VPN/Ethernet Switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for a secure internet connection with Talk2M Greatest possible protection through access control. Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

#### [EC61330 Cosy 131](#)

Industrial Internet Router 001616325-81

#### [Nur Bilder](#)

haben leider keine model/Artikel nr.

#### [EC6133C](#)

001616327-81 Cosy 131 WIFI Industrial Inet Router

#### [Ec51460](#)

COSY 141MPI INDUSTRIAL VPN ROUTER

#### [S7-300](#)

CPU 314C-2 PTP Kompakt-CPU with M

#### [EC61330](#)

Cosy 131 Industrial Internet Router

#### [VC61330-00MA/S COSY131LAN](#)

#### [Cosy 131 Industrial Internet Router](#)

<a href="#">777555</a>	Special procurement item
<a href="#">VPN Router eWON 2005 CD/ETHERNET</a>	
<a href="#">EW26201-00</a>	
<a href="#">EC61330-00-Q1 Communication Module IP Router, VPN,</a>	4 x 10/100Mb Ethernet, 2DI, 1DO, USB eWON Cozy BRAND
<a href="#">Ewon Flexy 205 Starter Kit STK205</a>	
<a href="#">Ewon Flexy 205 Starter Kit</a>	777555-81 STK205#Ewon Flb 204 = cannot be obtained
<a href="#">Flb 204</a>	
<a href="#">EC61330</a>	
<a href="#">ewon flexy 205</a>	
<a href="#">EC71330_00MA</a>	EAN: 2050007680710 COSY+ EtherNet 2621279-81
<a href="#">Cosy 131 WIFI Industrial Inet Router</a>	Manufacturer's part number: EC6133C
<a href="#">EC61330</a>	eWon Cosy 131 , 4xRJ45 ( 1x WAN port ve 3 x LAN port )
<a href="#">FLX3101_00</a>	Single ethernet extension board for Ewon Flexy Indus. Internet Router
<a href="#">EC 61330 COSY 131 ETHERNET ROUTER</a>	
<a href="#">WeC6133d</a>	
<a href="#">Ec6133c Ewon Cosy 131</a>	eWON COSY 131 VPN/Ethernet/WLAN 4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN + WLAN 802.11 b / g / n Output power 19dBm Wi-Fi Austekkanten included Note: When using accessory antennas, observe permissible transmission power SD card slot for configuring / device update, 2x DI and 1x DO, Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#">Ew05201</a>	ETHERNET GATEWAY MODULE 300MA 12-24VDC 5W
<a href="#">WeC61330 Ewon Cosy 131 Vpn/Ethernet</a>	4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#">Ew26201-00</a>	REMOTE CONNECTIVITY GATEWAY
<a href="#">Ewon-2001/Gprs</a>	ETHERNET GATEWAY MODULE 300MA 12-24VDC GPRS
<a href="#">E3w_Flb3202</a>	
<a href="#">WeW33204</a>	

[Wew26204](#)

[Wew40902f \(Replacement For Wew40902b\)](#)

[Ewon2005cd Vpn/Ethernet/Mpi](#)

[Wec61330 - Ewon Cosy 131 Vpn/Ethernet](#)

4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

[Wew2626b](#)

[Flexy10100\\_00ma](#)

[Flb3271](#)

[Ew26204](#)

MODEM

[E3w\\_Ec61330](#)

[Ec51460](#)

COSY 141MPI INDUSTRIAL VPN ROUTER

[E3w\\_Ew26201](#)

[Wew40902b](#)

[Wec61330](#)

Ewon COZY 131 VPN / Ethernet 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuring / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

[Cosy 131 , Wec6133d](#)

[Ewon2005cd Vpn/Ethernet/Seriell/Pstn](#)

[Cosy 141 Wec51410](#)

[Cosy 141 Wec51460](#)

[Wew2620b](#)

[Ewon Cosy 141 Vpn/Ethernet/Seriell](#)

[Ec6133c](#)

ROUTER

[Wec51460](#)

[Wew46261](#)

[Wew3326b](#)

[Wew40912b](#)

[Flexy20300](#)

[E3w\\_Flexy20100](#)

<a href="#">Wew2620a</a>	
<a href="#">Ew21205-00-16</a>	ETHERNET GATEWAY MODULE 300MA 12-24VDC GPRS
<a href="#">Ew26264</a>	
<a href="#">Ewon Cosy 141 Vpn/Ethernet/Mpi</a>	
<a href="#">Wew26261</a>	
<a href="#">Wew26201</a>	
<a href="#">Flx3101</a>	
<a href="#">Wew40902f</a>	
<a href="#">Wec6133d Ewon Cosy 131 Vpn/Ethernet/3g+-Modem</a>	4x RJ45 LAN / WAN 10/100 Base (integrated 4-way switch configurable) 1x USB port WAN connection via LAN and GSM / GPRS / EDGE / UMTS / HSPA + modem, SD card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#">E3w Flb3271</a>	
<a href="#">Ewon 2005cd</a>	
<a href="#">Ewon Cosy 131 Vpn/Ethernet</a>	WEC61330 4x RJ45 LAN / WAN 10/100 base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD card drive for configuration / device update Integrated web interface for configuration OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C
<a href="#">Flexy205</a>	Ewon Flexy 205 remote maintenance router 4x RJ45 LAN / WAN 10/100 Base (integrated switch configurable) 1x SD card slot for configuring / device update 2x digital input 1x digital output 2x slot for expansion cards Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function Up to 1500 variables (tags) for data management Alarm management via SMS and Email BASIC IDE / JAVA for free programming Integration of own HTML pages with eWON tags OpenVPN for secure internet connection Greatest possible protection through IP filters & access control Integrated data logging with up to 1,000,000 data points Power supply: 12-24 VDC Dimensions: 133 x 122 x 55 mm (H x D x W) Weight: <500 g Operating temperature: -25 ° C to 70 ° C
<a href="#">Fla3301</a>	Ewon Flexy expansion card serial 1x RS232 / 422/485 1x RS232 Usable as IO or VCOM interface For use in the base modules Weight: <300 g Operating temperature: -25 ° C to 70 ° C
<a href="#">Ewon 4005 Cd</a>	
	Ewon cosy 131 4x RJ45 LAN / WAN 10/100 Base (integrated 3-way switch configurable) 1x USB port WAN connection via LAN SD

[Ec61330](#)  
card drive for configuring / device update Integrated web interface for configuration Communication protocols to controllers (e.g., Siemens, Allen Bradley, Modbus, OMRON) with gateway function OpenVPN for secure internet connection with Talk2M Maximum protection through access control Power supply: 12-24 VDC Dimensions: 106 x 99 x 40 mm (H x D x W) Operating temperature: -25 ° C to 70 ° C

[Wec51410](#)

[E3w Flx3101](#)

[1422 – 0075 – 21 / Flexy20100\\_00ma/S](#)

[Ewon2101cd\\_Vpn/Mpi/Gprs\\_Qb](#)