

Ffe

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Ffe Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ffe Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
FFE vibration switch with manual reset	Model: 8000 - 000 Set level range: 0.5 ... 9 g (Factory setting: 3 g) Microswitch: SPDT / silver contacts Switching capacity: 5 A at 250 Vac or 30Vdc Ambient temperature: - 45...+85 °C Housing: Die-cast zinc alloy Mazak III with powder coat finishing electrical connection: M20 x 1,5 Protection: IP 66/67 to. BS EN 60529
Model: 8001 - 000	FFE vibration switch with manual reset Set level range: 0.5 ... 9 g (Factory setting: 3 g) Microswitch: DPCO / silver contacts Switching capacity: 5 A at 250 Vac or 30Vdc Ambient temperature: - 45 ... + 85 ° C Housing: Die-cast zinc alloy Mazak III with powder coat finishing electrical connection: M20 x 1,5 Protection: IP 66/67 to. BS EN 60529
VIPRATION SWITCH TYPE 3171	
Modell 8001 - 00	FFE vibration monitor with manual reset Adjustment range: 0.5...9 g (factory setting: 3 g) Microswitch: double pole changeover / silver contacts Switching capacity: 5 A at 250 Vac or 30 Vdc Ambient temperature: - 45...+85°C Housing: Die-cast with polyester paint Cable entry: M20 x 1.5 Degree of protection: IP 66 / 67 according to BS EN 60529

8001 - 000	FFE vibration monitor with manual reset Adjustment range: 0.5...9 g (factory setting: 3 g) Microswitch: double pole changeover / silver contacts Switching capacity: 5 A at 250 Vac or 30 Vdc Ambient temperature: - 45...+85°C Housing: Die-cast with polyester paint Cable entry: M20 x 1.5 Degree of protection: IP 66 / 67 according to BS EN 60529
3171MR & S	
Fire Fighting Type 3171	
Cable Gland	
8001-030	
8101 - 000	
Modell: 8001-010 (24 Vdc)	
Ffe-Ffe-Vibrationswö;Chter-Modell-3171-Ex-Mit-Handr3;Ckstellung-Istanbul-Turkiye	
Modell: 8001-030 (240 Vac)	
8001-010	
Fireray 50r	
Modell 8100 - 000	
8000 - 000	
Modell: 8001-020 (110 Vac)	
8000 - 000 (3171)	
8100 - 000	
3171 Ex D E	
Modell 8000-000	
8001-020	
Ffe 8000 - 000	
Ffe-3171mr-1-S Obsolete, Replaced By Ffe 8000 - 000	
3171 Ex	
8001 - 000	
Type:3171for Cooling Tower Replaced By 8001 - 000	