

Fischer



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Fischer Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Fischer Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
De90b20040p0000000000	Digital differential pressure transmitter PRO-LINE Measuring range channel 1 -25 + 25mbar Measuring range channel 2 no channel
DE2759M042BP00MW	Digital differential pressure transmitter Measuring range 0 ... 10 mbar Deviation from characteristic <= 1% Process connection plug-in nipple 6/4 mm and 8/6 mm hose Output signal / operating voltage 4 ... 20mA, 2-wire / 24VDC
67CFR-226 0-125 Psi-Regler	Anschluss des Reglers 1/4 " NPS
DVC2000 Series Digital Valve Controller	Single-acting, HART-based, digital valve controller. Temperature range is -40 to +85 deg. C Point-to-point signal: 4-20 mA Local display language: English Includes the CE mark for Europe Does not include mounting method, supply regulator, or drip pot. I/O Package: Digital Valve Controller Only Housing Style: B - Rotary and Sliding Stem Pneumatic & Conduit Connections: 1/4-inch NPT & 1/2-inch NPT Imperial Supply Pressure: 1.3 to 3.4 bar (20 to 49 psig) Approval: ATEX – Intrinsic Safe.
4KB 1-WIRE EEPROM	DS2433+
RNJ66T1199SN 014F395	RNJ JACK 11-99, 7 PIN, 20 SIZE
RNJ67T1199PN 014F395	RNJ PLUG 11-99, 7 PIN, 20 SIZE
DN40 PN40 EU03681738	
DVC2000 - AS PER SERIAL: F001176465	Construction: Aluminum Pipe Away Vent Connection: None Protocol: HART 5 Language: English Control Tier: Not App Action Type: Direct Diagnostic Tier: Auto Calibrate-AC Conduit/Air Port Plastic Plugs: No Approval Agency: ATEX Output/Supply Gauges: None Approval: Intrinsic Safe Custom Configuration: No Position Transmitter: No Input Signal: 4 to 20 mA dc Limit Switches: None Positioner Type: DVC2000 Housing Style: A Supplemental Attribute: Not App Relay Pressure Range: 3.4 to 7.0 barg (50 to 100 psig) World Area Selections: Conduit Connection: M20 Positioner Style: I/P Cable Gland: None Manu

DE85B21K42B90CMW0000	Differential pressure transmitter ECO-LINE Measuring Range: -25 .. +25 mbar Output Signal: 4 - 20 mA Supply Voltage: 24 V DC Pressure Connection: 6/4 mm and 8/6 mm hose successor model DE85
ME1201087BH90V00	0-0,6 BAR 4 -2mA 24 VDC
DVC6200 4-20 MADS PT-PT HARD	052-2015/1004714-1120-03-ATX Positioner, digital controller Digital Valve Controller
0-6 Bar DS11	
İscope Fmp30	
DE90580000P000000000	Digital differential pressure transmitter PRO-LINE Measuring range channel 0...60mbar Process connection G1/8 inside -Alu Output signal 4....20mA 3-wire Approval none
06401995	M12 coupling with 2 M PUR cable 5 pin
06401993	M12 coupling with 2M PUR cable 4-pin with coding steps
67CFRMAX SUPPLY : 250 PSISPRING RANGE :0-125 PSI	
DVC2000	F002636019
600-820 F1	
600-800	
Egab1.3	
600-782	
512 146	
13765x	
50491 Gb8	
De1602vdyb9d128	
E32fra32	
E18pressin	
Frau27	
E28pressin	
Stopper-E	
5622	
1e845714012	
E61 Pi	
Akku Set Fmp (Nimh)	

2e859802202	
Dualscope Mp0r Usb	
I2p-100	
600-823 F6	
Ds21010a20bk0w00	
68060	
R667x000502	
600-025	
34b6283x012	
600-771	
Pt 100 Sonda	
Ea14a	
E3 1031.1/6.2 S	
2bst.006009	
Ds21010a20bkw00u0006	Component tested differential pressure measuring and switching device Measuring range 0 ... 0.6 bar Application Thermal oil DIN 4754-2 / water flow 100 Component tested differential pressure measuring and switching device Measuring range 0 ... 0.6 bar Application Thermal oil DIN 4754-2 / water flow 100 Double scale: bar (outside) / psi (inside)
F.0005.5765 [ex.562-443-230]	
E51	
Rpackx00112	
F.0007.3301 [ex.568-293-088]	
1e825827082	
E3 1031.1/6.7 S	
Deltascope Fmp10	
Fhb-A Dyn 16 X 125/50 - 092036	
5624	
E58	
568.490.088	
61224	

Dbee 105z 049-120	
E18 Pi	
E61	
809623.03.037	
605-097 (Ex. 604-555) Dualscope-Mp0r	
48-187	
600-822 F4	
De46 L70041pn03mw	Dig.Differenzdr. Switch / Transmitter Basic measuring range - 100 ... +100 Pa
2450-7I	
De45	
67cfr-226	
Br225-Mc 163/24, 24vdc, Kvs=20 M3/H, Dn40/16	
Frau 32	
48-204	
26a5300x022	
601-793 Egab1.3	
1p788102192	
Isoscope Fmp 10	
E31043/87+b	
De45d80040pk03mw	
10a4557sxbn	FLOW METER
61209	
505528	
Ds3105fm29a1	
M8	
601-793	
Art.No. 602-221 Egab1.3-Fe (Order No. 901-735)	
S104a092-130	
562-089-101	

600-792 2.2mm Grun	
E61pressin	
Frau 27	
603-476	
De1602vdyyb90k00d0579	
7502	
99-903	
48-186	
48-183	
685b689u02	PC BOARD ICOM L-BOARD
00623-50522	
E40pressin	
685b737u01	PC BOARD MEMORY Q-BUS
600-769	
603-384	
600-226	
686b704u01	ETHERNET CARD
E40 / E61	
53mc5412a25bafxcxxxx	PROCESS CONTROLLER 120/240VAC 36VA
40pb3202a	I/O BOARD MODULE D-LOOP FOR HARMONY DCU SYSTEM
Fp-7	
Me12	ME12 pressure transmitter 0-600 mbar 4-20 ma G1 / 2 "
D10a1198r	
M10	
Stopper-A	
Ve3514tr7081	
00627-50558	
De505401f11e	
Aa/Mignon	
Bp9733-500	

50dpf110-3/Bvvabaaa-En	TRANSMITTER 24VDC OUTPUT MADC 4-20 RANGE 1-150 W C
513 226	
50pz1262b1x2	FLOW METER CONTROL UNIT
53su1111a1bdx	SUPERVISOR
De27b2m045bp00mw , De27b2m042bp00mw	
E50/51	
26a5288x032	
562-089-000	
Tw30 B190k000	
Fmp20 / 605-023	
Da0234801	
Fp7	
53mc2112a1xdx1	PROCESSCONTROL 120V 50/60HZ
E32	
61180	
600-434	
5621	
53mc5111a25baxxdxaxx	PROCESS CONTROLLER 120/240VAC 36VA
Ptc00-3-2024	PRESSURE TRANSMITTER 12-45VDC 0-600VDC 4-20MA
53mc4211a1bb1	PROCESS CONTROLLER DIGITAL 120V 50/60HZ
E6	
00626-50557	
Sch 1216	
Isoscope Fmp 30	
600-829 F11	
040771	
53mc5412abab1cxxxxx	PROCESS CONTROLLER 120/240VAC 36VA
600-772	
Dualscope Fmp20	
600-770	

11767258	
26a5316x012	
39a8550x032	
562 337 460	
40dp2000c	DCU CONTROLLER DISTRIBUTED CONTROL UNIT
18-999-4542	
95v 25w Att.Ba.2	
H1000aq	
53mc5412a24bbxxxxxx	PROCESS CONTROLLER
61176	
600-791 (1x10)	
16a5544x052	
685b719u01	Q-BUS MEMORY BOARD
1000840.01.005	
E28 Pi	
Me11	ME11 pressure transmitter 0-16 bar 4-20 ma G1 / 2 "
605-097	DUALSCOPE MP0R Handheld measuring device with integrated measuring probe for coating thickness measurement after magnetic induction and eddy current method Characteristics: - Intuitive operation with menu navigation and graphic display - The display automatically rotates like a smartphone - Wear-resistant carbide probe pole - Measurement modes: Standard, IMO PSPC (90/10 rule) and SSPC-PA2 - Measurement memory: 10,000 - USB interface for bi-directional data transmission - Support CD with software FISCHER DataCenter for evaluation and archiving of Measured values as well as PC-DATEX software for data transmission in Excel - with shock protection made of rubber - Manufacturer certificate - Measuring ranges: 0 - 2000 µm NE / Fe, 0 - 2000 µm Iso / NE The price includes case, protective cover, interface cable MP0R-USB, Carrying strap, 2 batteries operation manual
Ds3111ade09p1b2ba126	MAGMETER 1 INCH TUBE 285 PSI MAX
600-225	
D55ax1100aa	
De505401p11e	
16a5415x332	
600-768	

De46 Differential Pressure Transmitter	Flow rate: 32440 m ³ / h Pipe inner diameter: 792 mm. (800 x4 mm.) Pressure: 800 mmSS Temperature: 20 ° C Altitude: 568 meters Air Monitor - Volu Prob - 1 aluminum pitot traverse (2 pieces)
602-406	
50dpf100-2-Bvvbb-Ca-Ns	TRANSMITTER PRESSURE DIFFERENTIAL 24VDC 4-20MA OUT
50xm13bxad11aahd224	FLOWMETER 110V 0/6GPM SIGNAL CONVERTER MAGNETIC
E40 Pi	
De27	DE27 pressure transmitter -25 +25 mbar 4-20 ma 24 v dc
48-203	
Art.No. Ds1102va21b10w00	
Tam12(Ex.Slm12c/Bull-Te12x0)	
53mc5412a25bac2dxxxx	CONTROLLER 120/240VAC 36VA
E120	
Ega-2h	
40pb3201a-Re	I/O BOARD MODULE A LOOP FOR HARMONY DCU SYSTEM
Ab25/90	
De2599koyyykd373	
M56240042	
602-563	MANUFACTURING CERTIFICATE M
603-390	
685b500u01	PC CONTROLLER BOARD
600-793 (1x10)	
Egab 1.3 Maã223;E Bohrinse Und Router	
624b355u02	MOTHER/DAUGHTER BOARD W/DISPLAY
9005-12490	CHART RECORDER MODEL 1390
1036777 Rietschoten 12424	
D50-Xm14-Bbax00	SIGNAL CONVERTER 120V 60HZ W/LED DISPLAY
685b522u04	SENSOR CARD
De46 L20041pn03mt	Dig.Differenzdr. Switch / Transmitter Basic measuring range - 50 ... +50 Pa

104	
09173	
E41 Pi	
10w921u01	
10b4657x012	
Anotest Ymp30-S 603-800	
De160vdyyb90k00d0579	
685b522u01	FET AI MUIX BOARD
Kleb	
Fk50	
40lc-1211a	CONTROLLER DUAL LOCAL DCI-4000 DLC
1321cbb01bcx11	CHART RECORDER MICRO-DCI
53mc5111a25bacdxaxx	PROCESS CONTROLLER 120/240VAC 36VA
1-Magmeter-Tube	TUBE 1INCH MAGMETER MAX 285 PSI
10201451	
De2699041yyld187	
Ds21040a23ak0000	
10a4555pxbh	FLOW METER
De1602vdyyb9d128 W597 Oil Flow Meter	
10a4658s	FLOW METER VA MASTER 689KPA 100PSIG 100F
846-738-2452375	
40pb3204a	I/O BOARD MODULE CIO FOR HARMONY DCU SYSTEM
00625-50556	
43676	