



Flexco

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Flexco Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Flexco Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
C2c	Art. Nr.: 30439 Zolltarifnummer.: 82034000 Ursprungsland: US
Flexco Hp2	Art. Nr.: 1/1/2,2,2-1/4&RP2 Zolltarifnummer.: 82034000 Ursprungsland: US
Flexco Hw2	Art. Nr.: 1/1/2,2,2-1/4&RP2
Flexco Alligator-Rs 187 S 1000nc-P	Mode -Beschrelbg. (N.4LT REF: [.4R3) in stainless steel (4 pcs / box)
Rs187j40/1000nc	Ad. Nr.: 54694 Galvanized steel Customs tariff no .: 73269098 Country of origin: US
Rs 187sj40/ L000ncs	Art. Nr.: 54706 stainless steel Customs tariff number: 73269098
Z10180	Carbide knives (blades) CT6
Z10180	Stainless steel knives (blades) PVT6 (S / S)
GASKET 16 * 34 MM INTERFACE INC TN9001	
R5-SE	
Flexco Alligator-RS – SE – 63/1.600	
Rivets SRC band thickness 9 - 1 mm	
Coupling rod NC - C	
AC6-1000-1 HD	Coupling rods
5-1/2-SE-40/1000	Rivet hinged connector Customs fee number. 73269098, Origin: US
AC-1.000-1	

Head scraper MSP-1000-200-Atex	
Secondary wiper RV900-Atex	
Flexco Band Hinge	1,8m
Flexco Band Hinge	1,5m
Flexco Band Hinge	1mt
Flexible Tape Hinge Rivet	Studded Rivet
RS SE-40/1.000	
FLEXCO SRC	Tape insertion nail
Flexco AC-800-1	
Flexco AC-1000	
RS-SE-32/800	
R5-SE-40/1000	
R2T MOUNTING APPARATUS	/ APPARATUS WIDTH: 300MM / MECHANICAL ADDITIONAL APPARATUS FOR DISCHARGE CONVEYORS
Flexco 190C	FLEXCO Bolt Solid Plate 190C Conveyor belt connection system "C" steel for conveyor belts up to 630 N/mm strength Strap thickness range 8 to 14 mm required minimum drum diameter 400 mm Bucket content: 100 pieces
190EE	FLEXCO Bolt Solid Plate 190EE "Everdur" conveyor belt connection system antimagnetic and non-sparking for conveyor belts up to 630 N/mm strength Strap thickness range 8 to 14 mm required minimum drum diameter 400 mm Carton content: 25 pieces
140EE	FLEXCO Bolt Solid Plate 140EE "Everdur" conveyor belt connection system anti-magnetic and spark-free for conveyor belts up to 400 N / mm strength Belt thickness range 5 to 11 mm required minimum drum diameter 300 mm Box content: 25 pieces
Flexco 190VP	FLEXCO Bolt Solid Plate 190VP conveyor belt connection system "VP Vulcanized Plate" for belt width 900 mm (5 x 180 mm) for conveyor belts up to 630 N/mm strength Strap thickness range 8 to 14 mm required minimum drum diameter 400 mm Box content: 1 piece
R5S-SE-26/650	FLEXCO Rivet Hinged R5S-SE-26/650 conveyor belt connection system Version stainless W.1.4401 for belt width 650 mm for conveyor belts up to 800 N/mm strength Strap thickness range 6 to 11 mm required minimum drum diameter 200 mm Box contents: 2 connector strips (without rivets and coupling rod!)
	FLEXCO Rivet Hinged R2S-40/1000 conveyor belt connection system Version stainless W.1.4401 for belt width 1000 mm for conveyor belts up to 400 N/mm strength Band thickness

R2S-40/1000	range 5 to 10 mm required minimum drum diameter 125 mm Box contents: 2 connector strips (without rivets and coupling rod!)
A84030663	
ALIGATOR RS 62	
Flex-Lifter-M	(Tape Width: 900-1500mm)
FLEXCO Bolt Solid Plate 140C	Conveyor belt connection system "C" steel for conveyor belts up to 400 N/mm strength recommended strap thickness range 5 - 11 mm required minimum drum diameter 300 mm Bucket content: 100 pieces
FLEXCO Wrench HW1	Socket wrench for impact wrench suitable for connector sizes 1, 140, 190, RP1, 375X, 550
FLEXCO punch HP1	for impact wrenches suitable for connector sizes 1, 140, 190, RP1, 375X, 550
FLEXCO Bolt Solid Plate 140VP	conveyor belt connection system "VP Vulcanized Plate" for belt width 900 mm (5 x 180 mm) for conveyor belts up to 400 N/mm strength
ITEC-220	FLEXCO electric tape cutter ITEC-220 230V / 50Hz Cutting depth max. 50 mm
RS-SE-26/650	
RS-SE-32/800	
RS-SE-55/1400	
R5 1/2-1000	
RS62	
FLEXCO punch HP2	HP2 for impact wrenches suitable for connector sizes 1½, 2, 2¼, RP2
FLEXCO Wrench HW2	HW2 Socket wrench for impact wrench suitable for connector sizes 1-1/2, 2, 2-1/4, RP2
FLEXCO quick coupling 5552	5552 suitable for HP and HW tools
FLEXCO chisel C2C	Z10180 suitable for connector sizes 1-1/2, 2, 2-1/4, RP2
R5-SE-40/1000	FLEXCO Rivet Hinged R5-SE-40/1000 conveyor belt connection system Version galvanized steel for belt width 1000 mm for conveyor belts up to 800 N/mm strength Strap thickness range 6 to 11 mm required minimum drum diameter 200 mm Box contents: 2 connector strips (without rivets and coupling rod!)
SRC	FLEXCO Rivets SRC mild steel Strap thickness range 9 to 11 mm suitable for connector types R5, R5½ Carton content: 250 pieces
PRIMER SCRAPER INDUSTRY TYPE	

1200MM	
BELT WIPER WITH PRIMER POL. TIP 650 MM.	
PRIMER SCRAPER INDUSTRY TYPE 800MM	
MMP-642	Band Width: 1000mm,FLEXCO
Super Screw 80	
5x18mm	coupling screw
2-G-300W	ANKER conveyor belt connector 2-G-300W paperbound with perlon coupling wire made of round material Ø 1.20 mm in galvanized version Pitch 3.67mm for belt width 300 mm Band thickness range 3.0 to 4.0 mm required minimum drum diameter 50 mm Box contents: 12 strips
G002-G-300W	ANKER conveyor belt connectors Type G002-G-300W made of strip steel 0.75 mm Galvanized version pitch 4.00 mm for belt width 300 mm Band thickness range 2.0 to 2.5 mm required minimum drum diameter 40 mm Contents of the carton: 12 strips including coupling rods
A3-300W	ANKER conveyor belt connector A3-300W Type A3-300W with welded cross wire from round material in normal version Pitch 3.67mm for belt width 300 mm Band thickness range 4.0 to 5.0 mm required minimum drum diameter 75 mm Box contents: 12 strips
A5-300W	ANKER conveyor belt connector A5-300W Type A5-300W with welded cross wire from round material in normal version Pitch 3.67mm for belt width 300 mm Band thickness range 6.5 to 8.0 mm required minimum drum diameter 125 mm Box contents: 12 strips
G001-G-300W	ANKER conveyor belt connector Type G001-G-300W made of strip steel 0.75 mm Galvanized version pitch 4.00 mm for belt width 300 mm Band thickness range 1.5 to 2.0 mm required minimum drum diameter 25 mm Contents of the carton: 12 strips including coupling rods
A40-S-300	
1-1/2C BAND FITTING	
1-1/2C BAND FASTENER NUT	
Alligator (2"-4")	Mechanical Fastener
Everdur	
R5-SE 63/1600	
RUBBER BAND NAIL 9-11MM-	
AC-1600 JOINT BAR	
375XSJ1200NCS	

RS62J40/1000NC	
NCS-1000-1	
R5S-SE-40/1000	
R5S-SE-32/800	
NCS-800-1	
20377	Extra nuts for connector number 1, 140, 190, RP1, 375X, 550
CEM-FR1510	
RS62SJ40/1000NCS	
HW3	NUTRIKER 2 1/2" (HW-3)
NUT BREAKER 2" (HW-2)	
TAPE DRILL TIP 2 1/2 " (HP-3)	
TAPE DRILLING TIP 2" (HP-2)	
FLEXCO R5-SE-55/1400	
FLEXCO SRC	250 pieces per box
CEM-FR1510	
R5-1/2 SE SRC C-D MECHANICAL RIVET NAIL	
R5-1/2 SE 55/1000 HINGE	
R5-1/2 SE 55/1200 HINGE	
R5-1/2 SE 55/1400 HINGE	
AC6-1200 -1 SPIRAL ARMORED STEEL ROPE Q10MM	
PLASTIC FILLER HOSE(8MM)	
SRC / 40529	
R5-SE 55/1400	1414 (15 Pakete)
Alligator connector RS125J47/1200NC	
Edp1*750	
140e Zolltarifnummer 84313900 Ursprung Us 1 P. = 25 Pcs.	
R5-Se-32/800	
112	

Ncs1-X	
R5-Se-48/1200	
Ac -500 -1	
Alligator V-Belt, Size 1182x8	
R2j-32/800anc	
2-1/2	
Rs187sj32/800ss	
47.25quot; Wide Black 3 Ply 330 3/16 X 1/16 Std	
P2p	
76875 - Drxm-42-535	
Rs187j24/600nc	
Ss1-32/800 Not Available,Alternative Ss1-900	
2-g-300w	
76965 - Ib4-1u	
Ss1-900	
Rstk4-12	
74692	
Rivet Nail Srf (We Need Part Number)	
Hb2	
Rs187j48sp	
W. 1.4401 / 1.4404 (Antimagnetisch)	
Band Supplement For R5-Se 26/650	
No. 550	
3-G-300w	
Nc187-X	
Src/D	Flexco nieten staal, 250 stuks
Crb-450	
Rs125j40/1000nc	
001437	
Rsc187-24	

R5-Se-55/1400	
Ezp1, 2000mm Gurtbreite - Not Available In Such Lenght	
Ss 204	
1-1/2e	
Rsc187-12	
R5-1/2-Se - 55-/1400	Flexco Rivet Hinged 1400mm staal
R6-Se-72/1800	
Lw95	
Hw1	
Rs187sj32/800ncs	
375XSJ1000NCS	
R6-Se-40/1000	
2vt460-600f	TRANSFORMER PRI 600V RATIO 5:1
Rsc187-6	
Lp-601-30/40/G-2 (03997)	
Rs187j32/800nc	
R6-Se-55/1400	
Fl11c (Roll X30 Meters)	
Alligator Steel Æ2	
Fsk Belt Skiver	
Medium For Belt Widths From 36? ? 60? (900 ? 1500 Mm)	
Fsk-1	
125-Ret-50	
R2j-20/500anc	
001443	
R5j-Se-32/800nc	
Acs6-1800-1	as an alternative to NCS-1800-1, as this is not stated in the supplier's European price list)
S1s	

Rs62sj12/300ss (Pack 1x4)	
Pt Max Belt Aligner For Belt L1000	
Rs125sj32/800ss	
Hw2	
Ezp1 230 - Unknown Product	
Kyh - 1900	
Rj187sj36	
5958315	
Pt Max Belt Aligner For Belt L800	
375XSJ650NCS	
Srg	
77549 - Shim-Kitm	
Nc-C	
HnCS 1,50	
40529	FLEXCO Rivets SRC mild steel Strap thickness range 9 to 11 mm suitable for connector types R5, R5½ Carton content: 250 pieces
R5-1/2-Se-48/1200	
Hsg 0 Sf/230v 50hz	
375xj1200nc-Sn	
Sre	
Rivet R2	
Srb	
Bandbreite Von 1200 - 1800 Mm	
Rs187sj40/100ncs	
Hp2	
Rs125sj32/800ncs	
R5-Se 26/650	
Mmp-684	
Rs125	
B1b	

76874 - Drxm 36 535	
845860ld , By 900960	
375xj650nc-Sn	
375XSJ800NCS	
Ac6-1400-1	Draad 9,60mm, staal, 1400mm
Ezp1, 2400mm Gurtbreite - Not Available In Such Lenght	
Rs125sj36/900ss	
Lg-2-C Hohe 51 100 Pcs	
4-G-300w	
R5-Se-40/1000	
Rtbs	
41720	
Z10180	
550j30ssc	
375xj650 Nc-Sn	
R5-1/2-Se-40/1000	
Lg1-1/2-C Hohe 38 100 Pcs	
Ezp1 218 - Unknown Product	
30894	Orange vulslang 30 mtr. 375 + 550
Ac6-1000-1	
R6-Se-32/800	
04305 Laser Belt Square	
Msrt-48e	
SRC (box 250 pieces)	
R2j-40/1000anc	
St5-5 Alligator / Flexco Zolltarifnummer 84798997 / Ursprung Us Nettogewicht : Ca. 0,02 Kg	
Rs187sj36900ss	
Hb1	
190e - 1 Box = 25 Pcs	

S2s
Alligator Rs187s
30003
R2j-26/650anc
Rs187sj24/600ncs
Ncs187-C
Ss 207
Rsc187
375xj1000nc-Sn
Msp-2000-200
Far - Pul Hd
900960
Crb46
69 7598
Mhs-24v
Ncs065-C Not Available, Hncs 1,50
R8-Se-48/1200
St5-5
190c (Bucket 1x100 Pcs)
2e
1-1/2e (Pack 1x25)
Bolt Solid Plate 3 (Pack X10)
001466
Hw3
Rs125j48nc
Srb-2m
R6-Se-48/1200
R5s Se 55/1400
Flex-Lifter M
C1c
6-G-300w

550sj1200ssc
190c (Pack X100)
140vp
5-G-300w
75612
1e
Ux1-Llss Not Available, W. 1.4401 / 1.4404 (Antimagnetisch)
Flsc-I-Bulk
RI 601 600mm
RS-Se-40/1.000
820/840-1cb
Crb34
30011
Rs187j47/1200nc
Rs62j32/800nc
76966 - Ib5-1u
R5j-Se-40/1000nc
Sra
Pt Max Belt Aligner For Belt L1200
Src
Nc-1000-1
Ac6-1200-1