

Flowrox

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Flowrox Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Flowrox Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
FR87503227	PVE100AKLVC10-333LF, SBRT Hose pinch valve in DN100 - Closed valve housing - Nominal size: DN100 - Installation length: 250 mm - Single-acting pneumatic drive with mechanical spring (fail close), min. supply air 6 bar, with electro-pneumatic positioner Siemens Sipart PS2 6DR5510-0NG00-0AA1, the Standard input signal is between 4 and 20 mA and an increasing signal value leads to Closing the valve - Flange holes: DIN PN 16 - Max. Working pressure: 10 bar - Material valve housing: aluminum epoxy coated - L = with opening tabs - Sleeve material: SBRT (styrene butadiene) - Max. Operating temperature: 110 ° C - F = filter regulator with pressure gauge - Customs tariff number: 84818099 - Country of origin: Finland - Weight per valve: approx. 110kg
FR87502817	SKW100M10-30S0-NR Intermediate flange knife gate valve in DN100 - Knife slide plate material: AISI 316 - Nominal size: DN100 - Housing material: gray cast iron / steel welded with epoxy coating - handwheel (open / close) - Max. Operating pressure: 10bar - Flange holes: DIN PN 16 - Installation length: 57mm - Max. Operating temperature: 75 ° C - Ring cuff: NO - Flush connections - Customs tariff number: 84818061 - Country of origin: Finland - Weight per knife

	pusher: approx. 30kg
FR87503228	SKW150AU2010-30S0-NR Intermediate flange knife gate valve in DN150 Material knife slide plate: AISI 316 - Nominal size: DN150 - Housing material: gray cast iron / steel welded with epoxy coating - Double-acting pneumatic drive with pneumatic spring (fail-open) and separate Air tank, min. 6 bar - Max. Operating pressure: 10bar - Flange holes: DIN PN 16 - Installation length: 64mm - Max. Operating temperature: 75 ° C - Ring cuff: NO - Flush connections - Customs tariff number: 84818061 - Country of origin: Finland - Weight per knife pusher: approx. 49kg
PVE40M10-631L	DN40 PN10 PVE
ROTOR ASSEMBLY PERISTALTIC PUMP-LPP-T65	TROYA PROSES-FR-Q350358
HOSE GUIDE LPP-T65 LPP-T65	TROYA PROSES-FRQ350750
ROTOR BEARING KIT PREST PUMP-KIT LPP-T65	TROYA PROSES-FR-80625
GEAR COUPLING PERISTALTIC PUMP	GEAR COUPLING LPP-T65-TRYPROS-FR-Q350358
FR87500139	SBRT10250/625/3L2 Replacement cuff SBRT for Hose pinch valve DN250 - Cuff Material: SBRT (Styrene Butadiene) - Pressure class: 10 bar - Inner diameter: 250mm - Cuff Length: 625mm - L = With opening tabs - Flange bores: DIN PN 10 - Max. working temperature: 110°C
FR87500139	SBRT10250/625/3L2 Replacement cuff SBRT for Hose pinch valve DN250 - Cuff material: SBRT (Styrene Butadiene) - Pressure class: 10 bar - Inner diameter: 250mm - Cuff length: 625 mm - L = With opening tabs - Flange holes: DIN PN 10 - Max. operating temperature: 110°C
LPP-T65GM10-2-0-N-D	
FXP65GM10-2-0-N-D,NR	
Fr87502439	PVE100A10-233LS, SBRT Pinch valve in DN100 - Nominal diameter: DN100 - Installation length: 250 mm - Double-acting pneumatic drive, min. Supply air 6 bar (open-close) - Flange bores: DIN PN10 - Max. Working pressure: 10 bar - Material valve body: aluminum epoxy coated - L = with opening tabs - Cuff material: SBRT (styrene butadiene) - Max. Operating temperature: 110 ° C - S = Magnetic proximity sensors