



Gems Sensor

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Gems Sensor Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Gems Sensor Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
6700-B-G-C16-A0-M-3-030-B	Pressure transducer 6700 B 4 - 20mA G Gauge C16 0-160 bar A0 G1 / 4 "external M IP68 Immersible cable 3 CE 030 30 meters cable B 0.15% / 0.5%
Typ: 3100-B-0010g-05-B-000	Pressure transducer B 4 - 20mA 0010G 0 - 10barG 05 G1 / 4 External Soft Seal B Industrial DIN 9.4mm 0 No Restrictor 00 No Cable Customs tariff number: 9026 2020 GB 0.208kg
3300b01b0a01b00v	
Typ: 3100-B-0016g-05-B-000	Pressure transducer B 4 - 20mA 0016G 0-16 barG 05 G 1/4 External Soft Seal B Industrial DIN 9.4mm (mating connector not supplied) 0 No Restrictor 00 No Cable Customs tariff number: 9026 2020 Country of origin: GB
FS925	flow switch
2600BGA1019M3GA005	Measuring range: 0-10mWG Pressure transducer
Rotor Flow	
2200AGG5008A2UA	
W977953	LS-800-4-SS-BN-SPDT-020-GR4-3 Level Switch
1200HGG3002A3UA	
3500-B-0001G-05-B-000	Pressure transducer Serie 3500 B 4...20 mA 0001G 1barG 05 G1/4 External Soft Seal B Industrial DIN 9.4mm 000 No Cable
6700-B-G-C16-A0-M-3-030-B	Pressure transducer 6700 B 4 - 20mA G Gauge C16 0-160 bar A0 G1 / 4 "external dış uzunluğu 11,40mm olmalıdır M IP68 Immersible cable 3 CE 030 30 meters cable B 0.15% / 0.5%
Seri: F119799	

B2010-LC02-LB-24VDC	Orifice 3/64 (Body) MOPD: 900 psi Cv 0.045 (Body) Body port configuration: 1/4-18 NPT female thread (in-line porting only) Voltage: 24V DC
B2012-LC02-LB-24VDC	Orifice 5/64 (body) MOPD: 270 psi Cv 0.105 (body) Body port configuration: 1 / 4-18 NPT female thread (in-line porting only) Voltage: 24V DC Minimum order quantity: 50 pieces
BG2007-01-LB-V-G1-204	
BG2005-01-LB-V-G1-204	
Art.-Nr.: 156268	RotorFlow RFS 2500 flow monitor Working range: 15.0 ... 75.0 l / min Connection thread: 1/2 "NPT Input: 24 VDC Housing: brass
LS-7 Type	Float switch Stainless / Stainless (Ext mount, 1/2 "NPT) Leads Item no .: 164870 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.495 kg
PS71	
CAP-300	Capacitive Level Sensor 1/4 "-18NPTM INTEGRAL 3- PIN GERMAN WET SINK Item no .: 240640
227202	ELS-1150XP Optic 1/2" NPT 5-28VDC FM Dry Sink NO Nickel Plated Steel
RFO-2500	Flow monitor RFO-2500 Brass 1/4" NPT (0.4 - 4) 2 - 20 L/min Item No.: 156261 Customs tariff number: 9026 1021 Country of origin: US Net position weight: 0.500 kg
3300B02B5G01E000	
06062	
DATE KOD:601	AGFA CORPORATION 094085-0109 REV B
PN 229206	
Model: LS-1700	Part No: 016-0026 Supply Voltage: 250 V AC-DC Current: 0.5 A, 50 VA
PN 2934 FS-3 Flow Switch	
LS-270	float switch 50VA, N.C. Type: LS-270 Item No.: 43982
VALVE,SOLENOID:3050,24VDC,1W,053/17,50PSI	
VALVE,SOLENOID:3050,24VDC,1W,358/16,50PSI	
Flow switch Gems Sensors FS-100E-A	
0-30 BAR 3100 GEMS(MET.8)	
GH3312-S20	

flow switch	45518 Brass, Lead Wires, 1/4" NPT female connection SPST, N.O. , 0.25GPM Type: FS-927 Item no: 70821
3101H150PG01E000	SUPPLY : 8 - 30 V.DC. CONNECTION: G 1/4 "" EXTERNAL RANGE: 0 - 150 PSIG OUTPUT:1 - 5 V. M12X1P(4-PIN) TEMP OUTPUT RANGE -40 °C to 125 °C
FS-927	flow switch Brass, Lead Wires, 1/4" NPT female connection SPST, N.O. , 0.25GPM Type: FS-927 Item no: 70821
10PG08E000	SERIAL XT41202TP-063-12-0210
3100T300PG0290000F 0-300PSI	
223060 REV C	
Art-Nr: 155421	Flow monitor type RFO-2500 Working range: 2-20 l / min Connection thread: 1/4 "NPT Input: 4.5-24 V DC Output: 4.5-24 V, pulse 25-225 Hz Art-Nr: 155421 Weight / St .: approx. 0.15 kg 1 pc 128,200 128,20 AL: N ECCN: Customs tariff number: 9026 1029 Country of origin: US Net position weight: 0.150 kg
Stu 009886 - 312 - 07 - 0030	
223060 Rev C	120 VAC HYPER THERM FLOW METER Please look at the attachment
020-3499	
Ls-1700 Tfe (174200)	float switch Material: PTFE Switch: SPST, 20 VA, N.C. Item No. : 174200 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.750 kg
Dm-133475	
Fs-6 0,4l/Min	
2200 B G B10 01 A 3 Ua	
3100b0016g05b00004	
Ls-800e-Pvc-K12-1-O-Dual	
Fs-550-E	
Ls-1700 Tfe (174100)	float switch Material: PTFE Switch: SPST, 20 VA, N.O. Item No .: 174100 Customs tariff number: 9026 1089 Country of origin: US Net position weight: 0.750 kg
020-3497	
Ls800e-Pvc-O-K12-Dual	
3100-B-0400s-02-B-0-000	
	Pressure transducer B - 4-20mA 0400S - 0-400 barS

3100-B-0400s-05-B-000	05 - G1 / 4 "Soft Seal B - Industrial Din 0 - No Restrictor 00 - No cable
Ls800e-No0101275	
Ls800e-Pvc-O-K12-1-Dual	
3300b06b0g18g000	
P/M-133475	
3300-B-300pg-02-9-0000f	
20va/T0241	
2200 B G A25 01 A 3 Ua	
Ls-2050-E	
Ls800e-O-Bcc-C-K6-2-0161610	
Wif-1250 / Water In Fuel Single Point Level Sensor	
145149	
020-3495	
Ls800e-O-Tm-N-S-4	
20va/T0242	
Xm800-3-Ss-Ss-3-50-1800-1.62g(Ex1.62dia)	
Ls800-2a-Br-Bn Spdt-20-Gr4-3	
Ls 1700	
Ls800-Pvc-Tpvc-K12-Gr1	
Gems Ls-400e-O-Tc-C-K6-3	DIP: 200 mm MONTAGEART: 33mm / G1 MINIMUM SIGNAL OUTPUT wird verwendet. KONTAKTZUFUHR: 220VDC ÖLTEMPERATUR: 0 ... 100°C KABELEINGANG: PG13,5 RACK Edelstahl
3100b0010g05g000	Please look at the attachment
Ps82	
20va/T0240	
Fs-926e-0.05-M-X-S-Ge169	
Fls3	