

Gessmann



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Gessmann Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Gessmann Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Kea/75	Double switching element V6 KEA75 Customs tariff number: 85365080
Dp120- 47lt Mi/ 103832 Potansimeter	DP120-47LT Mİ/103832 OHM:10K
Potentiometer Nonlinear 2x1,4 Kohm	1511Z07-054.009(T178C NR:2 2X3623 OHM)
Master Switch Yayı Kmfd/52	
Master Switch Bellow V64 Type For Gessmann Master	SICK
Cam Disk (Position Adjustment Disc) -	CAM DRIVE FOR GESSMAN BRAND "V64" MASTER CONTROLLER, GESSMAN
Without Holder Arm Joint And Impeller Section	GESSMAN BRAND "V64" MASTER CONTROLLER WITH HANDLE INSERT AND IMPELLER SECTION, GESSMAN
Plate And Impeller (Excluding	GESSMAN BRAND "V64" PLATE AND IMPELLER FOR MASTER

Potentiometer)	CONTROLLER, GESSMANN
Contact Part	GESSMAN BRAND "V64" CAN CONTACT "01" FOR MASTER CONTROLLER., GESSMAN KEA / 75
Gessman Brand	4A.380VAC.; 4 CONTACT OR SIEMENS P/NO:3SJ3020-5ZA11-ZD01-JOY DIRECTION 1-2 SPRING RETURN 1-0-1, GESSMANN V61L-02Z-A99(W1101518-020)
Joystick Bellow Kmd 66 Gessmann	
UGE1	wir brauchen das Teil auf dem Foto leider ist das typenschild nicht mehr lesbar
4110029286	Return spring V6 Execution 3 KMFD / 123 Customs tariff: 73202085 weak Please note the minimum order value
5209900023	Bellows black KMD 66 Customs tariff no .: 40169997 for compound drive V6 Weight approx. 100 grams
JOYSTICK (V64)	
VV64LB1-01ZC	
VV64RB1-01ZC	
KMD 66	Bellows black KMD 66 Customs tariff number: 40169997 for compound drive V6 Weight approx. 100 grams
V62L-02Z + 02Z-A060	Link drive V62 on the left 5300000306 V62L-02Z + 02Z-A060 Switching direction 1-2 return spring 2-0-2 4 contacts 2A 250VAC15 processing MS 22-0 Switching direction 3-4 return spring 2-0-2 4 contacts 2A 250VAC15 processing MS 22-0 Arrangement 02
V61LH-02Z-A060	Link drive V61 left Signal button Switching direction 1-2 4 contacts Contact program MS22-0 Detent 2-0-2 , Return spring
T1420	5240044004 Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm T 1420 Customs tariff number: 85333100 Connection diagram: 10202755 Linear with center tap Service life 10 ^ 6 switching cycles 2 watt max.wiper current 10 mA with connection board EP / 290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
V6	Potentiometer mounting option Customs tariff number: 85389099 Axis 6mm adjustment angle 2x 150 ° KNK / 05
B1 (M10)	Ball grip B1 (M10) KBAD / 22 Customs tariff number: 85371098 without internals KBAD / 22 M10 fastening element Type B1
5300002483	Compound drive V64.1 Left V64.1LB5T-06ZP-A99P444 Customs tariff number: 85371098 Ball handle B5 Push button on top Switching direction 1-2 return spring 6-0-6 12 contacts 2A 250VAC15 processing 881223V Potentiometer T1420 2x5 Kohm open IP 00 dimensions 1/100/101

T 1420	Wire potentiometer 2x10.0kOhm T1420 2 x 10.0 kOhm T 1420 Customs tariff number: 85333100 Connection diagram: EP / 290-40 Linear with center tap Service life 10 ^ 6 switching cycles 2 watt max.wiper current 10 mA with connection board EP / 290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
V11L-01ZP+01ZP-A05P444	Link drive V11 left KHN/100 Customs tariff number: 85371098 Switching direction 1-2 return spring 2 contacts 2A 250VAC15 settlement MSP 21 1 potentiometer T 1420 2x5 kOhm 1.5 W Switching direction 3-4 return spring 2 contacts 2A 250VAC15 settlement MSP 21 1 potentiometer T 1420 2x5 kOhm 1.5 W open IP 00 dimensions 1/110/111
V64 Einzelkontakt-Joystick	wird zum erstenmal eingekauft vom kunden V64LT-01ZP+01ZP
V62L-01ZP+01ZP	joystick,0-10V
10300008	bellows Version A black Neoprene 55 +/-5 Shore KMD 66
5300006282	Spur gear drive S2 left S2LS5-03Z-A05A050 Shift rod shortened -20mm Switching direction 1-2 return spring 1-0-1 5 contacts 2A 250VAC15 settlement 2xMS21 + MS 0 Offen IP 00 *835213
V64L-02ZP+02ZP-A050P444	Compound drive V64 left 5100400099 Customs tariff number: 85371098 Switching direction 1-2, return spring, 1-0-1 4 contacts 2A 250VAC 15, settlement MSP 21-0 1 potentiometer T1420, 2x5 kOhm, 1.5 watts Shift direction 3-4, return spring, 1-0-1 4 contacts 2A 250VAC 15, settlement MSP 21-0 1 potentiometer T1420, 2x5 kOhm, 1.5 watts open IP 00,
OEC 2-4-1	OEC 2-4-1-B-W1 T359 Customs tariff number: 85389099 Connection plan: EO/60-25 OEC 2-4-1-B-W1_EO/34-10 as from 0803652/30
5200000120 S2	spur gear drive S2LM-02RP-A050P443 KHS/2431 Customs tariff number: 85371098 Connection plan: EP/290-32 mechanical zero position lock Switching direction 1-2 Friction brake adjustable 3 contacts 2A 250VAC15 settlement MSP 21-0 1 potentiometer T 1420 2x2 kOhm 1 label with directional arrows open IP 00 just like 0508096
V8B3-2DK-3ZP	joystick (2 axes 4-way)
5132300046	VV85LDV-2ZS+2ZS-B-A98EPB11 KHL/2915 Connection plan: EB/85-227 Push button according to KBAD/593 (wired to Profibus) Switching direction 1-2 return spring 1-0-1 2 contacts 1.5A 24VDC13 settlement MSP-0 (wired separately) HALL sensor (analogue values + direction signals on Profibus) Switching direction 3-4 return spring 1-0-1 2 contacts 1.5A 24VDC13 settlement MSP-0 (wired separately) HALL sensor (analogue values + direction signals on Profibus) wired to Profibus EB/85-227, address 12
	Additional costs Hall sensors for

MKH2	V25/V85/V27/V28/V26/D85/V22
W1410375-010	Compound drive V85 left V85LPD-2ZS+2ZS-B-A01E452 Customs tariff number: 85371098 cross backdrop Shift rod with push button Switching direction 1-2, return spring 2 contacts 1.5A 24VDC 13, settlement MSP01 Hall sensor Switching direction 3-4, return spring 2 contacts 1.5A 24VDC 13, settlement MSP01 Hall sensor Matching electronics E452 Electronics for 2 axes EP/318-63 Voltage output +/-10V Input voltage 18-30VDC 16 pin insert CPC with wiring 500mm long Cover hood IP54, dimensions 1/132/133
W1101388-020	Link drive V11 left V11DPX-02Z+02Z-A050-0712658/20 Customs tariff number: 85371098 push button Special Scene "Slit" (SR3-4 locked) Switching direction 1-2 return spring 1- 0-1 4 contacts 2A 250VAC15 settlement MS 21-0 Switching direction 3-4 return spring 1-0-1 4 contacts 2A 250VAC15 settlement MS 21-0 open IP 00 dimensions 1/110/111 Form V11DPX-02Z+02Z-A050-0712658/20
W1019621-020	Link drive V11.1 left V11.1L-02Z-2xA05 Switching direction 1- 2 return spring 1-0-1 4 contacts 2A 250VAC15 settlement 2 x MS21 open IP 00 dimensions 1/110/111 Form V11.1L-02Z- 2xA05
5240044005	Wire potentiometer 2x10.0kOhm T1420 2x10.0kOhm T1420 Connection diagram: EP/290-40 Linear with center tap Service life 10 ⁶ switching cycles 2 watts max. grinder current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
V11LPD-01ZP+01ZP-A05P324	Link drive V11 left KHN/111 Customs tariff number: 85371098 with cross backdrop Ball grip and push button Switching direction 1-2, return spring 1-0-1 2 contacts 6A 250VAC11, settlement MSP 21 1 potentiometer 2x5 KOhm T 365 0.1W <1mA Switching direction 3-4, return spring 1-0-1 2 contacts 6A 250VAC11, settlement MSP 21 1 potentiometer 2x5 KOhm T 365 0.1W <1mA open IP 00 dimensions 1/111
V11LPD-01ZP+01ZP-A05P324 KHN/111	Link drive V11 left with cross backdrop Ball grip and push button Switching direction 1-2, return spring 1-0-1 2 contacts 6A 250VAC11, settlement MSP 21 1 potentiometer 2x5 KOhm T 365 0.1W <1mA Switching direction 3-4, return spring 1-0-1 2 contacts 6A 250VAC11, settlement MSP 21 1 potentiometer 2x5 KOhm T 365 0.1W <1mA open IP 00 dimensions 1/111 like 9807421 Customs tariff number: 85371098
5240044004	Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm T1420 Connection plan: EP/290-40 Linear with center tap Service life 10 ⁶ switching cycles 2 watt max. wiper current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8 identical to T130 1:1 interchangeable offer value
P5100300076	
	5300005300 Compound drive V11 right KHN/135 Customs tariff number: 85371098 Connection plan: - Palm grip B22 with attachment on the left 5 push button item 5 - yellow;

V11.1RB22-1-5D-02ZC-X-A0500C01	item 6 - black; Item 7- green; Item 8- red; Item 9 - blue Switching direction 1-2, return spring 4-0-4 4 contacts 2A 250VAC 15, settlement MSP21-00 1 OEC 2-1-1 with 12 meter cable and plug open IP 00, dimensions 1/110/111
V11LPB22AL-5D-02ZC+02Z-A0500C01	5300004906 Link drive V11 left KHN/134 Connection plan: - cross backdrop Palm grip B22-A 5 push buttons, item 5 red, 6 black, 7 yellow, 8 green, 9 blue Switching direction 1-2 return spring 4-0-4 4 contacts settlement MSP 21-00 with encoder OEC 2-1-1 8 bit gray code and 12 meter cable Switching direction 3-4 return spring 4-0-4 4 contacts settlement MSP 21-00 with encoder OEC 2-1-1 8 bit gray code and 12 meter cable
5300000145	Link drive VV85 right VV85RB24-6DWHA13IRD-2ZS+2ZS-B- EPB11-X KHL/1058 Customs tariff number: 85371098 Connection plan: EB/85-317 25/25 degrees Deflection angle 15° Palm grip B24 KBAH/ 62 Rocker button T-0-T in Pos 9 6 pushbuttons (ITW black) In positions 1,2,3,4,5,6 Rotary handle HA13 Color ring illuminated red Switching direction 5- 6 and 7-8 with return spring with Hall sensor system 2 contacts 2.5A 30VDC each direction MSP 21 Profibus address 43 16 external inputs / 16 external outputs 1x cable with 130 mm free length, 9 pin. DSUB for Profibus 1x cable with 210 mm free length, 37-pin D-Sub connector (I/Os) *same as 5130400018
5300000146	Multi axis controller VV85 left VV85LB24-6DWHA13IRD- 2ZS+2ZS-B-EPB11-X KHL/1061 Customs tariff number: 85371098 Connection plan: EB/85-317 deflection 20° Palm grip B24 KBAH/ 62 Rocker button T-0-T in Pos 9 6 pushbuttons (ITW black) In positions 1,2,3,4,5,6 Rotary handle HA13 Color ring illuminated red Switching direction 1- 2 and 3-4 with return spring with Hall sensor system 2 contacts 2.5A 30VDC each direction MSP 21-0 Profibus address 42 1x cable with 130 mm free length, 9 pin. DSUB for Profibus 1x cable with 200 mm free length, 37-pin D-Sub connector (I/Os) *same as 5130400019
Gessmann V64 Single Contact Joystick	
5240044004	Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm T1420 Customs tariff number: 85333100 Connection plan: EP/290- 40 Linear with center tap Service life 10 ⁶ switching cycles 2 watt max. wiper current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
VV64M-04Z+04Z-A110	Compound drive VV64
V3RPXD-03ZP+02Z-X-A99P054	Multi-axis controller V3 right Special backdrop "T rotated" Push button latching Switching direction 5-6 6 contacts S826 Contact program 812728 zero detent return spring Potentiometer T132 2x5k ohms Switching direction 0-8 4 contacts S826 Contact program 812728 zero detent return spring
	Spur gear drive S2 left W1107959-010 EP/14-1 with mechanical zero position locking Shift direction 1-2 friction

S2LM-02RP-X-A050P99-0207545	brake 1-0-1 3 contacts settlement MSP 21-0 P1 potentiometer 200 Ohm 20W T 135 R1 resistor 22 ohms 25W (3x68 ohms) 11W R2 resistor 39 ohms 5W R3 resistor 39 ohms 5W 1 terminal strip 4-pin wired EP/14-1 1 label
KMD66	bellows Version A black Neoprene 55 +/-5 Shore KMD 66
V10.1L-01ZP-A05P254	5140100015 Link drive V10.1 V10.1L-01ZP-A05P254 KHM/203 Customs tariff number: 85371098 Connection plan: EP/160-10 Left with handle Switching direction 1-2 return spring 1-0-1 2 contacts 2A 30VDC11 settlement MSP 21 1 potentiometer 2x5 KOhm T 320 0.8W <1mA wired to terminal strip according to EP/160-10 open IP 00 dimensions according to 1/141
V10.1L-01ZP-A05P254	Link drive V10.1 V10.1L-01ZP-A05P254 KHM/203 Customs tariff number: 85371098 Connection plan: EP/160-10 Left with handle Switching direction 1-2 return spring 1-0-1 2 contacts 2A 30VDC11 settlement MSP 21 1 potentiometer 2x5 KOhm T 320 0.8W <1mA wired to terminal strip according to EP/160-10 open IP 00 dimensions according to 1/141
V8B3-2DK-3ZP+3ZP-A050P184	5300003245 Compound drive V8 V8B3-2DK-3ZP+3ZP-A050P184 KHL/1540 Customs tariff number: 85371098 Palm grip B3 2 push buttons position 1+2 jack button Switching direction 1-2 return spring 3 contacts 1.5A 24VDC13 settlement MSP 21-0 Potentiometer T301 2x5 kOhm Switching direction 3-4 return spring 3 contacts 1.5A 24VDC13 settlement MSP 21-0 Potentiometer T301 2x5 kOhm open IP 00
5209900626	Double switching element V6 KEA/75 2A 250VAC 15 Weight per unit 30g **Successor of double switching element KEA/33!**
W1315985-010	Link drive V51 left V51LMN-4Z-A06 Customs tariff number: 85371098 Mechanical zero position lock by depressing Switching direction 1-2 return spring 2-0-2 4 contacts 2A 250V AC15, settlement MS 22 Open IP 00
V11L-01ZP+01ZP-A050P025	
Rheostat VO for shear 1&2 control -	- Serva hydration unit - N6/CR3821E
5209900618	Rosette with 4 screws for VV5 KGIC 185
5300020566	Double lever drive D64 D64S8QD/S8Q-04Z+04Z-A12 KHG/1940 Customs tariff number: 85371098 Shift rod on the left Shifter length +20mm T-handle + push button Shift rod on the right Shifter length +20mm T handle Axis 1 8 contacts Contact program MS214 4-0-4 detent return spring axis 2 8 contacts Contact program MS214 4-0-4 detent return spring
D64S8QD/S8Q-04AZ+04AZ-A12	Double lever drive D64 Shift rod on the left Shifter length +20mm T-handle + push button Shift rod on the right Shifter length +20mm T handle Axis 1 8 contacts, 4A 250VAC 15 Contact program MS214 4-0-4 detent return spring axis 2 8 contacts, 4A 250VAC 15 Contact program MS214 4-0-4 detent return spring

N6/CR3821E	
V62LT-02Z+02Z	
W1210618-020	Compound drive VV8 right VV8RB3-6DPA11SE-3ZP+3ZP-A050P174 KHL/1023 Customs tariff number: 85371098 Connection diagram: EP/130-542 Palm grip B3 6 pushbuttons (ITW) Pos.1 red, Pos.2 green, Pos.5 white, Pos.6 blue, Pos.7 yellow, Pos.8 black 1 potentiometer drive PA11 1 sensor button with evaluation electronics EY/42 (OR) Switching direction 5-6 return spring 1-0-1 3 contacts 1.5A 24VDC13 settlement MSP 21-0 Potentiometer T 239 2x5 kOhm Switching direction 7-8 return spring 1-0-1 3 contacts 1.5A 24VDC13 settlement MSP 21-0 Potentiometer T 239 2x5 kOhm Switching direction 11-12 return spring 2 contacts processing MSP 21 1 potentiometer T 375 2x5 kOhm (Imax=1mA) Circuit board with terminal strip open IP 00 dimensions 1/130/131
10300008	bellows Version A black Neoprene 55 +/-5 Shore KMD 66
5300002458	Compound drive V62 left V62LT-02ZP+02ZP-A05P444 Customs tariff number: 85371098 with deadman button Switching direction 1-2 return spring 1-0-1 4 contacts 2A 250VAC15 settlement MSP 21-0 1 potentiometer T 1420 2x5kOhm Switching direction 3-4 return spring 1-0-1 4 contacts 2A 250VAC15 settlement MSP 21-0 1 potentiometer T 1420 2x5kOhm open IP 00 1/100/101
3635.010.1267	V 64 POTANSİYOMETRELİ V64LT-01P+01ZP
6152000013	Portable control panel TS 2 TS2-SB1 KGID/147 with chest plate, shoulder strap, stand bracket ISO housing gray IP 65 dimensions 2/152/153 Form TS 2
KGID/147	6152000013 Portable control panel TS 2 TS2-SB1 KGID/147 with chest plate, shoulder strap, stand bracket ISO housing gray IP 65 dimensions 2/152/153 Form TS 2
T1420 2x5,0kOhm	T1420 Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm Connection plan: EP/290-40 Linear with center tap Service life 10 ⁶ switching cycles 2 watt max. wiper current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8 Successor to T130 1:1 interchangeable
V62LT-02Z+02Z/4-WAY 2 STAGE BUTTON	
V11.1RB22-1-5D-02ZC-X-A0500C01	Compound drive V11 right V11.1RB22-1-5D-02ZC-X-A0500C01 KHN/135 Customs tariff number: 85371098 Connection plan: - Palm grip B22 with attachment on the left 5 push button item 5 - yellow; item 6 - black; Item 7- green; Item 8- red; Item 9 - blue Switching direction 1-2, return spring 4-0-4 4 contacts 2A 250VAC 15, settlement MSP21-00 1 OEC 2-1-1 with 12 meter cable and plug open IP 00, dimensions 1/110/111
	Link drive V11 left V11LPB22AL-5D-02ZC+02Z-A0500C01

V11LPB22AL-5D-02ZC+02Z-A0500C01	KHN/134 cross backdrop Palm grip B22-A 5 push buttons, item 5 red, 6 black, 7 yellow, 8 green, 9 blue Switching direction 1-2 return spring 4-0-4 4 contacts settlement MSP 21-00 with encoder OEC 2-1-1 8 bit gray code and 12 meter cable Switching direction 3-4 return spring 4-0-4 4 contacts settlement MSP 21-00 with encoder OEC 2-1-1 8 bit gray code and 12 meter cable
W 1016409-010	Filter board EY/143 Connection plan: EY/142-10 for EY/142-10
5240044005	Wire potentiometer 2x10.0kOhm T1420 2x10.0k ohms T1420 Customs tariff number: 85333100 Linear with center tap Service life 10 ⁶ switching cycles 2 watt max. wiper current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
Controller	
V62L-01Z+01Z	
W 1103721-030	Compound drive V64 left V64L-05Z+05Z-0107231/1 Customs tariff number: 85371098 Switching direction 1-2 return spring 4-0-4 10 contacts 2A 250VAC15 Processing unprogrammed Switching direction 3-4 return spring 4-0-4 10 contacts 2A 250VAC15 Processing unprogrammed open IP 00 dimensions 1/150/151 Form V64L-05Z+05Z-0107231/1
S22LM-2ZP-A05P444EI05	Spur gear drive S22 left S22LM-2ZP-A05P444EI05 KHS/1924 Customs tariff number: 85371098 mechanical zero position lock lower grip ball half yellow Switching direction 1-2 return spring 1-0-1 2 contacts 2A 250 VAC15 settlement MSP 21 1 potentiometer T1420 2x5 kOhm Adaption electronics for 1 axis 4-12-20 mA ER/15-20 1 label open IP 00
OEC 2-4-1	OEC 2-4-1-B-W1 T359 Customs tariff number: 85389099 Connection diagram: EO/60-25 OEC 2-4-1-B-W1_EO/34-10
V62L-02ZP+02ZP-A050P444	Compound drive V62 on the left V62L-02ZP+02ZP-A050P444 Customs tariff number: 85371098 Switching direction 1-2, return spring 1-0-1 4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm Switching direction 3-4, return spring 1-0-1 4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm open IP 00
V61L-02ZP-A050P444	Compound drive V61 left V61L-02ZP-A050P444 Customs tariff number: 85371098 Switching direction 1-2 return spring 1-0-1 4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm
WITCH GEAR LİMİT SWITCH	Type:UGE1-50-4 , Ratios (n:1) :50:1,250 VAC,10 A, Contacts No:4
W 1015858-010	Gear limit switch GE1 GE1-50-4-U5-4x176° Customs tariff number: 85371098 Geared limit switch GE1 4 contacts 2A 250VAC15 Development 4x176° Gear ratio 50:1 Housing U17/13 IP 65 dimensions 3/200/201 Type UGE1-50-4-U5-4x176

V64.1 0,3-Z4.0.4 ms24	
5130900100	Bellows V8 KMD 214
5240044004	Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm T1420 Connection diagram: EP/290-40 Linear with center tap Service life 10 ⁶ switching cycles 2 watts max. grinder current 10 mA with connection board EP/290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8
5120100020	Compound drive V51 left V51LM-6R-X-A1301 Customs tariff number: 85371098 with mechanical zero position lock Shift direction 1-2 friction brake 4-0-4 6 contacts 24V processing MS 224-0-1 open IP 00 dimensions 1/120/121 Type V51LM- 6R-X-A1301
JOYSTICK (V51M-06R)	
10300008	Bellows Version A black Neoprene 55 +/-5 Shore KMD 66
P8R5-1Z-P-A03-P125-X	
5142200109	Compound drive V14 V14LB6KS8-04Z+02Z-A150+A060 KHOA/58 B6 with jack button Switching direction 1-2 return spring 6-0-6 8 contacts 2A 250VAC15 processing 26-0 (Mount 2 contacts in SR3 and 6 contacts in SR 4) Switching direction 3-4 return spring 2-0-2 4 contacts 2A 250VAC15 processing MS 22-0 (Mount 4 contacts in SR1) open IP 00
5142200108	Compound drive V14 V14LB6KS8-03Z+03Z-A110 KHOA/60 B6 with jack button Switching direction 1-2 return spring 4-0-4 6 contacts 2A 250VAC15 processing 24-0 Switching direction 3- 4 return spring 4-0-4 6 contacts 2A 250VAC15 processing MS 24-0 open IP 00
N6/CR3821E	Rheostat VO for Shear 1 & 2 Control - Serva Hydration Unit
HAGT444559P5	CONTROL SWITCH [YELLOW] WITH ROLLER
Compound drive VV64.1	VV64.1S5-00ZC-C041 Shift lever length -20mm Axis 1 / y-axis Return spring OEC 2-4-1 6 bit binary code Linear characteristic
Compound drive VV64	VV64S5-00ZC+00ZC-C041 Shift lever length -20mm Axis 1 / y-axis Return spring OEC 2-4-1 6 bit binary code Linear characteristic Axis 2 / x-axis Return spring OEC 2-4-1 6 bit binary code Linear characteristic
5300009186	Compound drive V62 on the left V62L-02ZP+02ZP-A050P444 Customs tariff number: 85371098 Switching direction 1-2, return spring 1-0-1 4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm Switching direction 3-4, return spring 1-0-1 4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm open IP 00
	Compound drive V61 left V61L-02ZP-A050P444 Customs tariff number: 85371098 Switching direction 1-2 return spring 1-0-1

5300008501	4 contacts 2A 250VAC 15, processing MSP21-0 1 potentiometer T1420, 2x5 kOhm
KAM SWITCH GEAR LİMİT SWITCH	Type:UGE1-50-4 , Ratios (n:1) :50:1,250 VAC,10 A, Contacts No:4
Compound drive VV64	VV64B1-01ZC+01ZC-A980C041 Ball grip B1 Axis 1 / y-axis 2 contacts Processing MSP 00 Zero detent Return spring Opto-electronic encoder OEC 2-4-1 6 bit binary code Linear characteristic Axis 2 / x-axis 2 contacts Processing MSP 00 Zero detent Return spring Opto-electronic encoder OEC 2-4-1 6 bit binary code Linear characteristic technically corresponds to positions 1+2
OEC 2-4-1	OEC 2-4-1-B-W1 T359 5241000061 EO/60-25
KBKQ 4444	W1114766-010 1008535/10
KEA/75	5209900626 Double switching element V6 KEA/75 **Successor to double switching element KEA/33!**
KMFD/123	5300016497 Return spring V6 Version 3 KMFD/123 weak Successor type to KMFD/52
KEA 75	
KMFD*52	
V64 D+-01Z 606 205 8 AXIS CONTROLLER 907913/3	8 directions 2 speed
5130200343	Compound drive V8 left BV8LB33DPA11-0ZP+0ZP-X KHL/3098 Customs tariff number: 85371098 Connection diagram: EB/85-1030 Ball handle B3, 3 pushbuttons Pos.1 red, Pos.2 green, Pos.3 black Potentiometer drive PA11 Switching direction 1-2 return spring 1 potentiometer T 426 2x5kOhm MSP21 0.5Watt Switching direction 3-4 return spring 1 potentiometer T426 2x5kOhm MSP21 0.5Watt Switching direction 11-12 return spring 1 potentiometer T430 2x5kOhm MSP21 0.5Watt Profibus interface board EB/85-1030 for Profibus with DIP switches DP voltage input 18-30Volt DC 110mA Temperature -20°C + 60°C with DSUB9 plug, no filter socket! IP 65 dimensions 1/130/131/286/287 Form BV8B3DDPA11-0ZP+0ZP+0ZP-X-0114473/01 0906506/10
W1014134-020	Compound drive V64 on the left V64LT-01Z+01Z Deadman button Switching direction 1-2 return spring 2-0-2 2 contacts 2A 250VAC15 without processing Switching direction 3-4 return spring 2-0-2 2 contacts 2A 250VAC15 without processing open IP 00 dimensions 1/100/101 Form V64LT-01Z+01Z 1014134/20
V64L-02Z +02Z (JOYSTICK)	5985.010.1935
V62L-01ZP+01ZP	
VV61L 01 ZP-A050P024	
5130900100	Bellows V8 KMD 214

PW1103721-030 S1306798/010-0012	V64LT-02ZP+02ZP-A050P025 250V,9 AMPER
W1015858-010	Gear limit switch GE1 GE1-50-4-U5-4x176° Customs tariff number: 85371098 Geared limit switch GE1 4 contacts 2A 250VAC15 Development 4x176° Gear ratio 50:1 Housing U17/13 IP 65 dimensions 3/200/201 Type UGE1-50-4-U5-4x176°
5100900058	Compound drive V64 on the left (4-0-4 / 4-0-4) V64LT-00+00 KHG/1806
W1021421-010	Compound drive V8 right V8B3-3D2WKPA11PA13-0ZP+0ZP-B KHL/2177 Customs tariff number: 85371098 Connection diagram: EP/130-599 Deflection +/- 20 degrees Ball grip B3 3 pushbuttons 80mA, color red, position 1,2,3 (1/286 Pos.2.3) 1 rocker switch T-0-T pos.7+8 according to KEM/92) 1 rocker switch T-0-T pos.4+6 1 pawl button return spring: strong 1 potentiometer drive PA11 (side shift) Return spring 1-0-1 Potentiometer 5 kOhm with trim potentiometer in A+E Input 5 volts, output 0.5-2.5-4.5 volts 1 potentiometer drive PA13 Return spring 1-0-1 1 potentiometer 5 kOhm, with trimming potentiometer in A+E Input 5 volts, output 0.5-2.5-4.5 volts Switching direction 5-6, return spring 1-0-1 (1xKMFA 141 / 1xKMFA 142) 1 potentiometer T397, 5kOhm with trim potentiometer in A+E Input 5 volts, output 0.5-2.5-4.5 volts Switching direction 7-8, return spring 1-0-1 (1xKMFA 141 / 1xKMFA 142) 1 potentiometer T397, 5kOhm with trim potentiometers in A+E Input 5 volts, output 0.5-2.5-4.5 volts Cable outlet in the SR 6 Housing 100mm deep Cable tail 200mm long wired to DEUTSCH plug, 4x DTM (4-3P, 1x DT04-12P), EP/130-599 (Item number on nameplate)
5130200095	Compound drive V8 V8B2-3ZPP+3ZP-B-X-P99+P99A05 KHL/2242 Customs tariff number: 85371098 Connection diagram: EP/269-10 with adjustable ball handle B2 SH135 Switching angle +/-30, +/-20 degrees, Switching direction 1-2 return spring 1-0-1 1 potentiometer T553, 10kOhm with directional contacts 1 potentiometer T603, 2x5kOhm Switching direction 3-4 return spring 1-0-1 3 contacts 2A 30VDC processing MSP 21-1. Burgess GP 1 potentiometer 2 KOhm T 244 0.8W <1mA Switching direction 15-16 return spring 1-0 2 contacts 2A 30VDC processing MSP 11 2 potentiometers 5 KOhm T 301 0.8W <1mA with 2 series resistors 1.8 KOhm in A+E wired with 2*LiYY 16x0.5 sqmm 250mm long on 2* 15-pin AMP connector Mate N Lok with Pins according to connection diagram EP/269-10 2 screw connections PG 16 Housing IP 65 Successor type to Art.No. 4366051;Part No.10928-105
V62 02ZP + 02ZP	
	Compound drive V8 V8B35-6DK-3ZP+3ZP-B-X-A050P184E50112 KHL/5048 Customs tariff number: 85371098 Connection diagram: EB/85-853 25 degrees / 25 degrees Ball grip B35 6x push buttons ITW colored (4 at the top, 2 at the front) Pos.3 green, Pos.4 red, Pos.12+11 black Pos.1 blue (raised), Pos.2 yellow (raised) Black jack button with weak spring Switching direction 1-2, return spring weak, without detent 1x conductive plastic potentiometer T 301, 2x5 KOhm

5300022281	3x contacts 2.5A 24VDC, MSP 21-0 Switching direction 3-4 like 1-2 Profibus DP 2x zero contacts brought in separately, jack buttons brought out separately Resolution of the analog values 10 bits Profibus address: 18 Housing with DSUB9 connector max. 130mm installation depth Connector position in SR8 (90 degrees rotated clockwise) Supply voltage and zero contacts on connector strip DFK-MC 1.5/10-GF-3.81 2x LED visible on the bottom of the housing (voltage present, Profibus online) Housing IP54 (Like 5130200351 protocol compatible, but with ball handle B35)
V64 Knk 01	
Vv64 03z M P 03z M P	
10501002	
V61l -01zp-A050p024	
23405e	
S22lt-2zp-A05p02?	
V64l-00-00	GESSMANN MAISTER SALTER MECHANISCHER BLOCK
V61.1-03zp+03z	
V64.1d-02zp	
Uge1 407 Xp	
Joystic Balg, Code: Kmd 66-V6	
V62l-03zp+03z	
Comb 50	COMB 50 ? Indefinite?
V3lt-01zp+02zp-A06p025	
Uge2-20-6	
2*4,529	
V61-04z	
Bvv8z3z3	
V61.1r-03z-A110	
5240002004 By 5240044004 T1420	
V61 Q59 6 A,	
V3t 1007 Is Not Produced The Alternative Is V3lt-02zp-A06p025	
V64 B3	
V11lpt02za080	

V64d-02zp+02zp	
V64l-06zp+06zp	Pot Code:T130c Nr.5 (2x10 Kohm)
V6/V66 Joystick	D-74211
V3lt-02zp-A06p025	
V62l-02z+02z-A060a050	
V64 Joystick-Einheit	
Uge1 25 4	
0715165/20-1	
V62lpd-03z+03z-A110	
V62lt-03+03-A99	
Vv61	
20400448	
5209900033	
T129cnr510.326 K Ohm	
W1213679-010 (Ex.010 5432)	
20400374	
5100300129 V62l-02z+02z-A07-B-S/Pv/W/X-0512358/20	
N6 03p	
3aa 972 714 A	
1k8.972.718	
Ge2-20-6-U-X Code:0502464	
Oec4-2-1-2	
Uge1-50-4	GEAR LIMIT SWITCH Type:UGE1-50-4 Ratios (n:1) :50:1,250 VAC,10 A Contacts No:4
V11l -01zp+ 01zp-A050p024	
5132200106	
V3lpt-02zp+02zp-A050p024	
V61r-04z-A140	
S22015397	
V62l 01zp 01zp A050p023	
P7-2-Z-P-X-A01p01	

V3I-02z+02z 4a 250v Ms229a08	
Kmd 66	5209900023 KMD 66 bellow Customs Tariff No .: 40169997 KMD 66 for compound drive V6x Weight about 100 grams
3sj3	
S22-250v-Ac-Dc	
Vv64b1-01zc + 01zc-A980c041	Composite drive VV64 VV64B1-01ZC + 01ZC-A980C041 Composite drive VV64 Bale handle B1 Axis 1: switching direction 1-2 2 contacts 2A 250VAC15 Settlement MSP 00 Switching sequence 1-0-1 return spring Opto-electronic coder T359 OEC 2-4-1 Output: 6-bit binary code, characteristic linear Supply voltage 18-30VDC Axis 2: switching direction 3- 4 2 contacts 2A 250VAC15 Settlement MSP 00 Switching sequence 1-0-1 return spring Opto-electronic coder T359 OEC 2-4-1 Output: 6-bit binary code, characteristic linear Supply voltage 18-30VDC
1hdh112000p0004	
V62lt-02zp+02zp-A99p074	
Aomani00e006 0902	
Ge1-20-8-U5	
5209900014	
3sx4144	
V3r-03z+04z 4a 250v Ms23a09 , Ms224a15	
Vv61z+msp2100+t368	
V5	
060 5987	
V62rt-03+03-X-A99	
20400376	
1k8.972.718.B	
Zusgs22000	JOYSTICK
Multi-Axis Controller V31 Right	W1217338-040 V31R-03Z-B-A110 Customs Tariff No .: 85371098 Switching direction 5-6 Return spring 4-0-4 6 contacts 4A 350VAC15 winding MS 24-0 Housing B 230 IP 54 Dimensions 1/150/151
Kea / 75	5209900626 KEA / 75 Double switching element V6 Customs Code No .: 85365080 2A 250VAC 15 KEA / 75 Weight per unit 30g * Double switching element KEA / 33 is no longer available!

5130200095	
Vv64lb1 03z 03z A110	
Bvv8b3wkp112zp2	
5144200004 Verbundantrieb V20 V20l-0zp+0zp-X-C71	
V62l-04z+04z-A140	
5240044004	Wire potentiometer 2x5.0kOhm T1420 2x5.0kOhm T 1420 Customs tariff number: 85333100 Connection diagram: EP / 290-40 Linear with center tap Service life 10 ^ 6 switching cycles 2 watt max.wiper current 10 mA with connection board EP / 290 and mating connector for attachment to: V 6 / D 64 / V 5 / V 3 / S 2 / S 6 / N 6 / P 7 / P 8 ***** Successor to T130 1: 1 interchangeable
Vv64ls5-01zp+01zp-A05p025	MASATER SENSOR SWITCH CONTROLLER
903435	
Oec 2-2-1	
V44-Nr-5713-001 Wnr. 875-974 A/20 - 16 Amp, 500 Dc-Ac - (By Vv64l-00+00)	
Bale Handle B1	Bale handle B1 ? Which thread?
V5lp-5+4-X-A99	
V10 1lb5w 03zp X P994 Ep 198 16	
V64 F.No. 101 1126/20 -01	
3sj3 Siviã199;Leri	
Oec 2-3-1-2	ENCODER 24V
V31lh-02z-B-Ps-A07	
V5rpx-2z+3z-A05a06	
5209900075 / Kmd 20	
(5209900148) Kmfd/03	
Return Spring Kmfd / 52	Return spring KMFD / 52 Which strength? For which F.No.?
V11.1l -01zp-A050p024	
Ge1-66-8-U5	
Oec2-2-1	
S22t-2zp-X	
V62rb3dk-03z+01z-A11a05	
061 3864-01	

A0mani00e006
Gs-5209900148
S22lt-2zp-A05p02
10a 380v 2sec
V62-04z+03z 250v 7a W
5209900023
5100300051 (Ex.970 1760i)
Vv64.1
5100900083/Xa99
V5lt-2zp+2zp-X
1303387/010-002
0512358/20-01
3 Sj 3 033 5aa08
V64t-03z+01z-A11a05
20400331
5240002003
V62lt-02zp+02zp-A0500p024
1hc0018219p0001 Oem!!
V64
S22t-3zp
V5-L-S5-P-Dv-2-Z-P+1-R-P-I-X-A05-P024-+a98-P022
Oec 4 2 1 2
10a-380v 2secá;Á;Á;
Kfs11
2v3h
V64 Knk/01
V62 Q31 6 A
5120100020 V51
V62 T 081 4389/10-1 -Gt; Nicht Mehr Lieferbar

V62-03z+03z 250v 6a W	
V44-Nr-6510-001 Wnr. 889-598-/1/1- Wnr. 881272/8, 16 Amp, 250 Dc-Ac, Tipo:Nv 4-03 Nr 6510-102 - Obso	
Vvl64I-M	
Kbkq 4444	W1114766-010 KBKQ 4444 Scenery KBKQ 4444 Customs Tariff Code: 85389099 as for 1008535/10
S1lt-01zp-A05p374	
0508854/20	
N61	
5209900008	
V64I-Kompatibler Kontakt Produktcode: Kea 75	
5209900044	