

Goetze

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Goetze Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Goetze Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
06-892600-20	
618tGFO-20-f/f-20/20 - PTFE	Series 618 Gunmetal pressure relief valve overflow control valve (only with tGFO) not component tested Gas-tight version of the spring cap for gaseous and liquid media without ventilation Valve size DN20 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN20 - 3/4" Outlet size: DN20 - 3/4" Seal PTFE Pressure range from 0.20 bar to 0.80 bar
Pressure regulator Regulator DN50 PN25 - DI	Standart:EN 1988
DN50 10 BAR	
810sGK-15-m/-15/ - FKM	Series 810 Brass safety valve TÜV CE component tested free blowing cylindrical design not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: male thread BSP-P Inlet size: DN15 - 1/2" Gasket FKM Pressure 5 bar fixed. Component code 1 19-2055.11.D/G.0.8. 1000000000484
	Series 412 Stainless steel safety valve TÜV CE component

412sGK-15-m/-15/ - PTFE	tested free blowing cylindrical design not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: male thread BSP-P Inlet size: DN15 - 1/2" Seal PTFE Pressure 6 bar fixed. Component code 1 20-2003.14.D/G.0.76. 1000000376889
851bGK-15-f/f-15/25 - FKM	Series 851 Gunmetal safety valve in corner shape TÜV CE component tested with bellows for gaseous media with rotary lift Valve size DN15 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN15 - 1/2" Outlet size: DN25 - 1" Gasket FKM Pressure 10 bar fixed Component code 1 22-666.15.8.D/G-F/K/S.0.33. 1000000493882
851sGK-15-f/f-15/25 S4 PTFE	Gunmetal safety valve in corner shape Series 851 TÜV CE component tested not gas-tight version of the spring cap for gaseous media with rotary lift Valve size DN15 Entry: female thread BSP-P Outlet: BSP-P female thread Inlet size: DN15 - 1/2" Outlet size: DN25 - 1" Spring bonnet without relief hole Seal PTFE Pressure 2.2 bar fixed. Customs Tariff No. 84814090 Component code 1 22-666.15.8.D/G.0.33. 1000000614473
15 450870 00	
628sGFL-15-f/f-15/15 PTFE 7,5 bar	
617tGFO-25-f/f-25/25 FE PTFE	
482mGFO-SP-50-FL/FL-50/50 GOX FKM BAM	Stainless steel pressure reducing valve in passage form with elastomer membrane for gaseous and liquid media without ventilation Back pressure 1-8 bar Valve size DN50 Entry: DIN cast flange connection Outlet: DIN cast flange connection Nominal inlet width: DN50 - 2" Nominal outlet width: DN50 - 2" BAM (CTE) tested materials for gaseous oxygen free of oil and grease Seal FKM BAM Pressure range from 1 bar to 8 bar
851t	
Lwd Nb60 76.90 H-76	
852tgfl-50-FI/Fl-50/80 Epdm	
77000044	
1160483	
C1.990.288 ~ Sealed Safety Valve 417 Bs+	
618tgfo-40-F/F-40/40 Ptfе	
Goe Daaе012961	
813mgk-25-M/-25/ Nbr	
618tgfo-25-F/F-25/25 Ptfе Baureihe 618	
76.97 H23	
352tgi-50-FI/Fl-50/80 Ptfе	

Goe Top C95 Groove1
Goe Top C86 Groove2
76.90 7-89
810sgk-25-M/-25/ Fkm
652sgk-40-F/F-40/40 Nbr
851sgk-15-F/F-15/25-Ptfe-8bar
1160490
851tgf0-25-FI/FI-25/40 Epdm 10 Bar
104207, Drg No 412365c
810sgk-20-M/-20/ Fkm
14021970 Obsolete
1160643
76.90 H-81 Si60 Bg 1100059030
5035005200
76.53-1700k Nb6022 67-341038-99
1384679 Hn60plz 7690 H-89 11-000776-10
701 157 00
76.90 H-75a3 Hn60 Cf S
Nb 60 H05
76.21-3000 10-000043-10
1368535
76.90 Hel 127 A2 Hn60 Cf S
618tgfo-15-F/F-15/15 Ptfe Baureihe 618
76.90 H-75 Fp70
852tgfl-40-FI/FI-40/65 Epdm
76.90 H30 Nb60
7697h23nb60
76.90 H-01 Nb60
851sgk-20-F/F-20/32 Ptfe
851sgk-15-F/F-15/25 Ptfe

76.90-4201
618 Dn 15 G1/2 0-8
Nb 60 H08
77000117
76.90 Hel 127 A2 Hn60 Cf S (Ab 26 St.)
810sgk-15-M/-15/ Fkm
77000090
76.62-5000k Nb6022 67-341295-99 (Ex 60-341295-70)
Hn60plz 7690 H-89 11-000776-10