



Halstrup-Walcher

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Halstrup-Walcher Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Halstrup-Walcher Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
9423.0005	Positioning system PSE232-8-CAO-W-0 Gearbox type: PSE232-8 Output torque: 2 Nm Output speed: 40 rpm Measuring range: 0 Supply voltage: 24VDC Interface: CA Software: 2074C / V168 PCB: V7474 Address switch: 0 Output shaft: W
PSE232-8/So-CA-O-W-0 14924	9423.0007 Positioning system country of origin: Germany Features: Gearbox type: PSE232-8 Drawing: 7300.010933 Output torque: 2 Nm Output speed: 40 rpm Measuring range: 0 Supply voltage: 24VDC Interface: CA Software: 2074C / V168 PCB: V7474 Address switch: 0 Output shaft: W set to: Adr 120, 1 MBd Version: Orange RAL2010
9612.0595	Differential pressure transmitter P26 Measuring range: +/- 15 Pa Measurement uncertainty: ± 0.5% FS/FS Output signal: 4 - 20mA Operating voltage: 24V AC/DC Switching outputs: 0 Execution: hw Display: 0 Time constant: 15 s Interface: 0 Pressure connection: laboratory nozzle Language: German Test certificate: - Weight per unit: 0.9 kg Net weight: 1.8 kg Customs tariff number: 90262020 country of origin: Germany
9614.0068	Differential pressure transmitter P29 natural gas Measuring range: 0 - 1kPa Measurement uncertainty: ± 0.5% FS/FS Output signal: 4 - 20mA Supply voltage: 24 VDC +/-10% Execution: hw Display: 0 Time constant: 25 ms Pressure connection: laboratory nozzle Language: German Test certificate: - Optional to the offered devices we offer you the following: - Factory calibration certificate according to ISO9001, with 10 measuring points, item no. 9601.0002 Price at € 73.60 - Calibration certificate according to DKD-R 6-1 with 11 measuring points, item no.

9601.0003	
9002.	
9003.0114	
9003.0757	
9030.1916	
9031.	
9031.0045	
9031.0074	
9031.0175	
9031.0238	
9031.0287	
9071.1091	
9071.1237	
9071.3205	
9431.0119	
9431.0210	
9462.0058	
9505.0001	
9612.0010	
9612.0012	
9612.0014	
9612.0031	
9612.0050	
9612.0108	
9613.0311	
9614.0002	
9614.0002	
9615.0003	
AD1000	
PSE433C	
Delta-P	PU/PI 4-20 ma 220v ac 0-100 mbar
P26.0.230.0-10mB.S.000	
9612.0164	Differenzdruck-Messumformer P26-4-24ACDC-+/-50Pa-S-0-0-0-0 Measuring range: +/- 50 Pa Measurement accuracy: ± 0.5% FS/FS Output: 4-20mA Supply: 24V AC/DC Switch contacts: 0 Execution: hw Display: 0 Step response time: 25 ms Interface: 0 Pressure connections: laboratory nozzle Language: German Calibration certificate: -
	ISO9001, with 10 measuring points, item no. 9601.0002 Optional to the

Factory calibration certificate according to	offered devices
Calibration certificate according to DKD-R 6-1	with 11 measuring points, item no. 9601.0003 Optional to the offered devices
9031.0612	differential pressure transmitter PIZ-+/-5mbar-1-PIZ-1-0-0 Measuring range: +/- 5 mbar Output: 4-20mA Supply: 10 - 32 V Step response time: 1 s Calibration certificate: - Case: 80x120 Measurement accuracy: +/- 1%
9002.0310	Measuring range: 0 - 500 Pa Output: 0 - 10V Measurement accuracy: +/- 1.0% Supply: 24 VDC Case: 80x120
9030.1752	Druckaufnehmer PI-Sensor Measuring range: 0 - 25 mbar Output: 4-20mA Measurement accuracy: +/- 1% Supply: 24 VDC Display: 3 1/2 digits Case: 120x122
9030.3216	Differential pressure transmitter PI4-+/-1mbar-1-24D-0-0-0 Measuring range: +/- 1 mbar Output: 4-20mA Measurement accuracy: +/- 1% Supply: 24 VDC Case: 80x120 Calibration certificate: -
P29-1-24DC-0...5kPa-S-0-0-0	9614.0100 Differential pressure transmitter Measuring range: 0 - 5kPa Measurement accuracy: ± 0.5% FS/FS Output: 0 - 10V Supply: 24 VDC +/-10% Execution: hw Display: 0 Step response time: 25 ms Pressure connections: laboratory nozzle Language: German Calibration certificate: -
PSE312-8-IO-0-0-0-54	9431.0411 Positioner System Transmission type: PSE312-8 Output torque: 2 Nm Output speed: 115 rpm Setting range: 256 rev. Supply: 24VDC Interface: OK option. Connections: 0 Brake: 0 Certification: 0 Degree of protection: IP54
HMGP-303M	
SE335-14/So-DP-0-0-0 24Volt DC	
PSW 335-14-DP-0-0-0 Servo	
PSW 335-14-DP-0-0-0	Positioner
9431.0224	Positioniersystem PSE312-8-DP-T-0-0-54 Gear type: PSE312-8 Output torque: 2 Nm Output speed: 115 rpm Adjusting range: 256 revolutions Supply: 24VDC Interface: DP option. Connections: T Brake: 0 Certification: 0 Protection class: IP54
Ps10-230v	
9003.0068	
9030	
Pu (0-25)mbar 1 230 0 0	
Pse232-8/So-Ca-O-W-0 14924	country of origin: Germany Characteristics: Gearbox type: PSE232-8 Drawing: 7300.010933 Output torque: 2 Nm Output speed: 40 rpm Measuring range: 0 Supply voltage: 24VDC Interface: CA Software: 2534B / V199 PCB: V7474 Address switch: Auto-Id Output shaft: W Version: Orange RAL2010 Weight net: 0.8 kg Customs tariff number: 85011099 Weight per unit: 0.8 kg
Ps27	Differential pressure transmitter 9613.0109 country of origin: Germany Characteristics: Output signal: 0 - 10 V Supply voltage: 24 V AC / DC Switching outputs: 0 Execution: hw Time constant: 20 msec Display: 0 Measuring range: 0 - 2.5 kPa Test certificate: -
9003.0071	
9003.0070 (Ex.9003.0037)	
Pu 10mbar 1 230 0 0	

