

Hatlapa

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Hatlapa Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Hatlapa Türkiye Distribütörü veya temsilcisi değildir.
Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*

Ürün	Açıklama
Ersatzteile / Spare Parts	
Part number : 84.05	Brake lining. Lower Part Drawing No.: 1.72068 Pos 84.05
Part number : 84.02	Drawing No.: 1.72068 Pos. 84.02.
Part number: 69-42-**	Machine screw cross recessed, brass, countersunk head, M8, Length --- 100pcs. 40mm with nuts
See list / Spare parts	
Air Compressor HATLAPA Type L 80II	Double compressor control TD 200
COMB SUCTION AND PRESS V/V 1ST STAGE	20.20.10
COMB SUCTION AND PRESS V/V 2ND STAGE	20.20.20
PISTON RING 20.30.10.40	
SCRAPER RING 20.30.10.50	
DOUBLE BEVELLED OIL CONTROL RING	20.30.10.60
SCRAPER RING	20.30.20.40
FACED COMPRESSION RING	20.30.20.50
GASKET 20.10.20	
GASKET 20.20.50	
GASKET 20.20.60	
PACKING RING 20.20.30	

PACKING RING 20.20.40	
SPARES FOR GEAR BOX	DRAWING NUMBER 320112 PINION SHAFT 318609 1pcs CYLINDER ROLLER BEARING 085676 2pcs
758160	
1.1. Cylinder head 1st stage	(code 03.3) 20.10.30 in catalogue
1.2. Cylinder head 2nd stage	(code 03.6) 20.10.60 in catalogue
113327 Partno :11	
Laying .07, 01.34 HATLAPA L 80 II	
Oil pumps .07, 07.1 HATLAPA L 80 II	
AIR PISTON COMPRESSOR HATLAPA L-20	, ser #:18.5805-ON (19,5M3/H // 40 bar // 1450 RPM // 5,5 kW)
20.20.20	COMB. SUCTION A PRESS. VALVE 2 STAGE
180619	
10.20.10.10	crankshaft Kurbelwelle for serial-no.: 04.4081-0 suitable for: compressor L35
Main Starting Air Compressor: L14	Duty: Main Starting Air Compressor Type: 1 x L14 Description: 2 stage, 2 cylinder air cooled, single acting compressor Capacity: 14 m3/h FAD (+/- 5%) Customer FAD required: As above Working Pressure: 30 bar G Speed: 1450 rpm Shaft Power: 3.5 kW Control Voltage: 220 / 230 V Lubrication: Splash Heat to be dissipated: 2.8 kJ/sec Cooling air flow rate: 17.2 m3/min Inspection: DNV GL on compressor portion only Standard Compressor Features: · Flywheel and flexible coupling: Fitted · Mounting Arrangement: Flexible (AV Mounts) · Air intake filter with silencer · Inter and after cooler · Air Pressure gauges on all stages: Supplied fitted, glycerine filled · Condensate unloading - Manual & Automatic (Auto 2nd stage only) · Safety valves on all stages · Pipe connection for compressed air outlet · Crankcase breather · Oil level inspection glass · Fusible plug Additional features: · Flexible Air Hose: Supplied loose with tube connection · Air temperature measurement: T
028674	
20.30.10.50	napier ring Nasenring for serial-no.: 04.4081-0 suitable for: compressor L35
161181	
002055	
10.30.10	cover for oil pump Ölpumpendeckel for serial-no.: 04.4081-0 suitable for: compressor L35
Parts List For Attached List	
62mmk3/120	

10.30.40	gear wheel for oil pump �lpumpenzahnrad for serial-no.: 04.4081-0 suitable for: compressor L35
10.30.70	sealing ring Dichtscheibe for serial-no.: 04.4081-0 suitable for: compressor L35
20.20.50	PACKING RING
20.40.20.20	con. rod bearing shell / 2 pcs.= 1 set Pleuellagerschale / 2 Stk. = 1 Satz for serial-no.: 04.4081-0 suitable for: compressor L35
314716-44065	Drawing SINGLE CONTROL COLUMN 3-0-3 Blatt1,2 pos.S1
30.20.10	separator Abscheider for serial-no.: 04.4081-0 suitable for: compressor L35
135725	
Coupling Tire	From L35 compressor Please look at the attachement
161179	
20.20.30	PACKING RING
20.20.40	PACKING RING
10.10.10.10	crank case L for serial-no.: 04.4081-0 suitable for: compressor L35
10.30.50	gear wheel of oil pump �lpumpenzahnrad for serial-no.: 04.4081-0 suitable for: compressor L35
L35 With Motor	Main Starting Air Compressor Technical Specification - 1143518R.1 Duty: Main Starting Air Compressor Type: 1 x L35 Description: 2 stage, 2 cylinder air cooled, single acting compressor Capacity: 19,5 m3/h FAD (+/- 5%) Customer FAD required: 19.5 m3/h Working Pressure: 30 bar G Speed: 950 rpm Shaft Power: 4 kW Control Voltage: 220 / 230 V Lubrication: Force fed by pump Heat to be dissipated: 3.3 kJ/sec Cooling air flow rate: 19,5 m3/min Inspection: Works test on compressor portion only
20.20.10	COMB. SUCTION A. PRESS. VALVE 1 STAGE
10.30.20	radial packing ring Wellendichtring for serial-no.: 04.4081-0 suitable for: compressor L35
10.10.20.20	crankshaft bearing Kurbelwellenlager for serial-no.: 04.4081-0 suitable for: compressor L35
10.10.70	o-ring O-Ring for serial-no.: 04.4081-0 suitable for: compressor L35
V105	hatlapa V105 compressor pressure valve / Verdichterdruckventil
20.40.10.20	con. rod bearing shell / 2 pcs.= 1 set Pleuellagerschale / 2 Stk. = 1 Satz for serial-no.: 04.4081-0 suitable for:

compressor L35	
002058	
10.30.30	o-ring O-Ring for serial-no.: 04.4081-0 suitable for: compressor L35
Serial No. 07.7714.3.1	
20.20.60	PACKING RING
020346	
008792	