

Hbm



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Hbm Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hbm Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
U10m/250kn	Tensile/compres. force trans.U10M/ 250kN Force transducer for tensile and compressive forces Strain gages system 350 Ohm Bayonet device connector (MIL-C-26482 series1 compatible) Nominal range 250 kN Rated output 2...2.5 mV/V With mounted base plate Measuring body material: stainless material Influence of bending moments compensated. HBM accuracy class: 0.04
1-Z30A/10KN	Precision force transducer for tensile and compressive loading Nominal force: 10 kN Class 00 per ISO 376 700 ohm strain gage measurement system TEDS (integrated electronic data sheet) Device plug connection Class only guaranteed with additional DKD calibration certificate
SG250	
3130.0239-G	
LY15-0.3/120	
SP4MC3MR/3KG-1	
HBM RTNC3/1T BVS13A ATEX E 108 X 0058211	LOAD CELL IT:244464 ART:S0058211
1-Z6FC3/200KG-1	load cell Rated load: 200kg Minimum division value: 0.0090% of Emax OIML R60 test report Accuracy class: C3 Measuring body: stainless steel Protection class: IP68 according to EN 60529 Type of cable: Shielded 6-core round cable, PVC Cable

	length: 3m
1-AD103C	Digital pick-up electronics for dosing applications. DC voltage amplifier with digital measurement signal processing for Output of scaled measured values. Direct computer connection possible. communication via RS 232 interface. Operating voltage 5 V DC stabilized. Test certificate for class III balances 10000d, 0.5 µV/e according to OIML
AE301S6	
1-Z30A/10KN	FORCE TRANSDUCER F7633
S9m-0,5kn	
RTNC3/ 2.2T	
LOADCELL HBM RTNC3/ 2.2T	
HBM C16-A C3-30T	
Z6-FC3	2+/-10% m V/V 50 KG
801009255	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ
T20wn/50nm	TORQUE TRANSDUCER 50NM 12PIN CONNECTION
K-T40b-001r-Mf-S-M-Su2-1-U	
P15rva2/50b	
K-U93-20k00-05-Y	
Rlblc1k	LOAD CELL
Ap02	
Abm75	
K-Pmx	
K-Ly43-3/120-3-7.5m	
Z6fc3	
P2va1/100bar	
1b121000	
1-Mp55	
K-T40b-200q-Mf-S-M-Du2-1-U	
Wg001	
1-Wa/10mm-T	DISPLACEMENT TRANSDUCERS
Z6fd1/30kg-1	
1-Tn/10knm	

1-Wa/2mm-L	
K-C10-25kn-Sb-N-1-S-W-P-B	
1-C6a 5mn	
U2a100kg	
K-T40b-500q-Mf-S-M-Du2-1-U	
Z6fc3-200kg	
Mp60	SIGNAL AMPLIFIER
Z6fc3/100kg-1	
Z6fc3/1t	
Ap815	
1-Z7ad1/2t	
Z6fc3/500kg-1	
1-Wa/20mm-T	TRANSDUCER STANDARD DISPLACEMENT 0-20MM W10TK
K-T40b-005r-Mf-S-M-Du2-0-S	
Sv-725.01a-S6	POWER SUPPLY 24V 110V 50/60HZ
Z7ad1/2t	
K-T40b-200q-Mf-S-M-Su2-1-V	
Z6fc3/200kg-1	
Abc-Pdp-B	AnyBus Communicator
Ae501	
Oec30	
Z953115.07	
1-Kab157-3	
1-Hlcb1c3/550kg-1	
T5-100nm	
P2va2/200bar	
Elcb2hs/550kg-1	
P3ic/10bar	
Z6fc3mi	
Vkk1-4a	

P15rva1/50b	
1-Wa/200mm-L	
Df30dp	
Db25p292780293	
1-Sac-Epwr15-Ce-2	
1-Px878	
K-T40b-500q-Mf-S-M-Du2-0-S	TORQUE FLANGE 500Q:
P2va1/500bar	
1-Mp85adp	
1-T20wn/100nm	
1-Px01pn	
1-Z6fd1/50kg-1	
1-U2b/1kn	FORCE TRANSDUCER
1-Vkk2-8a	
Ts101	TARE AND STORE UNIT
Ae301s6	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ 15-26V
1we2111	CONTROL
Mp60dp	PME AMPLIFIER SINGLE CHANNEL 24V 600AZ
Elcb2hs/1.76t-1	
Aed9301b	
K-Fs22-01-500-420	
K-T40-200q-Mf-S-M-Du2-0-S	
We2111	INDICATOR
Sp5c3	
1-Wgx002	
Hlcb1c3/2,2t	load cell Rated load: 2.2t Minimum Sharing: 0.0100% of Emax OIML R60 test report Accuracy class: C3 Measuring body: stainless steel Protection class: IP68 according to EN 60529 Cable Type: Shielded 6-core round cable, PVC Cable length: 6m
Ts40a	
P15rva1/500b	
C16ic3-60t	

Z7ad1/5t	
K-T10f-500q-Sf1-S-0-V6-N-N-15m	
1-Tim-Ec	
Pw16kr 100 Kg By 1-Pw16ac3/100kg-1	
1-Px455	
1-Cp42	
1-Mx840-Pakeasy	
X60	
1-Ad103c	DIGITAL TRANSDUCER MODULE
Rm4220	Strain Gauge Amplifier Module
Z6fd1/200kg-1	
K-Cal-F-D-7-B-S-S	
Z7ad1/500kg	
1-Kab14-15	
P15rva1/10b	
K-Wa-T020w-32k-K1-F1-2-8	
1 Ap03	
Z6fc4/200kg-1	
D-15d/Mont	
1-Mx840-Pakap	
K-U15-25k0-Sb-S-U-B-U	
3-3312.0182	
1-P3mbp/2000bar	PRESSURE TRANSDUCER 2000BAR
K-Z6 -F-C3-200-N-6-N-N	
Vk20a	
K-Wa-T-020w-32s-S2-F1-2-8-10	TRANSDUCER STANDARD DISPLACEMENT 0-20MM IP45
K-P8ap-235-14-T9-0-K-1	
Z6fd1/20kg-1	
Elcb2hs/220kg-1	
Ak22	

T20wn-10	
P2va1/3000bar	
1-Z70	
T5/50nm	TORQUE TRANSDUCER 50NM 7PIN CONNECTION
Ab22a	
Ae301	
P3ic/50bar	
1p3mbp100bar	TRANSDUCER
1-Kab405.30a-3	
K-T40b-200q-Mf-S-M-Su2-1-U	
1-Pw18c3/10kg	
Z6fc4/20kg-1	
Z6fd1-100kg	
Z6fc3 ? 50kg - 2mv/V	
Z7ad1/1t	
1-U2a/20t/Zguw	KNUCKLE EYE FOR TRANSDUCER GALVANIZED
C2/50kn	
Pme-Mp55	MODULE CARRIER/FREQUENCY AMPLIFIER 4.8HZ
1-Caseclip	
K-P3mb-010b-A	PRESSURE TRANSDUCER 10BAR W/3M CABLE
1ml30	
1-Sp4mc3mr/75kg-1	
Z6fc4	
P3icp/1000bar	
K-C9c-05k0-07m0	
T4a50nm	
1-Ae501	
C9c-1kn	
Ap01i	
1-Kab149-6	
1-Sp4mc3mr/50kg-1	

P3ic/2500bar	
1-Ab22a	
P2va1/2000bar	
Cp13	
Hlcb1c3 4.4t	
T40b-500q-Mf-S-M-Su2-0-S	
1-Teds-Db-15p	
K-Ly41-6/350	
P3ic/1000bar	
1-Sp4mc3mr-30kg-1	
1-Kab272-2	
3-4412.0007	
Elcb2hs/1.1t-1	
P2va1/5000bar	
1-Z6fd1-100kg-1	
C2200	TRANSDUCER
P15rva2/10b	
1-Kab154-6	
Mpz1604012 Dmont	
1-3130.0239-G	
K-U15-250k-Sb-S-U-B-J	
1-Ly11-3-350	
1-X60	
K-U10m-125kn	
Aed 9101b, By Aed9101d	
Z7ac3/5t	
Z6fc6/50kg-1	
1tg002	
C2100 Kg	
1-Pw4c3	

1-Thermo-Mxboard	
K-U10m-2k50-Sb-N-1-S-N-U-B-B-0	
Mpz1604012 + D-Mont	
Vkk2-8	
Z6fd1	
1kab01063	
C9b50kn	
K-Ly4-3-05-120-0	
1-Smstrb4-350-2	
Ap01	
1-Scout55	
T20wn20nm	
Ab12	
H35-5k-Se (Series/Model 793) 3mv/V	
1-Wa/300mm-L	
Ly81-1.5/120	
K-Kab-T-0153-01-015-S015	
1-Ae301s6	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ
P15rva1/200b	
Mx840a	
Hlcb1c3 2.2t	
P3ic/500bar	
1-Kab150-6	
Z63c200kg	
1-C9b-1-Kn	
1-Tn/200nm	
K-T40fm-020r-Mf-S-M-Du2-A-S	
1-Wa/50mm-T	
K-Ry81-1,5/350	
P15rva2/100b	

Db15p333120182	
1-Px01	
Messkonverter-Mc3	
1-Wa/50mm-L	
Tg009b	
P2va1/7000bar	
1-Tb1a/5knm	
Z6fc6	
U15-25kn	
208479a	RACK W/POWER SUPPLY
1-P15rva1/100b	
1-Wa/500mm-L	
K-Wa-L-020w-31-S-S2-F1-2-8-050	
Z6fc3/20kg-1	
1-Z7ac3/10t	
Z6fc6/200kg-1	
1-U2a/100kg	LOAD CELL
P3ic/20bar	
Z7ac3/10t	
K-Cal-T-W-1-B-S-S-2-0	
1-Mp85a	
I-Aei01	
1-Vk20a	
1ab12	
C16ad1-60t	
D-Mont	
1/4-18npt	
Z6fd1/100kg-1	
Blcb1c3/550kg-1	
1-Kab139a-6	
K-Pw6c-N-C6-10-N-6-6-A	

P15rva2/20b	
S9m-0,5kn	
1-Ws/Zb 12 Alternatif	
T22-5nm	
1-Pw16ac3/50kg-1	
1-Kab153-6	
K-T40b-005r-Mf-S-M-Du2-1-S	
K-Wa-L-200w-31s-S2-F1-2-8-10	
Kab0104-10	
Vkk 1-4 By Vkk1-4a	
Vkk2-8a	
Z6fc4/100kg-1	
Z7ac3/2t	
C9b2kn	
U15-50kn	
P3ic/100bar	
MI30b	
P3icp/10bar	
1-Tn/5knm	
1-Ap08	
1-Ly81-0.6/120	
1-Pmx	
1-Px02	
1-Wa/100mm-T	
1-U2a/20t/Zgow	KNUCKLE EYE FOR TRANSDUCER ROLLER BEARING
P2va1/1000bar	
1-Ae101	
K-Ly41-1,5/350	
K-T40b-005r-Mf-S-M-Du2-O-U	
Usrtm25k15100	LOAD CELL

1-Mx440-Pakeasy	
Fit/H1sr2	LOAD CELL 50KG
K-T40b-003r-Mf-S-M-Su2-1-U	
Mvd2555	
K-T10fs-001r-L-Sf1-G-0-V0-N	
We2110	
D-Teds/Mont-Db	
Z6fc3/50kg-1	
1-C9c/100n-100n-01m5-Y-S	
Z7acc3/Zt	
1-Ly81	
1-Z7ad1/10t	
Z4a	
Z6fd1/500kg-1	
U3/0.5kn	FORCE TRANSDUCER 0.5KN
T40b-005r-St-S-M-Su2-0-S	
1-Smstrb4-120-2	
Z6fc3 ? 100kg ? 2mv/V	
P15rva1/20b	
1-Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ
1-Kab272-0.2	
C9b-10kn	
Z6fc4/500kg-1	
U15-10kn	
Mp55	CARRIER FREQUENCY AMPLIFIER
1-We2111	
1-T4a/5nm	
1-Mp60	
K-T40b-500q-Mf-S-M-Su2-1-U	
P3ic/750bar	

Blcb1c3/1.1t-1	
433010071	
1-Pw16ac3/75kg-1	
1-Kmr-30t	
1-C9b2kn	
Pme-Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ
Hlc-40kn	
Z7acc3	
Z6fc3/10kg-1	
K-Ry81-6/350	
1-Wa/10mm-L	
K-U1a-050n-A-K	FORCE TRANSDUCER 50N 6M CABLE
1-Ntx001	
K-P3-Mb-200b-Yá;Á;	
1-Mc2a	
Z30a/100n	
Pw2ac3	
K-Wa-T-050w-32k-K1-F1-2-2-003m-10m	
1-T4wa-S3/10nm	
Z6fd1/1t	
1-Kab153-15	
K-T40b-200q-Mf-S-M-Du2-0-S	
P3ic/200bar	
1-Ae301	
Pw18c3-20kg	
1-Subhd15-Male	
Kwa-T05w-32k-K1-F1-2-	
K-C9c-100n-05m0-F-T	
K-T40b-001r-Mf-S-M-Du2-A-U	
1-Z6fc3/200kg-1	
Z6fd1/10kg-1	

Z6fc3/30kg-1	
1-Wa/20mm-L	
P15rva2/500b	
1-Kab154-15	
Z6fd150kg	
1-Tb1a/100nm	
P15rva2/200b	
Z6fc4/50kg-1	
1-Mx878b	
1-U2a/200kg	load cell Rated load: 200kg Accuracy class: 0.1 Measuring body: stainless steel Protection class: IP67 according to EN 60529 Cable Type: Shielded 6-core round cable, thermoplastic elastomer Cable length: 3m
K-T40b-002r-Mf-S-M-Su2-1-U	
T20wn/10nm	TORQUE TRANSDUCER 10NM 12V 12PIN CONNECTION
Ae101	
K-Rtn-S-C3-150-N-12-N-N-S-S	
K-T40b-200q-Mf-S-M-Du2-1-S	
T20wn-50	
Dq809	
Z6fd1/5kg-1	
1mc55	
1-Ehls-Icp-B-2	
Z6fc3-500kg	LOAD CELL
1-Ly61-1.5/120	
1-Tn/500nm	
Pw15ahc3mr	
K-Ry81-3/350	
1-Cx22-W	
1-C16ac3/60t/Eexd	
1-Wa/100mm-L	
1-Kab271-3	

Hlcb1c6-220kg	
1-X60-Np	
Ap04	
K-Wa-L-200w-31s-S2-F1-1-8-10m	
K-T40b-200q-Mf-S-M-Su2-0-U	
P3ic/2000bar	
1-P3mbp-1000bar	PRESSURE TRANSDUCER 1000BAR
1kab133a	
Z6fc6/100kg-1	
C9c-50kn	
P2va1/200bar	
1-Mp30	
P3ic/3000bar	
1-Z6fc3/500kg-1	
Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ
1-Hlcb1d1/550kg-1	
C9b-50kn	
1-Vkk1r-4	
Blcb1c3/1.76t-1	
K-T40b-500q-Mf-S-M-Du2-1-S	
C2/10kn	FORCE TRANSDUCER 10KN 3M CABLE
Slb700a/06-1	
K-Wa-T-020w-32k-K1-F1-2-2-3m	
1-Wa/2mm-T	
1-Z7ad1/5t	
1-Pw15phc3/10kg-1	
K-T40b-500q-Mf-S-M-Du2-0-U	
Pw16ac3mr	
Mp85adp	
K-Ly4-350-07-1-2-25	

1-T5/20nm	
U2b-1kn	
K-Cal-T-W-5-B-S-S-2-0	
H358-5k-Se 3mvv	
C2/20kn	FORCE TRANSDUCER 20KN 2MV
Catman Easy	
Fit/1sa31/10kg	LOAD CELL 10KG
P3icp/100bar	