



Hydrokomp

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Hydrokomp Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hydrokomp Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
KMP-5-03-014	Coupling mechanism plate, 3-fold for compressed air max. 20 bar NW 5, can be coupled without pressure, O-ring flange connection Positioning tolerance to the counterpart: radial +/- 0.2 mm, axial +0.5 mm Fastening screws, cylindrical pin u. O-rings included. Customs tariff number 84122120
KNP-5-03-007	Coupling nipple plate, 3-fold for compressed air max. 20 bar NW 5, can be coupled without pressure, O-ring flange connection Positioning tolerance to the counterpart: radial +/- 0.2 mm, axial +0.5 mm Fastening screws, cylindrical pins u. O-rings included. Installation dimensions according to E-KMP-5-03-007 Customs tariff number 84812010
KN-460-5-S007k	Coupling nipple, UD, hardened pmax = 300 bar, NW 5, Installation element, short, under pressure detachable Coupling elements must be approx. 2-3 mm before touching the sealing surfaces within the positioning tolerance be guided. Positioning tolerance: radial +/- 0.2 mm, axial + 0.5 mm Installation dimensions according to Data sheet 3-100 Housing plasma nitrided. Customs tariff number 84812010
I need price and delivery on (2) KN-160-5-S001K Fittings,	

KN-160-5-S001K	that mate with to a KM-460-5-N001 port. I need the part number verified and the dimensions of the fitting. Thank you.
Hydrokomp	
Hydrokomp	
Hydrokomp	
Hydrokomp	
KN-460-5-EG002	Coupling nipple, M24x1.5 ,UD pmax = 400 bar, NW 5, Screw-in element, under pressure detachable Installation dimensions according to drawing E-KN-460-5-EG002 External thread M24x1.5
6011-001-N001	
Kn-460-5-Eg 003	
Kmp-460-5-K015	
Ase-016-08-03-001	
Ab03006/1-B-Nr-160003	
Kmp-460-5-K013	
Km-460-5-Eg 008	
Kn-460-5-Eg001	Coupling nipple, M28x1, AND pmax = 350 bar, NW 5 Insertion element, under pressure coupled Installation dimensions according to drawing E-KN-460-5-EG001 or catalog sheet 3-100 Customs tariff number 84812010
Kmp5-Ko 52	
Kmp-460-5-K004	
Km-460-5-N001	
Kds-5-06-002	
Duhh-70-5-002	
Dhsp-Dhs-020-001	
Kn-460-5-S001l	
Kn-460-5-Eg002	
Kn-460-5-S001k	
Kmp-460-5-K-024	