



Keithley

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Keithley Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Keithley Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
2400 DIGITAL SOURCEMETER	
2400 Sourcemeter	
DAQ6510/7700+40 Channel Kart	DAQ6510/7700
KUSB-488B	
2612b-3y-Ew(Optiononly)	
2002/Mem1	
2001/Mem2-Us	
Pdma32	
6487-5y-Ew-Std	
8101-4trx	
3390	
C/7751-5y-Std	
2430caldu	2430 CALIBRATED W/ DATA + UNCERT
4288-7	
7012-S	4X10 MATRIX CARD

7754-3	
7020-D	
2425-C-Us	
2400 Newport Cornerstone 260	
2790-L	
6517 B - Electrometer/ High Resistance Meter	
7045	
2001-M	DMM NAVY NSN7Z6625-01-425-9735
4200-Scs/F-Nosmu	SEMI CHARACTERIZATION SYST W/FPD, NO SMU
Cab-307	
1754	
Kusb-488b	
2600-Std-Res	CALIBRATION STANDARD 1G OHM RESISTOR
6485-3y-Ew-Std	
7072	8X12 SEMICONDUCTOR MATRIX CARD
M1151	
26600-1	
2636a	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, SOUR
196dmm	MULTIMETER
130	
6487/E	
P/N 6011	
2790-H	SOURCEMETER SWITCH W/1 HI V CARD 10M OHM
5804	
2420 (Ex. 228a)	
7058	LOW CURRENT SCANNER CARD
617	
2612b	
7154-102-02c	
176	
Mb32-01	
2500int-2-Si	
2510	
2268-100-8	
C/2604b-3y-17025	

S2008033	
2461	
4804	
7702	DIFFERENTIAL MULTIPLEXER MODULE, ACCESSORY TYPE:DIFFERENTIAL MULTIPLEXER MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION D
7024-10	
130130a	
7755	
7708	DIFFERENTIAL MULTIPLEXER MODULE, ACCESSORY TYPE:DIFFERENTIAL MULTIPLEXER MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION D
2420-C	
2790-HI	
Kusb-3100	
2110-220	
2220j-30-1	
C/6517b-3y-17025	
2510-Rh	
2001-Tcscan	THERMCPL/GEN PURPOSE SCAN CARD
2306-Pj	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2000-3y-Ew	
6221 Dc	
2600-Acs-Pk1	2636B BUNDLE WITH ACS BASIC EDITION, (1) 8101-PIV, (4) 4200-TRX-1, (1) KUSB-488B
7153-Trx	
2000-Us	HIGH PERFORMANCE 6-1/2 DIGIT DMM AND 1751 TEST LEADS
C/2000-3y-Data	
7751-Ew	
Mb-01	
3791-Cit	
S46-6666	S46 W/4-SP6T
Dda-06	
236-Ilc-3	
8606	
4200a-Scs	
4200-Man	

7152	
62202182a	SOURCE METER, DC CURRENT, 11W, SOURCE METER FUNCTION:CURRENT SOURCE, OUTPUT POWER:11W, SOURCE CURRENT RANGE: 2NA TO 100MA, RESISTANCE MEASUREMENT R
C/Data	
C/2110-5y-17025	
Kusb-3108	
2100/120cal	(PRICE/EA) CALIBRATED WITH CERTS, KEITHLEY P/N 2100/120 SKU # 59T7566
2200-20-5	POWER SUPPLY, AC-DC, PROG, 0-20V, 5A, 100W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:5A, POWER RATING
2500int-2-Igac	
C/6514-3y-Std	
7708-5y-Ew-Std	
Sta-300	
708b	
2015	
Dda-08	
Mb36-04	
2000/2000-Scan	
7700-3y-Ew-Std	
Ctm-05	
2600-Triax	
7168	
7710	
3732-3y-Ew	
2182-Kit	
7011-S	QUAD 1X10 MULTIPLEXER CARD
7018-S-Nms	MULTIPLEXER 28 CHANNEL 3P MULTIPIN NO CONNECTOR
1507a	
7078-Trx-12	
2280s-60-3	
2500intfcpc	
Kusb-3102	MULTI-FUNCTION USB DAQ MODULE
7407402	
Das-8	
1753a	

2306-Vs	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2001/Mem1	
Mb31-02	
7078-Trx-3	
Kpci-3116a	HIGH RESOLUTION MULTIFUNCTION BOARD
7009-5	
Mssr-32	
2100	
3750	
2600-Fix-Trx	
2000/E	
C/2602b-3y-17025	
2100/100	
8607	
3722mtc15mm	
2000-102-02f	
2110-240-Gpib	
Mb41-03	
2400-C-3y-Ew-Std	
2600-Kit	
S40-Q009-12	S40 Q009 W/OPTIONS
7011-C	
4288-5	
2790-3y-Ew-Std	
C/2604b-5y-17025	
6220-3y-Ew-Std	
62212182a	
7012-C	(PRICE/EA) 4X10 MATRIX CARD, ROHS COMPLIANT: NA
2600-Tlink	
Ca-563c	
S46-Sp6t-Kit-40	SP6T 40GHZ RELAY
2200-32-3	POWER SUPPLY, AC-DC, PROG, 0-32V, 3A, 96W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32V, OUTPUT CURRENT:3A, POWER RATING:
Ca-568-Xa	

Das1802hrda	METER
6487-3y-Ew-Std	
C/2420-3y-Std	
C/Newdata(Optiononly)	
2000-162-02f	
169	
7067	FOUR-WIRE SCANNER CARD
Shv-Ca-553-1	
7707	
2001-3y-Ew	
C/Newdataiso	
2110-220-Gpib	
130a	
S46-66665678a	S46 W/4-SP6T, 4-SPDT/RADIALL
3706a-Nfp	
6485	
3722mtc3mm	
C/2700-3y-Std	
6147	
Ctm-05/A	
S46I-LI00-0000a	1X12 MICROWAVE SWITCH SYSTEM
7015-St	
7174a	8X12 HI SPEED LO I MATRIX CARD
5806	
2107-30	
Hv-Cs-1613	
7173-50	
191refurb	
Mb38-07	
4200-Mtrx-2	
Pc8382	
Cab-305	
5805-12	
174	
7700	

Kpci-Pio24	
2000-20	DMM WITH 20 CHANNEL SCAN CARD
Dpp-45acp	
2440	SOURCE METER, DC VOLTAGE CURRENT, 55W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE: 200M
2790-Hh	
3723-St	
3720-St	
M1121	
7007-05	
2401	
3402-F	SIGNAL GENERATOR, 2-CHANNEL, SIGNAL GENERATOR TYPE:BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTERNAL HEIGHT:87MM
2100/230-240	6 1/2 DIGIT DMM SET TO 230-240V
3722	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:DUAL 1 48, HIGH DE
6524	SOFTWARE, ACCESSORY TYPE:SOFTWARE, FOR USE WITH:KEITHLEY MODEL 6517B ELECTROMETER / HIGH RESISTANCE METERS, FEATURES:HIG RESISTANCE MEASUREMENT, ROHS
2420-Us	
8009	RESISTIVITY TEST FIXTURE
6220	
M53121	ENCODER
7712	
Cab-308	
707a	
3706a-5y-Ew	
263	CALIBRATOR/SOURCE
2231a-30-3	
3722-3y-Ew-Std	
2502-Us	
3401-R	SIGNAL GENERATOR, 1-CHANNEL, SIGNAL GENERATOR TYPE:BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTERNAL HEIGHT:87MM
3722-Mtc-3	
6522-3y-Ew-Std	
Hv-Ca-571-3	

2303	
3402-R	SIGNAL GENERATOR, 2-CHANNEL, SIGNAL GENERATOR TYPE:BURST / EXTERNAL WIDTH / PATTERN / PULSE, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTERNAL HEIGHT:87MM
Kpci-3104	
4200-Scs-Pk1	
Cab-1800/S	
8503	
2182a-Us	
Gm-Ps-6	
3730-3y-Ew-Std	
20002000scan	
6514-Us	
Pio-24	
7006-1	
2520kit1	
2001	
82790-9247/E	
2280-001	
5807-7	
Ssio-24	
4288-4	
7078-Pen	
6221/2182a/J	DELTA MODE SYSTEM @ 90V
3732-St-R	
2010-Us	DIGITAL MULTIMETER
2611a	
4299-4	
Pdis08	
85504a	
4200-Scs/C-Nosmu	SEMI CHARACTERIZATION SYST W/O FPD, SMU
2268-150-5	
S46-Tw	
Mb45-01	
7011-Mtc-1	
6011	
Hv-Ca-554-3	HV TRIAX CABLE, 3 M, MALE TO MALE

2000-Scan-20	
2410-C-Us	
2268-80-10	
Knm-Ps-Conn01	
Mb-Res20ohm	
2010-3y-Ew	
2602a	SOURCE METER, DC VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, S
Sta-Tc	
6487-Us	PICOAMMETER
C/2790-3y-Std	
Part No: 5806	
6482	
Mdb64	
S46t-Bb66uuuuuuuuua	S46 W/2-SP6T (T), 2-SP6T U/T 8-SPDT U/T
7705	
2657a-Pm-200	HI-VOLTAGE 200V PROTECTION MODULE
Pio-12	
775a	
7705-Mtc-2	
Knm-Dcv42	
Mb37-T	
872872a	
2700/E	
3300 Lcz	
2400 Sourcemeter	
2602b-5y-Ew	
2010/E	
73009445/J	
2302-Pj	BATTERY SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:15V, OUTPUT CURRENT:5A, POWER RATING:60W, INPUT VOLTAGE:
2290-5	
192	
871	
S40-Sq01	HYBRID REED RELAY CARD
3730	

2260b-80-40	
3730-St	
2401-3y-Ew-Std	
128	
D1541-96	
7002	
Exp-16	
7711-Bnc-Sma	
7709	MATRIX MODULE, ACCESSORY TYPE:MATRIX MODULE, FOR USE WITH:KEITHLEY MODEL 2700, 2701, 2750 DMM DATA ACQUISITION DATALOGGING SYSTEMS, FEATURES:6X8 MAT
Hv-Ca-554-X	
Sm-Idc5	
2260b-30-108	
6485/E	PICOAMMETER @220V
3721mtc15	
865	
7999-2c	
14242-2	
2182a	
248-Shv	
Rsa6106b	
2303-Pj	
7025-10	
2002-U_s	
Ca-559-2a	
2000-20/E	
3706a-3y-Ew	
5808	
2400-U_s	
3723-St-1	
26600-3	PICOAMMETER LOGARITHMIC 10 TO THE 13TH
Stp-37	
6514-5y-Ew-Std	
2015-P	AUDIO ANALYZING DMM
160	

871a	
8008	
4288-10	
7001	SWITCH MAINFRAME, 80-CH, 100MHZ, NO. OF CHANNELS:80, SAMPLING RATE:-, INPUT VOLTAGE MAX:250V, INPUT CURRENT MAX:1A, BANDWIDTH:100MHZ, EXTERNAL HEIGHT:
S46-Spdt-Kit-40	
2425-U_s	SOURCE METER, VOLTAGE CURRENT, 100W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV TO
C/6220-3y-Std	
820rb	
2268-20-42	
8010	
6167	
Kpci-3110a	
248/E	
3724-St	
2200-60-2	
2750-U_s	
230	
6517b-Ilc-3	
7015-S	40 CHAN SOLID ST MULTIPLEXER
2015-P/E	
2750	
Sta-U	
2400-Lv-U_s	
17501	
2110-100	
4299-5	
2510-At	
2200-30-5	
179a	
2400-Ccald	2400-C, CALIBRATED, WITH CERT AND AS FOUND AND AS LEFT DATA IS PROVIDED TO THE CUSTOMER (Z540)
6514/E	ELECTROMETER AT 220V
3401-F	
M1000	

2260b-800-1	
236	
2601a	SOURCE METER, DC VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, S
17502-5	
C/2182a-5y-17025	
428prog	
2601b	
3722-3y-Ew-Std(Optiononly)	
1600a	
C/2110-3y-Std	
3740	GENERAL PURPOSE CARD, ACCESSORY TYPE:GENERAL PURPOSE CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:32 INDEPEN
6430	
2016-P/E	
2303-Nms	
7011-R	
7752	
4288-9	
869	
708a	SINGLE SLOT SWITCHING MATRIX MAINFRAME
2400-5y-Ew-Std	
2510-Cab	
2016/E	THD 6.5 DIGITAL MULTIMETER @ 220V
2182a-5yr-Ew	
7790	
7035-5y-Ew-Std	
Hv-Ca-554-.5	
Pc9532	
2260b-80-13	
7633	
2260b-800-2	
7006-2	
261	
2430-C	SOURCEMETER
78500-9244/G	

2110-120	
S46-66665678	
175175a	MULTIMETER
614	
2450-Ecvcube	
2500int-Sma	
Tr280d	
2400-Lv	(PRICE/EA) LOW VOLTAGE SOURCEMETER
Usb-B-1	
3323a	
500p-2-Main	
7788	
Sm-Odc5	
C/Newdata	
C/6517b-3y-Data	
4200 Scs	
Sta-1800hc	
4210-Cvu	4210 CAPACITANCE VOLTAGE UNIT 1KHZ-10MHZ
2230g-30-1	
5805	
2260b-30-72	
8696	
Kusb-3116	(PRICE/EA) 16-BIT PERFORMANCE USB MODULE
3790-Kit50-R	
8010-Dtb-220	
7002-Rmk-1	
2230-30-1	DC POWER SUPPLY, PROGRAMMABLE, TRIPLE OUTPUT, 90W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:3, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30
2425-C	
Kusb-3160	
4225-Pmu	
2600-Ban	
N5-0233-0000	
2651a-Kit-3	
6485-5y-Ew-Std	

Kpci-488lpa	
248-Mhv	
Pio96j	
237	VOLTAGE SOURCE PROGRAMMABLE 125/250VAC
2306-Us	
2110-240	
7053	HIGH CURRENT SWITCH CARD
3721	
6517-Tp	
Acs-Basic	ACS BASIC EDITION SOFTWARE FOR COMPONENT TEST
2281s-20-6	
Stp-100	
Stp-100u	
2635b	
237-Alg-2	
2520	
7024-3	
7036	40 CHAN SINGLE POLE RELAY CARD
2308	PORTABLE DEVICE BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUT
2304-Disp	
7002-5y-Ew-Std	
Lcz Meter	
6522	SCANNER CARD, ACCESSORY TYPE:SCANNER CARD, FOR USE WITH:KEITHLEY MODEL 6517B ELECTROMETER / HIGH RESISTANCE METERS, FEATURES:10-CHANNEL, LOW CURRENT,
2425	
7708-3y-Ew-Std	
2260b-80-27	
7007-4	
6146	
Pdiso-8	
C/6485-3y-Std	
2302	
C/2790-5y-Data	
2430	
182	

Das-802	
2700/7700/E	DMM/DATA ACQUISITION SYSTEM W/20 CH MULTIPLEXER
C/Tracechart	
7707-Mtc-2	
8681	
2410-C	
S46-Sp4t-Kit	
Dac-02	
2306-Disp	
M1141	
2288	
195a	MULTIMETER 5.5 DIGITS
7401	
873f	
Shv-Ca-553-3	
Rel-16/W	
2636b	
6221-3y-Ew-Std	
61600-9252/B	
2016	
2635a	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT-VOLTAGE SOURCE / DMM / ELECTRONIC LOAD / POWER SUPPLY / WAVEFORM GENERATOR, SOUR
6517b/E	
616	
706	
2604b	SOURCE METER, VOLTAGE CURRENT, 40.4W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:100MV T
7056	
2611b	
4299-6	
2306	BATTERY / CHARGER SIMULATOR, 15V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2, OUTPUT VOLTAGE:15V, OUTPUT VOLTAGE 2:15V, OUTPUT CURRENT:5A
2260b-30-36	
175a	
3791-Kit78-R	
172	

199	
2750/E	
2410-Us	
Mb31-05	
194	
2220-30-1	POWER SUPPLY, BENCH, DUAL RANGE OUTPUT, 90W, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:2, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT C
2440-5y-Ew-Std	
Stp-36	
4225-Rpm	
2502	
3732	MATRIX CARD, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:QUAD 4 28, ULTRA-HIGHDENSITY
2220g-30-1	
197	
2500intfcapc	
2260b-250-4	
2100120	
Kickstartfl-Hrma	
2001/Mem2	
Mbus-Pwr-Euro	
3731	MATRIX CARD, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:6 16, HIGH SPEED, REED RELAY
7797	
7711	
Ca-18-1	
6220-Us	
2260b-800-4	
2290-10	2290-10 10kV Power Supply
2000-Scan	
She-1101	
2268-40-21	
Mb31-03	
175av	
5801	

237-Trx-Tbc	
S1600	
Ctm-10/05a	
2260b-250-9	
Shv-Ca-553-2	
2420	
6517b-3y-Ew-Std	3 YEAR KEITHLEYCARE GOLD PLAN
4801	
2000-112-02d	
5809	
2187-4	
707b	
Das-16	
Stc-37	
S46t-Spdt-Kit-26t	
Cab30	
2000-Ew	
2500int-4-Ipg1	
Mb38-02	
2110-120-Gpib	
M1541-96	
7700-Ew	
2604b-5y-Ew	
S46-Spdt-Kit	
2410-5y-Ew-Std	
Mb38-05	
6221-Us	
2410	
7706	
Dmm7510	
2510-3y-Ew-Std	
8605	
Cab-1284cc-2	
3720-Mtc-3	
7011-Mtc-2	

Mb45-02	
7999-5	
She-1103	
6521	
7014	
Das-801	
7002-Hd	
2002	
Ca-559-0a And Ca-559-2a	
580	
2450-Ec	
7079	
7153	MATRIX CARD, 4X5, 2POLE, 1.3KV SWITCH, ACCESSORY TYPE:MATRIX CARD, FOR USE WITH:KEYSIGHT MODEL 237 SIMILAR SOURCE MEASURING UNITS, ROHS COMPLIANT: N
3706-Bkpl	
7001-5y-Ew-Std	
237-Alg-2	
7999-3	
Ca191	
Keithley-4200a-Scs-Nicht-F3;R-Den-Wiederverkauf-Istanbul-Turkiye	
6172	
6221/2182a-Us	DELTA MODE SYSTEM
487	
Probe For 6487	
Mb-05	
7702-5y-Ew-Std	
2602a-3y-Ew	
3720	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:60 DIFFERENTIAL CH
197a	
3732-Mtc-1.5	
S40-P011	
3706-Ban	
S46-66661234a	
1701b	

Hv-Ca-554-1	
8009 - Resistivity Test Fixture	
She-1102	
7020	
8680	
2401.-Us	
S46-666612345678a	
2634b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
Sta-16	
7073	
Mb39-01	
4803	
2440-C	5A SOURCEMETER WITH CONTACT CHECK
6220-Westinghouse	
Lr:8028	
2000-Benchkit	
6514	ELECTROMETER, 20PA TO 20MA, 2V TO 200V, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:2V TO 200V, VOLTAGE MEASURING RANGE AC:2V TO 200V, CURRENT MEASURIN
7023	
8610	
2790-A	SOURCEMETER SWITCH W/1 HI V CARD 1M OHM
7065	
Keithley 2400	
Mb41-02	
27007700	DMM / DATA ACQUISITION, 6-1/2 DIGIT, DMM TYPE:BENCH, VOLTAGE MEASURING RANGE DC:100MV TO 1000V, VOLTAGE MEASURING RANGE AC:100MV TO 750V, CURRENT MEAS
4802-10	
6485-Us	
C/2410-3y-17025	
2015/E-Nok	
7111-S	
1685	
2002/Mem2	8.5D DMM W/128K MEMORY
She-1100	
2001-Scan	

2614b	SOURCE METER, VOLTAGE CURRENT, 30.3W, SOURCE METER FUNCTION:CURRENT/RESISTANCE/VOLTAGE MEASURE, CURRENT/VOLTAGE SOURCE, SOURCE VOLTAGE RANGE:200MV T
7013-S	
2182a-3y-Ew	
2303-Nms-22741	
C/3390-3y-Std	
2100-3y-Ew-Std	
6517	
6221/2182a:2182a-3y-Ew-Std	
2600-Alg-2	
2002/Mem2-Us	8.5D DMM W/128K MEMORY
874f	
3732-St-C	
7751	
14308b2	
2420-3y-Ew-Std	
2700-3y-Ew	
4200-Scs/F	SEMI SYSTEM W/2 MPSMU FPD
Sta-08	
Das-1802st-Da Obsolete	
Kpci3160	
2612a	
7007-2	
2000	
2651a	
7078-Trx-1	
611009301/F	
7078-Trx-5	
6517a Obsolete/Replacement 6517b	
6517-Rh	
4299-1	
Sw433	
2520int-1-Ge	
7158	
2260b-250-13	
2015/E	

169-Dmm	
6487	PICOAMMETER / VOLTAGE SOURCE, DMM TYPE:BENCH, CURRENT MEASURING RANGE DC:2NA TO 20MA, NO. OF DIGITS / ALPHA:5-1/2, DMM RESPONSE TYPE:TRUE RMS, RANGING
3722mtc15	
2280s-32-6	
610	
1651	
2657a	
Dda-08/16	
Mb40-02	
7001-3y-Ew-Std	
2440-Us	
4299-3	
Lsi22	
840a	
7078-Trx-Gnd	
C/2604b-5y-Data	
S46-4400123456a	
2182a/E	
2600-Iac	
4200-Scp2-3y-Cal	
6221	
Kpc1-3110	
2304a	
740	
2268-60-14	
Pio-Hv	
C/2182a-3y-Std	
237-Bnc-Trx	
6517-Ilc-3	
7018-S	
7154	SCANNER CARD 10-CH HIGH-VOLTAGE 1100V 2POLE
7703	
C/2182a-5y-Std	
2200-30-5-Ew	

3721-Mtc-3	
2400-Intrlk	
7753	
2107-50	
2000/E/2000-Scan	
2400	
02500-0700-0003	
6011-10	
3724	MULTIPLEXER CARD, ACCESSORY TYPE:MULTIPLEXER CARD, FOR USE WITH:KEITHLEY MODEL 3700 SYSTEM SWITCH W/ HIGH PERFORMANCE DMM, FEATURES:DUAL 1 30, FET, RO
3740-St	
775a5152	
Mssr-32-14071-Pc6432	
C/6487-5y-17025	
Mb47-K-05	
Ucpdisco-8	
2001-Us	
2602b	
6220/2182a-Us	
Stp-50-C	
4180	
Model 2401	
7078-Trx-20	
8502	
2010	
50013202caim1	
2700	
Hv-Ca-554-1	
3706a-S	
Ot-2000-3-12812-D	
2700-5yr-Ew	