



Krom Schroder

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.

Krom Schroder Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Krom Schroder Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Tzi 7,5-12/100w	ignition transformer new order no. for 34331383 For high voltage ignition of gas and oil burners High voltage 7.5 kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V ~ TZI 7.5-12 / 100W Ignition transformer new order no. for 34331383 For high-voltage spark ignition of gas or oil burners 7.5 kV high voltage Output current: 12 mA at 50 Hz 100% duty cycle Mains voltage: 230 V AC Stat. Product number 85043200 Country of origin: DE
Dmg S2610	For measuring pressure, negative pressure and differential pressure of air and non-aggressive, gaseous media, digital display, switchable pressure units, hold function for current measured value, display of minimum and maximum measured values, plasticized PVC housing with securing magnet Measuring range: ±1000 mbar, accuracy: ± 1.0 % of measured value, resolution: 0.01 (up to 199.9); 0.1 (from 200) mbar, max. positive pressure: 3 bar Stat. Warennummer 90262020 Ursprungsland: DE
Uvs 10d0g1	UV-sensor For monitoring gas burners in intermittent operation, EC type-tested and certified in conjunction with Elster Kromschrder automatic burner control units Series 10 Quartz glass heat guard Rp 1/2 internal thread - M20 cable gland Stat. Warennummer 90275000 SK
74960445	UV-Photozelle fr UVS 10 Accessory Stat. Warennummer 90329000 SK
Vgbf 25r10-1	Gas pressure regulator Spring-loaded, with inlet pressure compensation membrane and Zero closing, for Keeping the adjustable pressure constant DN 25 Rp internal thread pu max. 1 bar Lock screw in the entrance For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar) Stat. Lot number 90322000 Country of origin: SK
TZI 5-15/100W	84331381 ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~

DG 50U-6	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, with socket
GRSF 25R	03150674 Non-return gas safety device, flameproof at combustion with air To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread Flameproof up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar city gas, hydrogen
DG 500UG-4	84447040 gas pressure switch IP65 / Kapsto conical plug in the lower part, Gold contacts 24/250V For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 100-500 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP65
DKR 250Z03F100D	03149246 Ring damper for air and flue gas For continuous control of a volume flow DN250 Installation between two DIN flanges PU max. 300 mbar With free shaft end temperature range
DKR 300Z03F450D	03149252 Ring damper for air and flue gas For continuous control of a volume flow DN 300 Installation between two DIN flanges PU max. 300 mbar With free shaft end Temperature range 450°C resounding
Length compensation GRSF 25R	03150679 gas non-return device For use with GRSF 25R (03150674) for exchange GRSF 25R50 (03150645) Overall length 174 mm DN 25 G male/female thread PU max. 5 bar
CG 225R01-DT2WF1	84741205_S compact unit The product contains 'Substances of Very High Concern' (SVHC?s) in a concentration > 0.1% by mass according to REACH contain. With filter or dirt trap, pressure regulator, pressure monitor, valve(s) and quantity setting to save and regulate atmospheric burners, forced draft burners, forced draft boilers up to 400 kW, EC type tested and certified Size 225 Rp internal thread PU max. 100 mbar pressure regulator Mains voltage 220/240 V~, 50/60 Hz 2 valves ,pressure switch, filter
GRS 25R	03150669 gas non-return device To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread PU max. 25 bar
DG 50U-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With

	screw terminals and M16 cable gland, IP54
88000043	VAS 350R/NW gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 3 Certification: EU certified Inlet: DN 50 (2") Outlet: DN 50 (2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
Flame guard	'When replacing IFW 15-T 84359010; (without transformer)' please follow the conversion instructions. This is permitted within the scope of European directives product only be used for replacement purposes. For multiple flame monitoring with IFS 110/111IM, for intermittent Operation Ionization or UV monitoring Mains voltage 220/240 V~, 50/60 Hz, for grounded or unearthed networks
Ignition transformer	new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
VMO 120R05M10	Measuring aperture To supplement valVario routes or as Single product Size 1 Inlet: DN 20 (3/4") Output: DN 20 (3/4") Rp internal thread pu max. 500 mbar (7 psig) Basic (no accessories possible) Measuring nozzle Aperture diameter 10 mm
88600122	
Gdj40ro40	
Vg65a03nd93	
Van4o32r02n31	
74912692	
Bvg65/50z05	
Pfs778l-3/1t/N	
85231050	
Uvs 1	
Dg 6u-3	
Vg20r02lk061d	
Dg 150 U-3	
88000011	
Ifd 244-3/1w	Automatic burner control unit replaces Mat.No.84620025 + 84620035, compatible Ignites and monitors gas burners, for continuous operation, display for indicating program status and flame signal intensity, IP 54, EC type-tested and certified, FM and CSA approved Series 200 Ionization control

	Restart in the event of flame failure Safety time on start-up: 3 s Safety time during operation: 1 s Mains voltage: 230 V AC, 50/60 Hz Stat. Warennummer 90268020 Ursprungsland: DE
Zt42	
Dg50u-3	
88300180	
DI3a	
84367720	
Vg15/10r01t6	
Zkih 300/100r	pilot burner For safe ignition of gas burners, with forced air supply 300 mm in length Additional 100 mm Rp internal thread ZKIH 300 / 100R Pilot burner For safely igniting gas burners, with forced air supply Length: 300 mm Plus 100 mm Rp internal thread Stat. Lot number 84162080 Country of origin: DE
Vas115r/Nw	
Dm160z80-160	
Tzi 5/15/20r	
Vg20/25	
88300177	
Van120r/Nw	
Gdj25r04	
74105884	
Vg10r01n60	
74923048	
75442337	
Cg340r01-Dt2wf1	E2495 84742200 SIEHE ANHANG
Vas125n/Lqgr	
Rv40kf	
Kfm100	
Vr20r01nt31d(Ex.Vr20r01nt61d)	
84444970	DL 5AT Air-pressure switch For monitoring of air and flue gas pressures, for Overpressure Negative pressure and differential pressure, FM approved Adjustment range 0,2-2 ' WC (0,5-5 mbar)

[Cg 120r01-Vt2wf1](#)

compact unit The product contains' Substances of Very High Concern '(SVHC? S) in a concentration> 0.1 mass% acc. REACH contain. With filter or strainer, pressure regulator, Pressure switch, valve (s) and quantity setting for securing and regulating atmospheric Burners, forced draft burners, fan-assisted Boilers up to 400 kW, EC type tested and certified Size 120 Rp internal thread pu max. 100 mbar Adjustable ratio pressure regulator Mains voltage 220/240 V ~, 50/60 Hz 2 valves pressure switch filter CG 120R01-VT2WF1 Combination control There is / are 'Substances of Very High Concern concentration of more than 0.1 mass% contained in this product With filter or dirt trap, pressure regulator, pressure switch, valve (s) and flow adjustment for safeguarding and control of atmospheric burners, forced draft burners and fan-assisted boilers up to 400 kW, EC type-tested and certified Size 120 Rp internal thread pu max. 100 mbar Adjustable variable air / gas ra

[3155152](#)[88003382](#)[88000016](#)[84329111](#)[Dg 50 U-3](#)[Gb50f023](#)[88003923](#)[Gt50-30m20e](#)[Uvd1](#)[Tzi-7,5/100w](#)[Dg 150u-3](#)[Vgbf 40r40-3](#)[DI03a](#)