

Kromschrder

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Kromschrder Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Kromschrder Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
84444400	Pressure switch for air For monitoring air and flue gas pressures, for positive pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as "special-design pressure 90262080
Ifs 110im-5/1/1t	Automatic burner control New construction stage. Function and terminal assignment remain the same. *** Only for replacement *** Ignites and controls gas burners, for intermittent operation, with ionization or UV control, single-electrode operation possible, multi-flame control possible, EC type-tested and certified For grounded mains Fault lock-out in the event of flame failure Safety time on start-up: 5 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240 V AC, 50/60 Hz Stat. Warennummer 90268020 Ursprungsland: DE
Bcu 460-10/1lw3gbd2s3	Burner control, 400 series On-site housing, for control, ignition and monitoring from impulse-controlled, modulating or stage-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV probe UVS. Display of the Program status, device parameters and Flame signal. Manual mode. Diagnosis and adjustment of the Device parameters over optical interface and PC software BCSoft. EU certified, AGA, FM, EAC and CSA approved, certified for systems up to SIL 3 (corresponds to PL e). Standard version Safety time start-up tSA: 10 s Safety time operation tSB: 1 s Air valve control Mains voltage: 230 V ~, 50/60 Hz Ignition transformer TZI 7.5-12 / 100 Stat. Product number 85371098 Country of origin: DE
	BCU 460-10/1LW3GBD2S3 Burner control, 400 series On-site housing, for control, ignition and monitoring from impulse-controlled, modulating or stage-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation

88610183	with UV probe UVS. Display of the Program status, device parameters and Flame signal. Manual mode. Diagnosis and adjustment of the Device parameters over optical interface and PC software BCSoft. EU certified, AGA, FM, EAC and CSA approved, certified for systems up to SIL 3 (corresponds to PL e). Standard version Safety time start-up tSA: 10 s Safety time operation tSB: 1 s Air valve control Mains voltage: 230 V ~, 50/60 Hz Ignition transformer TZI 7.5-12 / 100 Stat. Product number 85371098 Country of origin: DE
84326116	
CG 30R03VW5CWZZ	Compact unit Dreizler version With sieve, two safety valves and Servo pressure regulator to secure and Rules of atmospheric burners, Forced draft burners, Fan-assisted boilers, EC type tested and certified Size 30 Special variant Stat. Product number 84814090 Country of origin: DE
elektrod ZMI 25L700	
DG50U-3	,2.5-50 MBAR,1/2,0-250V AC,COG GAS Pressure Switch
BCU 370WFEU0D3B1	88600953
IFD 244-5/1WI	Automatic burner control replaces mat.no. 84620046 + 84620056 + 84620059, compatible Ignites and monitors gas burners, for continuous operation, Ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization monitoring Restart after flame failure Start-up safety time: 5 s Safety time operation: 1 s Mains voltage 230 V ~, 50/60 Hz Integrated electronic ignition Stat. Lot number 90268020
VK 80F10T5A93D	85311060 Gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and Air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN 80 Flange according to ISO 7005 pu max. 1 bar Mains voltage 220/240 V ~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Screw plugs in the entrance and exit Amount adjustment Stat. Product number 84814090 Country of origin: DE
FMS 080-16	48115105 Flange mounting kit Nominal width: DN 80 / PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 pc Refalit gas seal, incl. WAZ HTB approval according to VP 401 HTB approved up to 5 bar incl. labeling 8 hexagon bolts, M16 nuts 14 U-washers, hardened, hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommendation of tightening torques calculated according to DIN 30690-1 Stat. Lot number: 90329000
IC 50-60W30TR10	For outputting rotary movements (0-90 °), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, Protection class IP 65 Series 50, with increased torque Running time 60 s / 90 ° Mains voltage 230 V ~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm Stat. Product number 85011010 Country of origin: DE
IFD 258-5/1W	gas burner control replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V ~, 50/60 Hz
BIO 140HB-100/35-(26)E	Burner for gas, for installation in burner quarl Burner size 140 Longer flame shape For natural gas 100 mm length of the steel tube from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Code number of the burner head 26 Construction status E Stat. Lot number 84162080 Country of origin: DE
BIO 125HB-100/35-(2)E	Burner for gas, for installation in burner quarl Burner size 125 Longer flame shape For natural gas 100 mm length of the steel tube from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Code number of the burner head 2 Construction status E

TZI 5-15/100W	Ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V ~
IFD 258-3/1W	Automatic burner control replaces mat. no. 84620610 IFS 258-3 / 1W, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after Flame failure, switchable Start-up safety time: 3 s Safety time operation: 1 s Mains voltage 230 V ~, 50/60 Hz
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Business, EC type tested and certified in conjunction with magpie Kromschrder automatic burner control units Series 10 Quartz glass thermal protection Rp 1/2 internal thread M20 screw connection Stat. Lot number 90275000
TZI 5-15/20W	
IFD244-5/1 WI	
GIK 25R02-5	
IFD 258-10/1Q	Automatic burner control replaces mat. no. 84620450, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type-tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Start-up safety time: 10 s Safety time operation: 1 s Mains voltage 120 V ~, 50/60 Hz Stat. Lot number 90268020 Country of origin: DE
ZKIH 150/100R	Pilot burner For the safe ignition of gas burners, with forced Air supply 150 mm length An additional 100 mm Rp internal thread
GRS 25R	To prevent creeping and sudden movements Backstep, for Gas, air and oxygen, DVGW tested and registered DN 25 G female thread pu max. 25 bar
84447250	DG 6U-3 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), negative pressure (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
BCU 580W C0F3U0D0K2-E	Burner control Control cabinet installation housing, for control, ignition and Monitoring of pulse-controlled, modulating or step-controlled Gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV probe UVS. Height Lifetime thanks to exchangeable power module for failsafe Outputs. Display of the program status, the Device parameters and des Flame signal. Manual operating mode. Diagnosis and Setting the Device parameters via optical interface and BCSoft PC software. Series: Version for pilot and main burners Market: EU certified, certified for systems up to SIL 3 (is equivalent to PL e) Mains voltage: 230 V ~, 50/60 Hz Valve proving system: No. Power control: air valve control Flame monitoring: With ionization or UV signal Stat. Lot number 90268020
OCU 500-1	Control unit For connection to a control unit (FCU 500 or BCU 500). depiction the device status in plain text, language switchable, Reading from Process values, statistics and parameter values, Control and Setting of connected throttle valves in Manual operation, for Fastening in a control cabinet door, protection class IP 65, suitable for 22 mm mounting grid, connection with the Control unit via 4-pin Control cable, cable length up to 10 m, suitable Connector parts in Scope of delivery of the OCU. 500 series German, English, French, Dutch, Italian, Spanish Stat. Lot number 90268020 Country of origin: DE
	Ignition transformer in the housing For high-voltage ignition of gas and oil

TGI 7-25/20W	burners High voltage 7 kV Output current 25 mA at 50 Hz Duty cycle 20% Mains voltage 230 V ~ Stat. Lot number 90268020 Country of origin: DE
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas / air) increases, negative pressure (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54 Stat. Lot number 90262080 Country of origin: DE
CG340R01 VT2WFIZ	
DG 6U-3	84447250 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 50U-3	Gas pressure switch 84447350 For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 50B-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP 54
DG 6U-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for setting the switching point, can be used as a " pressure monitor special Bauart ", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure increases (gas / air), vacuum (Air), differential pressure (air-air) Electrical connection: With 4-pin plug, without socket Stat. Lot number 90262080
QA 400Z100-160	Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 400 m3/h, measuring range: 32-650 m3/h(b) Intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulses/m3 pu max. 16 bar Stat. Warennummer
QA 40R25-40	Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 40 m3/h, measuring range: 3.3-65 m3/h(b), Rp internal thread, DN 25, E1: 10 pulses/m3, E200: 500 pulses/m3 pu max. 4 bar, for gas and air Stat. Warennummer 90281000 Ursprungsland: SK
TC 218 R05T	TC 218R05T K 220/240VAC 10VA IP54 Pmax 500 mbar
VAS 115R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws Stat. Lot number 84818099 Country of origin: DE
VAH 115R/NWBE	Flow rate controller with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Valve seat: Reduced Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws

DG 10U-3T	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 1-10 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54 Feedback: Blue control lamp for 230 V~ Stat. Commodity number 90262080
VAS 125R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws Stat. Lot number 84818099
VAH 125R/NWAE	Flow rate controller with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the left side of the junction box: connector for Valve (3 pole) Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Stat. Lot number 84818059
DG 50B-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
IC 20-60W3E	88300077 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010 Country of origin: DE
IC 20-30W3E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
74921672	Adaptersatz IC20/IC40 auf DKG/DKL /B
74921671	Mounting kit IC20/IC40 single application /B accessories
IC 40A2A	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 40, parameterizable via optical interface Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68001, operating mode 06, 3-stage operation with one or two digital inputs, running time: 6 s Stat. Commodity number 85011010 Country of origin: DE
88202695	VAS 665F05LW3B/PP/PP gas solenoid valve For automatic shut-off, normally closed, for Natural gas, LPG and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 6 Nominal width: DN 65 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: slowly opening, fast closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the left side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, exit: screw plug Accessories on the left, input: screw plug Stat. Lot number 84818079 Country of origin: DE

DG 150B-3	84447400 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
ZMI 16B800R	ionization ignition burner With an ignition and monitoring electrode to be on the safe side ignition of Gas burners, with forced air supply 16mm burner size For natural gas 800mm length Rp internal thread Stat. Commodity number 84162080 Country of origin: DE
ZMI 16B800R	
DL 3A-3	air pressure switch For monitoring air and flue gas pressures, for overpressure, Vacuum and differential pressure, EU certified Setting range: 0.2-3 mbar, can be used as a "pressure switch". special Type" Housing: With threaded connection Rp 1/4 and Hose connection with handwheel Electrical connection: With screw terminals Stat. Commodity number 90262080 Country of origin: DE
IFC 120/20R05-20MMPP/20-60W3TR10	Linear actuator with actuator To control continuously regulated combustion processes, linear Relationship between input signal and flow rate, Turndown ratio 25:1, for Gas and air, EU certified Size: 1 Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 test sockets Accessories on the left: 2 locking screws Actuator: IC 20 Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Stat. Commodity number 85011010 Country of origin: DE
DG 150U-3	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
IFD 258-10/1W	gas burner control replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
TC 2R05W/W	tightness control To check two safety valves upstream and/or after burner run, with adjustable measuring time (5-30 s) to adapt to different test volume, leak rates and inlet pressures, EU certified For fast opening individual valves Rp internal thread PU max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz Stat. Commodity number 90262020 Country of origin: DE
IFD 258-10/1W	84621650 A.1520-008838 FW01AF CE-0063BT1310
ZAI K 84228010	Atmospheric ionization pilot burner For safe ignition of gas burners, power approx. 3 kW Tapered ring screw connection for 8 mm pipe, supplied loose Stat. Commodity number 84162080 Country of origin: DE
IFD 258-5/1W	
TC 410-1T 84765810	tightness control Within the scope of European directives, this product only used for substitute purposes. For checking two safety valves, with adjustable test duration for adapting to different test volumes, leak rates and inlet pressures, for fast opening valves, EC type tested and certified In the plug-in housing Check before or after burner run External pressure switch Test duration: 10-60 s Mains voltage 220/240 V~, 50/60 Hz
TSC 100B065-300/35-Si-1500	Ceramic tube set for BIC burners Made of silicon carbide, with seal Burner size 100 Conical shape Outlet diameter 65 mm Length 300mm 35 mm distance between the furnace flange and the front edge of the burner disc SiC infiltrated with silicon Up to 1500 °C (melting point silicon 1380 °C)

BIC 100HB-0/35-(37)E	Gas burner with connection for ceramic tube Burner size 100 Longer flame shape For natural gas 0 mm length of the steel pipe from the furnace flange 35 mm distance between the furnace flange and the front edge of the burner head Burner head identification number 37 Construction status E
BCU 460W3P2C0D0000K1E1-/LM400WF000E1-	burner control On-site housing, for controlling, firing and monitoring from pulse-controlled, modulating or stage-controlled gas burners. For Continuous operation with ionization monitoring or UV monitoring with UV probe UVD. Intermittent operation with UV sensor UVS. display of program status, the device parameters and the flame signal. manual operation mode. Diagnosis and adjustment of device parameters above optical interface and BCSoft PC software. EU certified, FM and EAC approved, certified for systems up to SIL 3 (corresponds to PL e). Series: standard version Mains voltage: 230 V~, 50/60 Hz Ignition transformer: 8 kV, 12 mA, ED 100% Flange plate: M32 Valve monitoring system: None High Temperature Operation: None Input function: None
ZE 14-12 A1 35mm	spark plug Thread M 14 x 1.25, thread length 12 mm Total length of wire from end of thread 35 mm Central electrode Kanthal A1, D= 3.5 mm Beru - No. 0009.340.040
Connex L.Spannst. L4X40 1.4568 annealed	Connex L.Spannst.
UV photo cell (P 578) for UVS	Accessories new order no. for 04065304
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
BR 140 L35	Elektr.Stab
TGI 5-15/100R	Ignition transformer in the housing For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 115 V~
ARP GAS REGULATOR VALVE GIK 65F02-6	KROMSCHODER GIK 65F02-6 AIR/GAS RATIO CONTROL DN65, PU MAX 200 MBAR
ARP GAS REGULATOR VALVE GIK 15R02-5	GIK 15R02-5 AIR/GAS RATIO VALVE, RP THREAD, 200 MBAR
48115104	FMS 065-16 flange mounting kit Nominal width: DN 65 /PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 4 hexagonal screws, nuts M16, 6 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690_1
ZKIH 300/100R	pilot burner For safe ignition of gas burners, with compulsory air supply 300mm length Additional 100mm Rp internal thread
BIO 125HB-500/435-(2)E	Burner for gas, for installation in burner quarl Burner size 125 Longer flame shape For natural gas 500 mm length of the steel pipe from the furnace flange 435 mm distance between the furnace flange and the front edge of the burner head Identification number of burner head 2 Construction status E
sealing block assembly VPS8/05LKG	
TZI 7,5-12/100W	ignition transformer new order no. for 34331383 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ Stat. Commodity number 85043200 Country of origin: DE
UVS 10D0G1 843 15200	
74960445 UV TUBE FOR UVS 10	
74960611	

DG10U-3 84447300	
TC318R05T (84765710) 220/240VAC	
DG50U-3 84447350	
DG150U-3 84447500	
GT 50-30 T 20 E (16302441)	
DG10U-5 84447306	
DG150U-5 84447506	
BCU460-3/1W3 GBU	
DG6U-6 84447251	
IC40A2A 74105751 100-230V 8.4VA	
TC410-10/230V50Hz 100 BIS 600SEC	
IFD 258-5/1W	84621630 gas burner control replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
TZI 5-15/100W 230V 50-60Hz 5KV 15mA	
IFS 110IM-3/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent operation, Ionization or UV monitoring, single-electrode operation possible, multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 3 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
IC 40A2A	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 40, parameterizable via optical interface Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68001, operating mode 06, 3-stage operation with one or two digital inputs, running time: 6 s Stat. Commodity number 85011010 Country of origin: DE
74918602	Test connection G1/4 Ms+AFM /B Gauge connection made of MS with seal Stat. Commodity number 90329000 Country of origin: DE
03175467	Socket EN 10242-M2-1/2-Zn-A sleeve Stat. Commodity number 90329000 Country of origin: QU
61006050	Alternative high pressure welding sleeve A-G 1/2"x 35 mm PN 100 Material C22.8N (P250GH)
61006051	Alternativ Screw for high-pressure welding sleeve G 1/2", galvanized steel with copper sealing ring
TZI 5-15/100W	ignition transformer new order no. for 34331381 For high-voltage ignition of gas and oil burners High voltage 5kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ Stat. Commodity number 85043200 Country of origin: DE
VGBF 50..40	74922193 Spare parts pack consisting of membranes, O-rings and Insert-k. Stat. Commodity number 90329000 Country of origin: SK

VAS 115R/LW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Slow opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Accessories on the right: 2 test points pu and pd Accessories left: 2 test points pu and pd
BIO 50HB-300/235-(37)D	Burner for gas, for installation in burner quarl Burner size 50 Longer flame shape For natural gas 300 mm length of the steel pipe from the furnace flange 235 mm distance between the furnace flange and the front edge of the burner head Burner head identification number 37 Construction status D
BIO 65HB-300/235-(34)E	Burner for gas, for installation in burner quarl Burner size 65 Longer flame shape For natural gas 300 mm length of the steel pipe from the furnace flange 235 mm distance between the furnace flange and the front edge of the burner head Identification number of the burner head 34 Construction status E
IFD 258-3/1W	gas burner control replaces mat. no. 84620610 IFS 258-3/1W, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
IBA 125Z05/40A2A	Throttle valve for air with actuator For continuous or stepped control of a volume flow Nominal diameter: DN 125 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 500 mbar (200" WC) Type: Penetrating Actuator: IC 40 Running time: Adjustable from 4.5 to max. 75 s Mains voltage: 120-230 V~, 50/60 Hz Torque: 2Nm Control: analogue input 4-20 mA and digital inputs Parameter set: 68026, operating mode 21, 2-point operation, Running time: 7.5s Consisting of: 88300104 88300087 Stat. Commodity number 85011010 Country of origin: DE
IC 20-30W3E	88300076 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010 Country of origin: DE
VK 100F10T5A93D	85311070 gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN100 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting
VFC 125/25R05-20MMPP	linear actuator To control continuously regulated combustion processes, linear relationship between input signal and flow rate, Turndown ratio 25:1, for Gas and air, EU certified Size: 1 Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Cylinder: 20 Accessories on the right: 2 test sockets Accessories on the left: 2 locking screws Stat. Commodity number 85011010 Country of origin: DE
GIK 65F02-6	equal pressure regulator To keep a constant pressure ratio of 1:1 DN 65 Flange according to ISO 7005 PU max. 200 mbar Test sockets in the inlet and outlet For gas, EC type tested and certified Stat. Commodity number 90322000 Country of origin: SK
FMS 065-16	flange mounting kit Nominal width: DN 65 /PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 4 hexagonal screws, nuts M16, 6 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690_1 Stat. Commodity number: 9032900

DG 60VC5-5W	gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 10-60 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact Stat. Commodity number 90262080 Country of origin: DE
DG 500VC5-5W	gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 150-500 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact
UVS 10D4G1	UV probe 84315204 ur monitoring of gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass UVS 1 adapter (28 mm (1.1")) M20 screw connection Stat. Commodity number 90275000 Country of origin: SK
86414 SET Membrane	Ersatz C50 + C52 / SET Diaphragm replacement C50 + C52
GFK 50R10-6	With filter mat made of random fiber fleece (polypropylene), for clean from gas (natural gas, town gas, liquid gas, biogas) and air, EC type tested and certified DN 50 Rp internal thread PU max. 1 bar Test sockets in the input and output
IFS 110IM-10/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 10 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz
IFS 110IM-10/1/1N	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 10 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 110/120 V~, 50/60 Hz
PRESSURE SPANNER KROMSCHÖDER DG6U-3	
BCU480-3/10/1LW1GB	88610728
DG 50 U-3 2,5-50mbar	
DG 60VC5-5W	84448230 gas pressure switch For monitoring gas and air pressures, also for Biogas, factory set switching point, EC type tested and certified Setting range 10-60 mbar Switching point adjustable via hand wheel Compact design Rp 1/4 internal thread El. Connection with 4-pin plug, without socket changeover contact
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
VGBF 80F40-3	gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
VP57/05NW 3	ventil
	Electronic pressure gauge Art: 03352142 -1000 to +1000 mbar. For measuring pressure, negative pressure and differential pressure of air and gaseous non-aggressive gases, digital display, switchable pressure units,

DMG S2610	hold function for current measured value, display of smallest and largest measured value, Soft plastic protective case with holding magnet Measuring range: ± 1000 mbar, accuracy: $\pm 1.0\%$ of Measured value, resolution: 0.01 (to 199.9); 0.1 (from 200) mbar, max. overpressure: 3 bar
IC 50-60W30E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Steady control
TZI 7,5-12/100W	84331383 ignition transformer new order no. for 34331383 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
GIK 25R02-5	03155134 equal pressure regulator To keep a constant pressure ratio of 1:1 DN 25 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified
DG 150U-3	84447500 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 50U-3	84447350 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), vacuum (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
VK 80F10T5A93D	85311060 Gas Motorventil For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN 80 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting
FMS 080-16 flange mounting kit (optional)	48115105 Nominal width: DN 80 /PN 16 according to DIN 30690-1 and DVGW Information G19 consisting of: 1 piece Refalit - gas seal, incl. WAZ HTB approval according to VP 401 up to 5 bar HTB approved including marking 8 hexagonal screws, nuts M16 14 washers, hardened hardness class 200 HV and 2 serrated lock washers, DIN 6798, incl. recommended tightening torques calculated according to DIN 30690-1
DKR 50Z03H450D	72701260 Ring damper for air and flue gas For continuous control of a volume flow DN 50 Installation between two DIN flanges PU max. 300 mbar With manual adjustment Temperature range 450°C resounding
FDU 510W1T2/1O1-0K1	84368012 Flame Warden For flame signalling, EU certified Series: For intermittent operation Mains voltage: 230 V~, 50/60 Hz Flame control: ionization Switch-off threshold: 2 micro A Response time after flame failure: 1 s Flame signal: 1 NC, 1 NO contact Flame Signal Strength: No output Connection plug: With screw terminals
TC 410-10T	84765820 tightness control External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz Within the scope of European directives, this product may only be used for replacement purposes. For checking two safety valves, with an adjustable test duration to adapt to different test volumes, leak rates and inlet pressures, for quick-opening valves, EC type tested and certified. In the plug-in housing Check before or after burner run
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschroder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
	Balanced pressure regulator with solenoid valve For securing and

VAG 2-/40R/NWAE	regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: Without inlet flange Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs
VA62-/40R/NWAE	
IC 20-60W3TR10	actuator 88300069 For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 60 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Three-point step control Feedback potentiometer: 1000 ohms
BIO 140RB-50/35-(47)E	Article number: 84008018 Electric rod BR 140 L35 74330411
Electric rod BR 140 L35	
IFD 258-10/1W	gas burner control replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series Ionization or UV monitoring Immediate lockout or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
VGBF 40R40-3	Gas pressure regulator Spring, with a form compensation membrane and Zero degree, to Constant keeping of the adjustable pressure DN 40 RP inside thread PU max. 4 bar Closure screw in the entrance and output Checked and certified for gas, EC patterns Set to 20 mbar (range 10-30 mbar)
MHP32/7417	
QA 400Z100-160	flow meter For non-calibratable gas metering, display of consumed quantity, with pulse generators E1 and E200 Nominal flow: 400 m3/h Measuring range 32-650 m3/h(b) intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulse/m3 PU max. 16 bar QA 400Z100-160 Flow meters For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 400 m3/h, measuring range: 32-650 m3/h(b) Intermediate flange DN 100, E1: 1 pulse/m3, E200: 187.5 pulses/m3 PU max. 16 bar
IC 50-60W30E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Steady control
REFALIT flange seal DN 100 - HTB PN 10/16	DIN 2690, without bores, 115 x 162 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
VAS 120R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
IC 50-15W15TR10	74215213 Actuator To submit rotating movements (0-90 °), for activity From gas and Air flaps, position feedback via external readable Position indicator, Protection class IP 65 50 series 50, with increased torque Duration 15 S/90 ° Network voltage 230 V ~, 50/60 Hz Torque 15 Nm Three-point step control Corpus potentiometer 1000 ohms
MC202-D00/MC202-F10	

DG 150U-3	84447500 Gas pressure To monitor gas and air pressing, also for Biogas, with a handwheel for switching point setting, can be used as " print monitor special Bauart ", EU certified Setting range: 30-150 mbar Function: switches with increasing overpressure (gas/air), negative pressure (Air), differential pressure (air air) Electrical connection: with screw terminals and M16 cable screw connection, IP 54
IC 20-30W3TR10	88300068 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Three-point step control Feedback potentiometer: 1000 ohms
DG 50U-6	84447351 gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, with socket
IC 20-30W3E	88300076 actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control Stat. Commodity number 85011010900 Country of origin: DE
VG40R02	
QA 25R25-40	47102525 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 25 m3/h, measuring range: 2.5-40 m3/h(b) Rp internal thread DN 25, E1: 10 pulses/m3, E200: 500 pulses/m3 pu max. 4 bar, for gas and air
GIK 25R02-5	03155134 equal pressure regulator To keep a constant pressure ratio of 1:1 DN 25 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified
GFK 25/32	Spare parts pack, consisting of 10 filter mats and 10 O-rings
TC 410-1T	tightness control 84765810 Within the scope of European directives, this product only used for substitute purposes. For checking two safety valves, with adjustable test duration for adapting to different test volumes, leak rates and inlet pressures, for fast opening valves, EC type tested and certified In the plug-in housing Check before or after burner run External pressure switch Test duration: 10-60 s Mains voltage 220/240 V~, 50/60 Hz
74960445 UV photo cell (P 578) for UVS accessories	new order no. for 04065304
DM25R25-40	
VAS 125R/NW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
GIK 50R02-5	equal pressure regulator To keep a constant pressure ratio of 1:1 DN 50 Rp internal thread PU max. 200 mbar Test point in the outlet For gas, EC type tested and certified
BVA 100Z05	Drosselklappe fr Luft Zur stetigen oder stufenen Regelung eines Volumenstroms Nennweite: DN 100 Rohranschluss: Einbau zwischen zwei DIN-Flansche Eingangsdruck: pu max.
IC 20-15W3E	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection

	class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
IC 50-60W30TR10	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm
IC 50-60W30TR10	actuator For rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable position indicator, Degree of protection IP 65 Series 50, with increased torque Running time 60 s/90° Mains voltage 230 V~, 50/60 Hz Torque 30 Nm Three-point step control Feedback potentiometer 1000 Ohm
BCU 370.....I1	
GT50-60T20 (16302311)	
IFD 454-10/1/1T	
TZI 7,5-12/100W (Discontinued part)	Ignition transformer new order no. for 34331383 For high-voltage ignition of gas and oil burners High voltage 7.5 kV Output current 12 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~ Stat. Commodity number 85043200 Country of origin: DE
VAG 125R/NWAE	Gleichdruckregler mit Magnetventil Zum Sichern und Regeln des Gasdruckes, Druckregler Klasse A nach EN 88, Magnetventil Klasse A nach EN 161, für Gas und Luft, auch für Biogas, pu max. 500 mbar (7 psig), mit Kontroll-Lampe, IP 65 Baugröße: 1 Zertifizierung: EU-zertifiziert Eingang: DN 25 (1") Ausgang: DN 25 (1") Rohranschluss: Rp-Innengewinde Öffnungsverhalten: Schnell öffnend, schnell schließend Netzspannung: 230 V~, 50/60 Hz Elektrischer Anschluss: M20-Verschraubung Ventilsitz: Normal Anschluss-Set für Luft-Steuerdruck psa: 1 Klemmring-Verschraubung, 2 Mess-Stutzen pd und psa Zubehör rechts: 2 Verschluss-Schrauben
75421971	Spring 10-30 mbar, red Spring (red) for GBF 40, VGBF 25-40 (10-30 mbar) and VAR 25-40 (10-25 mbar) for outlet pressure changes for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 10 - 30 mbar for VAR 25 and VAR 40, Outlet pressure range 10 - 25 mbar
75421980	Spring 25-45 mbar, yellow Spring (yellow) for GBF 40, VGBF 25-40 (25-45 mbar) and VAR 25-40 (26-40 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 25 - 45 mbar for VAR 25 and VAR 40, Outlet pressure range 26 - 40 mbar
75421990	Spring 40-60 mbar, green Spring (green) for GBF 40, VGBF 25-40 (40-60 mbar) and VAR 25-40 (41-55 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 40 - 60 mbar for VAR 25 and VAR 40, Outlet pressure range 41 - 55 mbar
75422000	Feder 55-75 mbar, blau Feder (blau) für GBF 40, VGBF 25-40 (55-75 mbar) and VAR 25-40 (56-70 mbar) für Ausgangsdruck-Umstellungen: für GBF 40, VGBF 25 und VGBF 40, Ausgangsdruckbereich 55 - 75 mbar für VAR 25 und VAR 40, Ausgangsdruckbereich 56 - 70 mbar
75422010	Spring 70-90 mbar, black Spring (black) for GBF 40, VGBF 25-40 (70-90 mbar) and VAR 25-40 (71-86 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 70 - 90 mbar for VAR 25 and VAR 40, Outlet pressure range 71 - 85 mbar
VAS 120R/LW	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Outlet: DN 20 (3/4") Pipe connection: Rp internal thread Opening behaviour: Slow opening, fast closing Quantity setting: With quantity setting Mains voltage: 230 V~,

	50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
GRSF 25R	03150674 Non-return gas safety device, flameproof at combustion with air To prevent creeping and sudden Gas withdrawal, for Gas, air and oxygen, DVGW tested and registered DN 25 G internal thread Flameproof up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar city gas, hydrogen
Spring 85-105 mbar, white	Spring (white) for GBF 40, VGBF 25-40 (85-105 mbar) and VAR 25-40 (86-100 mbar) for outlet pressure changes: for GBF 40, VGBF 25 and VGBF 40, Outlet pressure range 85 - 105 mbar for VAR 25 and VAR 40, Outlet pressure range 86 - 100 mbar
VGP 20R01W6	gas solenoid valve For automatic shut-off, normally closed, fast opening, fast closing, for natural gas, town gas, liquid gas, biogas and air, Class A according to EN 161, EC type tested and certified DN 20 Rp internal thread PU max. 150 mbar Mains voltage 230 V~, 50/60 Hz Connection with rectifier adapter and standard socket
QA 65Z50-40	Durchflußmengenähler Zur nichteichpflichtigen Gasmengenählung, Anzeige der verbrauchten Menge, mit Impulsgebern E1 und E200 Nenndurchfluss: 65 m3/h Messbereich 6-100 m3/h(b) Zwischenflansch DN 50, E1: 1 Imp/m3, E200: 250 Imp/m3 pu max. 4 bar, für Gas und Luft QA 65Z50-40 Flow meter For metering gas where no calibration is required, display of the quantity consumed, with E1 and E200 pulse generators Nominal flow rate: 65 m3/h, measuring range: 6-100 m3/h(b) Intermediate flange DN 50, E1: 1 pulse/m3, E200: 250 pulses/m3 pu max. 4 bar, for gas and air
BCU480-5/3/1 LW3G	
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
REFALIT flange seal DN 50 - HTB PN 10/16	DIN 2690, without bores, 61 x 107 x 2.0 mm, code. according to DIN 30690-1: date of manufacture, material, 2.2 certificate and torque calculation for screws 5.6 for flange connections according to DIN 30690-1 and DVGW Information Gas No. 19
Length compensation GRSF 25R	gas non-return device For use with GRSF 25R (03150674) for exchange GRSF 25R50 (03150645) Overall length 174 mm DN 25 G male/female thread PU max. 5 bar
QAe 250Z100-40	Flow meter with electronic counter header For non-calibratable gas metering, display of consumed quantity, key date value, key date, instantaneous flow and High resolution of the amount consumed, with a pulser E200 Nominal flow: 250 m3/h Measuring range 20-400 m3/h(b) intermediate flange DN 100, E200: 187.5 imp/m3 pu max. 4 bar, for gas and air Interface for M-Bus QAE 250Z100-40 Flow meter with electronic counter head For metering gas where no calibration is required, display of the quantity consumed, key date value, key date, current flow guess and high resolution of the quantity consumed, with E200 pulse generator Nominal flow rate: 250 m3/h, measuring range: 20-400 m3/h(b) Intermediate flange DN 100, E200: 187.5 pulses/m3 pu max. 4 bar, for gas and air M-Bus interface
UVS 10D0G1	UV probe For monitoring gas burners in intermittent Operation, EC type tested and certified in connection with magpie Kromschöder automatic gas burners Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
UVS.10D0G1	
74921998	Find VA2 /B
DG 150B-3 84447400	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 30-150 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number

	90262080 Country of origin: DE
DG 500B 84447450	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 100-500 mbar Function: Switches when overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Stat. Commodity number 90262080 Country of origin: DE
DG 50U-3 84447350	gas pressure switch For monitoring gas and air pressures, also for Biogas, with hand wheel for switching point adjustment, can be used as a "pressure switch". special Type", EU-certified Setting range: 2.5-50 mbar Function: Switches with increasing overpressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
BIO 125HB 35	
BIO 125HB 35 / repair kit set	
DL 3A-3	air pressure switch For monitoring air and flue gas pressures, for overpressure, Vacuum and differential pressure, EU certified Setting range: 0.2-3 mbar, can be used as a "pressure switch". special Design type" Housing: With threaded connection Rp 1/4 and Hose connection with handwheel Electrical connection: With screw terminals
VAS 115R/NQ	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
VAA 240R/NQ	Air Solenoid Valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
TC 3R05W/W	tightness control To check two safety valves upstream and/or after burner run, with adjustable measuring time (5-30 s) to adapt to different test volume, leak rates and inlet pressures, EU certified For fast or slow opening individual valves Rp internal thread PU max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz
UVC 1D1G1A	UV flame detector For continuous operation to monitor gas burners in connection with Kromschöder burner controls BCU or PFU..U. series 1 Thermal protection made of quartz glass Rp 1/2 internal thread and cooling air connection M20 screw connection Mains voltage 100-230 V~, 50/60 Hz
PFF 704T/N	Flame Warden Within the scope of European directives, this product only used for substitute purposes. For flame signaling or for Multi-flame control with PFS/PFD Series 700 For intermittent operation, ionization or UV monitoring With 4 independent flame monitors Switchable from 220/240 V~ to 110/120 V~, 50/60 Hz, for grounded or floating networks
GFK 65F10-6	gas filter With filter mat made of random fiber fleece (polypropylene), for clean from gas (natural gas, town gas, liquid gas, biogas) and air, EC type tested and certified DN 65 Flange according to ISO 7005 PU max. 1 bar Test sockets in the input and output
Spare parts pack GRP 65	Spare parts pack, consisting of 1 filter mat and 1 O-ring
TZI 7,5-20/33W	IGNITION TRANSFORMER new order no. for 34326116 For high-voltage ignition of gas and oil burners High voltage 7.5kV Output current 20 mA at 50 Hz Duty cycle 33%, mains voltage 230 V~
VALF VAS125-R/NW+VAH1-/NWAE+VMV1-/25R05I	VAS125-/R/NW VAH1-/NWAE VMV1-/25R05I REQUIRED AS COMBINED, ASSEMBLED. INPUT - OUTPUT THREAD WILL BE ON DN25 CONNECTION

VG 15/12R18NT31	FLANES. IMAGES ARE ATTACHED gas solenoid valve For automatic shut-off, normally closed, for Natural gas, town gas, liquid gas and air, class A according to EN 161, EC type tested and certified DN 15/15 Rp internal thread PU max. 1.8 bar Quick opening, quick closing 220/240V~, 50/60Hz Junction box with terminals, IP 54 Locking screw in the entrance Stat. Commodity number 84814090 Country of origin: SK
UV photo cell (P 578) for UVS accessories	74960445
VAG 240R/NWAE	Balanced pressure regulator with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 2 Certification: EU certified Inlet: DN 40 (1 1/2") Outlet: DN 40 (1 1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve Seat: Normal Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs
VK 100F10T5A93D	85311070 gas engine valve For automatic shut-off, normally closed, slowly opening, fast closing, for natural gas, town gas, liquid gas and air, too suitable for biogas and landfill gas, class A according to EN 161, EC type tested and certified DN100 Flange according to ISO 7005 PU max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISI Metal junction box with terminals, IP 54 Locking screws in the input and output quantity setting Stat. Commodity number 84814090 Country of origin: DE
VGBF 80F05-3	86050220 gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 0.5 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
spring 5-12.5 mbar, -	75426230 Spring for GBF 80 and VGBF 80 for outlet pressure changes for GBF 80 and VGBF 80, packed in a bag, with Additional plate for changed outlet pressure, Outlet pressure range 5 - 12.5 mbar
IFD 244-3/1W	art nr 84621025 gas burner control replaces mat. no. 84620025 + 84620035, compatible Ignites and monitors gas burners, for continuous operation, ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved 200 series ionization monitoring Restart after flame failure Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz Stat. Item number 90268020 Country of origin: DE
VGBF 50F40-3	gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 50 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
Spring 220-350 mbar, black/green	Spring (black/green) for VGBF 50 (220- 350 mbar) and VAR (221-340 mbar) for outlet pressure changes: for VGBF 50, Outlet pressure range 220 - 350 mbar for VAR 50, Outlet pressure range 221 - 340 mbar
VAG 115R/NWBE	Balanced pressure regulator with solenoid valve For securing and regulating the gas pressure, pressure regulator Class A according to EN 88, class A solenoid valve according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Valve seat: Reduced Connection set for air control pressure psa: 1 Compression fitting, 2 Test nozzles pd and psa Accessories on the right: 2 screw plugs Stat. Lot number 84818059 Country of origin: DE
VMV 115R05P	fine adjustment valve To supplement valVario routes or as a single product Size: 1 Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Pipe connection: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Housing

	type: Basic (no accessories possible) Accessories above: screw plugs
VAG115R/NWBE 8	
IFS 110IM-3/1/1T	gas burner control New construction status. Function and pin assignment are stayed the same. Within the scope of European directives, this product only used for substitute purposes. Ignites and monitors gas burners, for intermittent Operation, Ionization or UV monitoring, single-electrode operation possible, Multi-flame monitoring possible, EC type tested and certified For grounded networks Lockout after flame failure Safety time start-up: 3 s Safety time operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V~, 50/60 Hz
G650 Elster	turbine type EK220 in combination with gas meter box
VAS 125R/NQ	gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Outlet: DN 25 (1") Pipe connection: Rp internal thread Opening behaviour: Quick opening, quick closing Quantity setting: With quantity setting Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 screw plugs Accessories on the left: 2 locking screws
VGFB 80F40-3Z *Price + FertNote*	gas pressure regulator Outlet pressure adjusted on customer request If pressure is missing, set to standard 20 mbar Spring-loaded, with pre-pressure compensation membrane and zero degree, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 PU max. 4 bar Locking screw in the input and output For gas, EC type tested and certified Special outlet pressure range Wh:150-230mbar pe:4bar Pas:160
JSAV 80F40-0 shut off	
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
GDJ 50R04-4	03155040 Pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 50 Rp internal thread pu max. 400 mbar Measuring nozzle in the entrance For gas, EC type tested and certified Set to 20 mbar Stat. Commodity number 90322000900 Country of origin: SK
03089206	Spare parts pack GDJ/GIK 50 (EXISTING A MEMBR. AND SEAL) Stat. Commodity number 90329000900
VGFB 80F40-3	Gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero termination, for Keeping the adjustable pressure constant DN 80 Flange according to ISO 7005 pu max. 4 bar Closing screw in the entrance and exit For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar)
DG 6UG-3	84447270 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP54
IFD 258-10/1W	84621650 Gas burner control unit replaces mat. no. 84620650, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
	Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame

IFD 258-5/1W	signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
DG 50U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG6U-3	84447250 DG 6U-3 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 10UG-4	Gas pressure switch IP65 / Kapsto cone plug in the lower part, Gold contacts 24/250V For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 1-10 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP65
UVC 1D0G1A	84320305 UV flame detector For continuous operation to monitor gas burners in connection with Kromschröder burner controls BCU or PFU..U. Series 1 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection Mains voltage 100-230 V~, 50/60 Hz
DG 50U-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With 4-pin plug, without Power outlet
BIC 50-65-100	SURVEILLANCE FITTING 24 MM, 6 CORNER, Ø 16 GLASS ORDER NO:50.62.110
BR.Eins.k BR 165RB 35 (17)	74970431
VG 40/33R10NT33	Gas solenoid valve For automatic locking, closed without power, for Natural gas, Town gas, liquid gas and air, class A according to EN 161, EC model tested and certified DN 40/33 Rp internal thread pu max. 1 bar Quick opening, quick closing 220/240V~, 50/60Hz Connection box with terminals, IP 54 Closing screw in the inlet and outlet
TC 1C05W/W	Leak check 84765552 To check two safety valves before and/or after burner run, with adjustable measuring time (5-30 s) for adjustment different Test volume, leak rates and inlet pressures, EU certified For cultivation on CG pu max. 500 mbar Mains voltage: 230 V~, 50/60 Hz Control voltage 230 V~, 50/60 Hz
VAD 115R/NW-25B	Pressure regulator with solenoid valve To secure and regulate the gas pressure, pressure regulator Class A according to EN 88, solenoid valve class A according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65, FM and CSA approved Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the right side of the connection box: plug for Valve (3 pole) Output pressure range: 2.5-25 mbar
VK 50F10T5A93D	Gas engine valve 85311040 For automatic locking, closed without power, opening slowly, quick closing, for natural gas, town gas, liquid gas and Air, too Suitable for biogas and landfill gas, class A according to EN 161, EC model tested and certified DN 50 Flange according to ISO 7005 pu max. 1 bar Mains voltage 220/240 V~, 50 Hz Valve housing AISi Metal connection

	box with terminals, IP 54 Closing screws in the entrance and exit Quantity setting
TC 410-10T	Leak check This is permitted within the scope of European directives product only be used for replacement purposes. For checking two safety valves, with adjustable Test duration to adapt to different test volumes and leak rates and Inlet pressures, for quick opening valves, EC type tested and certified In the plug-in housing Test before or after the burner runs External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz
GDJ 25R04-0L	Pressure regulator 03155033 Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 25 Rp internal thread pu max. 400 mbar Without measuring point Just for air Set to 20 mbar
TC 410-10T	Leak check 84765820 This is permitted within the scope of European directives product only be used for replacement purposes. For checking two safety valves, with adjustable Test duration to adapt to different test volumes and leak rates and Inlet pressures, for quick opening valves, EC type tested and certified In the plug-in housing Test before or after the burner runs External pressure switch Test duration: 100-600 s Mains voltage 220/240 V~, 50/60 Hz
VGBF 40R40-3	Gas pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero termination, for Keeping the adjustable pressure constant DN 40 Rp internal thread pu max. 4 bar Closing screw in the entrance and exit For gas, EC type tested and certified Set to 20 mbar (range 10-30 mbar) Stat. Commodity number 90322000 Country of origin: SK
VAS 120R/NW	Gas solenoid valve 88000004 pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 20 (3/4") Output: DN 20 (3/4") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
IC 20-30W3TR10	88300068 Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: three-point step control Feedback potentiometer: 1000 ohms
BVA 50Z05	88300100 Throttle valve for air For continuous or step control of a volume flow Nominal diameter: DN 50 Pipe connection: Installation between two DIN flanges Inlet pressure: pu max. 500 mbar (200 "WC) Design: Penetrating
DG 50UG-6K2	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With 4-pin plug, with socket Feedback: Red/green control LED for 24 V~/=
DG 500U-3	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 100-500 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 150UG-3K2	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 30-150 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With screw terminals and M16 cable gland, IP54

Feedback: Red/green control LED for 24 V~/=	
SWITCH DG 150U-6	
SWITCH DG6U-6 (84447251) 0.5-6.5 MBAR	
GIK 20R02-5	Constant pressure regulator To maintain a constant pressure ratio of 1:1 DN 20 Rp internal thread pu max. 200 mbar Measuring nozzle in the outlet For gas, EC type tested and certified Stat. Commodity number 90322000
84768505	CG 25R03VW5CWZZ
75438978	Spring 100-160 mbar, black/red Spring (black/red) for VGBF 25-40 (100-160 mbar) and VAR 25-40 (101-150 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 100 - 160 mbar for VAR 25 and VAR 40, Output pressure range 101 - 150 mbar
7542197	Spring 10-30 mbar, red Spring (red) for GBF 40, VGBF 25-40 (10-30 mbar) and VAR 25-40 (10-25 mbar) for output pressure changes for GBF 40, VGBF 25 and VGBF 40, Output pressure range 10 - 30 mbar for VAR 25 and VAR 40, Output pressure range 10 - 25 mbar
75421980	Spring 25-45 mbar, yellow Spring (yellow) for GBF 40, VGBF 25-40 (25-45 mbar) and VAR 25-40 (26-40 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 25 - 45 mbar for VAR 25 and VAR 40, Output pressure range 26 - 40 mbar
75421990	Spring 40-60 mbar, green Spring (green) for GBF 40, VGBF 25-40 (40-60 mbar) and VAR 25-40 (41-55 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 40 - 60 mbar for VAR 25 and VAR 40, Output pressure range 41 - 55 mbar
75422000	Spring 55-75 mbar, blue Spring (blue) for GBF 40, VGBF 25-40 (55-75 mbar) and VAR 25-40 (56-70 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 55 - 75 mbar for VAR 25 and VAR 40, Output pressure range 56 - 70 mbar
75422010	Spring 70-90 mbar, black Spring (black) for GBF 40, VGBF 25-40 (70-90 mbar) and VAR 25-40 (71-86 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 70 - 90 mbar for VAR 25 and VAR 40, Output pressure range 71 - 85 mbar
75422020	Spring 85-105 mbar, white Spring (white) for GBF 40, VGBF 25-40 (85-105 mbar) and VAR 25-40 (86-100 mbar) for output pressure changes: for GBF 40, VGBF 25 and VGBF 40, Output pressure range 85 - 105 mbar for VAR 25 and VAR 40, Output pressure range 86 - 100 mbar
75438979	Spring 150-230 mbar, black/yellow Spring (black/yellow) for VGBF 25-40 (150-230 mbar) and VAR 25-40 (151-220 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 150 - 230 mbar for VAR 25 and VAR 40, Output pressure range 151 - 220 mbar
75438980	Spring 220-350 mbar, black/green Spring (black/green) for VGBF 25-40 (220-350 mbar) and VAR 25-40 (221-340 mbar) for output pressure changes: for VGBF 25 and VGBF 40, Output pressure range 220 - 350 mbar for VAR 25 and VAR 40, Output pressure range 221 - 340 mbar
VAS 125R/NQ	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 25 (1") Output: DN 25 (1") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
IFD 258-10/1W	Gas burner control unit 84621650 Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 10 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz

VAS 1-/25R/NWSL	Gas solenoid valve 88006295 pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Input: Without input flange Output: DN 25 (1") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Feedback: signaling switches and optical Position indicator, left-hand side Electrical connection: M20 screw connection Accessories on the right: Reserved for right in the direction of flow Bypass valve VAS 1 Accessories on the left: 2 locking screws
JSAV 100F50/1-0	Safety shut-off valve 03151136 Switch-off pressure set to 120 mbar New version: inlet pressure up to 5 bar Breathing line connection required To secure all fittings associated with a gas pressure regulator downstream are EC type tested and certified DN 100 Flange according to ISO 7005 pu max. 5 bar Upper response pressure pdo Without measuring point pdo set to 120 mbar
RFM 16RB100	Bourdon tube pressure gauge For displaying pressures, overpressure-proof, with Zero point correction, for gas and air Measuring range 0-16 bar R external thread Overpressure 100mm visible scale diameter
RFM 6RB100	Bourdon tube pressure gauge For displaying pressures, overpressure-proof, with Zero point correction, for gas and air Measuring range 0-6 bar R external thread Overpressure 100mm visible scale diameter
IC 20-30W3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
IFD 244-3/1W	Gas burner control unit Ignites and monitors gas burners, for continuous operation, Ad for Program status and flame signal strength, IP 54, EC type tested and certified, FM and CSA approved Series 200 Ionization monitoring Restart after flameout Safety time start-up: 3 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
IFD 258-5/1W	Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
CG 10R70-D2W5BW	Compact unit With dirt trap, pressure regulator, two solenoid valves and Quantity setting for securing and regulating atmospheric burners, Fan burners, fan-assisted boilers up to 50 kW, EC model tested and certified Size 10 Rp internal thread pu max. 70 mbar Pressure regulator with starting gas level pd max. 40 mbar Mains voltage 230 V~, 50/60 Hz Electrical connection with rectifier adapter without Power outlet Valve class B Pressure switch DG 35C
CGS71	
VAS 125R/NW	
VAS 115R/NW	Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: plug with socket Mounted on the right side of the connection box: plug for Valve (3 pole) Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
VAS 240R/NW	
IC 20-15Q3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 15 s/90° Mains voltage: 120 V~, 50/60 Hz Torque: 3Nm

Control: Continuous control	
VMO 1-/25R05M10	Measuring aperture 88015987 To supplement valVario routes or as Single product Size: 1 Input: Without input flange Output: DN 25 (1") Pipe connection: Rp female thread Inlet pressure: pu max. 500 mbar (7 psig) Housing type: Basic (no accessories possible) Accessories above: measuring nozzle Aperture diameter: 10 mm
VCH 1E25R/25R05NHEVVR3/PPPP/PPPP	Volume flow controller with two solenoid valves 88100240 For gas and air, also for biogas, with control lamp, IP 65, complete assembled and checked for leaks Size: 1 Certification: EU certified Inlet: DN 25 (1") Pipe connection inlet: Rp internal thread Output: DN 25 (1") Pipe connection output: Rp internal thread Inlet pressure: pu max. 500 mbar (7 psig) Module 1: 1. Valve opens quickly, closes quickly Module 2: 2nd valve with volume flow controller, connection for Air control pressure: compression fitting Module 3: Fine adjustment valve Mains voltage: 230 V~, 50/60 Hz Flow direction: From left to right
VMO 365R05M50	Measuring aperture 88033176 To supplement valVario routes or as Single product Size: 3 Inlet: DN 65 (2 1/2") Output: DN 65 (2 1/2") Pipe connection: Rp female thread Inlet pressure: pu max. 500 mbar (7 psig) Housing type: Basic (no accessories possible) Accessories above: measuring nozzle Aperture diameter: 50 mm
IFD 258-5/1W	84621630 Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
DG 500B-3 32Z	Gas pressure switch Bottom housing part rotated For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 100-500 mbar Function: Switches when the overpressure increases Electrical connection: With screw terminals and M16 cable gland, IP54 Packaging: Pack of 32
DG500B-3 32Z	
DG500B-3 32Z	
IFD258-5/1W	
DKR 200Z03F350D	Ring throttle valve for air and flue gas For constant control of a volume flow DN 200 Installation between two DIN flanges pu max. 300 mbar With free shaft end Temperature range 350°C
GDJ 15R04-4	Pressure regulator Spring-loaded, with pre-pressure compensation membrane and Zero degree, none Blow-out line required to keep the air constant adjustable pressure DN 15 Rp internal thread pu max. 400 mbar Measuring nozzle in the entrance For gas, EC type tested and certified Set to 20 mbar
DG 6UG-5	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) With gold-plated contacts: Yes Electrical connection: With 4-pin plug, without Power outlet
VAS 780F05NW3B/PP/PP	Gas solenoid valve For automatic locking, closed without power, for Natural gas, Liquefied gas and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 7 Nominal diameter: DN 80 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the left side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, output: screw plug Accessories on the left, input: screw plug

VAS 780F05NW3B/PP/PP	Gas solenoid valve For automatic locking, closed without power, for Natural gas, Liquefied gas and air, class A according to EN 161, with blue control lamp, IP 65, FM approved, EU certified Size: 7 Nominal diameter: DN 80 Pipe connection: Flange according to ISO 7005 Inlet pressure: pu max. 500 mbar Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Mounted on the right side of the junction box: M20 screw connection Lateral processing: Basic Accessories on the right, input: screw plug Accessories on the right, output: screw plug Accessories on the left, input: screw plug
IFW 15-T *Discontinued part*	84359020 Flame guard 'When replacing IFW 15-T 84359010; (without transformer)' please follow the conversion instructions. This is permitted within the scope of European directives product only be used for replacement purposes. For multiple flame monitoring with IFS 110/111IM, for intermittent Operation Ionization or UV monitoring Mains voltage 220/240 V~, 50/60 Hz, for grounded or unearthed networks
FDU 520W1T2/1O1-0K1	Voltage 230 V 84368000 Flame guard For flame signaling, EU certified Series: For continuous operation Mains voltage: 230 V~, 50/60 Hz Flame monitoring: ionization Switch-off threshold: 2 micro A Response time after flame failure: 1 s Flame detection: 1 normally closed, 1 normally open contact Flame signal strength: No output Connection plug: With screw terminals
BCU460W3P2C0D1000K1E0-/LM400WF3O0E0	BURNER CONTROL UNIT
IC 20-30W3E	Actuator For emitting rotary movements (0-90°), for actuation of gas and Air flaps, position feedback via externally readable Position indicator, protection class IP 65 Series: 20, with potential-free limit switches Running time: 30 s/90° Mains voltage: 230 V~, 50/60 Hz Torque: 3Nm Control: Continuous control
MH 15	Pressure gauge shut-off valve Please send certificates to: m.systemtechnik@honeywell.com To protect a pressure gauge from pressure surges, for gas and air, DVGW tested and certified DN 15, Rp/R internal/external thread, pu max. 100 bar Set including; 03110621 4 piece Flat gasket 1/2" for pressure gauges CU version 99920281 2 piece Pressure gauge connection accessories for pressure gauge tap MH.. consisting of union nut G 1/2" and pressure gauge flat nipple 12 mm 99900135 2 piece Straight screw connection, type GERK On the one hand, cutting ring screw connection RVS 12 on the other hand, external pipe thread G 1/2" L series
03110621	Flat gasket 1/2" for pressure gauges CU version
99920281	Pressure gauge connection accessories for pressure gauge tap MH.. consisting of union nut G 1/2" and pressure gauge flat nipple 12 mm
99900135	Straight screw connection, type GERK On the one hand, cutting ring screw connection RVS 12 on the other hand, external pipe thread G 1/2" L series
48136000	DH 15R50 Push button faucet To protect a pressure gauge from pressure surges, for gas and air, EC type tested and certified DN 15 Rp internal thread pu max. 5 bar Set including 1 piece 03110615 Pressure gauge seal 1/2" - Cu Profile seal with internal centering G 1/2", copper
03110615	Pressure gauge seal 1/2" - Cu Profile seal with internal centering G 1/2", copper
61004415	KH 15R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 15 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
61004425	KH 25R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 25 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
61004440	KH 40R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested

	and certified DN 40 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
61004450	KH50R50B Ball valve Yellow lever handle For manual shut-off, for natural gas, town gas, Liquefied gas, air, water and heating oil, EC type tested and certified DN 50 Rp internal thread pu max. 5 bar (HTB up to 0.1 bar) Housing: brass, ambient temperature: -20 to +60 °C
34331381	84331381 Ignition transformer For high-voltage ignition of gas and oil burners High voltage 5 kV Output current 15 mA at 50 Hz Duty cycle 100% Mains voltage 230 V~
DG 50U-3	84447350 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 2.5-50 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
DG 6U-3	84447250 Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as a pressure monitor special Design", EU certified Setting range: 0.4-6 mbar Function: Switches when the overpressure (gas/air) increases, negative pressure (air), differential pressure (air-air) Electrical connection: With screw terminals and M16 cable gland, IP54
UVS 10D0G1	84315200 UV probe For monitoring gas burners in intermittent mode Operation, EC type tested and certified in conjunction with magpie Kromschröder gas burner controls Series 10 Thermal protection made of quartz glass Rp 1/2 internal thread M20 screw connection
IFD 258-5/1W	84621630 Gas burner control unit Replaces mat. no. 84620630, compatible Ignites and monitors gas burners for continuous operation Ionization monitoring, switch-off sensitivity adjustable, display for program status and flame signal strength, IP 54, EC model tested and certified, FM and CSA approved Series 200 Ionization or UV monitoring Immediate shutdown or restart after flame failure, switchable Safety time start-up: 5 s Safety time operation: 1 s Mains voltage 230 V~, 50/60 Hz
VAG 115R/NWBE	88000141 Constant pressure regulator with solenoid valve To secure and regulate the gas pressure, pressure regulator Class A according to EN 88, solenoid valve class A according to EN 161, for gas and air, also for Biogas, pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Valve seat: Reduced in size Connection set for air control pressure psa: 1 Clamping ring screw connection, 2 Measuring nozzles pd and psa Accessories on the right: 2 locking screws
VAS 115R/NW	88000003 Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 230 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
GDJ 40R04-0L	03155034 Pressure regulator Spring-loaded, with pre-pressure compensation membrane and zero termination, none Blow-out line required to keep the adjustable pressure constant DN 40 Rp internal thread pu max. 400 mbar Without measuring point Just for air Set to 20 mbar
BCU480-5/3/1LW3GB	
RVS 50/LF03W60S1-3	Control valve with solenoid valve For controlling continuously regulated combustion processes, linear Relationship between input signal and volume flow, Control ratio 100:1, for Gas and air, EU certified DN 50 Valve seat L Flange according to ISO 7005 pu max. 360 mbar Mains voltage 230 V~, 50/60 Hz 60 s running time Three-point step control Solenoid valve

VAS 115R/NQ	connection box with terminals Gas solenoid valve pu max. 500 mbar (7 psig), with control lamp, IP 65 Size: 1 Certification: EU certified Inlet: DN 15 (1/2") Output: DN 15 (1/2") Pipe connection: Rp female thread Opening behavior: Quick opening, quick closing Quantity adjustment: With quantity adjustment Mains voltage: 120 V~, 50/60 Hz Electrical connection: M20 screw connection Accessories on the right: 2 locking screws Accessories on the left: 2 locking screws
GRSF 15R	03150672 Gas non-return valve, flameproof combustion with air To prevent gradual and sudden Gas return, for Gas, air and oxygen, DVGW tested and registered DN 15 G internal thread Flame transmission resistant up to pu max. 5 bar natural gas, LPG pu max. 1.5 bar town gas, hydrogen
Vav 125r/Nqak	
Vg 8r03q6g	
Bvh 100z01a	
Vgbf 40f40-3	
Rv 65/Nf02t60e	EINSTELLVENTIL
Bvgf 100/80z05	
Vg40 R02-Nt33	
75440163	
Dg 110vc8d-5w	
84391045	
Gik 20r02-5	
Rvs 3/Hml03w60e-3	
Vas 350f/Lq	
Vas 8100f05lw3b/Pp/Pp	
Dkr 150z03h100d	
Ic 50-60w30e	Actuator For Transmitting rotary movements (0-90 �), for Actuation of gas and air valves, position feedback via externally readable position indicator, enclosure IP 65 Series 50, with higher torque Running time: 60 s / 90 � Mains voltage: 230 V AC, 50/60 Hz Torque: 30 Nm Continuous control
Tsc 100b065-300/35-Si-1500	
Tc 410-1k	
Vfc 365/65r05-25pppp	
Gik 40r02-5	
Akt 150f50tas	
Vk 200f10t5hg93	
Vk 50f10w5xa43d	
Vg 6r05t6	
Gfk 80f10-6	
Gik 15r02-5	
Vg 40/33f10nq33	
85205036	

Gik 50r02-5l	pilot burner For the safe ignition of gas burners, with forced air supply 150 mm length An additional 100 mm Rp internal thread ZKIH 150 / 100R Pilot burner For safely igniting gas burners, with forced air supply Length: 150 mm Plus 100 mm Rp internal thread Stat. Product number 84162080 Country of origin: DE
Zkih 150/100r	
Vg15r02/Nd31	
03150677	
Var 40f05-1	
Vk 65r10t5a93d	
Bio 50kb-40/35-(34)d	
84331381	
Vg 15/12r18nq31	
84447500	
Vas 232r/Nq	
81937190	
Bvh 50z01a	
Bica 65hb-0/35-(34)d	
74921343	
Bic 65mb-0/35-(104)e	
Ifc 125/25r05-15pppp/20-60q3t	
88000107	
Jsav 40r40/2-3	
85317121	
74214547	
Uvs 10d0g1	UVS 10D0G1 UV-sensor For monitoring gas burners in intermittent operation, EC type-tested and certified in conjunction with Elster Kromschröder automatic burner control units Series 10 Quartz glass heat guard Rp 1/2 internal thread M20 cable gland
Vg 25/15r18nq31	
Bic 100hb-0/35-(37)e	
Vas 340r/Nq	
Van 240r/Nw	
Uvs6	
Gfk 40r10-6	
Bvg 125/100z05	
3109016	
Bio 80kb-50/35-(8)e	
Bic-65	
Vk 250f05t5ha93	
Ifc 365/65r05-32pppp/20-60w3t	

Gfk 150f10-3	
Var 80f05-1	
93 3421309	
Tsc 80m075-300/35-Si-1500	
Bic 140mb-0/35-(75)e	
Dg 300vc8d-5w	
Vas 115r/Nw	Gas solenoid valve For gas, air and biologically produced methane, pu max. 500 mbar (7psig), with pilot lamp, IP 65, FM and CSA approved Size 1 EU certified Inlet: DN 15 (1/2") Outlet: DN 15 (1/2") Rp internal thread Quick opening, quick closing With flow adjustment Mains voltage: 230 V AC, 50/60 Hz Electrical connection: M20 cable gland Accessories, right: 2 screw plugs Accessories, left: 2 screw plugs Stat. Warennummer 84814090 Ursprungsland: DE
Bic 100mb-0/35-(118)e	
Rsg 100/65-0	
Tsc 80b040-250/35-Si-1500	
Vad 125r/Nq-100a	
Gfk 125f10-3	
85265010	
Vah 120r/Ngae	
Dg 300/300vc4-6w	
DI 40k-3	
Vg 6r05q6	
Vk 50r10t5a93d	
3352510	
Vas 110r/Lq	
Tc410-10t	DICHTUNGSREGLER
85206072	
DI 3,5k-3	
3109017	
35440829	
Vav 120r/Nwak	
Tgi 7,5-12/100w	Zündtransformator
Rvs 3/ImI02w60e-3	
Vk 40r10t5a93d	
7 193 5010	
Dg500b-3	100-500 Mbar PRESOSTAT
Bvaf 150/125z05	
Tsc 140b070-300/35-Si-1500	

Vas115r/Lw	
74921976	
Vgbf 50f05-3	
Vas 250r/Lq	
Ic 20-30w3e	actuator To deliver rotary movements (0-90 °), for Operation of gas and Air dampers, position feedback via the outside read Position indicator, protection class IP 65 Series 20, with floating limit switches Running time 30 s / 90 ° Mains voltage 230 V ~, 50/60 Hz Torque 3 Nm Constant control Stat. Product number 85011010 Country of origin: DE
Rsg 200/140-0	
03089125	
Vg 20r03nq31dmvz	
Zio 200rb-50/35-(20)d	
84099840	
Zic 165rbl-0/35-(20)d	
Vad 350r/Nq-100a	
Vgbf 50f10-3	
03155023	
Vas 240r/Nq	
Gdj 15r04-0l	
Vav 350r/Nwak	
Vk 50r10w5xa43d	
Bio 80hbl-100/35-(34)f	
74482442	
72702070	
Vas 340r/Lq	
Bvgf 150/125z05	
Vg 6k03q6g	
Var 50f05-2	
Vas 240f/Lw	
Bio 50rb-50/35-(39)d	
Ic20-30w3e	
Bic 125hbl-0/35-(9)e	
Vg 65f02nq33dmvz	
Gik 50r02-5	
84583011	
Ic 40a2ar10	
Bva 150z05	
Vg 50f03nt33dmvz	

Vk 50f40w5xg43d
Fpt Br 65-100/950/500/50
88005614
84391080z
Vas 780f05lq3b/Pp/Pp
Vas 9125f05na3e/Pp/Pp
86044010
Bic 80rbl-0/35-(11)e
Bic 65rb-0/35-(37)e
Tc 2r05w/K
Vgp 15r02q6
3150634
Bvaf 40/25z05
84447379
Ifc 125/25r05-20pppp/20-60q3t
DI 5ag-31
Vas 125r/Nw
Jsav 25r40/2-0
Bic 100rb-150/185-(109)fr
Akt 32f50tas
Vg 10r01t6
Vg 8r05q6
Vg 8r18q6
Bio 50hb-100/35-(37)d
Akt 40f50tas
Vad 240r/Nq-100a
Akt 50r50tas
Bvaf 150z05
Bic 140rb-0/35-(47)e
Vag 350r/Nqae
Fpt Br 140-220/1150
Tzi 7,5/100
Vas 232r/Lw
Vg 15r03nt31dmvz
84447253
Bvg 80/65z05
60dj Z

74920589	
Vas 8100f05lw3e/Pp/Pp	
72701540	
Zic 200rbl-0/35-(25)d	
Dkr 400z03f450d	
Vgp 15r02w6	
Var 25r05-2	
3109431	
Vah 125r/Nqae	
Bic 140hb-0/35-(26)e	
84230090	
DI 150ag-32	
Bvg 150/100z05	
Bic 65/50hbr-100/235-(108)er	
74 489310	
Ifc 110/10r05-08pppp/20-60w3t	
74918152	
Vg 40r03lq33dmvz	
84447256	
Dkr 125z03f450d	
88000141	
Tc 3r05q/Q	
Ifc 365/65r05-25pppp/20-60q3t	
Var 100f05-2	
Uvc 101g1a	FOTOSEL
DI 4,5kg-3	
03352504	
Vas 8100f05nq3e/Pp/Pp	
84214030	
Bvaf 150/100z05	
Bic 125mb-0/35-(26)e	
Vgbf 100f05-3	
8 193 5200	
Akt 125f50tas	
Akt 32r50tas	
88020010	

Akt 40r50tas	
Zic 165rb-0/35-(17)d	
84315204	UVS 10D4G1
Ziow 200	
Msvs	
DI 40kg-3	
Vav 240r/Nwak	
Vk 40r10w5xa43d	
Vgp 20r01w6	
24 0854802	
Bio 140hb-100/35-(26)e	
Van 120r/Nq	
Vg 25r03nt31dmvz	
Ifc 120/20r05-08pppp/20-60w3t	
Vg 15r03nq31dmvz	
Vas 110r/Nq	
M 264983	
Vas 120r/Lw	
Vfc 350/50r05-32pppp	
Vgbf 40f10-3	
Pfp 700t/N	
Tsc 140a120-300/35-Si-1500	
Gfk 32r10-6	
74336310	
Var 40r05-1	
Tsc 80b033-250/35-Si-1500	
Dkr 400z03h450d	
Tc 410-1n	
Vas 120r/Nq	
Bio 140kbl-50/35-(67)e	
Akt 15r10tas	
Vas 350r/Nq	
Vas 250r/Nq	
84315010	
Vas 225r/Nq	
Tc 2r05q/K	
03110012	

Dkr 500z03f100d
Gfk 40r40-6
Gik 150f02-6l
Fpt Br 80-125/1300/700/50
Vg 20r03lq31dmvz
Dkr 150z03h450d
Vgbf 15 R40-1
88002297
85231710
Rvs 40/Kf05w60e-3
Bvg65/40zo5
Vas 250r/Lw
Van 120r/Nw
Vah 115r/Nqbe
Bio 80hb-100/35-(16)f
Vas 232r/Nw
74105751
Dkr 450z03h100d
84347010
Vg 15/10r01q6
85231010
Zio 165hbl-100/35-(24)d
88012146
Bvg 150/125z05
Gik 20r02-5l
Vk50f
Gik 25r02-5
Tc410-1t
Vad 120r/Nq-100a
Van 250r/Nw
3 416 0010
Gfk 100f60-6
Dg 110vc5-5w
Bio 80rb-50/35-(6)e
Vk 50f80t5hg93d
Bic 50rb-0/35-(39)d
85256860

Dkr 100z03f450d
Gik 65f02-6l
Var 65f05-1
Gdj 40r04-0l
Zio 165hb-100/35-(18)d
Vgbf 40f05-3
Vg 15r03lq31dmvz
Vg 40/32r02lq31dmvz
Bioa 65rb-50/35-(37)d
Vgbf 100f40-3
Vg 40/32r02lt31dmvz
Tc 1c05q/K
Gik 100f02-6l
Vad 125r/Nw-100a
Vgbf 50f05-3v
Dg 500vc4-5w
Uvs 10d4g1
Bio 65kb-50/35-(46)e
Gfk 65f60-6
85231012
Gdj 15r04-0
Vas 110r/Lw
88611509
Vk 65r31t5a93d
Kfm 160 R B 100
Vg8r05t6
Vas 225r/Lw
Bvhs 50z01a
Ic 40sa3ar10
Vg 6k05q6
Gdj-25 R04-Zr1
Fpt Br 100-150/700
Tsc 50b028-300/135-Si-1500 Z
Vk 40f10t5a93d
74918682
Vas 665f05lq3b/Pp/Pp
Akt 25r10tas

Van 240r/Nqsr	
Tsc 100m180-300/35-Si-1500	
Bio 140kb-50/35-(66)e	
Gdj 50r04-0l	
Van 115r/Nwsr	
Zic 165hb-0/35-(18)d	
Vas 665f05nwsr3b/Pp/Pp	MAGNETISCHES VENTIL
72700560	
Vfc 120/20r05-15pppp	
84447520	
71937010	
Gik 20r02-5b	
Van 250r/Nq	
Rvs 65/Mf02w60e-3	
Ziow 165	
84447020	
Gik 50r02-5lb	
Vgp 25r01q6	
Vas 240f/Lq	
75422071	
84234040	
74921345	
3152149	
Fpt Br 65-100/500	
Din3384	
Bio 140rb-50/35-(47)e	
Vas 9125f05na3b/Pp/Pp	
8 604 6010	
Vg 50/39r10nt33	
Gik 40r02-5b	
39 0539311	
Van 120r/Nwsr	
75448580	
Var 100f05-1	
84214040	
Rvs 2/Aml10w60s1-3	

Vgp 25r01w6
Ifs 135b-3/1/1t
Tc 3r05k/K
Tsc 125m260-300/35-Si-1500
Vk 50r40t5a93d
Bic 140rbl-0/35-(54)e
Gik 25r02-5lb
74923041
Ifc 365/65r05-40pppp/20-60q3e
85256863
Bic 125rb-0/35-(15)e
DI 11kg-3
74330414
Van 240r/Nq
Vas 340r/Nw
Vg 50/39r10nq33
Var 40f05-2
Vad 120r/Nw-100a
Dg 150/300vc4-6w
Vas 8100f05nw3e/Pp/Pp
Dg 250c8d-5s
Vg 50f03lt33dmvz
Dg 300vc5-5w
Gfk 50f10-6
Vas 115r/Lq
Akt 10 R 50
Ifc 365/65r05-40pppp/20-60w3t
Dkr 20z03f100d
DI 5ag-32
Bio 100hb-100/35-(37)e
Vk 65f10w5xa43d
Gfk 15r40-6
Dkr 200z03f100d
72703710
Gdj 25r04-0l
J78r 1
Air-pressure switch Switch housing drilled out (Rp1 / 8 connection) For

DL 3a-3tz	monitoring of air and flue gas pressures, for overpressure, negative pressure and differential pressure, EC type tested and certified Adjustment range 0.2-3 mbar, can be used as "pressure monitor of special design" ' Housing with screw terminals, threaded connection Rp 1/4 and hose connection with handwheel Electrical connection with screw terminals Blue Control Lamp for 220/240 V ~ DL 3A-3TZ Pressure switch for air switch housing on-drilled (Rp1 / 8 connection) For monitoring air and flue gas pressures, for positive Pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as " special-design pressure switch " Housing with screw terminals, Rp 1/4 threaded connection and tube connection with hand wheel Electrical connection via screw terminals Blue pilot lamp for 220/240 V AC Stat. Lot number 90262080 Country of origin: DE
86046010	
J78r 1-L	
Akt 100f50tas	
Bvaf 40z05	
Vg 50r03lt33dmvz	
Vas 8100f05lq3e/Pp/Pp	
Dg 50u-3	
Ic 20-15w3t	
Bvaf 40/32z05	
Gdj 25r04-0	
Bvhr 100z01a	
Jsav 40f40/1-3	
Vr 25r01rt31d 220 V	
Van 120r/Nqsr	
Fpt Br 100-150/1300/900/100	
Bic 100rbl-0/35-(111)e	
Bic 80rb-0/35-(6)e	
Zio 200kbl-50/35-(38)d	
Vas 240r/Lw	
Bic 140lb-0/35-(60)e	
Bio 100kb-50/35-(41)e	
843 674 40	
Ifc 115/15r05-20pppp/20-60w3t	
85315316	
Gik 50r02-5b	
Bva150z05	
Tc 3r05q/K	
Pfu 760 Ltk1	
Vas 780f05lw3e/Pp/Pp	

Tc 1c05w/k	
Gfk 65r10-6	
Rvs 2/Bml10w60e-3	
Gik 15r02-5b	
74918138	
Vgbf 150 F 05-3	
74960352	
Dkr 500z03h100d	
Vgbf 100f10-3	
Gik 40r02-5l	
Vgp 10r02w6	
Vg 20r03nt31dmvz	
88012154	
84583010	
Tc 410-1t	
Tc 410-10t	
Gfk 20r40-6	
Vag 125r/Nqae	
Vk 150f04w5xg43	
Jsav 40f40/2-3	
Dg 150u-3	SWITCH
Bio 125rb-50/35-(15)e	
Dg 150vc8d-5w	
Gfk 100f10-6	
Gvrh 350ml02f1t6	
88000148	
Tsc 100b040-300/105-Si-1500	
Tsc 140b055-300/35-Si-1500	
Vas 120r/Nw	
35441256	
Akt 25f50tas	
Tc 410-10n	
Bic 50hb-0/135-(37)d	
Vg 50r03nt33dmvz	
Vas 665f05lw3e/Pp/Pp	
74922222	
3089123	

03200111
Bvaf 80z05
Ic 20-07q2tr10
3262045
Vas 240f/Nw
Gfk 65f10-6
Vas 240r/Lq
Vg 6k05t6
8 444 7350
Vas120r/Nwsr
34160010
03200124
60dj Lz
Ifc 350/50r05-25pppp/20-60q3e
Gdj 20r04-0l
Bic 140rbl-250/285-(54)er
88012860
74960023
88000146
Bva 40/25z05
Bio 100kbl-50/35-(52)e
Vag 350r/Nwae
Vas 780f05nw3e/Pp/Pp
Gik 15r02-5lb
Bic 65hb-0/35-(34)e
Gik 40r02-5lb
Bio 80rbl-50/35-(11)e
Vk 200f02w5xg43
Vas 365r/Lw
Vgbf 150f10-3
Vg 15/10r01t6
Vgbf 80f05-3v
Vg 25r03lt31dmvz
8 423 0100
Vk 40r40t5a93d
Vg 40r03nt33dmvz
Tsc 100b050-300/35-Si-1500

Kfm Mb: 0-250	
Vas 225r/Lq	
DI 5a-32	
Vg 50f03nq33dmvz	
8429 9748	
74921823	
3262067	
Ic 20-60w3e	
Bva 100/65z05	
Vav 120r/Nqak	
03152276	
Ic 40sa3dr10	
Bic 80mb-0/35-(57)e	
Tc 2r05k/K	
Ic 40sa3a	
Vmv115r05m	
84367030	
8 520 612 0	
Dg 60/300vc4-6w	
DI 24kg-3	
03152348	
Dkr 500z03h450d	
Vad 350r/Nw-100a	
Vas232r/Nwsr	
Jsav 80f50/1-0	
Van 115r/Nw	
DG 50U-6	Gas pressure switch For monitoring gas and air pressures, also for Biogas, with handwheel for switching point adjustment, can be used as " pressure monitor special Bauart ", EC type-tested and certified Setting range 2.5-50 mbar Overpressure (gas / air), underpressure (air), differential pressure (Air-air) EI. Connection with 4-pin plug, with socket Stat. Lot number 90262080 Country of origin: DE
Rvs 65/Mf02w60s1-3	
Tsc 50b020-300/135-Si-1500 Z	
88004435	
Gfk 200f10-3	
Tsc 200a180-300/35-Si-1500	
88300159	
Ifc 365/65r05-25pppp/20-60w3t	

Bvg 125z05	
DI 150a-32	
Vas 110r/Nw	
Vk 65 F 10 T5 A 93 Ds	
88202653	
Zio 200hb-100/35-(21)d	
Vag 115r/Nwbe	
85313126	
Var 80f05-2	
Bio 140hbl-100/35-(44)e	
Vas125r/Nwsr	
Tc 3r05w/W	
Bvg 50z05	
Rvs 65/Lf03w60s1-3	
Bvg 125/80z05	
Zio 200hbl-100/35-(23)d	
Vas 120r/Nwsr	MAGNETISCHER VENTIL POSITIONSSCHALTER
71939010	
Vav 350r/Nqak	
Dkr 65z03h100d	
Bio 125hb-100/35-(2)e	
Vg 25r03lq31dmvz	
Zio 165kb-50/35-(25)d	
Bic 80hb-0/35-(16)f	
Bio 100hbl-100/35-(49)e	
Vg 10r01q6	
Vgbf 80f40-3	
88001019	
Bvaf 125/80z05	
Tc 3r05w/K	
Vah 120r/Nwae	
Vas 780f05nq3e/Pp/Pp	
Bg 80/100	
Jsav 25r40/1-0	
DI 150ag-31	
Dkr 450z03f450d	
84447350	

Van 250r/Nqsr	
74920293	
Vas 665f05nw3e/Pp/Pp	
Tc 1c05k/K	
Vsbv 25r40-4	
35440784	
Tsc100b065-300	
Dkr 450z03h450d	
Ifs 135b-5/1/1t	Gas burner control *** only for replacement *** Ignits and monitors gas burners, for intermittent operation, Ionisation or UV monitoring, EC type tested and certified Lockout after flame failure Safety time start-up: 5 s Safety time Operation for V2: 1 s Safety time operation for V1: 1 s Mains voltage 220/240 V ~, 50/60 Hz, for grounded nets IFS 135B-5/1 / 1T Automatic burner control unit *** Only for replacement *** Ignites and controls gas burners, for intermittent operation, with Ionization or UV control, EC type-tested and certified Fault lock-out in the event of flame failure Safety time on start-up: 5 s Safety time during operation for V2: 1 s Safety time during operation for V1: 1 s Mains voltage: 220/240 V AC, 50/60 Hz, for grounded mains Stat. Lot number 90268020 Country of origin: DE Technical documentation can be found at: http://docuthek.kromschroeder.com/doclib/main.php?language=1&folderid=206030
74919901	
74105996	
Ic 20-07w2e	
Gfk 125f40-3	
Jsav 40r40/1-3	
Vag 120r/Nqae	
Doos3oo8	
Vag 240r/Nwae	
717893	
75448312	
Fpt Br 50-100/500	
03352506	
03200159	
Zic 200rb-0/35-(20)d	
88650057	
85257863	
Zio 200kb-50/35-(34)d	
84447355	
Bio 125rbl-50/35-(17)e	
Zic 200hb-0/35-(21)d	
85249151	

Dkr 350z03f100d
Dg 110c8d-5s
Dg 300vc4-5w
35448584
DI 50ag-32
Vgbf25r40-1
Vas 225r/Nw
Van 115r/Nqsr
Vg 25r03nq31dmvz
Ic 20-60q3e
75440160
Vg15r03nt31d
Vgbf 150f05-3
Vas 240r/Nw
Biow 80
Vas 350r/Lq
Bva 65/40z05
Tsc 140m360-300/35-Si-1500
Var 50f05-1
Tc 2r05w/W
74919312
Gik 150f02-6
Vg 65f02lt33dmvz
Vas 780f05nq3b/Pp/Pp
Bic 100lb-0/35-(123)h
Gfk 4071939010
Vg 40/32r02nt31dmvz
Gdj 50r04-0
Vfc 125/25r05-08pppp
Vag 120r/Nwae
Bva 150/100z05
Vas 8100f05lq3b/Pp/Pp
Bva 100/80z05
Ifc 125/25r05-08pppp/20-60q3t
Fpt Br 80-125/600
88012160

DI 50a-31	
Dg 40vc4-5w	
Vg 65f02nt33dmvz	
8 444 4400	
DI 3a-3	Pressure switch for air For monitoring air and flue gas pressures, for positive pressure, negative pressure and differential pressure, EC type-tested and certified Adjusting range: 0.2-3 mbar, can be used as "special-design pressureswitch" Housing with screw terminals, Rp 1/4 threaded connection and tube connection with hand wheel Electrical connection via screw terminals Stat. Warennummer 90262080 Ursprungsland: DE
Dg 150u-6t	Pressure switch for gas For monitoring gas and air pressures, also for biologically produced methane, with hand wheel for switching point adjustment, can be used as "special-design pressure switch", EC type-tested and certified Adjusting range: 30-150 mbar Positive pressure (gas/air), negative pressure (air), differential pressure (air-air) Electrical connection via 4-pin plug, with socket Blue pilot lamp for 220/240 V AC Stat. Warennummer 90262080 Ursprungsland: DE
84230050	
Vas 125r/Lw	
Fpt Br 140-220/1650/1100/100	
81941103	
Vg 50r03nq33dmvz	
Gfk 80f60-6	
Vad 240r/Nw-100a	
Vav 240r/Nqak	
Tsc 65m035-300/35-Si-1500	
Bic 50hb-0/35-(37)d	
84367520	
Bvhr 50z01a	
Vg 50f03lq33dmvz	
Vas 780f05lq3e/Pp/Pp	
Vas 115r/Nq	
3109018	
03352385	
Dkr 65z03h450d	
3109003	
Bio 125hbl-100/35-(9)e	
03200110	
Bic 80lb-0/35-(59)f	
Vgbf 150f05-3v	
8434 4920	
Gfk 32r40-6	

Bvhs 100z01a	
88003876	
Vgp 20r01q6	
Vav 115r/Ngbk	
Gfk 150f40-3	
Bvgf 150z05	
74923271	
Bvgf 100z05	
Van 115r/Nq	
Vas 240f/Nq	
R30-85205030	
74923285	
Ifc 365/65r05-40pppp/20-60w3e	
Vas 120r/Lq	
Bica 65rb-0/35-(37)d	
Gfk 40f10-6	
Vas 125r/Lq	
Ifc 115/15r05-15pppp/20-60w3t	
Vas 250r/Nw	
Zic 200hbl-0/35-(23)d	
88610003	
14541	
8 421 4050	
Ic 20-30w3t	actuator To deliver rotational movements (0-90 °), to Operation of gas and gas Dampers, position feedback on the outside read Position indicator, protection class IP 65 Series 20, with potential-free limit switches Running time 30 s / 90 ° Mains voltage 230 V ~, 50/60 Hz Torque 3 Nm Three-point step control IC 20-30W3T Actuator For Transmitting rotary movements (0-90 °), for Actuation of gas and air valves, position feedback via externally readable position indicator, enclosure IP 65 Series 20, with voltage-free limit switches Running time: 30 s / 90 ° Mains voltage: 230 V AC, 50/60 Hz Torque: 3 Nm Three-point step control
Vk125av	
Bvg65/40z05	
8 439 510 1	
Gfk 50r40-6	
Bvgf 150/100z05	
Bic 100rbl-150/185-(111)fr	
03200109	
Bio 100rbl-50/35-(111)e	
Fpt Br 125-195/950	

Biow 140
74959774
Vgbf 40f05-3v
Vg 20r03lt31dmvz
16010081
Akt 50f50tas
Fpt Br 125-195/1350/1000/100
Rsg 140/100-0
85234510
Zio 165rbl-50/35-(20)d
Tc 410-10k
Rvs 50/Mf02w60e-3
Gik 80f02-6
Bio 65rb-50/35-(37)e
Gik 25r02-5l
Bva 65z05
Vg 15r03lt31dmvz
84.398.164
Bio 125kbl-50/35-(21)e
Bva 150/125z05
Gdj15r04-4lz
15100111
Dg 60vc8d-5w
Vas 665f05nq3e/Pp/Pp
Bio 65hb-100/35-(34)e
Fpt Br 50-100/500/300/50
Vg 40/33r10nq33
Gfk 25r40-6
Dg 500vc8d-5w
Bic 140rb-250/285-(47)er
Vgbf 80f10-3
Vg 25/15r18nt31
84447573
Var 40r05-2
Vas 8100f05nq3b/Pp/Pp
Vg 50/39f10nq33

Vg8r05t6/220v	
Vgbf 65f05-3	
Van 240r/Nwsr	
Vad 115r/Nq-100b	
Vg 40/33r10nt33	
Vah 115r/Nwbe	
Dkr 300z03f450d	
Dg6u-5	
84099543	
Bvaf 100/80z05	
Akt 20r10tas	
Vah 240r/Nqae	
Vah 350r/Nwae	
81937200	
88300161	
88205351	
Bcu460-5/1 Lw3ds2b1/1	
03200379	
Tc 2r05q/Q	
Vk 150f04w5xa43	
Bvg 150z05	
Dg50b-3	2,5-50 Mbar PRESOSTAT
74919356	
Dkr 350z03h100d	
Biow 65	
3109434	
84444880	
84230080	
Vfc 120/20r05-20pppp	
Bio 125kb-50/35-(20)e	
Vav 115r/Nwbk	
Akt 80f50tas	
Kfm 60 R B 100	
84315200	
Dg 500vc5-5w	
Bg 50/65	
Vas 232r/Lq	

Ecomax 2 Mb 695
88012148
Bio 140rbl-50/35-(54)e
Ifc 350/50r05-32pppp/20-60q3e
74951926
Vg 8r05t6
Jsav 50f50/1-0
Vas 350f/Lw
Bioa 65hb-100/35-(34)d
Geh 20 R 10
Vg 50/39f10nt33
Bva 40z05
88301151
85312165
Bic 100hbl-0/35-(49)e
Vas 365r/Nq
Gik 80f02-6l
Zic 165hbl-0/35-(24)d
Vas 665f05lw3b/Pp/Pp
88000570
Vag 115r/Nqbe
Vg 8r03t6g
Gfk 25r10-6
88012166
Akt 65f50tas
74911637
Vas115r/Nwsl
Vas 350r/Lw
Tsc 200b107-300/35-Si-1500
Vg 40r03lt33dmvz
75448582
74923284
Vg 15/12r18nt31
Vg 8r18t6
Gik 65f02-6
71935010

Gfk 25-1
Tc 1c05q/Q
Dg 40vc5-5w
81943190
Zio 165rb-50/35-(17)d
Var 25r05-1
3109436
Bvaf 65/40z05
75442048
Bic 80hbl-0/35-(34)f
Gik 20r02-5lb
Vgp 10r02q6
Gfk40/50
Van 250r/Nwsr
Vg 40/33f10nt33
Dkr 15z03f100d
Tsc 140b085-300/35-Si-1500
84765528
7491-1637
Dkr 300z03h450d
Vg 6k03t6g
Vgbf 100f05-3v
Zio 200rbl-50/35-(25)d
Dkr 500z03f450d
74923085
Jsav 100f50/1-0
Gfk 40f60-6
Vg 65f02lq33dmvz
Vas 340r/Lw
Van 125r/Nw
Tsc 100b050-250/35-Si-1500
Bva 50/40z05
Vg 15/10r01t6g
Vk 40f10w5xa43d
842 210 23
03200108
Vk 65r10w5xa43d

Vk 200/100f40t5hg93
Van 125r/Nwsr
Vfc 365/65r05-40pppp
Rvs 3/ImI02w60s1-3
Vad 115r/Nw-100b
Vk 80f10t5a93ds
13110238
88650068
Vas 365r/Lq
Bcu460-3/1w3gbcbl/1
Gfk 50r10-6
Gdj 20r04-0
Biow 125
Ic 20-15w3tr10
Gfk 20r10-6
84444453
Gfk40r10-7
Gdj 40r04-0
Tsc 100a082-300/35-Si-1500
Vgbf 65f05-3v
Bio 100rb-50/35-(109)e
Vas 665f05lq3e/Pp/Pp
75421951
Bic 125rbl-0/35-(17)e
Vas 780f05lw3b/Pp/Pp
86049222
Bic 100rb-0/35-(109)e
Vg 40/32r02nq31dmvz
Vah 350r/Nqae
Dg 60vc4-5w
74924633
74918692
84447505
Gfk 15r10-6
3150674
Vg 50r03lq33dmvz
Vag 125r/Nwae

Rvs_3/Gml05w60s1-3
74921144
Dkr_100z03f100d
Gfk_250f10-3
Vav_125r/Nwak
84765710
Vas_350r/Nw
60djz
Vgbf_50f40-3
Vag_240r/Nqae
Vas_350f/Nw
Vg_40r03nq33dmvz
Bg_125/140
Van_125r/Nqsr
Vah_125r/Nwae
DI_3,3kg-3
Van_125r/Nq
Bic_140hbl-0/35-(44)e
DI_11k-3
88300076
72700760
Gik_15r02-5I
Vas_115r/Lw
Vas_350f/Nq