



Krone Filter Solutions Gmbh

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Krone Filter Solutions Gmbh Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Krone Filter Solutions Gmbh Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Filter Angaben:	Self-cleaning automatic filter, type KAF - Bernoulli DN 300 GGG-50, EN-GJS-500-7, 2.5 mm rubberized Connections: Nominal size: DN 30 DIN EN 1092-1 PN 10 Flushing outlet: DN 100 DIN EN 1092-1 PN 16 Operating conditions: Medium: sea water Operating pressure: Unknown (min. 0.6 bar during flushing) Design pressure: 6 bar Design temperature: 0 / + 80 ° C Operating temperature: Unknown Flow rate: 560 m³ / h Backwash quantity: 1.5 m³ Backwashing time: approx. 42 seconds Pressure loss clean: approx. 0.07 bar Differential pressure flushing: 0.11 bar + pressure loss clean Materials: Filter housing: GGG-50, EN-GJS-500-7 External parts: galvanized steel Inner parts: SS 316Ti Seals: NBR Filter element: Siebart: Edge gap sieve / basket sieve - perforated plate Filter fineness: 300 µm / 0.3 mm Material: SS 316 Perm. Differential pressure: 1 bar Equipment: Differential pressure switch: Aplisens, membrane made of Hastelloy Flush valve: DN 100, wetted parts duplex 1.4462 / 1.4469, pneum. drive Control: SPS - Crouzet Millenium III Supply voltage: 230V AC, 1 Ph, 50 Hz Control voltage: 24 V DC Corrosion protection: Inside: 2.5 mm rubberized Chemonit 33 Outside: epoxy RAL 5010 Interpretation: Classification and

	conformity assessment according to PED 2014/68 / EU Design based on AD2000
Kaf Dn 150 - 1201476-5	
Kdfk032.0305160040	KDFK double filter DN32, Gr. 3, screws, FPM, oil version, standard GGG-50 / FPM / studs / including. Chicks, adapters and Handle KDF double filter Closure with studs Flanges DN32 PN16 DIN 1092-1 PN 16 Design pressure 16 bar Material GGG-50, cover seal FPM Rooster chicks GGG Draining G 3/8 ", vent G 1/4" from VA Color RAL 5010
Idfk032.030221002501	Basket strainer double filter KDFK Gr. 3; 25 µm 204.00 408.00 Basket strainer for double filter KDFK Suitable for housing size 3 / DN32 / 40 / Filter fineness 25 µm, filter surface 440 cm ² Material 1.4301 / 1.