

## Kvt

Garanti: 12 ay  
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.  
**Kvt** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Kvt Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*



| Ürün                         | Açıklama                                                                                                                                                                                                                                  |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Td-175-12zi</a>  | 9,42 / 14,28" / 7,24" Press-fit rings for metallic materials 26686 PEM® TY-D® TD Sintered steel 4600 A, galvanized, colorless passivated                                                                                                  |
| <a href="#">F2/S23-M8x10</a> | Fastener with threaded bush Round head Ø 23 mm open bigHead® F2 / S23 Galvanized steel                                                                                                                                                    |
| <a href="#">Cls-M4-1</a>     | M4 / 0.97 / 7.87 Press-in nuts for metallic materials PEM® CLS / CLSS INOX 18/8 AISI 302/303, passivated                                                                                                                                  |
| <a href="#">Cls-M6-1</a>     | M6 / 1.38 / 11.18 Press-in nuts for metallic materials PEM® CLS / CLSS INOX 18/8 AISI 302/303, passivated                                                                                                                                 |
| <a href="#">Cls-M8-1</a>     | M8 / 1,38 / 12,7 Press-in nuts for metallic materials PEM® CLS / CLSS INOX 18/8 AISI 302/303, passivated                                                                                                                                  |
| <a href="#">MB850-090</a>    | 9/10 / 13.6 Sealing plug KOENIG EXPANDER® MB850 Drawing: MB850-090 Case hardening steel, galvanized Sleeve: Case-hardened steel, galvanized, thick-layer passivated Ball: Tempered roller bearing steel REACH: CAS-No 7439-92-1, Pb> 0.1% |
| <a href="#">MB850-070</a>    | 7 / 7.5 / 10.1 Plugging                                                                                                                                                                                                                   |

|                                |                                                                                                                                                                                                                   |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">MB 090</a>         | 9 / 8,8 / 22 Setting punch, mechanical for sealing plugs series MB Drawing: Setting punch Metr.MB 030-220 Tool steel tempered ~ 50 HRC                                                                            |
| <a href="#">MB 070</a>         | 7 / 6,8 / 18 Setting punch, mechanical for sealing plugs series MB Drawing: Setting punch Metr. MB 030-220 E Tool steel tempered ~ 50 HRC                                                                         |
| <a href="#">SKC550-050</a>     | 5 / 5,5 / 2,8 Sealing plug KOENIG EXPANDER® SKC550 Drawing: SKE-V-015.D_kvt Case hardened steel, blued Sleeve: case-hardened steel, blued Pen: Tempered steel, special oil film REACH: CAS-No 7439-92-1, Pb> 0.1% |
| <a href="#">M6 HUC/FEF 2,5</a> | M6 / 0.5-2.5 Blind rivet nuts Flat head, partial hexagon shank, open FASTEKS® FILKO HUC / FEF Galvanized steel, thick-layer passivated REACH: CAS-No 7439-92-1, Pb> 0.1%                                          |
| <a href="#">KNM5x0,8</a>       | M5x8 / 6.9 Threaded inserts with locking wedges Easy series KEENSERTS® KNM INOX 1.4305                                                                                                                            |
| <a href="#">KNM6x1</a>         | M6x10 / 8.8 Threaded inserts with locking wedges Easy series KEENSERTS® KNM INOX 1.4305                                                                                                                           |
| <a href="#">KNM8x1,25</a>      | M8x12 / 10.8 Threaded inserts with locking wedges                                                                                                                                                                 |
| <a href="#">KNM10x1,5</a>      | M10x14 / 12.8 Threaded inserts with locking wedges                                                                                                                                                                |
| <a href="#">KNM12x1,75</a>     | M12x16 / 14.75 Threaded inserts with locking wedges                                                                                                                                                               |
| <a href="#">FH4-M8-25</a>      | M8 / 25 / 9,6 Self-clinching studs for INOX and metallic materials PEM® FH4 INOX AISI 400, passivated                                                                                                             |
| <a href="#">FH-4MM-30ZI</a>    | 4 / 30 / 6 Press studs for metallic materials PEM® FH Hardened steel, galvanized, colorless passivated                                                                                                            |
| <a href="#">FH-M8-20ZI</a>     | M8 / 20 / 9.6 Self-clinching studs for metallic materials PEM® FH Hardened steel, galvanized, colorless passivated                                                                                                |
| <a href="#">99R10-01A1</a>     | 106320                                                                                                                                                                                                            |
| <a href="#">2600-LW/D6834</a>  | 105830                                                                                                                                                                                                            |
| <a href="#">V99S10-05AG</a>    | 106323                                                                                                                                                                                                            |
| <a href="#">UNN-32045-024</a>  | min. order?                                                                                                                                                                                                       |
| <a href="#">UNN-32045-013</a>  | min. order?                                                                                                                                                                                                       |
| <a href="#">Unn-32044-045</a>  | min. order?                                                                                                                                                                                                       |
| <a href="#">FH-M5-22ZI</a>     | M5/22/6.5 Self-clinching studs for metallic materials PEM® FH Hardened steel, zinc-plated, colorless passivated                                                                                                   |
| <a href="#">FH-M5-35ZI</a>     | M5/35/6.5 Self-clinching studs for metallic materials PEM® FH Hardened steel, zinc-plated, colorless passivated                                                                                                   |
| <a href="#">SO-M5-20ZI</a>     | M5/20/7.12 self-clinching bushings open, for metallic materials PEM® SO Hardened steel, zinc-plated, colorless passivated                                                                                         |

|                                         |                                                                                                                                                                                                                          |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">M8 HC/ROKS 5,0</a>          | M8 / 3-5 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                          |
| <a href="#">M8HUKO55 A2 (HUT/ROKS)</a>  | M8 / 3-5,5 / 548305 TUBTARA® HUKO (HUT/ROKS) INOX A2                                                                                                                                                                     |
| <a href="#">M6 HC/ROKS 4,5</a>          | M6 / 2,5-4,5 FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                                                                                             |
| <a href="#">M6HUKO50 A2 (HUT/ROKS)</a>  | M6 / 3-5 / 546525 TUBTARA® HUKO (HUT/ROKS) INOX A2                                                                                                                                                                       |
| <a href="#">M6-65 HBM/KS A2</a>         | ECOSYN-BCT M6-65 HBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, partial hex shank Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                             |
| <a href="#">M8-65 HHBM/KS A2</a>        | ECOSYN-BCT M6-65 HBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, partial hex shank Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                             |
| <a href="#">M5-55L20HBM/KSA2 ECOSYN</a> | ECOSYN-BCT M5-55L20 HBM/KS A2 (Sw7.0) Clamping range: 2.5-5.5MM Small countersunk head, partial hex shank Open, A2 stainless steel, length 20 mm Blind rivet nut ECOSYN-BCT Multigrip                                    |
| <a href="#">M10-65 HHBM/KSA2</a>        | ECOSYN-BCT M10-65 HHBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, full 6kt shaft Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                              |
| <a href="#">M10 HC/ROF 5,5 FASTEKS+</a> | FASTEKS FILKO M10 HC/ROF 5.5 TIN PLATED BLIND RIVET NUT CLAMPING RANGE: 3.0-5.0 MM PART-6KT SHANK, FLAT HEAD, OPEN, STAINLESS STEEL A2, Surface nickel strike + tin plating 5my shiny according to DIN 50965             |
| <a href="#">M5 HC/ROKS 3,5 FASTEKS+</a> | FASTEKS FILKO M5 HC/ROKS 3.5 TIN PLATED BLIND RIVET NUT CLAMPING RANGE: 1.5-3.5MM PART 6KT SHANK, SMALL COUNTERSUNK HEAD, OPEN, STAINLESS STEEL A2, Surface nickel strike + tin plating 5my shiny according to DIN 50965 |
| <a href="#">M4 HC/ROKS 3,0</a>          | M4 / 1,8-3 FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                                                                                               |
| <a href="#">M10 HC/ROF 5,5 FASTEKS+</a> | FASTEKS FILKO M10 HC/ROF 5.5 TIN PLATED BLIND RIVET NUT CLAMPING RANGE: 3.0-5.0 MM PART-6KT SHANK, FLAT HEAD, OPEN, STAINLESS STEEL A2, Surface nickel strike + tin plating 5my shiny according to DIN 50965             |
| <a href="#">M6-65 HBM/KS A2</a>         | ECOSYN-BCT M6-65 HBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, partial hex shank Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                             |
| <a href="#">M5-55L20HBM/KSA2 ECOSYN</a> | ECOSYN-BCT M5-55L20 HBM/KS A2 (Sw7.0) Clamping range: 2.5-5.5MM Small countersunk head, partial hex shank Open, A2 stainless steel, length 20 mm Blind rivet nut ECOSYN-BCT Multigrip                                    |
| <a href="#">M8-65 HHBM/KS A2</a>        | ECOSYN-BCT M8-65 HHBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, full 6kt shaft Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                               |
| <a href="#">M6 HC/ROKS 4,5</a>          | M6/2.5-4.5 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                        |

|                                                     |                                                                                                                                                                                                                          |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">M8 HC/ROKS 5,0</a>                      | M8/3-5 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                            |
| <a href="#">M4 HC/ROKS 3,0</a>                      | M4/1.8-3 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO® HC/ROKS INOX A2                                                                                                          |
| <a href="#">M5 HC/ROKS 3,5 FASTEKS+</a>             | FASTEKS FILKO M5 HC/ROKS 3.5 TIN PLATED BLIND RIVET NUT CLAMPING RANGE: 1.5-3.5MM PART 6KT SHANK, SMALL COUNTERSUNK HEAD, OPEN, STAINLESS STEEL A2, Surface nickel strike + tin plating 5my shiny according to DIN 50965 |
| <a href="#">M10 HC ROF 5,5 VERZINNT M10X21,3 A2</a> |                                                                                                                                                                                                                          |
| <a href="#">M5 HC ROKS 3,5 VERZINNT M5X11,6 A2</a>  |                                                                                                                                                                                                                          |
| <a href="#">M8 HC ROKS 5,0</a>                      | M8X17,4 A2                                                                                                                                                                                                               |
| <a href="#">M6 HC ROKS 4,5 A2</a>                   |                                                                                                                                                                                                                          |
| <a href="#">M6-65 HBMKS A2 M6X18</a>                |                                                                                                                                                                                                                          |
| <a href="#">M8-65 HHBMKS A2 M8X20</a>               |                                                                                                                                                                                                                          |
| <a href="#">M5-55L20 HBMKS A2 M5X20,0</a>           |                                                                                                                                                                                                                          |
| <a href="#">M4 HC ROKS 3,0 M4X10</a>                | A2                                                                                                                                                                                                                       |
| <a href="#">M10 HC/ROFG 5,5 FASTEKS</a>             | FASTEKS+ FILKO M10 HC/ROFG 5.5 Blind rivet nut, clamping range: 2.5-5.5MM Part 6kt shaft Flat head, closed, stainless steel A2, Surface: NI 0.5-2µ + SN GL 4-7µ DIN50965 (Tinned)                                        |
| <a href="#">M5 HC/ROKS 3,5 FASTEKS+</a>             | FASTEKS FILKO M5 HC/ROKS 3.5 TIN PLATED BLIND RIVET NUT CLAMPING RANGE: 1.5-3.5MM PART 6KT SHANK, SMALL COUNTERSUNK HEAD, OPEN, STAINLESS STEEL A2, Surface nickel strike + tin plating 5my shiny according to DIN 50965 |
| <a href="#">M8 HC/ROKS 5,0</a>                      | M8/3-5 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO HC/ROKS INOX A2                                                                                                             |
| <a href="#">M6 HC/ROKS 4,5</a>                      | M6/2.5-4.5 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO HC/ROKS INOX A2                                                                                                         |
| <a href="#">M6-65 HBM/KS A2</a>                     | ECOSYN-BCT M6-65 HBM/KS A2 Clamping range: 2.5-6.5MM Small countersunk head, partial hex shank Open, stainless steel A2 Blind rivet nut ECOSYN-BCT Multigrip                                                             |
| <a href="#">M8-65 HBM/KS A2</a>                     | M8 / 2.5-6.5mm Blind rivet nuts Multigrip small countersunk head, partial hexagonal shank, of fen ~ecosyn® BCT INOX                                                                                                      |
| <a href="#">M5-55L20HBM/KSA2 ECOSYN</a>             | ECOSYN-BCT M5-55L20 HBM/KS A2 (Sw7.0) Clamping range: 2.5-5.5MM Small countersunk head, partial hex shank Open, A2 stainless steel, length 20 mm Blind rivet nut ECOSYN-BCT Multigrip                                    |
| <a href="#">M4 HC/ROKS 3,0</a>                      | M4/1.8-3 Blind rivet nuts small countersunk head, partial hexagonal shank, open FASTEKS® FILKO HC/ROKS INOX A2                                                                                                           |
| <a href="#">CON SIL/ALY PSZCL M3X6</a>              |                                                                                                                                                                                                                          |

|                                             |                                                                                                                                                           |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">CON SIL/ALY PSZCL/SOX M3X10</a> |                                                                                                                                                           |
| <a href="#">CON SIL/ALY PSZCL M3X10</a>     |                                                                                                                                                           |
| <a href="#">CON SIL/ALY PSZCL/SOX M3X12</a> |                                                                                                                                                           |
| <a href="#">M 5 x 16 / X15 20146</a>        | Cylinder screws 3233675 with hexagon socket and extremely low head INOX A2                                                                                |
| <a href="#">M 4 / 4,3/12/1 1356</a>         | Discs 1117130 without bevel DIN 9021, ~ISO 7093 INOX A2 140 HV                                                                                            |
| <a href="#">300154612 C1-84721</a>          |                                                                                                                                                           |
| <a href="#">300122897, M4-Zi-095-35</a>     |                                                                                                                                                           |
| <a href="#">300148877 C1-51252-X1</a>       |                                                                                                                                                           |
| <a href="#">300104916</a>                   |                                                                                                                                                           |
| <a href="#">Ms204426ad3-5</a>               |                                                                                                                                                           |
| <a href="#">300155583 C1-88513</a>          |                                                                                                                                                           |
| <a href="#">145-M2</a>                      | 145-M2 M2 x 4 Gewindeeinsätze selbstschneidend für Thermoplaste Tappex® TRISERT® Zeichnung: 145M2                                                         |
| <a href="#">Drs M30x1,5 300104932</a>       |                                                                                                                                                           |
| <a href="#">300147017 C1-33898</a>          |                                                                                                                                                           |
| <a href="#">300139884</a>                   |                                                                                                                                                           |
| <a href="#">300137208 Smtso-M3-3 Et</a>     |                                                                                                                                                           |
| <a href="#">Cls-M8-2</a>                    |                                                                                                                                                           |
| <a href="#">Knhm 8x1.25</a>                 |                                                                                                                                                           |
| <a href="#">M10x1,5 Knhm</a>                |                                                                                                                                                           |
| <a href="#">Rs M17x1 300104892</a>          |                                                                                                                                                           |
| <a href="#">300103589</a>                   |                                                                                                                                                           |
| <a href="#">300104303 Sp-M5-1</a>           |                                                                                                                                                           |
| <a href="#">Knhml8x1,25</a>                 | M8 x 14 / 12.8 Threaded inserts with locking wedges heavy series, with 4 locking wedges, self-locking KEENSERTS® KNHML INOX 1.4305, Molykote (MIL-L-8937) |
| <a href="#">Drs M17x1 300104929</a>         |                                                                                                                                                           |
| <a href="#">300118793</a>                   |                                                                                                                                                           |
| <a href="#">Mb 600-070</a>                  |                                                                                                                                                           |
| <a href="#">145-M4</a>                      | M4 x 5,6 Gewindeeinsätze selbstschneidend                                                                                                                 |
| <a href="#">Ms20426ad3-5</a>                |                                                                                                                                                           |

[Artikel: 300110693 Mb 600-120 Ganz](#)  
[Rostfrei 12 Mm Durchm. Koenig](#)  
[Expander Dichtstopfen](#)

[300176102 \(Smtso-2,1-3 Et\)](#)

[300110724](#)

[Knhm 10x1,5](#)

[Ms21059I08](#)

[Exttool-030 300160392](#)

[300149529](#)

[Knm 8x1,25](#)

[300115288](#)

[Sp-M8-1](#)

[300155920 C1-86386](#)

[300103590](#)

[Ewtool 040-1](#)

[Rs M30x1,5 300104896](#)

[300171971 C1-110771](#)

[Ms20426ad3-7](#)

[300200039 Pb2500-Qw](#)