

Labino

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz. **Labino** Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Labino Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

Floodlight Distribution angle (beam) approx. 45° Irradiance: 50w bulb = 5 800 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") 35w bulb = 4 000 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") Visible light 50w: < 2 Lux Visible light 35w: < 2 Lux Midlight Distribution angle (beam) approx. 20° Irradiance: 50w bulb = 17 000 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") 35w bulb = 12 000 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") Visible light 50w: < 5 Lux Visible light 35w: < 3 Lux Spotlight Distribution angle (beam) approx. 3.5° Irradiance: 50w bulb > 65 000 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") 35w bulb > 45 000 $\mu\text{W}/\text{cm}^2$ at 38 cm (15") Visible light 50w: < 13 Lux Visible light 35w: < 10 Lux *Big divergence	Mains - Voltage i. 100 -230 VAC ii. Operated by separate PSU with self-selecting voltages Battery i. 2 200 mAh Lithium-Ion ii. Voltage: 14.8 V iii. Running time: 1 hour iv. Charging time: 1.5 hours Weight & Cables i. Weight battery operated: 1.9 kilos (4.19 lbs) ii. Weight mains operated: 1.4 kilos (3.09 lbs) iii. Cable length: 0.7 meters, fully extended 2.8 meters (9 feet) DISTRIBUTOR:	Handles i. Top Handle ii. Pistol Handle Additional Information i. Mechanical Stability (bulb): MIL-STD 810 ii. Service life (bulb): $\approx$ 2 000 hrs iii. Wavelength: UV-A, peak-365 nm iv. Start-up time: full power after 5-15 sec v. Material in housing: Magnesium Alloy vi. The housing is via pre milled slots prepared for mounting devices vii. CE approved viii. EN 62471 - Optical Safety: Risk class 3 (High Risk) Included: Mains: Lamp, Power Supply unit, UV Block Goggles Battery: Lamp, 1 Battery, UV Block Goggles
---	---	---

5. UV&White Light Sensor (Luxmeter)

Ařaėıda belirtilen zelliklerde UV&Beyaz Iřık lm cihazı.

UV Light Sensor	White Light Sensor
Spectral Range: 300 nm to 400 nm	Spectral Range: 400 nm to 700 nm
Sensitivity Region (FWHM): 325 nm to 395 nm	Sensitivity Region (FWHM): 485 nm to 600 nm
Operation Range: 0 to 50 000 $\mu\text{W}/\text{cm}^2$	Operation Range: 0 to 10 000 Lux (1 000 fc)
Accuracy: UV Light: +/- 4 %	Accuracy: Visible Light: +/- 3 %

rn	Aıklama
Apollo 2.0 Single Kit (1 reader, 1 sensor)	RADIOMETER I PHOTOMETER
MB 3.0 Zeus Mains UV LED light	
UV1224	Labino GX Orion UV "Mother" Unit Main unit 10 pcs. UV-LED Weight: 2.5kg Beam size (> 1200 $\mu\text{W} / \text{cm}^2$): 260 x 180 mm UV intensity at a distance of 38 cm (15 ") : approx. 4500 $\mu\text{W} / \text{cm}^2$ Suspension with chains and hooks (with UV on / off button only) (in compliance with ASTM E3022-15) (in compliance with Rolls-Royce RRES 90061) (in compliance with Airbus AITM6-1001) Customs tariff number: 85394900 Country of origin: Sweden
LED lamp Labino MB 3.0 Selene	battery version (ASTM E3022-2018) battery version (ASTM E3022-2018) Intensity: approx. 9,000 $\mu\text{W}/\text{cm}^2$ (at a distance of 38 cm) Battery in continuous operation: approx. 3 hours (+/-5%) 3 365nm UV LED , 1 piece white light LED 4 pcs batteries , 1 pc charger 1 piece car charger 1 pc. charging cable for charging during the ongoing operation 1 piece safety goggles 1 pc belt clip ,1piece rubber buffer,1 suitcase The lamp may only be used with the manufacturer's original batteries and charger, otherwise the guarantee will be void!
F101 Duv-35	
Apollo 1.0 Uv & White Light Meter	
Octg3	
Mpxl Uv Ps135	

[F99 Trigger Ballast 230 Vac](#)
[Ps135](#)

[Power Supply](#)

[Mpxl Uv Trac Pack / Standard With Charger](#)

[Octg2](#)