

Laurel Electronics



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Laurel Electronics Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Laurel Electronics Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
L20010DCV3	Main Board - L2 Standard Main Board, Red LEDs • Power supply - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 0 None • Analog Output (isolated) - 1 Isolated 4-20 mA, 0-20 mA, 0-10 V, -10 to +10V • Digital Interface (isolated) - 0 None • Signal Input (isolated) - DCV3 ±20.000 V
L20110KC	• Main Board - L2 Standard Main Board, Red LEDs • Power supply - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 1 Two 8A Contact Relays • Analog Output (isolated) - 1 Isolated 4-20 mA, 0-20 mA, 0-10 V, -10 to +10V • Digital Interface (isolated) - 0 None • Thermocouple Input - KC Thermocouple Type K, -347°C to 1372°C
LAUREATE SERIES 2 L20110P385C	• Main Board - L2 Standard Main Board, Red LEDs • Power supply - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 1 Two 8A Contact Relays • Analog Output (isolated) - 1 Isolated 4-20 mA, 0-20 mA, 0-10 V, -10 to +10V Digital Interface (isolated) - 0 None • Signal Input (isolated) - DCA2 ±20.000 mA
L20110P385C	Main Board - L2 Standard Main Board, Red LEDs Power - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 1 Two 8A Contact Relays • Analog Output (isolated) - 1 Isolated 4-20 mA, 0-20 mA, 0-10 V, -10 to +10V Digital Interface (isolated) - 0 None • RTD type - P385C Pt 100 DIN RTD, -202°C to 850°C
L20210P385C	Main Board - L2 Standard Main Board, Red LEDs • Power supply - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 2 Two 120 mA Solid State Relays • Analog Output (isolated) - 1 Isolated 4-20 mA, 0-20 mA, 0-10 V, -10 to +10V • Digital Interface (isolated) - 0 None • RTD Type - P385C Pt 100 DIN RTD, -202°C to 850°C

L2011OKC	
PSHK+ 0.05BBPG	Analog 0.050-10V
L20002dvc3	
L10000rmv1	
L10000p	
Lt-Dc	
Lt-Wm	
L50127fr,Box1calibrated	L50127FR,BOX1 CALIBRATED BY LAUREL
Lt-R	
Ltse60	
L50000FR	• Main Board - L5 Standard Main Board, Green LEDs • Power supply - 0 85-264 Vac or 90-300 Vdc • Relay Output (isolated) - 0 None • Analog Output (isolated) - 0 None • Digital Interface (isolated) - 0 None • Signal Input (isolated) - FR Dual-Channel Pulse Input Signal Conditioner
Lt-Rm	
L10000wm1	
Lt-Fr	
Lt-P	
L10000jc	
L40	
M24-M232-Mt1	
L10000r0	
Lt-Rtd	
Lt-Qd	
Lts60	
Qls	
Lt-Tc	
Lw10000p	
L10000p385c	
L70000fr	
M2010003ser26	DIGITAL PANEL METER 2 DISPALY RS232 6 DIGITS

Lts6	
L10000dcv1	
L50000vf1	
M4000002p4	(PRICE/EA) DIGITAL PANEL METER 2 DISPLAY 95-265VAC POWER BLACK CASE WALL MOUNT PROCESS SIGNAL 4-20MA
Lt-Sg	
M8001002p6	DIGITAL PANEL METER8 INDOOR BRIGHTNESS DISPLAY
L50001	
L70100fr	
Lt-Vf	