



Lumel

Garanti: 12 ay
 Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Lumel Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Lumel Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
N24 S210300e0	digital mater
P30U-101100E0	Lumel P30U analog output: 0 / 4-20mA, without SD slot, second relay, Supply voltage 85-253V AC / DC Version: English
ND20CT	Multifunction measuring device LUMEL multifunction measuring device ND20 230 / 400V Input current: 0.1A / 0.25A Input voltage: 57.5 / 100/230 / 400V AC Pulse output
ND20LITE22100M1	3-phase network meter, LCD 2:input 1/5A 2:U in. 3x57,7/100V, 3x69,3/120V, 3x230/400V 1:supply 85-253Va.c./d.c., 90-300Vd.c. 00:standard version M:English/Polish version 1:with test certificate Weight: 0.44 kg/pcs
02300763	
2000-100-0-2-02	
200320008	
EA 19N 12	
EA17NE20100000000	
HT20 LoT	
LCTB 62/30 200/5À cl.0.5 5VA	
LCTB 86/60 1000/5À cl.0.5 20VA	

MA 19N 800V	
N10-21110008	
N10-22120008	
N30U-200300E0	
NA5-TRU10410008	
P12U	
P17G	
P20Z	
P20Z-09321008	
p20z-09321008 4-20ma	
P300 101100E0	
RE71-01100E0	
RPL1-13200E0	
SM2 0128	
ND30IoT 2221MSM1	Power network analyzer (MQTT) 2:3x110/190V, 3x400/690V 2:2 relays,1 analog,2 Pt100 2:Ethernet, int. Memory 1:sup. 85-253Vac,90-300Vdc MS:MQTT protocol and supervisory relay M:English/Polish version 1:QI certificate
ND45 2011M001	Power network analyzer 2:inp.volt. 3 x 230/400 V 0:without add. inputs/outputs 1:sup. 85...253 V ac, 90...300 V dc 1:class measurement A/S M:English/Polish version 00:standard version 1:QI certificate
RE72 111100M0	Prog. controller 48x48 Output 1:1 relay Output 2:1 relay Output 3:1 relay Auxiliary voltage: 1 Uh=85-253Vac/dc Version: 00 standard version Language: M English version Check: 0 standard version
TRANSDUCER 50/4-20MA / T23CT	T23CT 1000M0 9900001 1:current 50A 0:without rail mounting kit 00:standard version M:English/Polish version 0:standard version
2150401	Transmitter P20 Pt100 (-200 to +850°C) 1:Output 0..20mA 1: Voltage 85-253 Vac/dc 01:input Pt100 -200...850 °C 00:default version P20 1101008 8: English version
P20 2201008	Mass converter P20 Pt100 (-200 to +850°C) 1:Output 4..20mA 1: voltage 20...85 V d.c., 20...65 V a.c 01:input Pt100 -200...850 °C 00:default version 8: English version
Mass converter P20	9900001 Out: 0-10V Uh: 20-85VDC / 20-65VAC P20 3201008
Na6tru00010007	
P30u-101100e0	TRANSDUCER
P20-2166001	
Lcts 155/80sc	
Lctb 104/80 1500/5a Cl.0.5 20va	
Lumel Stromwandler Typ Lcts 155/80sc	
P12u - Obsolete, Replaced By - P30u (E)(P)	
Lctb 62/30 200/5? Cl.0.5 5va	

Ea17-1000/5a
P43
N24 S240900e1
Kd744100261028
Ea17-1500/5a
Na6-Mgbu11420008
Lctb 86/60 1000/5? Cl.0.5 20va
02300765 , 1601pcb5-001 (Brand Kiewewetter)
N24 S24xx00e1
Lctb 62/40 600/5? Cl.0.5 7.5va
Typ P30o
P30u-101200e0
P43-211300e0
Ea17-250/5a
Analog Input Card For Kd7
P30o Transducer 2 X Universal Inputlu
P12u Transducer Flow Transmitter
200320008 Obsolete, Replaced By P30u-101200e0
Ea17-0-500v
Da101g3008
P20z Transducer Ac Akim D¼n¼őt¼r¼c¼
Na5tru00420008
N24 S243100e1
Typ Nd1 2200e1
N24 S240800e1
Ea17-600/5a
P12o
P30u-201200ex
72.13.500 De 72
Lctb 62/40 250/5? Cl.0.5 2.5va
Rs232/Rs485 Pd51a3008
Ea17-200/5a