

Mader



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.

Mader Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Mader Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
269500	Quick coupling socket shutting off on one side nominal size 7,2 brass design with male thread Type:66 Temperature range:-20 °C to +100 °C Material of seal:NBR Material of valve body:Brass design Material of valve:Brass design Material of springs, snap rings:Stainless steel 1.4310 Connection: G 1/4 a DN 7,2
35232	
P/N: 219507 Type: L150.0156	
P/N: 216331 Type: Se-K-6-22	
226926 (L123.1050)	
214996	HE-K-K-6-1-25-75 Robust lifting unit -- with sealed ball guide Impact force 150 - 220 N (at 6 bar) Repeat accuracy ± 0.02 mm
Nsi-R6-60-S-B	
216135(Am00946)	
Lv422054	
P/N: 246844 Type: Rse-K-6-8-R-P	
Me1222	
Se-P2-4-14	
Rse-P1-4-4-R-H(216135)	
Pdi-040-0005-I-P-M-M6k5-Sa	
219599 (L093.6023)	
Nsm-T8-2p-Pnp-5	

215896 (Am00691) Nsi-R6-80-S-B	
216374	SES-K-6-25-H -- Swivel unit size 6 Heavy duty version Driving torque (effective) 6.5 Nm Angle of rotation continuously adjustable 0-190 ° Repeat accuracy $\pm 0.01^\circ$ hydraulic cushioning external, hardened stop system no loss of the end position screwed proximity switch in the stop sleeve -- double-acting drive cylinder
226952 (L123.4156)	
Am00919	
P/N: 216136 Type: Rse-P1-4-4-L-H	
Pse-4-6-1005	
Mgw-B-64	