



Madgetech

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Madgetech Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Madgetech Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Hitemp140x2-Td-Fp-12	mt-901913-00 Data logger with rigid probe 508 mm and flexible probe 305 mm, including NIST certificate 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (probe only), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), storage 32,700 Measured values, IP68
mt-900140-00	HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering
mt-900211-00	HiTemp140-FP-12 data logger with flexible probe 305 mm, including NIST certificate at 30 ° C and 140 ° C Measuring range -60 ° C ... + 260 ° C (only probe), data logger -40 ° C ... + 140 ° C, max. 4 bar (60 PSIA), memory 32,700 Measured values, IP68 HiTemp140 with flexible probe available with various probe lengths, please specify model when ordering
mt-900992-00	PR140 pressure logger with NPT connection can be used up to 6.9 bar, IP68, 25 mm x 58 mm, food safe for autoclave validation and Steam sterilization
mt-900998-00	PR140 pressure logger with flush top can be used up to 6.9 bar, IP68, 25 mm x 51 mm, food safe for autoclave validation and Steam

	sterilization simple interface
mt-900319-00	IFC400 USB interface for HiTemp140, PR140 various accessories, consumables, ... for HiTemp140 / Pr140
mt-900097-00	Replacement battery ER1425S-HT for HiTemp140 / PR140 Lithium, 3.6 V, 500 mAh, size 1/2 AA up to 150 ° C
mt-900229-00	O-ring set for HiTemp140 series
mt-900332-00	KEY RING END CAP fastening cap with eyelet for HiTemp140, PR140, RHTemp1000 series (for IS certified loggers only if installed by the manufacturer)
mt-902011-00	SVP Secure System - MadgeTech 4 Secure Validation Software Package IQ/OQ/PQ Secure Software Validation Workbook and Software Package, 21 CFR Part 11
mt-900385-00	MT-AluCase-18 transport and storage case Internal dimensions 44.45 x 34.04 x 14.99 cm / external dimensions 47.63 x 38.10 x 15.24 cm / foam insert can itself be adjusted RTDTempX data logger with 12 inputs
mt-902173-00	RTDTempX12 temperature data logger, Pt100, 12 channels Measuring range -200 °C to +850 °C (depending on sensor) ****RTDTempX data logger with 12 inputs***
Pt100	Pt100 probe for "dry heat sterilization / dehydrogenation" Sensor Pt100 4-wire class AA according to DIN IEC 751; probe Sheath 1.4541, diameter 3 mm, probe length: 150 mm, bendable; Transition sleeve stainless steel 6 x 40 mm, encapsulated; Fiberglass cable insulated with steel braiding, length 5 m; Application range up to 350 ° C (dry heat sterilization + dehydrogenation process); Connection free ends; Customs number: 9025 9000 Origin country: Germany
RHTemp1000Ex	902154 MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate
MadgeTech IFC400 USB interface	900319 for HiTemp140, PR140 and 1000 data loggers
MT-902213-00	FM certified (no ATEX approval!) MadgeTech RHTemp1000IS data logger Humidity + temperature (intrinsically safe, Class I, Division 2, Groups A, B, C & D), including NIST traceable Certificate, measuring range 40°C ... + 80°C / 0 ... 100% RH, Memory 16,384 measured values
MT-902154-00	ATEX, IECEx, FM 3610 Certified MadgeTech RHTemp1000Ex data logger Humidity + temperature Measuring range 40°C ... + 80°C / 0 ... 100% RH, memory 16,384 measured values, intrinsically safe, ATEX / IECex specifications see website, incl. traceable NIST certificate
Madgetech	
Madgetech	
MT-902170-00	MadgeTech TCTempX4LCD data logger, 4 channels, thermocouple 4 channels for thermocouple (type J, K, T, E, R, S, B, N), with Display, incl. battery and USB Micro B cable, without sensor (please order separately) Origin: US Customs #: 9025 8050
MT-900140-00	MadgeTech HiTemp140-1 data logger, probe 27 mm rigid with 27 mm long rigid immersion probe, measuring range -200...+260°C

	(probe only), 32,700 readings, IP68, incl. NIST Certificate at 30°C and 140°C Origin: US Customs No.: 9025 1900
HiTemp140	-40+ -140
MT-902154-00	MadgeTech RHTemp1000Ex data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Measured values, intrinsically safe, ATEX/IECex Specifications see website, incl. traceable NIST certificate
MT-902208-00	MadgeTech RHTemp1000Ex-KR data logger humidity+temperature with key ring end cap, measuring range 40°C...+80°C / 0...100%RH, memory 16,384 readings, intrinsically safe / Intrinsically Safe, ATEX/IECex specifications see website, incl. traceable NIST certificate
MT-902213-00	ATTENTION ! The RHTemp1000IS data loggers have no (!) ATEX approval. (intrinsically safe, Class I, Division 2, Groups A, B, C & D), incl. NIST traceable certificate, measuring range 40°C...+80°C / 0...100%RH, memory 16,384 readings
MT-902218-00	MadgeTech RHTemp1000IS-KR data logger humidity+temperature Measuring range 40°C...+80°C / 0...100%RH, memory 16,384 Readings, with installed Key-Ring end cap, intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D, incl. traceable NIST certificate
MT-902214-00	ATTENTION ! The Temp1000IS data loggers have no (!) ATEX approval. Temp1000IS-1 data logger, probe 25mm Measuring range 40°C...+80°C, memory 65,536 measured values, with 25 mm probe and standard (flush bottom) end cap (intrinsically safe / Intrinsically Safe, Class I, Division 2, Groups A, B, C & D), incl. NIST certificate traceable certificate The Temp1000IS is available with the following probe lengths: 1", 2", 5.25", 7". The Temp1000IS is available in the "Flush
MT-900319-00	for HiTemp140, PR140 and 1000er Datenlogger
MT-900319-00	MadgeTech IFC400 USB-Interface HiTemp140, PR140 und 1000er Datenlogger
Hitemp140-1	HiTemp140-1 data logger with immersion probe 27 mm, incl. NIST certificate at 30 ° C and 140 ° C Measuring range -200 ... + 260°C (probe only), 32,700 Measured values, IP68
Prhtemp2000	
Rfprhtemp2000a	
Ew-18010-15	
Avs140-1	AUTOCLAVE VALIDATION SYSTEM: INCLUDES (1) HITEMP140 DATA LOGGER WITH NIST CALIBRATION CERTIFICATE, IFC400 INTERFACE CABLE, (1) LICENSE MADGETECS FDA
Shock101-50-Eb	
Block Data Loger	
Ifc200 Usb-Interface Für Madgetech Standard	Datenlogger Serie u.a. für QuadVolt, OctVolt, QuadTcTemp2000V2, OctTcTemp2000V2, QuadThermoVault, OctThermoVault
Level1000	
Svp-Securesystem	IQ/OQ/PQ SECURE SOFTWARE VALIDATION WORK BOOK AND SOFTWARE PACKAGE.

Quadthermovault	
Rhemp101a - Humidity And Temperature Data Logger / Range -40°C To +80°C	
Pr140	
Rhemp101a	
Pr140-Lvl	
Hitemp 140-Fr	
Ifc200 Usb Interface Cable For Standard	
Hightemp 140-1	
Tc101a	
Ifc400	
Oct-Quad-Thermobarrier	THERMAL BARRIER FOR QUADTEMP AND OCTTEMP
Rhemp1000is	
Pr140 Pressure Data Logger	
Prtemp1000d-100	0-100 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER
Rfc1000	
Pr 140 Range : 0 To 5 Bar Pressure Data Logger For High Temperatures	
Prtemp1000d-500	0-500 PSID, DIFFERENTIAL PRESSURE, TEMPERATURE RECORDER
Pr140 - Pressure Data Logger / Range 0 To 5 Bar	
Avs140-6 Autoclave Validation System	
Rfrhemp2000a	
Ifc400 Interface	
Ifc200	
Prtemp140-Npt	HIGH TEMPERATURE PRESSURE DATA LOGGER WITH NPT PORT TOP
Hitemp140-1 High Temperature Pressure Data Logger	
Hitemp140x2 Dual Probe Data Logger	
Octthermovault	8-CHANNEL OVEN TEMPERATURE PROFILER AND AMERICAN POWER SUPPLY
Hp-1	
Hitemp140x2	
Avs140-6	AUTOCLAVE VALIDATION SYSTEM: INCLUDES (5) HITEMP140 DATA LOGGERS AND (1) PR140 NPT WITH NIST CALIBRATION CERTIFICATES FOR ALL, IFC406 MULTIPLEXER DOCK
Prtemp1000is-300-Psig	