

Mayr



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Mayr Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Mayr Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
ROBA -ES 19"	If the keyway is optional, the Ø16 part with the keyway and the Ø8 part will be without the keyway (if not, it can be without keyway in both parts)
EV028 FEM-240M-25	brake spring actuated - electromagnetically released Supply voltage 220 - 240 VAC Brake disc thickness 18 - 26mm ZTN85052000
EV028 FEM-480M-25 (Alternative for pos1)	spring actuated - electromagnetically released Supply voltage 380 - 480 VAC Brake disc thickness 18 - 26mm ZTN85052000
ENCODER KIT E 028 2 ENCODERS (BO / BG / V)	
Brake EV 028 FEM-240M-25	4453-281511-000000 Gewicht: 25 KG / ST Zolltarifnummer: 85052000
Brake EV 028 FEM-480M-25	
1/932,333	BO 19H7
8185947	018.100.2 Roba switch 24V Size1
0925011 Clutch	
ROBA SWITCH, 20/017.000.2	
0002340	
0002341	
0009560	

0010104-1
0014374-1
0023963
0034214
0113426-1
02/450.715.0
02500272
055.010.6
0802739
0911954
0921798
0921840
1/100.210/25/DIN 6885-1
1038577
140 / 030INT6
14940000A12DIN10DIN
19/940.000.A
2/017002
2/490.710.0
2/932.333/24/24
20/017.002
200/899.000.01S
207473
238596
3/490.825.0
3/910.400
32/891.100.0
32/891.104.1
4/931.333
4000021
400v 3A EL3219
4041259
4041261
4083775
4102233
440GT27121

53/k13.301.2s (OEM for AWG)
60/891.020 /1S (OEM)
6600059
7000145
7000379
7000616
7000789
7001407
7001939
70027450
7003503-2
7005098-1
7005404-1
7006026
7008384-1
7008644
7009839-1
7011039
7011668
7011897
7012443
7013308
7014348-1
7014718-1
7016439
7018142
7019183
7021842
7024940-2
7026782
7029674
7032790
7043859-1
7057399-1
7062073

7064394
8/100.110
8164595
8165389
8167145
8180151
8180154
8180160
8194546
8195779 P1100263 (OEM)
8199286
8202506
8204985
8205516-1
8212378
8226141 OEM!!
8229877
8245887
8259099
8259633
8261610
8263178
8263448
8264037
8284032
891.124.1S
932.333
940.000.A
9500
951.221
EAS-NCC-0/490.525.0.D
Gr.3/150.100
LR108927 oem
ROBA DS C25 X C32 10/951.441/25/32 ROBA-DS10.951.441
ROBA-Rurschnabe - Gro?e 1
S7100764

MTC 32A	
7014518	sliding hub Load-holding, friction-locking safety clutch ROBA sliding hub size 5 Type 170.312 drill 65mm H7 Nut: DIN 6885 BI.1 JS9 Installation width drive element w: 120mm liner long : 128mm nominal torque 1400 to 2100 Nm Please note: For manufacturing reasons, the bore in this version is now provided with a recess on the side of the adjusting nut according to catalog no. K.123.V15.DE
mayr® Item No.: 7022838	ROBA®-topstop® Type-tested, reliable safety brake according to the Machinery Directive ROBA top stop size 120 Type 899.000.02 wave Shaft: 24mm Fit shaft: k6 Bore: 24mm Fit: F7 Solenoid 12V Flange housing (motor side) Centering Z1: 110mm Fit: F8 Pitch Circle: 130mm bearing flange (output side) Centering Z: 110 mm Fit: j6 Braking torque 30 Nm overexcitation required with release monitoring proximity switch PNP normally open Optional operation with ROBA-brake-checker possible: - ROBA brake checker plus DC size. 2 types 028.600.2 - ROBA brake checker plus DC size. 2 types 028.100.2 - ROBA brake checker DC size. 2 types 058.600.2 according to catalog no. K.899.V15.DE Design as delivered with mayr serial number X3111821!
mayr® Item No.: 8185947	ROBA-switch 24V quick switching module size 1 Type 018.100.2 Input voltage 24V DC Output voltage 6, 8, 12, 16 V DC, freely selectable Operation with overexcitation or derating integrated DC-side shutdown maximum current load 5.0 amps at <= 45° C ambient temperature 2.5 amps at max. 70° C ambient temperature Degree of protection IP00 Approvals: UL, CE according to dimension sheet no. M.0181002.D
Roba-DS 40	
Art.-Nr.: 7059366-1	EAS® - compact® synchronous clutch The best-selling, backlash-free safety clutch EAS compact size 2 Type 494.525.3 hub (key) Bore: 35mm Fit: H7 Groove: DIN 6885 sheet 1 JS9 hub/494. (Adjusting spring) Bore: 35mm Fit: H7 Groove: DIN 6885 sheet 1 JS9 Sprocket yellow 92Sh-A attitude Torque: preset Limit torque for overload 40 to 100 Nm according to catalog no. K.490.V17.DE
Art.-Nr.: 7054515	EAS® sp Pneumatically switchable, infinitely variable Safety clutch for optimal adjustment of the moments of disengagement EAS Sp Gr. 1 Type 456.125.8 hub Bore: 30mm Fit: H7 Groove: DIN 6885 sheet 1 JS9 Recess: on the stator side Limit switch normally closed hub (elastic coupling) Bore: 40mm Fit: H7 Groove: DIN 6885 sheet 1 JS9 Limit torques for overload 25 to 150 Nm according to catalog number K.406.V09.D Execution as supplied with mayr serial number ZO125794!
0800157	limit switch Type 055.000.5 mechanical actuation Version in light metal housing Switching capacity changer 250VAC / 15A Degree of protection IP54 Execution according to our drawing no. F001010000003M1 according to dimension sheet no. M.0550005.D
3/490.600.1S	
Roba Es-24	
ROBA-ES Size 24, Type 940.033.A	
8180151	mayr art.-no.: 8180151 ROBA-switch Quick-Switch Rectifier Size 10 Type 017.000.2 Input voltage 100 - 250 V AC Output voltage 45 - 113 V DC Operation with overexcitation or power reduction Maximum Current Load 2.0 Amp. at <= 45° C Ambient temperature 1.0 Amp. at max. 70° C Ambient temperature Protection rating IP65 (clamping IP20) Test mark: UL, CE according to dimensions sheet no. M.017+002.D
mayr art nr 8180152	Type 017.000.2 ROBA-Switch fast switching rectifier 1.8 amps at <=45 C ambient temperature
403800	ES24 sprocket green 64Sh-D fit to ROBA-ES size 24, type 940.620.A S Art.8272656 as with mayr serial no. YO123472

6600102	Roba-D Torsionally stiff, flexible full jet coupling 5/911.101. Hub 1/P8f 91- Bore 90 Fit H7 Slot DIN 6885 BL.1 Dimension (M/Z) M with adjusting screw (S) S set screw thread M/Z M
EAS®-HSE	mayr® item no.: 7085554-1 high-speed safety clutch EAS-HSE size 3 Type 4139.60411 clamping ring hub Bore: 30 mm Fit: H6 clamping ring hub (Type 9210.) Pos. Article designation Bore: 30 mm Fit: H5 Torque setting: 300 Nm Limit torque for overload 185 to 370 Nm Balancing quality of safety coupling G2.5 based on 3000 rpm / ROBA-DS unit G2.5 based on 5000 rpm
EAS-HSE size 3 Type 4139.60411	shrink disk hub bore: 45 mm fit: H6 shrink disk hub large MF bore: 45 mm fit: H5 adjustment torque: 300 Nm torque limit for overload 185 to 370 Nm Safety coupling dyn. balanced G2.5 at 3000 rpm / ROBA-DS unit G2.5 at 5000 rpm.
ROBA-DS 7025339-1	Compact, torsionally rigid, backlash-free shaft coupling ROBA-DS Gr. 160 Type 953.221 Clamping ring hub 1 / clamping outside Bore: 60 mm Fit: H7 Clamping ring hub 2 / clamping outside Bore: 60 mm Fit: H7 Assembly Delivery: in individual parts Nominal torque 2600 Nm Impact torque 3900 Nm Bore-related, frictionally transmittable torque of the shaft/hub connection according to .Observe the catalog or a comparable fit. according to catalog no. K.950.V17.DE Version as supplied with mayr® serial number X2124729!
0007063-4	ROBAR slip hub Load-holding, friction-locking safety clutch ROBA slip hub size 4 Type 100.210 hub Bore: 40mm Fit: H7 Groove: DIN 6885 BI.1 JS9 Installation width drive element w: 16mm liner Length: 22.5mm Sprocket disc 1x17.02 Number of teeth: 21 Number of tracks: 1 Attitude Torque: 600 Nm Rated torque 550 to 1100 Nm according to catalog no. K.123.V16.DE
0066190	Roba Stop GR4 Proven, reliable, electromagnetic safety brake 802.410.3 24V Cable length: 400mm hub Hole: pre-drilled=7mm Braking torque 6 Nm according to catalog K.800.V06.D
7003458 smartflex	Reliable, flexible and permanently backlash-free metal bellows coupling smartflex size 0 type 932.333 Reduction bushing 1 Bore: 8mm Fit: H7 Reduction bushing 2 Bore: 14mm Fit: H7 Nominal torque 16Nm Bore-related, frictionally transmittable torque of the shaft/hub connection; Reducing bush 1 max. 9.6 Nm with fit H7/h6 or comparable pass game. Reducing bushing 2 max. 16 Nm with fit H7/h6 or comparable fit play. according to catalog no. K.932.V11.DE Version as supplied with mayr® serial number TN123064!
4.804.410.3	Roba-stop 6 Nm Brake gear: 2 pcs Brake Pad: 2 pcs
0002344	ROBAR slip hub Load-holding, friction-locking safety clutch ROBA slip hub size 2 Type 100.110 hub Bore: 25mm Fit: H7 Groove: DIN 6885 BI.1 JS9 Installation width drive element b: 12mm liner Length: 17mm Rated torque 26 to 130 Nm according to catalog no. K.123.V16.DE Version as supplied with mayr® serial number Y5101762!
ROBA-guidestop size 35	Type 3854.001D1 holding force: 4400 N LONG TYPE VERSION
ROBA-guidestop size 35	Type 3854.001D1 holding force: 2200 N SHORT TYPE VERSION
RSM 8/891.100.0	
8193517	DS100BGR.Lamellenpack.Erz. f.Type 953.--1 Spare part suitable for ROBA-DS size 100, type 953.001, mayr item no. 7018797, mayr serial number Z9109084
Brake Checker- 20/059.500.2	
0925117	Robotic GR.3 540,100S 24V rotor Bore 17mm Fit: H7 Nominal torque 10Nm
	EAS® duty torque The perfect overload protection for extruders EAS duty

7036236-9	torque size 6 Type 4043.70400 hub Bore: 120mm Fit: H7 Groove: DIN 6885 Sheet 1 JS9 Hub elastic. coupling Bore: 85mm Fit: H7 Groove: DIN 6885 Sheet 1 JS9 Assembly Delivery: control flag pressure flange Attitude Torque: 3926 Nm Hub (pos.1), overload module with cam ring (pos.2) and flange hub with claw ring (Pos.3) each completely balanced with balancing quality G2.5 based on 1500 1/min. Limit torque for overload 2800 to 5600 Nm according to catalog no. K.4043.V04.DE Version as delivered with mayr serial number GN102011!
7055376-1	EAS® duty torque The perfect overload protection for extruders EAS duty torque size 5 Type 4043.70400 hub Bore: 120mm Fit: H7 Groove: DIN 6885 Sheet 1 JS9 Hub elastic. coupling Bore: 85mm Fit: H7 Groove: DIN 6885 Sheet 1 JS9 Assembly Delivery: control flag pressure flange Attitude Torque: 3956 Nm Hub (pos.1), overload module with cam ring (pos.2) and flange hub with claw ring (Pos.3) each completely balanced with balancing quality G2.5 based on 1500 1/min. Limit torque for overload 2000 to 4000 Nm according to catalog no. K.4043.V04.DE Version as delivered with mayr serial number V8124020!
REF.NO:300726	RELIABLE SPRING LOADED SAFETY BRAKE ROBA STOP-M, TYPE:891.100.1, SIZE:500, BORE: 60MM, H7
7005586	Roba slip hub load-holding frictional safety clutch type 100.210 bore 20mm Fit: H7 DIN6885 sheet 1JS9 Installation width of drive element b: 10mm liner length: 15mm Rated torque 70-130NM
7004734	Roba DX Threshing tires, play-free, elastic metal bellows coupling GR.3 931,333 Clamp cable 1 Bore: 35mm Fit H7 DIN 6885 sheet 1JS9 Clamping hub 2 Bore 35mm Fit H7 DIN 6885 sheet 1JS9
ROBA 20/017.000.2SO	
7018797-1	ROBA®-DS Compact, torsionally rigid, backlash-free shaft coupling ROBA-DS size. 100 Type 953.001 Hub 1 feather key Bore: 65mm Fit: H7 Groove: DIN 6885 BI.1 JS9 Hub 2 key Bore: 65mm Fit: H7 Groove: DIN 6885 BI.1 JS9 assembly Delivery: in individual parts Nominal torque 1600 Nm Shock torque 2400 Nm according to catalog no. K.950.V17.DE Version as delivered with mayr® serial number Z9109083!
P.No. 8224265	
8194231	
Eas24006055	
60/891.020 /1s ()	
8173908 / Ac3.34/0/5/1/1/4/H/3	
Lr108927	
0921840 Sicherheitsbremseroba-Stop M Gr. 250typ 891.010.0 S	
8195570	
017 000 2s	
14624150	LIMITER
Ds63/K21.301.1s (Sg40so) With K21r63g4	
7000782/F15i	
2/484.525.4/41.28/	
1038054	
8236423	
440g-T27121 Elektromagnetische Schalter	

25/951.001/30h7/30h7	
1000/891.011.2/180	
437.401.0	
2/494.505.4/32/28	
4/436.705.8	CLUTCH COUPLING
7011897 Sicherheitsbremse Roba-Stop M Gr.32type 897.100.0	
Art.-Nr.: 7000603	
0022011-1	
7000570	
7018887-1	
8222958	
7000772	
200-500v Alternatif T= 0.05-2 Sec R : 0?-10m?	
Roba-Stop X1067996 0598 804.410.3 24v 25w 6nm , By Roba-Stop Type 802	
Type 952.000 S	
7049021-1	
7005522-1	
Smartflex-1/932.333 7000782/F15i	
8188960	
8168010	BRAKE
To101910 7000130	
8164590/F45	
1/025.000.6	
2/891.105.2/24/15 Bremse	
0035082	
Type: 110.110 Roba-Rutschnabe Gr. 1 Old Description, New Type: 100.110 Roba- Rutschnabe Gr. 1 Mit Standardkettenrad Or Ohne Kettenrad (Ask Customer)	
X10688081002 Spitzenlast-Bremse Roba-Stop Typ 10/863.614.3 180v 135w 620 Nm D=55 Mm	
28/940.011.P/28h6/25h6	
7043859-1 Kupplung Roba - Ds	
P/N: 8212406 Type: 891.080.1 S	
3/911.310/20/28	
1/932.33/16/24	

00041401498 3 100 110
Roba-Stop Type 802
0802866 Schalter Ultime
920301/F45
7000722
Kupplung Mayr Roba-Ds 25/951.881/28/28/6885/1, Tn1170064
P/N: 8180152 Type: 017.000.2
0911954 Durchrastkupplung Type 490.600.1 S
017.000.2s
03/P60.112.2/230-480v
Type 024.000.6
8212378 Eas1 Bgr 440.704.0 So Miy Nachschmierung
1/100.210/25/Din 6885-1
055.010.6 Schalter Endplatte
100.210
0921798 Sicherheits-Bremseroba-Stop-M Gr.150
802741
Roba Es-19/24(D??,16?19)
7001030
30100002
Rsm-X1 Rotor
1009083
911.400
Easnc3/4505150
8181677-1
8229877 Coupling Roba-Ds 10/951.443 S
Eas-Nc Gr. 1 Type 450.515.0, Konusbuchse, Bohrung 25 Mm
Type: 100.110 Roba-Rutschnabe Gr. 1 Ohne Kettenrad
M5125178, 7001030 Smartflex
100.110
7024940-2 Eas - Compact Synchronkupplung
Art. 8180152 20 Type. 017.000.2
8164595 M100 Rotor Ko So
8185299

1920665	
Eas2/400.405.1	
N4103484	
7000145 Kupplungroba-Es Gr. 19typ 940.000.Akatalog Nr.: K.940.V13.De	
0920427	
Mayr Art No. 0922157	ROBA-stop-M Reliable, spring-loaded safety brake ROBA-Stop M Gr.32 Type 891.210.1 p hub Hole: 25mm Fit: H7 But: DIN 6885 BI.1 JS9 Magnetspule20V Cable length: 400mm Braking torque 32Nm with coil holder for manual release IP65 Version as supplied with may serial number U6115177
8180125	Type 017.000.2 ROBA-Switch fast-acting rectifier
Eas14006055	
2/133.110/35/40	
0924188	
8200652 Laufruhiger, Permanenterregter Gleichstrommotor	
8226142 !!	
8226141 !!	
F039004004n	
Type 135.110	
2/100.110/20/6885-1/7	
38034000 Friction Clutch2/100.110/20 Size2	
X1068161 0794	
8004103	
0800157 Limit Switch055.000.5 /0598	
Eas Nc 1/450.805.0s 09141011201 Oem	
8200652 Gearmotor Type K11.201.1 S 24 V Dc, 180 W 3500 Min-1 Ip69k	
7001030 Kupplung1/932.433/11/19 Mit Metall. Wellrohr	
7053534-1	
Roba-Ds Gr.160 Type 953.261 Ds Torsionally Stiff, Backlash-Free All-Steel Coupling	
7011897 Bremse	
8204839	
7046838	
0002354 Type 100.210	
3/123210	
899.000.200	

M5125178 Bo 11 H7/19 H7	
Type 95.00	
0920806	
8263534	
7038231-1	
0002341 Sicherheitskupplung Roba-Rutschnabe 2/100.110	
0013947-1	
5/100.312/1	SAFETY CLUTCH 1IN BORE ROBA SLIP HUB
0056403	
14005051	CLUTCH
Din 6885	
4000022	
7000789 Metallbalgkupplung	
100/951.551	
8180152 Gleichrichter	
8186566	
226686 (7025897-1)	
64/896.10?.31/24/25/6885/1 Bremse	
Roba Dc	
20/019.100.2	
0910626	
055.000.5	
2/494.605.4/32/28	
Art Nr. 7000625	Metal bellows coupling smartflex Reliable, flexible and permanently backlash-free smartflex size 2 Type 932.333 Bellows long (8 waves) Raduzierbuchse 1 Bore: 24mm Fit: H7 Reducing socket 2. Bore: 24mm Fit: H7 Nominal torque 100 Nm
Eas-Nc Gr. 4 Type 451.615.0, Konusbuchse, Bohrung 50 Mm	
8200652 Dc-Antrieb	
7053535-1	
0017284-1	
58104519 4/500.100	
7005404-1 Kupplung Manipulationssicheren	
Easnc24505150	
Roba Es-19/24(D???.16?14)	
Eas-Nc Gr. 4 Type 451.615.0, Konusbuchse, Bohrung 55 Mm	

150/891.070.1 S Bremse Komplett Mit Rotor
150/891.080.1 S Bremse Komplett Mit Rotor
0924188 Bremse, Motor Schubbewegung X/Y 891.124.1 Roba-Stop-M891.124.1mayroba- Stop-M
8202845
8192149
Roba-Rurschnabe - Grã246;Ã223;E 1
Roba-Dx
52/K11.20 1.1 S
Eas-Nc / 450
0925011/0410
32/891.0101so
2/484.825.0/32h7/3
1/123.210.25.6885-1
0800157
Roba Es-19/24(D???.16?15)
7011039 Roba-Stop M Gr.100type 891.100.0sicherheitsbremse
Type 135.210
Type 940.000.A
7009836
T4126906 Smartflex-Wellenkupplung 7000772 Bo 11h/7 16 H7
017._00.2
2/017.000.2 Roba Switch Schnellschaltmodul
Roba-Ds-16/953.551
500.100-Gr.4
0920440
P/N: 7000572 Type: 932.333 (Gr.1)
X1068161
Eas4/4374010
017.000.2
Art.-Nr.: 7013484
7012443 Elektromagnetkupplung
410.400.0
0066190

055.000.5 0607	
E08405000000110	
20/017.000.2	
2/400.505.5	CLUTCH ELECTRO MAGNETIC 25MMH7 24VDC 30W
0/454.605.4/15/25	
931333	
Tthd-10009-140	
Roba 95.000	
0004135	
Art-Nr. 8180151	
100/891.101.0 Bremse J6102362 X1050307 Netzspannung 207v, Leistung 90w, Haltekraft 180nm	
8204985 Elektromagnetische Bremse	
Type 100.110 (0000080)	
7000712	
932.433	
Robatic Gr. 3 Type 500.100	
7021842 Roba Dxdrehsteife, Spielfreie, Elastische Metallbalgkupplungroba-Dx Gr.0type 931.333	
Eas-Nc Gr. 3 Type 450.515.0, Konusbuchse, Bohrung 45 Mm	
8200652 Getriebemotor Type K11.201.1 S 24 V Dc, 180 W 3500 Min-1 Ip69k	
135.110	
Robasproc-1/110.110	
8187550 Roba-Stop-M Elektromagnetische Sicherheitsbremse	
Bremse Rn M1110001 0/100.110 000008	
8212807	
0013975-1	
024.000.6	
0014180-1	
400v 3ael3219 Gleichrichter Bremse Mayr 1/024 400v 3a	
8165389 Roba-Stop-Mfederbelastete Sicherheitsbremsetype 891.030.1 S	
0017284 1	
0550025	

6/580.100 S
932_333_Ä216;30h7
055.010.6 Limit Switch
E55002000
8206997 ()
2/437.601.0
8227570
0802471
8185591
Pmctendo Ac3.34/0/5/1/1/4/H/3 Motoren 8173908
03/P60.112.3/230-480v .
0921798 Sicherheitsbremseroba-Stop M Gr. 150typ 891.040.0 S
T9119697 1/932.333 Bo
10/017.000.2
Roba Es-19/24 (D??19?19)
Easnc+0550005
M1110001 Art 000008
Type 450.715.0
32/891.100.0 Sicherheitsbremse Roba-Stop M Gr.32type 897.100.0
Eas4365008
Roba/Rn1/135.111/25h7/6885-1/20h7/6885-1
4000023
0802866 Schalter Ultimelimit Switch
Easnc01/4536100
0034214 Kupplung Type 500,102
S7100764 0019274 1/300.510 Replaced By 0019274-1
4376000
8180152 Hochgeschwindigkeits-Gleichrichter Gr. 20; 200-500vac; 1, 8a
7017903-3
0800157 Schalter
Endschaltertyp 1 220v
7000738
7001180

[P/N: 0000768-2 Type: 100.110 Roba-
Rutschnabe Gr. 1 Mit Standardkettenrad](#)

[P/N: 8180160 Type: 017.000.2](#)

[Ms24/25](#)

[932 333](#)

[8180152](#)

[0970347](#)

[Roba Es-19/24\(D??,15?19\)](#)

[3/911.310/20/20](#)

[Type 450.615.0](#)

[Art.-Nr.: 7001225 Smartflex Gr.3 Type 932.333](#)

[Eas-Ncc-0/490.525.0.D](#)

[148148](#)

[0802459](#)

[K443.01.037.000.1.1.0](#)

[0801959](#)

[8165878](#)

[00041401498 3/100.110](#)

[24/940.611.Ap/22/25](#)

[Rsm-Ss Rotor](#)

[0802741](#)

[3/310.610/L3=90 Kupplung](#)

[Type 100.110](#)

[1/012.000.2](#)

[7021842 Kupplungroba Dxdrehsteife, Spielfreie,
Elastische Metallbalgkupplungroba-Dx Gr.0type
931.333](#)

[7057399-1 Eac-Gespererte Kupplung](#)

[0128835](#)

[S5110897](#)

[3/802.410.3 So](#)

[7002602](#)

[6.820.610.1](#)

[0802866](#)

[8200210](#)

[4041921](#)

[Flexible Intermediate Ring For Art. 8208063](#)

0004161
Eas-Nc Gr.3 Type 450.615.0, Konusbuchse, Bohrung 45 Mm
7000850 Kupplung 3/932.333
055.000.05
7029406
0/100.110/30/6885-3/30 /
24/940.611.Ap/17/22
7009302-1
7009839-1 Eas-Nc Synchronkupplung / Durchrastkupplung
7017647
1-932.3-3-24-15-1-R
40000021
800.410.3
8200652
K11.201.1 S
1/012.000.2 0801959 Centralina Freno
0916413 Eas Sm-Zr Sicherheitskupplung Eas- Sm-Zr 1/400.016.0s 24v
Roba-Es/24/940.122.24/28
910470-S0
Roba-Lastic1/131.110/25/17
8200760
7029406 Bremse Vertikale Achseroba-Stop-M Gr.16, Type 891.100.2
Nm38740 Nh2 K4142272
0802871
0019274-1
0022012-1
Eas3/400.605.0
Roba-Es 19/940.011zap.15h719h7
2/494.505.4/40/40
7032790 Kupplung
8197213
7014566