

Michell

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Michell Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Michell Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
EA-XP-TX	Basic model: Easidew PRO XP 2-wire trace moisture transmitter with 3/4 "UNF-16 process connection for gases (4-20mA current loop, heavy-duty version for field use, explosion & flame proof). Standard measuring range -110 / + 20 ° C dew point + EX2 Local display: integrated in the transmitter housing with viewing window + C2 Sensor protection: Standard HDPE filter for Easidew sensors (protection against fine particles > 10 µm) + D2 Sensor block: 3/4 "UNF stainless steel sampling block (with 1/8" NPT gas ports for inlet / outlet) + E1 Mounting bracket: Without mounting bracket + F2 Material certification: BS EN 10204 3.1 Material Certificates + G1 Housing material: aluminum + H1 Measuring range: -110 to + 20 ° C (-148 to + 68 ° F) dew point measuring range
I7000-XP	Basismodell: Interchangeable RH and Temperature Sensor
I7000-XP-B1	%RH output signal: 0-1 V
I7000-XP-C2	Temperatursignal: No temperature output
Cea-M20-Npt-Ss	

Ms/0/232616	
Dt722-Sd-H-T0-02-Cc-F02	
Apt-Pan	
St-3217-Pc	
Ms/0/232615	
Msa299-295	
Sf52-Tx-2-S-D3-B	
Hf132-Sb1xxxxx	Transmitter for humidity and temperature room sensor, 3/4-wire version. Power supply: 15 ... 40 VDC / 12 ... 28 VAC, accuracy @ 23 ° C $\pm$ 5K: $\pm$ 3% RH / $\pm$ 0.3K, application / measuring range: 0 ... 50 ° C / 5 ... 95% RH, housing: ABS / IP30, output signals: OUT1: 4 ... 20 mA = 0 ... 100% RH, OUT2: 4 ... 20 mA = 0 ... 50 ° C.
Cg-M20-Ss	
Cea-M20-Bsp-B	
A000350	
9934042	
Cg-M20-B	
Ea2-Tx-80hd	
Cea-M20-Npt-B	
Hf320-Sba3xxxx	Transmitter for humidity and temperature Version: room mounting, 2x2-wire version, application range: -40..60 ° / 0 ... 100% RH, power supply: 12 ... 28 VDC, accuracy: $\pm$ 2% RH / $\pm$ 0, 3K, output signals: OUT1: 4 ... 20 mA = 0 ... 100% RH, OUT2: 4 ... 20 mA = 0 ... 100 ° C.
Ea2-Cab-02	
Cea-M20-Bsp-Ss	
Epr-Brk	
Ea2-Tx-100-Hd	
Ea2-0I-Hyg-100-Hd-Ac-Sc08	
Epr-Is-2	
Ms/0/232614	