

Nash Elmo



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaőabilirsiniz.

Nash Elmo Markası, tedarik sresi iin ltfen bizimle iletiőime geiniz.

Firmamız Nash Elmo Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariő durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
S835071	pos30.01 as originally installed in serial number 814 540 010 001 CONTROL DISC AS 158KG
S835126	pos 30.01 as requested TIMING DISC AS FT / 1.4404 155KG
S835076	Pos 30.02 as originally installed in serial number 814 540 010 001 TIMING DISC BS 158KG
S835131	pos 30.02 as requested TIMING DISC BS FT / 1.4404 155KG
S844940	Pos 35.01 as originally installed in serial number 814 540 010 001 HOUSING FINISHED PROCESSING 1.5 DIVISION 525KG
S844985	pos. 35.01 as requested HOUSED UNCOVERED 416KG
S838377	ventilplatte = S838377 ; 2BE340/42 0,250kg
S838387	pos 37.03 Gewindebolzen S838387 0,115KG
2BV20710NQ047B G 2BV	L-BV2 LIQUID RING VACUUM PUMP IN BLOCK CONSTRUCTION ***** Alternative successor model ***** CONNECTION FOR CAVITATION PROTECTION MAIN MATERIALS: COVER, HOUSING: GRAY CAST IRON TIMING DISC: CERAMIC WHEEL: BRONZE WITH 3-PHASE MOTOR (50 / 60HZ) UL 1450, E225239, IE3 / NP RAL 9006: WHITE ALUMINUM 1-PAINTED electrical data 380-420VD / 660-725VY_50HZ_IE3 50HZ_4,0KW_SF = 1.38 50HZ_10.3 AD / 6.0 AY 440-480 VD_60 HZ_IE3 60HZ_6,1KW_SF = 1.03 60HZ_10.1 AD 460 VD_60 HZ_NP 60HZ_6,1KW_SF = 1.03 60HZ_8,6AD Net weight: 61,000 KG AL: N, ECCN: N Nomenclature number: 84141089 Country of origin: DE
	8641176016000 Product description G-BH1 GAS RING COMPRESSORS VACUUM PUMP / COMPRESSOR INSULATION CLASS F, PROTECTION CLASS: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM DIE CASTING WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50 / 60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR

2BH14007AH16	OPERATION WITH FREQUENCY CONVERTER UP TO 5000 MIN-1 RAL 9006: WHITE ALUMINUM 1-PAINTED electrical data 0.85 KW_50 HZ 0.95 KW_60 HZ 1.5 KW_87 HZ 200-240 VD / 345-415 VY_50 HZ 220-275 VD / 380-480 VY_60 HZ 380 VD_87 HZ 4.2AD / 2.4AY_50 HZ 4.0AD / 2.3AY_60 HZ 4.0 AD_87 HZ Print data -160 / 160 MBAR (50 HZ) -160 / 160 MBAR (60 HZ) -140 / 130 MBAR (87 HZ) Net weight: 14,000 KG AL: N, ECCN: N Nomenclature number: 84141089 Country of origin: DE
2BL20611AK506B-Z	G_2BL2 Additional option: F56S21 Product description L-BL2 VACUUM PUMP, AIR-COOLED WITH LIQUID RING PUMP L-BV7 (VERSION 2BV7061) INCL. CONNECTION POSSIBILITIES FOR ACCESSORIES STANDARD DESIGN SYSTEM MATERIALS: COPPER / BRASS / EPDM VACUUM PUMP: CAST IRON / STAINLESS STEEL / BRONZE STAINLESS STEEL COVERING WITH OVERFLOW electrical data 220-240VD_50HZ_IE3 50HZ_1,40KW_SF = 1.57 50HZ_7,5AD 220-240VD / 440-480VY_60HZ_IE3 60HZ_1,8KW_SF = 1.42 60HZ_8.6 AYY / 4.3 AY 230 VYY / 460 VY_60 HZ_NP 60HZ_1,80KW_SF = 1.42 60HZ_7.3AYY / 3.65AY Net weight: 55,000 KG AL: N, ECCN: N Nomenclature number: 84141089
2BV51310KQ017B-RAL5002	Product description L-BV5 liquid ring vacuum pump in block design, connection for cavitation protection Main materials: Lid, housing: GRAY CAST IRON Control disc: cast iron Laufard: bronze with 3-phase motor (50 / 60Hz) UL 1450, E225239, IE3 / NP RAL 5002: ULTRAMARINE BLUE 1 coat of paint Electrical data: 380-420VD / 660-725VY_50Hz-IE3 178kg
2BH14007AH06	8641176006000 Product description G-BH1 GAS RING COMPRESSORS VACUUM PUMP / COMPRESSOR INSULATION CLASS F, PROTECTION CLASS: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM DIE CASTING WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50 / 60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR OPERATION WITH FREQUENCY CONVERTER UP TO 5000 MIN-1 RAL 9006: WHITE ALUMINUM 1 COATING electrical data 0.70 KW_50 HZ 0.83 KW_60 HZ 200-240 VD / 345-415 VY_50 HZ 220-275 VD / 380-480 VY_60 HZ 3.8AD / 2.2AY_50 HZ 3.75AD / 2.15AY_60 HZ Print data -120 / 120 MBAR (50 HZ) -130 / 130 MBAR (60 HZ) Net weight: 13,000 KG AL: N, ECCN: N Nomenclature number: 84141089
2BV51310KQ017B G_2BV	Product description L-BV5 LIQUID RING VACUUM PUMP IN BLOCK CONSTRUCTION CONNECTION FOR CAVITATION PROTECTION MAIN MATERIALS: COVER, HOUSING: GRAY CAST IRON TIMING DISC: CAST CAST IRON WHEEL: BRONZE WITH 3-PHASE MOTOR (50 / 60HZ) UL 1450, E225239, IE3 / NP RAL 9006: WHITE ALUMINUM 1 COATING electrical data 380-420VD / 660-725VY_50HZ_IE3 50HZ_10,5KW_SF = 1.43 50HZ_30.2 AD / 17.4 AY 440-480 VD_60 HZ_IE3 60HZ_14,7KW_SF = 1.18 60HZ_28.5 AD 460 VD_60 HZ_NP 60HZ_14,7KW_SF = 1.02 60HZ_25,0AD Net weight: 178,000 KG AL: N, ECCN: N Nomenclature number: 84141089 Country of origin: DE
	8604270100000 L-BV2 LIQUID RING VACUUM PUMP IN BLOCK

2BV20700NK016B	CONSTRUCTION CONNECTION FOR CAVITATION PROTECTION MAIN MATERIALS: COVER, HOUSING: GRAY CAST IRON TIMING DISC: CERAMIC WHEEL: BRONZE WITH 3-PHASE MOTOR (50 / 60HZ) VOLTAGE SWITCHABLE MOTOR UL 1450, E225239, IE3 RAL 9006: WHITE ALUMINUM 1 COATING electrical data 220-240VD_50HZ_IE3 50HZ_2,6KW_SF = 1.54 50HZ_13,3AD 220-240VD / 440-480VY_60HZ_IE3 60HZ_3,7KW_SF = 1.23 60HZ_15.0 AYY / 7.5 AY 230 VYY / 460 VY_60 HZ_NP 60HZ_3,7KW_SF = 1.23 60HZ_12.2AYY / 6.1AY Net weight: 46,000 KG AL: N, ECCN: N Nomenclature number: 84141089 DE
8692000911000	Spare parts kit Net weight: 0.400 KG Size / dimension: mm Material: AL: N, ECCN: N Nomenclature number: 84149000 Country of origin: DE
8692000070000	Spare parts kit 2BV7060 / 2BV7061 Net weight: 0.200 KG Size / dimension: 70X70X100 mm Material: AL: N, ECCN: N
2BH13007AH06	8641076006000 Product description G-BH1 GAS RING COMPRESSORS VACUUM PUMP / COMPRESSOR INSULATION CLASS F, PROTECTION CLASS: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM DIE CASTING WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50 / 60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR OPERATION WITH FREQUENCY CONVERTER UP TO 5000 MIN- 1 RAL 9006: WHITE ALUMINUM 1 COATING electrical data 0.25 KW_50 HZ 0.29 KW_60 HZ 200-240 VD / 345-415 VY_50 HZ 220-275 VD / 380-480 VY_60 HZ 2.1AD / 1.2AY_50 HZ 1.74AD / 1.0AY_60 HZ Print data -100 / 100 MBAR (50 HZ) - 100 / 100 MBAR (60 HZ) Net weight: 9,000 KG
2BH18000AK16	G_2BH1 ***** Successor type for 2BH18007AH17 ***** Product description G-BH1 N GAS RING COMPRESSORS VACUUM PUMP / COMPRESSOR WITH IE3 / NP MOTOR INSULATION CLASS F, PROTECTION CLASS: IP55, UL-NO.E225239 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: COVER, HOUSING: GRAY CAST IRON IMPELLER: DIE-CAST ALUMINUM WITH 3- PHASE MULTI-VOLTAGE MOTOR FOR 50/60/70/85 HZ IE3 _NEMA PREMIUM, IP55 UL 1450 AND CSA 22.2 NO.68-09 RAL 9006: WHITE ALUMINUM 1 COATING electrical data 220- 240VD / 380-420VY_50HZ_IE3 50HZ_6.3KW (20.4AD / 11.8AY) 220-240VYY / 440-480VY_60HZ_IE3 60HZ_7.3KW (24.0AYY / 12.0AY) 230 VYY / 460 VY_60 HZ_NP 60HZ_7.3KW (24.0AYY / 12.0AY) 85HZ_10.2KW (20.0AD) Print data -320 / 300 MBAR (50 HZ) -300 / 280 MBAR (60 HZ) -220 / 210 MBAR (85 HZ) Net weight: 122,000 KG AL: N, ECCN: N Nomenclature number: 84141089 Country of origin: DE
AHF80 VAC ALL IRON ANSI	43554B804D000
	8644301000003 Product description G-BH1 GAS RING COMPRESSOR VACUUM PUMP/COMPRESSOR INSULATION CLASS F, PROTECTION DEGREE: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: DIE CASTING ALUMINUM WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50/60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR OPERATION WITH FREQUENCY CONVERTER UP TO 5000 RPM

2BH13001AH16	RAL 9006: WHITE ALUMINUM 1-WAY COATING electrical data 0.40KW_50HZ 0.50KW_60HZ 0.69KW_87HZ 200-240VD /345-415VY_50HZ 220-275VD /380-480VY_60HZ 380VD_87HZ 2.4AD /1.4AY_50HZ 2.4AD /1.4AY_60HZ 2.4AD_87HZ print data -120 /130 MBAR (50 Hz) -150 /160 MBAR (60 Hz) -90 /90 MBAR (87 HZ) Net Weight : 11,000 KG AL:N, ECCN:N
S845139	CASING Net Weight : 250KG AL:N, ECCN:N Commodity number 84149000 Country of origin CN Pref: NALL
2BE43002BY4-Z	EXT_2BE4 Additional option: K95 2BE4 Net weight : 0 KG With the following configuration: MLFB complete 2BE43002BY4 .Text finding VACUUM PUMP WITHOUT DRIVE .Text finding WITHOUT A PARTITION .Text finding CAST IRON/STEEL .Text finding PACKING BOX WITH INTERNAL .Text finding BARRIER LIQUID WETTING .Text finding MADE IN CHINA CE/Atex documentation language English Sentences documentation 1 Material testing melt analysis 2.2 certificate for main parts Color RAL5005 signal blue Layer thickness 140 µm total layer thickness Balancing Static Water pressure test WITHOUT Vibration measurement WITHOUT Storage temp. measurement WITHOUT Nekaltest WITHOUT Noise measurement WITHOUT Layer thickness measurement WITHOUT Dimension control WITHOUT Test RPM STANDARD Test intake pressure STANDARD Test compression pressure STANDARD Additional sign with text WITHOUT Specials-1 WITHOUT Specials-2 WITHOUT Specials-3 WITHOUT Specials-4 WITHOUT Specials-5 WITHOUT AL: , ECCN: COMMERCIAL Statistical goods number 84141089 Country of origin CN
2511158505	TAPERED ROLLER BEARING HTF48685g3SAUR4/48620Dg
Nash SC-4	
2BL21012AK506B-Z G 2BL2	Additional option: S23 Product description L-BL2 VACUUM PUMP, AIR COOLED WITH LIQUID RING PUMP L-BV7 (VERSION 2BV7070) INCL. CONNECTION POSSIBILITIES FOR ACCESSORIES STANDARD VERSION SYSTEM MATERIALS: COPPER / BRASS / EPDM VACUUM PUMP: CAST IRON/STAINLESS STEEL/BRONZE WITH EXTERNAL COOLING CONNECTION electrical data 220-240VD_50HZ_IE3 50HZ_2.4KW_SF=1.67 50HZ_14.3AD 220-240VD/440-480VY_60HZ_IE3 60HZ_3.5KW_SF=1.3 60HZ_16.1AYY/8.1AY 230VYY/460VY_60HZ_NP 60HZ_3.5KW_SF=1.3 60HZ_13.2AYY/6.6AY Net Weight : 68,000 KG
Type:ECL 503 VACUUM PUMP	no:400/6 gasket
2BH76200AK262-Z	(K41+K35) Side channel blower WITH IE3/NP MOTOR PROTECTION TYPE: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM RAL 9006: WHITE ALUMINUM 1-TIME COAT *** Barrieta hot storage grease Metal outdoor fan *** electrical data 220-240VD/380-420VY_50HZ_IE3 50HZ_3.45KW(11.6AD/6.7AY) 220-240VYY/440-480VY_60HZ_IE3 60HZ_4.0KW(13.0AYY/6.5AY) 230VYY/460VY_60HZ_NP 60HZ_4.0KW(13.0AYY/6.5AY) 87HZ_5.8KW(11.0AD) Print data -570/480 MBAR (50HZ) -510 /410 MBAR (60HZ) -390/260 MBAR (87 HZ)

2bh1600 7ah16 Z	
17201441	
2bx1042	8623901029000 THREADED FLANGE WITH PIPE THREAD TO DIN ISO 228, FOR 2BH190 / 91 Net weight: 1,700 KG Size / Dimensions: mm Material: EN 10025-1.0035, NBR (Fe.Leg./Kautschuk,)
Baureihe 2bv2 071	
2bh13007ah06	Product description G-BH1 GAS RING COMPRESSOR VACUUM PUMP / COMPRESSOR INSULATING CLASS F, GUARD TYPE PROTECTION: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM DIE CASTING WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50 / 60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR OPERATION WITH FREQUENCY CONVERTER UP TO 5000 MIN-1 RAL 9006: WHITE ALUMINUM 1-FINE PAINTING electrical data 0.25 KW_50 HZ 0.29 KW_60 HZ 200-240 VD / 345-415 VY_50 HZ 220-275 VD / 380-480 VY_60 HZ 2,1AD / 1,2AY_50 HZ 1,74AD / 1,0AY_60 HZ print data -100 / 100 MBAR (50 Hz) - 100 / 100 MBAR (60 Hz) Net weight: 9,000 KG AL: N, ECCN: N Statistical commodity code: 84141089 Country of origin: DE _____ P_r_e_f: _ _N_
2bh14007ah06	
2bx1041	THREADED FLANGE WITH PIPE THREAD TO DIN ISO 228, FOR 2BH15 / 16 (SUCTION AND PRINT SIDE CONNECTION) 2BH76 ... N (SUCTION SIDE ONLY) Net weight: 0.500 KG Size / Dimensions: 112X80X30 mm Material: EN 10025-1.0035, NBR (Fe.Leg./Kautschuk) AL: N, ECCN: N Statistical commodity number: 73079100
2bh19107hh27	8641975127000 Product description G-BH1 GASRINGVERDICHTER VAKUUMPUMPE/KOMPRESSOR ISOLIERST.-KLASSE F, SCHUTZART SCHUTZART: IP55 FÜR VER. UND HOR. INSTALLATION HAUPTMATERIALIEN: DECKEL, GEHÄUSE: GRAUGUSS LAUFRAD: ALUMINIUM MIT 3-PHASEN SPANNUNGSBEREICHSMOTOR FÜR 50/60HZ UL 1450 UND CSA 22.2 NO.68-09 IP55 GEEIGNET FÜR STERN/DREICK ANSCHLUSS RAL 9006: WEISSALUMINIUM 1-FACH ANSTRICH elektrische Daten 16,5 KW_50 HZ 19,0 KW_60 HZ 345-415 VD /600-720 VY_50 HZ 380-480 VD /660-720 VY_60 HZ 35AD /20AY_50 HZ 36,5 AD /21,0 AY_60 HZ Druckdaten -410 /370 MBAR (50 HZ) -340 /300 MBAR (60 HZ) -340 /300 MBAR (60 HZ) Nettogewicht : 282,000 KG AL: N, ECCN: N Statistische Warennummer: 84141089 Ursprungsland: DE Prüf: N ALL
2bh13037ah06	
0000251225000	
	Art nr. 8641376026000 Product description G-BH1 GAS RING COMPRESSOR VACUUM PUMP / COMPRESSOR INSULATING CLASS F, PROTECTION: IP55 FOR VER. AND HOR. INSTALLATION MAIN MATERIALS: ALUMINUM DIE CASTING

[2bh16007ah26](#)

WITH 3-PHASE VOLTAGE RANGE MOTOR FOR 50 / 60HZ UL 1450 AND CSA 22.2 NO.68-09 IP55 SUITABLE FOR OPERATION WITH FREQUENCY CONVERTER UP TO 5000 MIN-1 RAL 9006: WHITE ALUMINUM 1-FINE PAINTING electrical data 3.0 KW_50 HZ 3.45 KW_60 HZ 5,0 KW_87 HZ 200-240 VD / 345-415 VY_50 HZ 220-275 VD / 380-480 VY_60 HZ 380 VD_87 HZ 12.5AD / 7.2AY_50 HZ 12,6AD / 7,3AY_60 HZ 12.0 AD_87 HZ print data -260 / 270 MBAR (50 Hz) -240 / 230 MBAR (60 Hz) -220 / 210 MBAR (87 HZ) Net weight: 35,000 KG AL: N, ECCN: N Statistical commodity code: 84141089 Country of origin: DE Pref: N ALL

[0000251162000](#)

[2bh15007ah16](#)

[2382036601000](#)