



Nivelco

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Nivelco Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Nivelco Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Typ: Rdg-402-0	Artikelnr.: SS-RDG-403-0 Tuning fork limit switch NIVOSWITCH for liquids Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A Customs tariff number 9026 1029 00 Country of origin Hungary
Typ: Rvg-403-0	Artikelnr.: SS-RVG-403-0 Fork & extension ECTFE coated Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A
Typ: Mrc-205-03	Magnet float switch Article number: SS-NIVOPOINT Process connection: 2 "BSP 2 switching points L1 = 224mm L2 = 369mm Lges about 450mm
Artikelnr.: Ss-Rcp-401-3	Ultrasonic compact transmitter for liquids RCM, probe L = 125mm Stainless steel housing Installation length L = 125mm Connection 1 "NPT 3-wire DIN connector Power supply 12 ... 55 V DC
2972	
4x085g0022ydo/10ppm	
9026102900	
DKD-471-F	
DRC2A22M	
DRH-3A2-2	

DTE6512M
EASY TREK SCD-330-4
EASY TREK SCD-34J-4
EASY TREK SPB-380-4
EasyTREK SCD-340-4
F291765
HBN5104S
HPA4204S
HPN4104S
KLP2040M
KSH303M
KSK-201-0
KSP2010M
MAK-100-0
MBL-515-2
Mi-NWP 130-1
Mi-SONAR-N SGV 342-2
MKA-210-0
MKA2108M
MKA-211-1
MKG-210-0
MLB-112-0
MultiCONT PRW-24A-1
NAA1010M
NAA1050M
NAW1040S
NIVOMAG MKA-210-0 EXW
NIVOMAG MKU-210-0
NIVOMAG-MKA-210-0
NIVOPRESS NAA-102-0
Nivocap CKK-140-1
NLN1201M
NLP1051M
NLP-110-1
NLP-120-0
NPK4310S

NPK4408S
NPK4690S
NWN-105-1
NWN1051M
NWN1101M
NWP-105-1
NWP-110-1
NWP1101M
NWP-120-1
NWP1201M
PKK 312-3
PKK-312-1
PKK-312-4
RCM 310-3
RCM 401-3X66
RCM4008S
RCM-402 L Ex
RCT-402-M
RCT-403-M
RFM-404-A
RHR-520-1,NIVOCONT (2M)
RHR-525-1,NIVOCONT (2.5M)
RKH-50-1
RLH-303-3
SAP-300-0
SEN-362-8EX
SGP- 390-2
SGP-390-6 Ex
SGV3804M
SPA370AS
SPA-380-4
SPA-380-4M
SPA-390-4
SPA3904S
SPA390M

SPB-380-4	
SPB-390-4	
SPB-39N-8	
SSA-262	
STA-480-1	
WGM1404M	
WGP1404S	
MKA-220-0	
SS-RCM-401-3	Ultrasonic compact transmitter for liquids RCM, probe L=125mm Housing stainless steel Installation length L=125mm Connection 1" BSP 3-wire DIN connector Power supply 12...55 V DC
SS-NIVOCONT	Type KKH-222-5 2-channel conductive limit switch with 5 electrodes 24V ... 240V AC/DC Medium temperature max. 80°C Pmax 1 bar 2x SPDT 250V, 8A 24VDC, 8A Process connection 1-1/2" BSP polypropylene
SS-RCM-401-3	Housing stainless steel Installation length L=125mm Connection 1" BSP 3-wire DIN connector Power supply 12...55 V DC
Mka-211-1 Nivomag Type Level Switch	
Mba-535-6m-400-00	
Drh-3a2-2 Drucksensornipress- Messbereich: 0...10 Barg- Genauigkeit: 0,5 %- Ausgang: 4...20 Ma	
Wgp1404s Pilotrek Pulse Radar Level Transmitter	
Krk5125m	
Wgm1404m Pilotrek Pulse Radar Level Transmitter	
Sep-38n-2	LEVEL TRANSMITTER ULTRASONIC 2WIRE
Npk4310s Nivopress Hydrostatic Level Transmitter	
Mbl-515-2 Nivotrack	
Mka-210-8	
Rcm-401-3	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 125mm probe material: stainless steel 4.4571 Degree of protection in connection plug: IP65 Process connection: 3-wire DC / DIN connector Supply voltage: DC 12 - 55V
Rcm-301-3 Sensor	
Ac-22 Sound Siren	
Spa 390-4	
Rcm-400-3	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-drach DC, DIN connector Supply voltage: DC 12 - 55V
Kkh-222-5	
Naa1050m Halter	

Krk-522-4	Bivocont Conductive electrode relay according to enclosed legend Assembly: U-rail assembly SUPPLY VOLTAGE: 24 V AC / DC Extent: 2 potential-free contact Protection class: IP20 Origin: Hungary customs tariff number: 90261029
Rcm3103m 9026102190	
Rcm4008s Nivoswitch Vibrating Fork Level Switch9026102900	
Nwp1051m	
Tbj-520-2	
Nwn-105-1 Float Level Sensor Ls1.1, Ls1.2	
Nln1201m Nivofloat Float Level Switch	
4x085g0022ydo/10ppm Sonde	
2860 Type Rcm-401-3	
Ksp2010m Nivocont Conductive Socket	
Npk-46-60	
Sat-304-0	
Npk4305m / 9026102190	
Rcm-301-3	
Rcm-400-3 Level Switch Nivoswitch	
Klp2040m Separator	
Easytrek Spa-370-4	
Rcm4158e	
Ksk-201 Electrode	
Separator Rkk-312-4m	
Krk-512-5	
Echotrek Stp-462-4	
Drucksensor Nivelco Nipress Drh-3a2-2	
Dtf6512m Nivopress Hydrostatic Level Transmitter	
Spb-370-8ex	
Easytrek Spa-380-4	
12440	
Nivofloat Nwn-105-1 Schwimmerschalter	
Ss-Sen-362-8	Integrated 2-wire ultrasonic compact transmitter for liquids EchoTREK - Type SEN-362-8 Measuring range: 0.4 ... 7m (60 kHz) Housing: stainless steel Process connection: flange DN80 / PN16, stainless steel Analog output 4-20mA + HART / Ex
Drc2a22m Drucksensor	
	Vibrating bar Limit switch for powder and granules, operating temperature: -20 ° C ... 110 ° C, oscillating rod: stainless steel

Mi-Switch-Nst Rkh 502-1	(1.4571), housing made of aluminum, process connection: G 1 1/2 "high power relay output, vertical installation, length: 207 mm, Supply voltage: 20-255 V AC / DC Output: SPDT, potential-free relay; 8A 250V AC
Nwp1051m Nivofloat Tilting Float Level Switch	
Spb-390-4 Easytrek	
Npk4408s Konverter	
Rhr-520-1,Nivocont (2m)	
Hbn5104s Microtek Tdr Level Transmitter	
Spa-380-4 Konverter Ebene Easytrek	
Naw1040s Adapter	
Spb-380-4 Ultrasonic Level Transmitter Easytrek	
Nivotrack Mta-500	
Drl-4a2-2	
Npk-43-10	
Rcp4013m	
Ctr-211-8 Nivocap 1.1m	
Rcm-400-3 (Art. Nr. 9701001850000000)	
Mlb-112-0 Magnetic Level Indicators	
Drucksensor Drh-3a2-2m	
Ksh303m Elektroden-Halter	
Easytrek Scd-310-4	
Rkh-502-1	
Sap- 200-0	
Npk4310m / 9026102190	
Rkr-503-5ex	
Spa370as Easytrek Ultrasonic Level Transmitter	
Nwp-110-1 Float Cable Level Sensor For Sewerage And Effluent	
Rcm4003	METER
Klp-201-0	
Krk-512-5 Level Control Relay	
Ss-Spb-370-8	Ultrasonic compact transmitter for liquids Housing PVDF, IP68 Measuring range 0.35 ... 8m (60 KHz) Connection 1 "or 2" BSP Power supply 12 ... 36 V DC Output 4-20 mA + HART / Ex ia
Naa1010m Leitungsverbinder	
Echotrek Stp-480-2	
Spa390m Easytrek	

Krk5125m Grenzschalter
Npk-44-15
Kln2100m
Krk-512-5 Sensor
Hpn4104s Microtrek Tdr Level Transmitter9026102190
Mbl-515-2 Magnetostrictive Level Transmitters
11705
1262
Krk-512-5 Conductive Level Switch
Pew-215-6ex
Npk4690s Hydrostatic Level Transmitter
Kln-205-0
Rfm-404-A Nivoswitch
Sap-300-0 Display
Spt-39f-3 Ultraschallwandler-Level, 3-4m, 4-20ma, Easytrek
Ksh-203
Rcm4013m
Krk5125m Grenzschalter Nivocont
Npk-43-07
Kkh225m
Nivomag Mka-210-4
Pmm-312-1
Drh3a22s 9026102190nipress Pressure Transmitter
Schalter Endplatte Ebene Rcp-401-6m
Easytrek Spb-380-4
Nivofloat Nwn-110-1 Float Level Sensor Pear-Shaped For Wastewater, Neoprene.Kabel
???-220-0 R42573i Schwimmerschalter Niveau
Nivopress Npk-431-0
Npk-45-25
Sgv3804m Echotrek
Spt-390-4
Mlb-112-0 Nivoflip
Krk5125m Nivocont Conductive Level Control Relay

Spt-390-H	
KIn-220	
505-1	
Tbc-521-2	
4x085g0023ydo/20ppm	
Obsolete - Easy Trek Sca-360-4 - Replaced By - Echotrek Stp-462-4	
Rcm-400-M	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-wire DC, M12 connector Supply voltage: DC 12 - 55V
Easytrek Spa-390-4	
Rcm-401-M	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 125mm probe material: stainless steel 4.4571 Degree of protection in connection plug: IP65 process connection: G1 Process connection: 3-wire DC / M12 connection, plug Supply voltage: DC 12 - 55V