

Nuova General Instruments



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Nuova General Instruments** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Nuova General Instruments Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Type: D7/C	Homologated: ASME VIII DIV.1 - UV Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: 1/2" NPT Gasket: VITON (-20 / +200 °C) Set Pressure: 10,50 bar Relief Flow: 125,27 SCFM 15,6 °C Fluid: AIR
D10/C Replacement	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 843,17 Kg/h 0 °C
D10/Cs 0,86	4Bar
D10	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 42,00 bar Relief Flow: 2509,34 Kg/h 0 °C Fluid: AIR
D10/C 2012 G/S/L 0.77 0.5	-20/275 C DN 3/8"x3/4" PRESSURE SAFETY VALVE
D10 / 25bar / 1/2"	
D10/S	copy of s.n. 010242577 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 754,9
CW14N_D10/CS 4BAR	and 3BAR 2pcs.
D10/C	Homologated: TEST NGI Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: G.3/4" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure: 0,50 bar Relief Flow: 82,4 Kg/h 0 °C Fluid: AIR

G20/L 6,00bar	copy of s.n. 018069854 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 EPDM (-50 / +150 °C) 6,00bar 14048,7 Kg/h water
G20/L 5,00bar	copy of s.n. 018069851 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 5,00 bar 12824,65 Kg/h water
GAUGE,PRESSURE:	TYPE BOURDON TUBE,PRESSURE RANGE 0-4 BAR,DIAL SIZE 100 MM,CONNECTION SIZE 1/2 IN,CONNECTION TYPE MNPT,CONNECTION LOCATION BOTTOM,CASE STAINLESS STEEL GR.316,ENCLOSURE RATING IP68,STANDARD EN 837,SPECIAL FEATURES DRY CASE,SOLID FRONT DRAWING:3871-KK-VD-IV2715966400001 PAGE 6,10 POS:39,93,TAG/EQUIP NO:2100-PI-21088,PON:7500063866
8.SMA 0-400 41M 1 FPM	
G20/L 5,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 5,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
G20/L 6,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 6,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
D10/CS G1/2" G3/4" 4 Bar	Type: D10 / CS Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge Flow Rate: 192.3 Kg / h Fluid: STEAM
D10/CS G1/2" G3/4" 4.5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge Flow Rate: 211.28 Kg / h Fluid: SATURATED STEAM
D10/CS G1/2" G3/4" 7 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.00 bar Discharge capacity: 305.89 Kg / h Fluid: SATURATED STEAM
D10/CS G1/2" G3/4" 7,5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 324.77 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 4 Bar	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge capacity: 190.07 Kg / h Fluid: SATURATED STEAM
	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO

G10/S G1" G1" 4.5 Bar	228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge capacity: 208.83 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 7,5 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 320.99 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 8 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 8.0 bar Discharge capacity: 399.61 Kg / h Fluid: SATURATED STEAM
Type: D10 ,Homologated : CE IV	material : Brass CW614N, Connection In : 1/2" NPT Connection Out: -- Gasket : Viton (-20/+200 C) Set Pressure : 4 BAR Relief flow : 287,09 Kg/H0 C Fluid : Air P/N# 810-CT-14V
D10/CS	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 45,00 bar Relief Flow: 2998,58 Kg/h 0 °C Fluid: AIR
Y001 D7 G.1/4" ISO 228	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: EPDM (-50 / +150 °C) Set Pressure: 2,50 bar Relief Flow: 102,86 Kg/h 0 °C Fluid: AIR
D7	Homologated: TEST NGI Material: Brass CW614N Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 0,30 bar Relief Flow: 22,84 Kg/h Fluid: STEAM Copy of S/N 018077521
für 4 BAR	
CW614N	für 4 und 3 Bar
008183161	
008365627	
009234585	
009274576	
009274734	
011376529	
012163181	
012312650	
013232305 / 013232306	
015466419	
017580806	

017580819	
019542172	
019542184	
019543432	
CW614N	
G10/S	
G14/L	
G20/L	
KR	
D10/CS 4 bar	copf of sn. 01813 brass CW614N1772
G20/S	Homologated: CE IV Material: Brass CW614N Conn. In: 1" NPT Conn. Out: G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 23,00 bar Relief Flow: 10415,46 Kg/h 0 °C Fluid: REFRIGERANT copy of s.n. 013359003
SFBSPG-V-10-S6-S-S-6-15-NTM	GAUGE,PRESSURE:0-10BAR,1/2IN,NPT,100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 10)-B-A-BB-X-SN-SY,
manometer: 0-0.2 Kg/cm2 ,316L 1/2	
Manometer: 6" 1/2" NPT	Model 1.40.2.S.G MGS 40 6" DIAL 1/2" Bottom Coupling Monel 400
Model 1.40.2.A.G MGS 40	6DIAL 1/2 Bottom Monel400
MGS18 1.18.2.A.E/0-25/41M + M3D	
see List	
Model: D7 CE IV	Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure: 12,00 bar Relief Flow: 301,27 m3/h 0 °C Fluid: AIR
G14/L 1" T.C	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: 1" T.C. Conn. Out: G.1" ISO 228 Gasket: KALREZ (-20 / +250 °C) Set Pressure: 2,50 bar Relief Flow: 406,19 Kg/h 0 °C Fluid: AIR
G10/L G.3/4" ISO 228	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: G.3/4" ISO 228 Conn. Out:G.1" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure:2,50 bar Relief Flow: 220,08 Kg/h 0 °C Fluid: AIR
Safety valve mixed type G14/L-MS in 1" triclamp	(DN50,4) out 1" gas ISO 228 set 2,5 bar (Kalrez seal, CE trademark)
Safety valve mixed type G10/L-MS in 3/4" gas	ISO 228 out 1" gas ISO 228 set 2,5 bar

Nr.020503610	Type: D10 D10 Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 404,05 Kg/h 0 °C Fluid: AIR
Z7	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 8,00 bar Relief Flow: 272,12 Kg/h 0 °C Fluid: AIR
D10/S SAFETY VALVE 8.8 BAR	
Copy of S/N 021522519	Type: D10 D10 Quantity: 10 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 14,00 bar Relief Flow: 871,89 Kg/h 0 °C Fluid: AIR
COPY OF S.N. 021443294	Type: D10/C D10/C Quantity: 1 Homologated: CE IV Material: Brass CW614N (nickel plated) Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 3,70 bar Relief Flow: 180,86 Kg/h Fluid: STEAM
E5/LS600	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1/2" ISO 228 Conn. Out: G.1" ISO 228 Gasket: VESPEL (-196 / +250 °C) Set Pressure (bar gauge): 350,00 bar Relief Flow: 5509,73 Kg/h 0 °C Fluid: AIR
D10/CS	copy of s.n. 019563438 Homologated: CE IV Material: Brass CW614N Conn. In: 1/2" NPT Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 30,00 bar Relief Flow: 487,89 Kg/h 0 °C Fluid: REFRIGERANT
D series relief and safety valve 11 bar	Relief valve: 1 timed automatic, 1 manual Safety valve 1/2" Drain valve manual 3/4" and 1" Automatic drain valve 3/4" and 1"
10G/S/L0.86	
Z21	
D14	
1 1/2 - 8 Bar Sealed Safety Valve In Hydrophoric Tank	
005201338	
016301867 - Safety Valve	
D10/S (copy of s.n. 013319176.)	Homologated: CE IV Material: Brass CW614N Conn. In: G.1 / 2 "ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 ° C) Set Pressure: 11.00 bar Relief flow: 696.45 kg / h 0 ° C Fluid: AIR
D10011087651	
D7 Cw614n G.1/4"	480 Kg/h 0 °C
	copy of s.n. 015253023 Type: B38/L Homologated: ASME VIII DIV.1 - UV+CE IV Material: SS AISI 316L Conn. In: 2" ANSI

Type B38/L	150 Conn. Out: 2" ANSI 150 Gasket: METALLICA (-196 / +450 °C) Set Pressure: 12,00 bar Relief Flow: 19127,71 lb/h 15,6 °C Fluid: AIR
20g/S/L - 0,83 - 12bar	
½ - 10 Bar Sealed Safety Valve In Air Tank	
011087651	
B20/P	
½ - 4 Bar Sealed Safety Valve In Hot Water Tank	
D10/C 2014	
Z20	
10g/S/L - 0,86 - 12bar	
D10 Cw614n G.1/2"	930,37 Kg/h 0 °C
C 10 2009	