

Opto 22

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Opto 22 Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Opto 22 Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.





Ürün	Açıklama
Opto 22, G4ODC5R , 139-2292000	
Opto 22, G4OAC5A5, 139N-2085938	
MP240D4	ELECTRONIC LOAD RELAY 24-280 VAC 4 A
000777555-81	Manufacturer: OPTO 22 # Manufacturer part number: SNAP-AIMA # Order number: 3405273
AIMA-4	OPTO 22# Manufacturer Part Number:SNAP-AIMA-4# Order number:4472123
MP240D4-17	Solid State Role
G4 ODC24	OUTPUT 60VDC 3A 24V LOGIC
IDC5B I/O MODULE	
007376B	
DC60S524	
G4-Pb4	
Snap-Rackdinb-Each	
Snap-Aima-32-Fm	SNAP 32-CH -20MA TO +20MA ANALOG CURRENT INPUT MODULE-FM APPROVED
G4-Odc5a	
Odc-24	
G4 Idc5	Input Module
Snap-B4m	B-Series 4 Module Rack
Snap-Aod-29	
G4d16r	Opto 22 Mystic Brick Controller Kit
G4a8l-Cover	
Qac-5q	
Iac5p	
Snap-Odc5r5fm	
G4-Ad4	
G4lc32f1m	
Snap-D8mc-P	
Iac-5a	
Snap-Idc-32-Fm	

Snap-B3000ha	
G4-Batt32	
Ad-18t	
Oac24a	
G4ls	
G4oac24ama	
Snap-Pac-Rck12-Fm	
Snap-Psudin	
Strap8	
240d45-18	
Snap-Rackdin	
Ad-4	
Pb32h	
Odc-5	
Groov-Svr-Win-Snap	GROOV SERVER FOR WINDOWS FOR SNAP PAC ONLY
Pb16mds	
Snap-It-Wm4	
Snap-Aoa-23	
N-Tron700-Pm	
005157d	
G4-Odc24-1.5a	
Snap-Odc5rfm	
Fuseg4	
Pb-16p1	
Ca2	
Snap-Idc5q	
Snap-Aitm-C	
001818b	
Optoemu-Snr-Dr1	ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI
Ex-2	
001836cw	
Brickstrap	
Fuse01g4	
G4-Mod-Sockets	
005246c	
Pb-32p2	

R0430	
001828d	
N-Tron7506gx2	
Groov-Ar1	GROOV BOX
380d25	
B1	
Ac38a	
Snap-Pac-R2-W	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS-
Iac-5aq	
Ad2t	
Pb-16s	
4860000-7617	CLASSIC CONTROLLER
240a45	
Snap-It-Pm-Ads	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
Ad17t	
Snap-Aiv-32	I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST
Snap-Enet-D64	
Ad14t	
Snap-Idc-16	
005157c	
G4d16l-Cover	
240d50	
M4sarc	
G4brickbase	
Til114	
Da-6	
G4iac24	I/O Module
Snap-Aitm-8-Fm	
Snap-Idc5ma	
Snap-Hd-Acf6	
Ioprojectpro	IOPROJECT PROFESSIONAL SOFTWARE SUITE, FOR USE WITH:OPTO22 SNAP PAC LEGACY SYSTEM CONTROLLERS AND I/O UNITS, KIT CONTENTS:IOPROJECT PROFESSIONAL COMPL

Iac15a	
G41dc5-Input10-32vdc	
Ac40b	
Snap-Odc5snkfm	
G4-Pb16hc	
G4ad24	
Dc60s-3	
Snappacr2	
001788b	
Snap-Aov-25	Dual Channel Output Module SNAP-A0V-25
G4 Oac5afm	
139	
Snap-Idc5-Ht	
Snap-Brs	
Dc60s-5	
Z240d10-17	
Oac15c	
Ad-3	
Ac-8a	
G4d16r-Brain-Board	
Fuse05	
Oac5	OAC5 AC Output Relay Module OAC5 OPTO 22
Odc5p	
G4abrick	
G4-Ad16	
G4lc325x	CONTROLLER 200 MYSTIC
Pci-Ac5	
Snap-Scm-Profi	
Ssr-Hs	
Snap-TeX-Fb16-H	
Snap-Fieldconb	
Optoterminal-G75	CONTROLLERS, DISPLAY, METER DISPLAY TYPE:TFT-LCD COLOUR, DISPLAY RESOLUTION:640 X 480 PIXELS, SUPPLY VOLTAGE RANGE:10VDC TO 26VDC, OPERATING TEMPERATU
Snap-Hd-Cbf6	
Od6	
Optoemu-Cts-2000-600	

G4-Ad18	
Snap-Pac-S1-W	PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE W1
120d3	
Snap-Rokdin	
Snap-Pac-Eb1-W	I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC
Cac15	
G4odc5afm	
Ad-10t	
Od2	
Circuitcard	
Snap-Odc5src	
8	
G4-Oac5a5	
Snap-Scm-W2	
Fuseg4b	
G4-Swin	
007308d	
Oac-5	
Snap-Pac-S2	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, LEADED PROCESS COMPATIBLE:NO, P
Icmoc3012	
B3000	
Snap-Aitm	
N-Tron702m12-Pk	
N-Tron516tx-A	
120a10	
Ca10	
G4-Lc32sxf1m	
001830f	
005158g1	
Snap-Fuse10ab	
Da8 Power Module	
Optotermcable-G70	
Snap-Odc-32-Src	

Snap-D4mc	
Ad15t	
Ad-16t	
Snap-Odc5r	4-Ch Reed Relay Digital Output Module SNAP-0DC5R
Snap-Oac5ma	
Oac5-10pack	10PK AC Output Relay Module OAC5 OPTO 22
G4rcommkit	
G4oac15a	
Iac-5	
G4-Idc5k	
Snap-TeX-32	
Snap-B4	
001772a	
Snap-Iac-K-16	
M4-Ethernet	
Snap-Enet-S64	
N-Tron517fx-A-St-S	INDUSRTIAL WIRELESS RADIO, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS:1, SUPPLY VOLTAGE MAX:49VDC, SUPPLY VOLTAGE MIN:20VDC
G4-D16r	
G4-Ad11	
Pb24-Hq	
Model : Mp 240 D4	
Pb-16md	
4187	
Snap-Aod-29-Hfi	
Snap-Aoa-23-Isrsc-Fm	
240di45	
G4strip	
G4-Aitm	
N-Tron716tx	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC
Hh6	
575di45-12	
G4idc5d	
006015b	

480d15-12	
100023	
Odc24	
G4-Idc-5ma	
Strap2q	
E2	
G4-Lc32isa	
Snap-Airt-d-1k	
22lc4a	
Snap-B12-Mc	
G4-Idc5q	
B5	
Oac5ah	
Pb4h-6771	
G4-Iac24	
G4p2245a	
B6	
Snap-B12m	SNAP B-Series 12-module Rack
32n107e	
Fuse02b	
N-Tronntsfp-Tx	
Od8	
005081aw	
001234b	
Snap-Aoa-23-Isr-c	
Snap-Pac-Eb1-Fm	
Snap-Aima-Isr-c	
G4lc32sx	Opto 22 Mystic 200SX Processor Module 200SX
Snap-Hd-G4f6	
Snap-Aoa-23-Ih	
Pactermssd	PAC TERMINAL SECURE STRATEGY DISTRIBUTION (SSD) (DOWNLOAD)
Pb16l	
185175a01	PC BOARD G4HDM
Ic545j	
B3000-B-Gt	
Strap4q	

001830a	
Snap-It-Rm-D64	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
001774b	
57456	
G4-Idc24	
Snap-Rck-B2m	
P240d4-17	
Idc-5d	
Snap-TeX-Drc10	
Snap-Idc-32d	
Hh8	
G4aiva	CIRCUIT BOARD ANALOG I/O
Snap-TeX-Cbe6	
Snap-Brs-Ha	
Ac-24at	
P120d2	
G4-Odc5r5	
G4-Ps245a	
G4b200	
Ac-42	
Pb-16t	
001848g	
200sx	
B2	
G4-Ad7	
Pb-Sa	
G4-Ior	
Ac36	
Snap-Rpsw	
001842d	
Snap-Aiv-Hdb-Fm	
Pbmoa	
Snap-M64	
Snap-Idc5fm	
Ac422	

8883	
G4-Oac5a	
84113310	
Mp380d4	
Da-3	
Snap-Up1-M64	PROGRAMMABLE LOGIC CONTROLLER, METER DISPLAY TYPE:LED, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:MULTIFUNCTION 64-POIN
Oac-27	
G4-A8p	
Snap-Odc5snk	
Snap-Hd-Bf6	
Ac-34	
Snap-Pac-Eb1	
001836fwo	
M4lcsx	
G4-Odc5	
G4-Oac24a	
308tx-N	
Snap-Aima-Ih	
G4-Ad12	
G4rax	Opto 22 Mystic Brick Controller Kit
Snap-TeX-Mr10-16c	
Oac5	
Ac-37	
SmiaC5	
Icmoc3040	
G4oac5ama	
G4-Oac5ma	
Snap-Aiv-72h	
G4-Odc24a	
G4ps24xb	
Optointmb	
G4idc5	
Optoterminal-G70	CONTROLLER OPERATOR INTERFACE, DISPLAY RESOLUTION:320X240, OPERATING TEMPERATURE RANGE:-10C TO +60C, PEAK REFLOW COMPATIBLE (260 C):NO, FOR USE WITH:S
Odc-5a	

G4lc32sxser	
M4ps48d	
Snap-Fuse1ac	
Snap	
G4-Idc5b	
G4odc5r	
G4lc32arc	Opto 22 Mystic Brick 485 Interface Module
Snap-Airt-d-10	
Idc-5q	
Snap-Rck-M2b	
Snap-Oac5-Ifm	
Icilq55	
G4-Pem-Nuts	
6017c	
G4odc5r5fm	
G4-Iac5a	
Ad-6t	
Snap-Aivrms-I-Fm	
Aml21fba2aa	
G4-Ad25	
480d25-12	
Snap-Hd-Bf1	
G4lc32ram	
Pb-16a	
Snap-Scm-232	
G4lc4c	
Snap-Aima-Hdb-Fm	
Snap-Air400k-8	
G4 0ac5	Output Module
001792d	
Pb16he	
M4ps125d2	
889	
Dc60p	
001830j	

G4da10	
Snap-Odc5-Ifm	
Snap-Lcm-4	
240d3	
Snap-Aivrms-I	
Ic4n27	
Da4t0	
Ad-5t	
Snap-Omr6-A	
001836kwo	
Snap-Modtool	
Groov-Ar1-Snap	GROOV BOX FOR SNAP PAC ONLY
G4pb32dec	32-channel I/O Module Rack for DEC Computers 5292
G4-Da4	
G4hdm	
Pb-4r	
G4da6	
Ps115-1.5a	
G4strapb	
Odc-24a	
Odc22	
N-Tron306fx2-N-St	
Mp240d2	
G4-Lc32isaser	
Snap-Pac-S2-W	PROGRAMMABLE CONTROLLER, WIRELESS, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WI
N-Tron702m12-W	WIRELESS RADIO WITH 3 MIMO ANTENNAS
Pb-16h	
Oac24h	
001784a	
Snap-Pac-Rck8	
Snapaima4	
G4iac15a	
Snap-Iac-A-16	
Safetycover	
Mp240d4	

575d4521	
Snap-It-Emu1	OPTO 22 ENERGY MONITORING UNIT
Lcm4proc	PC BOARD
Ictd	
Snap-Idc5g	
Mp240d4-17	
Optoemu-Cts-0750-150	
240d107	
Ac-8	
Oac-5adc	
Pb-16hc	
1662	
Pb-4h	
Snap-Rackdinb	
M4-Ps120a	
240d10-17	
G4-Lc32mb	
Pb32p2w	
Snap-Aiv-4	
Snap-Pac-Rck4	
Snap-B8m	
007308e	
Icmoc2a4010	
Snap-Pid-V	
Da-4	
Term1	
Pb4md	
G4fuse4a	
Fuse125	
380d45	
Snap-Airate	
000201uwo	
G4-Idc5d	
Snap-Pac-Eb2-Fm	
Odc-15	
001848d	

G4-Ad3	
Sb1-Rs485	
N-Tron304tx-N	
Dc200p	
Z240d10	
G4-D16I	
G4b2	
G4oac5a	
5300-0003	
Ich11av2	
575d30-Hs	
Groov-At1	GROOV BOX
G4 Iac5	Input 120 VAC 5Volt Logic 591
Snapscm232	
Ad-13t	
Ad-7	
M4-Rtu	MODULAR CONTROLLER, FOR USE WITH:FACTORYFLOOR SOFTWARE, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO
Snap-Iac5fm	
Oac5a	Opto 22 OAC5A Output Relay Module
Snap-B3000-Brain	
Snap-Aima-I	
Snap-D12mc	
Groov-At1-Snap	GROOV BOX FOR SNAP PAC ONLY
G4ad26	
G4-Iol	
001828h	
G4 Odc5	ODC5 Output Module
Ac24t	
Snap-Aoa-3	
001838d	
Pb4a	
G4-Oac-5afm	
G4 Oac5	Opto 120V Fuse 890
Da7t	

Snap-Pac-R2	
Strap2	
Snap-Fuse2ab	
Optoemu-Cts-1250-400	
Idc5f	
Icmct273	
Snap-Pdprs64	
G4-Idc5g	
Snap-Omr6-C	
G4-Pb32r	
Iac-5q	
001784b	
Pb16ma	I/O BOARD
Optoterminal-G20	
Idc-24	
G4dbrick	
Odc5r	ODCR5 Dry Contact Output
P240d4	
Snap-Rck-M2pb	
Snap-Ailc-2	
Lc2dc	
M4senet-100	COMPUTERS, NETWORK INTERFACE CARDS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS COMPLIANT: NO
G4-Ra	
G4d32eb2	ETHERNET I/O MODULE, 32 CH, LENGTH:266.7MM, EXTERNAL WIDTH:177.8MM, EXTERNAL DEPTH:100.3MM, FOR USE WITH:G4D32RS MISTIC DIGITAL RACK, ACCESSORY TYPE:E
G4hdmr	
Snap-Idc5d	4 Channel DC Input Module IDC5D
Fuse05b	
Snap-Scm-Ssi	
Snapodc5r Snap-Odc5r	
Snap-Pac-R1-W	PROGRAMMABLE CONTROLLER, WIRELESS, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, FOR USE WITH:SNAP PAC SYSTEM, SIGNAL INPUT TYPE:ETHERNET, RS-
Oac-15	
005158f	
G4-Ram4m	

Opto22odc5	
120d10	
001788k	
G4-Odc5fm	
Snap-Idc-32n	
G4-Pb8h	
Iac5e/24	
G4odc5	
Snap-Paclc	LEARNING CENTER, KIT CONTENTS:SNAP PAC LEARNING CENTER GUIDE, PAC PROJECT 8.0 SOFTWARE WITH PAC PROJECT DOCUMENT, FOR USE WITH:ETHERNET-BASED SYSTEMS
Snap-S2din	
Snap-Up1-D64	CONTROLLERS, FOR USE WITH:SNAP ULTIMATE I/O ETHERNET BRAIN 64 POINT DIGITAL, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO ROHS COMP
Snap-A0a-23-Isrsc	
Pb4moa	
Snap-Aov-27	
Snap-It-Rm-Ads	MONITORING UNIT RACK-MOUNTED
Pb-32hq	
G4-Da5	
Idc-5b	
G4lc4a	
Opto-22-B6	
Snap-Odc5srcfm	
Ad1	
N-Tron7026tx	ETHERNET SWITCH, MANAGED, 24 COPPER PORTS, 2 MINI-GBIC PORTS, RACKMOUNT
Snap-Pac-R2-Fm	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER ON-THE-RACK-FM APPROVED
Ac-6	
Optodriver	
Odc-5q	
G4-Ad5	
G4 Idc5d	Input Module
Snap-Odc-Hdb-Fm	
Snap-Aiv-I	
G4idc5-Swnc	
Dc60s3	

240d10	
Plc-Manual-Cd	
Snap-Up1-Ads	
Snap-Iac5ma	
E-31a	
G4pb16l	
Snap-Aiarms	
Snap-D12mc-P	
Fuse01g4b	
Snap-Pac-Sb2	
Odc15a	
G4-Odc-5ma	
Oac-15a	
Snap-TeX-Mr10-16	
Snappacr1	
M4-Sser	
G4-Rs	
Snap-D12m	
N-Tron508fx2-A-St-S	ETHERNET SWITCH, MANAGED, 6 COPPER, 2 FIBER, MULTIMODE, ST, PLUG-AND-PLAY, STD. TEMPERATURE
Lcm4-Serial	
Snap-Aiv2-I	
Ac40c	
Iac5	AC Input Module IAC5 OPTO 22
Oac5a-11	
G4-Ad13	
Snap-Scm-St2	
Snap-Aov-5	
Snap-Aivrms	
Fuse01g4	
Snap-TeX-Cbs6	
141	
25904	
Snap-Aiv	2 Channel Analog Input Module AIV
Snap-Odc-32-Src-Fm	
Snap-D6mc	

416105	
Snap-Pac-Rck8-Fm	
Snap-Odc5asn	
Snap-Aiarms-I	
G4-Hdal	
32n106e	
Til111	
Snap-Pac-Eb2-W	I/O PROCESSOR WIRELESS, CURRENT RATING:750MA, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, AC
G4-Hdar	
G4-D16I-Base	
Idc-15	
Oac-5a5	
Snap-Aictd-4	
Snap-Io4ab-Lc	LEARNING CENTER, KIT CONTENTS:LEARNING CENTRE USERS GUIDE, ETHERNET/IP PROTOCOL GUIDE, ETHERNET/IP CONFIGURATOR, FOR USE WITH:OPTO22 SNAP INPUT / OUTP
Optoemu-Pt600	
007308f	
G4ac5	
Snap-D4mc-P	
M4ps240a	
Optoemu-Act-0750-100	
Snap-Aiv-8	
G4-Lc32arc	
G4-Idc15	
G4-Pb32h	
Ac-30a	
G4-Strap	
Snap-Odc-32-Snk	
24oa45	
Snap-Enet-Rtc	
N-Tron900b-N	
Snap-Ailc	
G4ram1m	
Snap-D8mc	

G40ac24a	
G4ra-Card	
Mp-120d2	
Odc5	ODC5 Output Module
Ca8	
G4-A8I-Base	
P240d2	
120d45	
Snap-Odc5a-Ifm	
Optoemu-Cts-0750-70	
22-Iac5	
Snap-Aima-4	
Snap-Ps5-24dc	24 VDC Logic Power Supply OPTO 22
Snap-TeX-Cbo6	
Ad8	
8882	
Masarcf	
G4-Ad22	
Snap-Aimv2-4	
G4-Rd	
Oac-5p	
Da-8	
Dc60mp	
551ps5014	
Dc 60 Mp	
Optointab	
Snap-Scm-Can2b	
240di10	
N-Tron716fx2-St	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V
Idc-5bq	
Fuse01b	
Idc5q	
Pb-8ah	
Hh4	
G4a8r	Opto 22 Mystic Brick Controller Kit

M4-Enclosure	
005247b	
Groov-Svr-Win	GROOV SERVER FOR WINDOWS
B200	
Snapidc5a	
G4pb32jy-In	32-channel I/O Module Rack
Oac-24	
Idc5	Input Module
G4-Odc24	
P120d4	
Snap-Aictd-8	
G4-A8l	
Model: Dc 200 Mp	
Snap-Scm-485-422	
Ic817cd	
G4-A8r	
Snap-Oac5-I	
Snap-Aipm-3v	
Snap-Pac-Sb1	
Idc5p	
G4-Pb16h	
G4ad19	
Cjc	
575d15-12	
Pci-Ac51	
240a25	
240d30-Hs	
Z120d10	
Snap-Pac-R1	PROGRAMMABLE CONTROLLER, FOR USE WITH:SNAP PAC SYSTEM, ACCESSORY TYPE:PROGRAMMABLE AUTOMATION COMMUNICATION, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW
Ac-7a	
G4pb16j	
G4pb24	
G4-Lc32int	COMM BOARD
Pb32p2wo	

Da-3t	
B3000-B	
Fuse.125b	
G4lc32isalt	
Snap-Ps5	
590-0513-00	
Snap-Aiv-32-Fm	ANALOG INPUT MODULE, 5VDC, 150MA, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, VOLTAGE RATING:5VDC, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.5
G70	
Snap-Pac-Rok	SNAP-PAC REDUNDANCY OPTION KIT, 32VDC, VOLTAGE RATING:32VDC, LENGTH:93.98MM, EXTERNAL WIDTH:83.82MM, EXTERNAL DEPTH:46.36MM, ACCESSORY TYPE:SNAP-PAC R
Snap-It-Rm-Uads	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
G4-Exl	
Groov-Snap-Upg	SNAP UPGRADE TO
001848e	
Da-4t	
Pcie-Ac51	
Iac24a	
Opto 22 Odc5q Quad Pak 4-Channel Dc Output 5-60 Vdc, 5 Vdc Logic	
70odc5	
G4-Ad10	
G4ad6hs	
240di25	
240a10	
Ad-6hs	
240d25	
Ich11c1	
Odc5q	
G40dc24	I/O Module
Lc32sxf	
Ic4n35ssm	
G4oac5fm	
Ac42at	
Snap-Fuse1ab	

Pb16	
G4-Base	
716tx	ETHERNET SWITCH
Pbsc	
Ac40a	COMPUTERS, INTERFACE CARDS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, FEATURES:FIBER OPTIC REPEATER, 120VAC, ROHS COMPLIANT: NO
001717a	
Snap-Aima2-I	
Snap-It-Pm12	SNAP PAC SYSTEM 12-MODULE ENCLOSURE, NEMA 3R, META
Snap-B3000-Modbus	SNAP Modbus I/O unit B3000 BRAIN
Snap-Odc5a-I	
Idc5a	
B11	
Snap-Idc5-Fast	
Snap-Scm-Mch16	
Snap-It-Rm-Pac-R1	SNAP IT RM RACK WITH A PAC-R1
G4da8	
Pb16k	
G4ad20	
Snap-Pac-Rck12	
G4d16ls-Cover	
Lc2	
G4odc24	
Optoemu-Snr-3v	CURRENT SENSOR, 8 CHANNELS, 0.2%, ACCURACY %:0.2%, ACCURACY:0.2 %, EXTERNAL DEPTH:11.4CM, EXTERNAL HEIGHT:34.3CM, EXTERNAL WIDTH:15.2CM, INPUT VOLTAGE
005078a	
Ad-10t2	
Snap-Aitm-4i	
Snap-Pac-R1-Fm	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLLER-FM APPROVED
Ic2502	
Snap-B16mc	
G4-Ad17	
Snap-Airate-Hfi	
G4d16r-Cover	
Da-5	

G4-Lc4	
Snap-Aiv-72	
Snap-B6	
005746b	
240d2s	
Snap-It-Rm16	SNAP PAC SYSTEM 16-MODULE ENCLOSURE, METAL, RACK-M
G4fuseclip	
Pci-Ac28	
Softpac	
G4odcs	
006876b	
Snap-Lcsx	
Snap-B16mc-P	
Oac5a/120	
Dc60s5	
001842e	
Odcq-5	
Ad7 Non Rohs Analog Input Module	
005326b	
22	
Oac-5a	
001842f	
Smidc5	
Snap-Label-4b	
Pbmd	
001744b	
N-Tron904fx-Sc	SLIDE IN MODULE FOR 900 SERIES CHASSIS, 4 FIBER, MULTIMODE, SC CONNECTORS
G4b100	
001788l	
G4mservo	PC SERVO BOARD ASSEMBLY
Ac-28	
B3000-B-Omux	
G4lc4b	
G4-Idc5	
N-Tron708fx2-St	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:8, SUPPLY VOLTAGE MAX:30VDC, SUPPLY VOLTAGE MIN:10V

Snap-It-Pm-Ads-Plus	CONTROLLERS, PEAK REFLOW COMPATIBLE (260 C):NO, LEADED PROCESS COMPATIBLE:NO, ROHS COMPLIANT: NO
Snapidc32	
Pb-4ah	
Snapphorp	
Optotermcable	
240d25-17	
Snap-Modlatchb	
Snap-Iac5a	
Snap-D4m	
Smapa0a3	
N-Tron702-W	INDUSRTIAL ETHERNET SWITCH, NO. OF PORTS:8, NETWORK SPEEDS:10 / 100 GIGABIT, NO. OF PORTS 10/100TX:6, NO. OF PORTS 100FX:2, SUPPLY VOLTAGE MAX:30VDC
Pb16j	
001784d	
5196b	
Snap-Aima-32	I/O MODULE, VOLTAGE RATING:5V, CURRENT RATING:150MA, LENGTH:83.13MM, EXTERNAL WIDTH:82.55MM, EXTERNAL DEPTH:18.29MM, FOR USE WITH:OPTO22 SNAP PAC SYST
Pb-24	
Snap-Strap	
Pb32hqwo	
Ocb-003	
Fuse02	
Ac-5	
1848	
480d45-12	
Ad11t	
Iac24/120	
Pb16h	
Snap-Fuse7.5ab	
Iac-15	
Snap-Idc5-Fast-A	
Term-2	
N-Tron702-W-Pm	
Optoemu-Snr-Dr2	ENERGY MONITORING UNIT WITH DEMAND RESPONSE CAPABI
B4pamux	

N-Tron709fx-St	ETHERNET SWITCH, MANAGED, 8 COPPER 1 FIBRE, MULTIMODE, ST CONNECTOR
Snap-Pac-Eb2	
Iac15n	
Snap-Pac-R1-B	SNAP PAC R-SERIES PROGRAMMABLE AUTOMATION CONTROLL
G4-Pb32dec	
Ac30b	
Ieee488	
Output-Switch	
Optoopcserver	
G4d32eb2-Upg	
G4-Reg	
M4dualarc	
E1	
240d45sp	
Hh10	
Snap-Ps24	
Snapodc32s	
Ac31a	
Snap-Pac-Rck16-Fm	
Snap-Pac-Rck4-Fm	
Snap-TeX-Mr10-4	
G4-Odc24afc	
120d5	
Snap-TeX-Rckcap	
007214d	
Ac38b	
Optotermcable-G75	
Input-Switch	
Snap-Aima	Analog Current Input Module
Snapaov5	
Snap-Odc-Hdb	
G4da9	
M4rtux	
Snap-Wirestrapb	
Pb-24q	

Snap-B3000-Enet	
Snap-Idc5k	
N-Tron712fx4-St	ETHERNET SWITCH, MANAGED, 12 PORT 8 COPPER, 4 FIBER ST CONN
G4-Pb8	
Ac422-001734a	
001828g	
Snap-Aitm-I	
Snap-Mr10	
001662a	
Pb16s1	
Snap-Pac-S1-Fm	SNAP PAC REDUNDANCY OPTION KIT, NO. OF DIGITAL INPUTS:-, NO. OF DIGITAL OUTPUTS:-, ACCESSORY TYPE:I/O MODULE, EXTERNAL DEPTH:44.4MM, EXTERNAL WIDTH:10
Snap-Odc-32-Snk-Fm	
Snap-Pac-Rck16	
001788j	
Ac47	
Snapenetd6 Snap-Enet-D64	
Snap-Idc5	Digital Input Module
N-Tron708tx	
G4ps245b	
Snappacrc8	
G4-0ac5a	
Snap-Aitm2-I	
Zxr0pt022b1	
Lcm4	
240d45-17	
Snap-Modfusehldrb	
Snap0dc32src	
Snap-Aipm-3	
001836cwo	
Anapaitm	
Pacprojectpro	SOFTWARE, KIT CONTENTS:PAC PROJECT PROFESSIONAL COMPLETE SOFTWARE SUITE, DOCUMENTATION ON CD, PLUS PRINTED DOCUMENTATION, ACCESSORY TYPE:PROJECT PROFE
Snap-Aiarms-I-Fm	
Snap-Fuse4ab	

Odc-5r	
Zxropto22b1	
Snap-B16m	
G4-Lc32sx	
G4-Pb4r	
Snap-B8mc-P	
Ad12t	
N-Tron306fx2-N-Sc	
Snap-Idc5fast	
G4Id-Card	
Snap-Scm-Bb4	I/O RACK, ACCESSORY TYPE:BREAKOUT BOARD, FOR USE WITH:OPTO22 SNAP PAC SYSTEMS, LEADED PROCESS COMPATIBLE:NO, PEAK REFLOW COMPATIBLE (260 C):NO, ROHS C
Snap-Odc5-I	4 Channel Isolated DC Output Module SNAP-0DC5-i
Snap-TeX-Fb16-L	
Led-Spcv-Lv100w	
G4-Lax	
Jumpers	
Snap-Aova-8	
G4fusesockets	
Snap-Idc-Hdb-Fm	
G4-Odc5r	
Mp120d2-00	
G4-Pb24	
Snappacr16	
Factoryfloor	
Pbma	
001792j	
Pacdisplaypro	
Pb24wo	
G4rpanel	
Snap-B3000	
120d25	
Snap-Aitm-2	
Snap-M16	
Iac5	
Icpc846	

001788m	
Ic80n	
Snap-Psdin	
001792k	
001836jw	
Snap-It-Pm-R1ads	SNAP IT PANEL MOUNT PAC-R1 ADS BOX
Snapodc5sr	
Bds4opt23a01	
Snap-Idc-32dn	
Snap B3000	SNAP Ethernet Brain Module
N-Tron308tx-N	
Snap-Idc5-Sw	
Opto22idc5	
Snap-Odc5r5	
Ac31b	
G4ps245a	Opto 22 Mystic Brick Power Supply Module
001792h	
Ga0dc5	
Snap-Aictd	
Optoemu-Act-0750-250	
G4-Odc15	
G4-Oac5	
G4-Ps24xa	
240d45	
G4a8rcover	
Snap-Iac-16	
G4-D16p	
Odc5a	Output Module
Ich11a550	
N-Tron900-Pm	
Snap-Lcsx-Plus	
Snap-Airtid	
Ca4	
M4rtuf1m	
G4-D32rs	

[G4-Rax](#)

[Od-4](#)

[G4-Ad8](#)

[Snap-Ps5u](#)

[006352a](#)